

# INDIRECT FIRED HEATERS



**FVO-200**



**FVP-200**

Model	FVO-200 Oil	FVN-200 Natural Gas	FVP-200 Propane
Heat Capacity	200,000 btuh	200,000 btuh	200,000 btuh
Fuel Tank Capacity	23 US gallons	External N/A	External N/A
Operating Time	15 hours		
Fuel Consumption	1.50 GPH	200 CFH	2.18 GPH
Power Requirement	115 Volt / 15 Amp	115 Volt / 15 Amp	115 Volt / 15 Amp
Heat Exchanger	16 Gauge Fully Welded 304 Stainless Steel	16 Gauge Fully Welded 304 Stainless Steel	16 Gauge Fully Welded 304 Stainless Steel
Fan Motor	1/2 HP @ 1,725 rpm 1,500 CFM	1/2 HP @ 1,725 rpm 1,500 CFM	1/2 HP @ 1,725 rpm 1,500 CFM
Ignition	Direct Spark Ignition	Direct Spark Ignition	Direct Spark Ignition
Air Outlet	One 12" diameter	One 12" diameter	One 12" diameter
Wheels	Two 12" pneumatic Two 6" swivel Lockable casters	Two 12" pneumatic Two 6" swivel Lockable casters	Two 12" pneumatic Two 6" swivel Lockable casters
Approval	cETLus	cETLus	cETLus
L x W x H	51.5" x 27" x 43.5"	53.5" x 27" x 39.5"	53.5" x 27" x 39.5"
Weight	330 lbs	280 lbs	280 lbs
Nozzle Size/ Gas Pressure	1.10 x 70A @ 145PSI	3.5" W.C.	3.5" W.C.

**OPTIONS**  
For all FV-Series



12" x 12 ft Hitex Ducting



Remote Thermostat Control  
with 25 ft Cord

