

INSTRUCTION MANUAL



Solar Bilge Pump
Model # 750-7AH-G

Introduction

This compact, self-contained Solar Bilge Pump lives in the bottom of a dinghy or other small craft. A float switch inside the unit detects incoming rain water. The pump will then activate and will discharge the water through the $\frac{3}{4}$ inch discharge outlet. Connected to the outlet is a drain hose which is ran overboard.

There is a 2 watt glass solar panel mounted to the top of the enclosure in order to keep the interior battery charged and at peak condition when exposed to sunlight.

Prepare For Use:

Remove the wire tag from the side of the unit on your test switch see figure 1. This will allow the pump to operate.

Installation:

Place Solar Bilge Pump in your dinghy making sure it is placed in direct sun light. The solar panel is what is recharging the battery. The pump is able to be permanently mounted to the floor of your dinghy using the four holes directly on the bottom. Connect a $\frac{3}{4}$ " ID hose to the Pump using a Stainless Steel hose clamp. Place the other side of the hose outside of the dinghy making sure the hose is secured as so it will not fall back into the dinghy. See typical installation photo figure 2.

Please note:

The sea joule bilge pump systems turns on in about 2" of water and leaves behind approximately $\frac{1}{2}$ " of water. You can tip the boat to pool the remaining water toward the bilge pump, this helps the pump to pump out as much water as possible from the boat.

REMOVE TAG



Removing tag
Figure 1



Typical Installation
Figure 2



Sea Joule Marine Inc.

E-mail: sales@seajoule.com, Web Site: www.seajoule.com

Test switch:

To test operation of the unit push the lever down on the side to turn on pump, see figure 3

Storage:

At the end of the season remove the Solar Pump from the boat and **disconnect the black wire**. During the winter keep it inside to avoid freezing temperatures. At the beginning of the next season connect the black wire and place the Solar Pump in the sunlight for a few weeks before putting it back in the dinghy or manually charge the battery. (Replace battery after 3 to 4 years of use).

Maintenance:

Clean solar panel with mild soap.

Remove pump from enclosure and remove cover from bottom of pump and clean any debris.

Notes:

Do not sit on the Solar Bilge Pump.

Do not submerge pump under water. This pump is designed to maintain a low level of water in your dinghy not refloat it.

Keep this in mind, should a gas container spill in your dinghy this pump will transfer the gas overboard as it does for water. You are responsible for the over-board discharge of all hazardous materials.

SPECIFICATIONS:

Pump rate: 750 GPH

Discharge Outlet: 3/4"

Battery: 12 volt Gel Cell 7 amp. Hour

Weight: 10 Lbs.

Solar charge: 2 Watt (150 milli amp max.)

Solar controller: Float Voltage 13.5 volts

Fuse : 5 amp.



Test switch
Figure 3

1 Year Warranty

All products of Sea Joule Marine Inc. are warranted to be free of defects of material or workmanship. Liability is limited to repairing or replacing at our factory, without charge, any material or defects which become apparent in normal use within 1 year from the date the equipment was shipped. Equipment is to be returned, shipping charges prepaid and will be returned, after repair, shipping charges paid. If unit was submerged under water warranty is void.

Sea Joule Marine Inc. shall have no liability for damages of any kind to associated equipment arising from the installation and /or use of the Sea Joule Marine Inc. products. The purchaser, by the acceptance of the equipment, assumes all liability for any damages which may result from its installation, use or misuse, by the purchaser, his or its employees or others.