Page 1 of 6 **ER-002**

IRRITATION. HARMFUL IF INHALED.

		1. PRODUCT & COMPANY IDENTIFICATION					
1.1	Product Name:	t Name: HELMET LINER REFRESHNER					
1.2	Chemical Name:	Aerosol					
1.3	Synonyms:	NA					
1.4	Trade Names:	Helmet Liner Refreshner					
1.5	Product Uses & Restrictions:	Aerosol Cleaner					
1.6	Distributor's Name:	Bike Brite, Inc.					
1.7	Distributor's Address:	25000 Euclid Ave., Suite 200, Cleveland, Ohio 44117					
1.8	Emergency Phone:	Infotrac: 800-535-5053 International: 1-352-323-3500					
1.9	Business Phone / Fax:	800-927-4833					
		2. HAZARDS IDENTIFICATION					
2.1	Hazard Identification:	This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). DANGER! FLAMMABLE AEROSOL. PRESSUREIZED CONTAINER MAY BURST IF HEATED. HARMFUL IF SWALLOWED. HARMFUL IN CONTACT WITH SKIN. CAUSES SERIOUS EYE					

(inhalation). Hazard Statements (H): H223 - Flammable aerosol. H229 - Pressurized container may burst if

Classification: Aerosol 2; Acute Tox. 4 (oral); Acute Tox. 4 (dermal); Eye Irrit. 2A; Acute Tox. 4

heated. H302 - Harmful if swallowed. H312 Harmful in contact with skin. H319 - Causes serious eye irritation. H332 - Harmful if inhaled.

Precautionary Statements (P): P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on open flame or other ignition P251 - Do not pierce or burn, even after use. P261 - Avoid breathing fume/gas/vapor/spray. P264 - Wash hands and exposed skin areas with soap and warm thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/eye protection/protective clothing. P301+P312- IF SWALLOWED: Immediately call a POISON CENTER/doctor if you feel unwell. P330 - Rinse mouth. P302+P352 - IF ON SKIN: Wash with plenty of water. P321 -Specific treatment see this container label or section 4 of this SDS. P362+P364 - Take off contaminated clothing and wash it before reuse. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC ppm ppm ppm ES-TLV STEL PEAK STEL CHEMICAL NAME(S) CAS No. RTECS No. **EINECS No.** TWA STEL IDLH OTHER HYDROCARBON PROPELLANT 68476-86-8 NA 270-705-8 30-60 NA NA NF NF NA (A46) Flam. Gas 1; Liq. Gas 1; Acute Tox. 4; H220, H280, H332 NF NF NA AQ-HF HELMET FRESH NA 30-60 2 NA NA NA (PROPRIETARY) Acute Tox. 4; Eye Irrit. 2A; Skin Irrit. 2; H302, H312, H315, H319, H332

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.
		<u>Skin</u> :	If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.
		Inhalation:	Remove victim to fresh air at once

Page 2 of 6 **ER-002**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/31/2016 4. FIRST AID MEASURES - cont'd 42 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. None expected. Inhalation: 4.3 Symptoms of Overexposure: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. 4.4 Acute Health Effects: Moderate irritation to eyes and skin. 4.5 Chronic Health Effects: No harmful or chronic health effects are expected to occur from a single accidental ingestion. Target Organs: 4.6 Eyes 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 2 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 3 **PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: FLAMMABLE AEROSOL. Level 2 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids or/or exposed gases if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished. Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. When exposed to high temperatures, may produce hazardous decomposition products such as oxides of carbon (e.g., CO, CO₂) and nitrogen (e.g., NO_x) and smoke. Extinguishing Methods: 52 Water, Foam, CO₂, Dry Chemical, Halon (if authorized) 5.3 Firefighting Procedures: As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressuredemand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Do not eat, drink, or smoke while handling this product. 7.2 Storage & Handling Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat and open flames. Special Precautions: 7.3 Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.

Page 3 of 6 **ER-002**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 5/31/2016 SDS Revision: 1.0 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: NOHSC OTHER ppm (mg/m³) CHEMICAL NAME(S) STEL ES-TWA ES-STEL ES-PEAK STEL TI V PEL IDLH **HYDROCARBON** NA NA NF NF NF 5 NA NA MIST **PROPELLANT** AQ-HF HELMET FRESH NA NF 2 NF NA NA (PROPRIETARY) Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general Controls: exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8 4 Eye Protection: Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available. 8.5 Hand Protection: Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. Body Protection: 8.6 No special body protection is required under typical circumstances of use and handling. necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Aerosol spray 9.2 Odor: No odor 93 Odor Threshold: NA pH: 9.4 NA 9.5 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 9.6 NA Range: 9.7 Flashpoint: NA 9.8 Upper/Lower Flammability NA Limits: 99 Vapor Pressure: NA 9 10 Vapor Density: NA 9.11 Relative Density: NA 9.12 Solubility in Water: NA 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA 9.16 Viscosity: NA 9.17 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stability: This product is stable. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO₂) and sulfur (SO₂). Products: Hazardous Polymerization: 10.3 Will not occur. 10.4 Conditions to Avoid: Open flames, sparks and high heat. Incompatible Substances: 10.5 None known

Page 4 of 6 **ER-002**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/31/2016 11. TOXICOLOGICAL INFORMATION Inhalation: YES Absorption: YES 11.1 Routes of Entry: Ingestion: YES 11 2 Toxicity Data: This product has not been tested on animals to obtain toxicological data. Toxicology data for some of the components in this mixture, found in scientific literature, are presented below: Aq-Hf Helmet Fresh (Proprietary): Acute dermal toxicity (rabbit) LD₅₀ >1,000-2,000 mg/kg; Acute inhalation toxicity (rat) LD₅₀>10-20 mg/L; Acute oral toxicity (rat) LD₅₀>300-2,000 mg/kg (literature values). 11.3 Acute Toxicity: See section 4.4 Chronic Toxicity: 11.4 See section 4.5 11.5 Suspected Carcinogen: No. 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices NE Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There is no specific data available for this product. Effects on Plants & Animals 122 There is no specific data available for this product. 12.3 Effects on Aquatic Life There is no specific data available for this product. 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13 1 Waste disposal must be in accordance with appropriate Federal, state, and local regulations 13.2 Special Considerations U.S. EPA Waste Number: D001 (characteristic - ignitable). 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) - until 12/31/20; or UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) IATA (AIR): 14.2 ID8000, CONSUMER COMMODITY, 9 (LTD QTY, IP VOL ≤ 0.5 L); or Лħ, UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.3 IMDG (OCN): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) TDGR (Canadian GND): MARK PACKAGE ("LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT 14.4 LTÉE" ≤ 1.0 L) or UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.5 ADR/RID (EU): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L) SCT (MEXICO): UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L) 14 7 ADGR (AUS): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION SARA Reporting 15.1 This product may contain 2-Butoxy Ethanol a substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 15.5 Other Federal Requirements: This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B5, D2B (Flammable Aerosol, Other Toxic Effects)

Page 5 of 6 **ER-002**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 5/31/2016 15. REGULATORY INFORMATION – cont'd State Regulatory Information: No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). California Prop. 65: WARNING: This product contains chemical(s) known to the State of California to cause cancer or reproductive harm. 15.8 Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC. (Xi), Risk Phrases (R): 36/37/38 - Irritating to eyes, respiratory system and skin. Safety Phrases (S): 2-23-24-26-36-45 - Keep away from children. Do not breathe fumes/spray. Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing. In case of accident or if you feel unwell seek medical advice immediately and show this container or label. 16. OTHER INFORMATION DANGER! FLAMMABLE AEROSOL. PRESSUREIZED CONTAINER MAY BURST IF HEATED. HARMFUL IF Other Information: SWALLOWED. HARMFUL IN CONTACT WITH SKIN. CAUSES SERIOUS EYE IRRITATION. HARMFUL IF INHALED. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing fume/gas/vapor/spray. Wash hands and exposed skin areas with soap and warm thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/protective clothing. IF SWALLOWED: Immediately call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of water. Specific treatments see this container label or section 4 of this SDS. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep

comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention. Protect from sunlight.

California Prop. 65: WARNING: This product contains chemical(s) known to the State of California to cause cancer or

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of our knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and NO WARRANTIES OF ANY TYPE, EXPRESSED OR IMPLIED, ARE PROVIDED INCLUDING THE WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties

Do not expose to temperatures exceeding 50 °C (122 °F). KEEP OUT OF REACH OF CHILDREN.

must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

reproductive harm.

See last page of this Safety Data Sheet.

Terms & Definitions

Disclaimer

16.3

Page 6 of 6 **ER-002**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/31/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. | Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:			
ACGIH	American Conference on Governmental Industrial Hygienists		
С	Ceiling Limit		
ES	Exposure Standard (Australia)		
IDLH	Immediately Dangerous to Life and Health		
OSHA	U.S. Occupational Safety and Health Administration		
PEL	Permissible Exposure Limit		
STEL	Short-Term Exposure Limit		
TLV	Threshold Limit Value		

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


0	Minimal Hazard		
1	Slight Hazard		
2	2 Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		

TWA Time Weighted Average

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

Α			
В	(EV)		
С		THE STATE OF THE S	
D		The state of the s	
Е			
F		The state of the s	





plash Goggle





Synthetic Apr



Dust Respirate

Full Face Respirator

Dust & Vapor Half-Mask Respirator

Full Face Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE Not Established	
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition	Minimum temperature required to initiate combustion in air with no other				
Temperature	Temperature source of ignition				
LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that wil					
explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will				
explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2 Moderate Hazard			
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
₩	Use No Water		
ОХ	Oxidizer		
TREFOIL	Radioactive		



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals			
	S			
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal			
ppm	Concentration expressed in parts of material per million parts			
TD _{io}	Lowest dose to cause a symptom			
TCLo	Lowest concentration to cause a symptom			
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects			
TC, TC _o , LC _{lo} , & LC _o				
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	Bioconcentration Factor			
TL _m	Median threshold limit			
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	OT U.S. Department of Transportation			
TC	Transport Canada			
EPA	U.S. Environmental Protection Agency			
DSL	Canadian Domestic Substance List			
NOHSC	National Occupational Health and Safety Commission (Australia)			
NDSL	Canadian Non-Domestic Substance List			
PSL	Canadian Priority Substances List			
TSCA	U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			
WGK	Wassergefährdungsklassen (German Water Hazard Class)			
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System			

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	*	(A)		\odot	®		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

1		1	*			×	×
С	E	F	Ν	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond	A Park		\cdot		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment