



PRODUCT SPECIFICATION

Product	Disposable Nitrile Glove, 240mm, 8.0g
Article Reference	ZK80WW
Material	Acrylonitrile Butadiene Copolymer Latex
Color	Bright White
Size	XS / S / M / L / XL
Finishing	Finger-tip Textured, Powder Free, Extended Long Cuff
Applications	Light Industrial, Janitorial, Food Handling, Labs, Cleanrooms
Packaging	100 pieces of gloves in a dispenser box / <i>double sealed bags (cleanroom)</i>
Storage Condition	Store in a cool and dry place <30°C
Shelf Life	3 years
Grade	Available in AQL 1.5 / AQL 4.0

PHYSICAL DIMENSION & SPECIFICATIONS

Item: ZK80WW	XS	S	M	L	XL
Hand Size	6	7	8	9	10
Width	75±5mm	85±5mm	95±5mm	105±5mm	115±5mm
Glove Length	300mm (min)	300mm (min)	300mm (min)	300mm (min)	300mm (min)
Cuff Thickness	0.08±0.02mm	0.08±0.02mm	0.08±0.02mm	0.08±0.02mm	0.08±0.02mm
Palm Thickness	0.13±0.02mm	0.13±0.02mm	0.13±0.02mm	0.13±0.02mm	0.13±0.02mm
Finger Thickness	0.19±0.02mm	0.19±0.02mm	0.19±0.02mm	0.19±0.02mm	0.19±0.02mm
Weight	6.8g ±0.2g	7.2g ±0.2g	8.0g ±0.2g	8.5g ±0.2g	9.0g ±0.2g

TECHNICAL SPECIFICATIONS

	Standard	Before Ageing	After Ageing
Force at Break (N)	EN 455-2	min. 6N	min. 6N
Tensile Strength (Mpa)	ASTM D6319	min.14	min.14
Elongation (%)	ASTM D6319	500	400

HARMONIZED STANDARDS

ASTM D6319, ASTM D6124, EN455 1-4, EN420:2003 + A1:2009, EN 1186, EN 374 1-5, EN 16523-1
ISO 10993- 1:2018;5:2009; 10:2013, ISO 15223-1:2016, ISO 1041:2008 + A1:2013, ISO 16604:2004,
ISO 3071:2020, ISO 13485:2016, ISO 9001:2015, FDA 21 CFR 177.2600

ORDERING INFORMATION

Size	XS (5.5-6)	S (6.5-7)	M (7.5-8)	L(8.5-9)	XL(9.5-10)
Code	ZK80WW - XS	ZK80WW - S	ZK80WW - M	ZK80WW - L	ZK80WW - XL

MANUFACTURED FOR: ZENK PRIVATE LIMITED

ADDRESS: Tullymore, Churchill F94 D7D6

County: Donegal, Ireland

CONTACT: +353 89 974 0957

EMAIL: info@zenkgroup.com

