



A Steel fixing set in concrete (or similar solid foundations/hardstanding) to manufactures specification, which allows both the wheel and frame to be locked securely.

7FT X 5FT TONGUE AND GROOVE TIMBER SHED. DIP TREATED SOFTWOOD. STERLING BOARD ROOF AND FLOOR. 2 PERPEX WINDOWS. SHED TO HAVE A MINIMUM INTERNAL STORAGE AREA OF 2.5M2. WHEN PROVIDING CYCLE STORAGE IN A SHED A MINIMUM OF 1SQM IS REQUIRED FOR GARDEN TOOLS. SHED TO BE SET ON CONCRETE BASE WITH A STEEL FIXING FOR A BIKE TO SECURE BOTH WHEEL AND FRAME. TO HAVE SECURE LOCK TO BS3621:2004.

REV.	DESCRIPTION	DATE
CLIENT Obsidian Developments		
JOB TITLE St Clears, Camarthen.		
DRAWING TITLE Timber Shed Detail		
SCALE @ A3 1:25	DATE October '21	DRAWN BY PC
JOB NO. 2128	DRAWING NO. SHED-01	REVISION -



10 Gold Tops
Newport
NP20 4PH

t. 01633 844970
e. info@hammond-ltd.co.uk