

## Quotation

## ZUMTOBEL Group

ZG Lighting (UK) Limited  
Durhamgate  
Spennymoor  
County Durham DL16 6HL  
Tel: 0191 365 2222

**Blaenau Gwent County Borough Council**  
**Community Services**  
**The Energy Centre**  
**Lime Avenue**  
**Ebbw Vale NP23 6GL**  
**Attention Mr. Jac Sargent**

Sales person: John Gibbs  
Tel.: 07785248626  
E-mail: john.gibbs@zumobelgroup.com

Date: 19.04.2023  
Page: 1/7

**Project:** 0002283428 Llantarnam 3G Pitch New Build Works Cwmbran,  
Cwmbran  
**Quotation:** 25714845  
**Subject:** REV2 Subject To Approval  
**Customer no.:** 65373451

Dear Mr. Sargent,

We thank you for your valued enquiry and have pleasure in enclosing our formal quotation for the above project. The prices shown on this quotation are net and supersede all previous versions and revisions.

The prices quoted are for quantities as derived from your enquiry and are subject to ZG Lighting Limited Conditions of Sale which are included with this quotation, can be supplied on request, or can be found on our website. It is the responsibility of the recipient to ensure the quoted luminaire types and quantities comply with the specification requirements including all elements of ceiling integration.

This quotation remains open to an offer for purchase. Quantity amendments or orders in part may result in unit price increases at the discretion of ZG Lighting Ltd.

This quotation is valid until 19.05.2023 and any orders placed with reference to it after this date may be subject to review and change of pricing at our discretion. The quotation is based upon manufacture and delivery to a mutually agreed programme that will accompany any potential order. We reserve the right to charge for multiple deliveries or express shipments. In order to keep post procurement costs and complexity to a minimum and prevent any potential delays towards the end of a project, we strongly recommend ordering a contingency pack of additional luminaires and spares to be placed at the time of the original order, as additional later orders may incur higher prices. Please contact our quotations department for further details.

Lead times for projects are available upon request from our Customer Services Team. As we have a large stockholding we suggest you contact us prior to order placement to confirm our best available delivery.

Please refer to appendix for additional information on Return of Products.


We trust our quotation will be acceptable, however should you require any further information please do not hesitate to contact us.




Yours faithfully for and on behalf of ZG Lighting Limited





The Quotations Team


Project: 0002283428 Llantarnam 3G Pitch New Build Works Cwmbran, Cwmbran

Net quotation: All prices are in GBP

Item no.	Description	Article no	Qty.	Unit price GBP	Total GBP
Notes	Please Check Quantities & Types				
Notes	All Columns & Brackets By Others				
Notes	Photocells & Time Clocks By Others				
Notes	IP65 Enclosures By Others				
Notes	1 x Days Commissioning Included				
Notes	Controls Mounted in Feeder Pillar				
Notes	Controls can be developed further if req				
	<b>IP 48L35-740 EWS BP 3550 CL1 M42 GY-S</b>	92905133	18	214.12	<b>3,854.16</b>
	<p>A state of the art LED road lighting lantern (medium) with 48 LEDs driven at 350mA with Extra Wide Street optic. Programmable LED driver. Class I electrical, IP66, IK09. Housing: die-cast aluminium (EN AC-44300), powder coated textured light grey 150 (close to RAL9006). Spigot: die-cast aluminium (EN AC-44300), unpainted. Enclosure: 5mm thick glass. Fixings: stainless steel. Supplied with Ø42mm spigot adaptor which can be fitted for post-top (0°/5°/10°/15°/20° tilt) or side-entry (-15°/-10°/-5°/0°/5°/10°/15° tilt). Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. Complete with 4000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.</p> <p>Dimensions: 718 x 224 x 114 mm Luminaire input power: 50 W Luminaire luminous flux: 7970 lm Luminaire efficacy: 159 lm/W Weight: 7.4 kg Scx: 0.066 m<sup>2</sup></p> <p>Material group: ME - Specifier Ranges <a href="http://www.thornlighting.co.uk/92905133">http://www.thornlighting.co.uk/92905133</a></p>				

Item no.	Description	Article no	Qty.	Unit price GBP	Total GBP
<b>76mm</b>	<b>ISARO PRO SPIGOT D76 M76 GY</b>	59010561	18	15.90	<b>286.20</b>
	External Ø76mm spigot for Road Lighting.  Material group: ME - Specifier Ranges				
<b>Floods</b>	<b>ALG4 432L120-740 PTR AI6AI6AI6 ANT</b>	96678659	24	1,569.88	<b>37,677.12</b>
	A high powered LED floodlight with asymmetrical 60° intense light distribution from 432 LEDs. External control gear (maximum driving current 1200mA) and wiring with H07 RN-F cable type with mini diameter 13mm, to be ordered separately. Class I electrical, IP66,IK08. Heatsink: die-cast aluminium powder coated dark sandy grey (close to RAL 7043). Mounting bracket and frame: dark sandy grey (close to RAL 7043). Cover: 4mm clear glass. Bracket mounted using fixation points available (one M20 screw or two M14 screws). Lowflicker operation (<1%) suitable for HDTV broadcasting. Complete with 4000K LED with Colour Rendering Index min.: 70.  Due to the unique calculation requirements of this product the photometric data is not provided here but design advice may be obtained from your local representative.  Dimensions: 530 x 757 x 685 mm  Weight: 30.11 kg Scx: 0.14m² at 0°  Material group: ME - Specifier Ranges <a href="http://www.thornlighting.co.uk/96678659">http://www.thornlighting.co.uk/96678659</a>				
<b>Driver</b>	<b>ALG4 GB 1750W 1.20A 520V 3CH HV DA</b>	96670169	24	749.89	<b>17,997.36</b>
	Class I, 1539W constant current DALI 2 programmable gearbox, with 3 independant output channels and IP66 enclosure, for TV broadcasting applications. Suitable for dedicated 432 LED Altis floodlight, to be installed remotely up to 200m from the floodlight. Nominal input voltage: 250-440, with stand-by mode, output current 1200mA with DALI 2 configurable single-channel, IEEE 1789 flicker recommended practice compliant suitable for super slow motion camera filming, surge level 10kV for both common mode and differential.  Connection from mains via terminal blocks. Mains supply must be fused according to local safety regulations.  Weight: 6.1 kg  Material group: ME - Specifier Ranges <a href="http://www.thornlighting.co.uk/96670169">http://www.thornlighting.co.uk/96670169</a>				
	<b>ALTIS G4G5 GB BRACKET 3BRICK STIRRUP ANT</b>	96671490	24	51.22	<b>1,229.28</b>

Item no.	Description	Article no	Qty.	Unit price GBP	Total GBP
	<p>2x brackets which allow the gearbox to be fixed onto the stirrup of the Altis floodlight 432L and 288L not "LB" version, only for post-top installation. Painted dark sandy grey (close to RAL 7043).</p> <p>It is NOT compatible with ALTIS LED 144L and 288L LB.</p> <p>Material group: ME - Specifier Ranges</p>				
<b>Visor</b>	<b>ALTIS G4G5 1 BRICK AJ VISOR</b>	96671498	72	123.90	<b>8,920.80</b>
	<p>Visor kit for 1 Altis LED module, to add and adjust a light distribution cut-off. Cut-off angle adjustable from 0° to 70°. Cut-off length adjustable from 0 to 70mm. Can be installed before or after installation on site. Finished black (close to RAL9005).</p> <p>Design advice can be obtained from your local representative.</p> <p>Material group: ME - Specifier Ranges <a href="http://www.thornlighting.co.uk/96671498">http://www.thornlighting.co.uk/96671498</a></p>				
<b>LITECOM</b>	<b>LITECOM CCD DALI-2</b>	22171127	1	933.45	<b>933.45</b>
	<p>Central DALI-2 certified automation controller for controlling up to 250 actuators to automate lighting and for the manual control of blinds and windows according to the time of day, maintenance interval, room occupancy or amount of daylight. New addressing and readdressing of all control units as well as total system configuration possible via web screens. Operation possible via tablets and smart phones.</p> <p>Dimming range 1 to 100%; actuator error feedback available; special LUXMATE DALI sensors and control units can be additionally connected to the DALI control lines With non-supplied LM bus output for the integration of Luxmate devices as well as 3 DALI lines with integrated power supplies for up to 100 DALI loads per DALI line, 1 TCP/IP Ethernet RJ45 and plug-in/screw terminals for the 230V AC supply.</p> <p>Supported IEC 62386 (DALI-2) parts regarding input devices: 101/103/301/303/304</p> <p>Automation controller housed in compact enclosure without rotating parts for installing on 35mm DIN rails; permitted ambient temperature range: 0...50°C; Dimensions: 160 x 91 x 62 mm, 9 HP of 17.5 mm each; weight: 0.6 kg</p> <p>Material group: NM - Zumtobel <a href="http://www.zumtobel.co.uk/22171127">http://www.zumtobel.co.uk/22171127</a></p>				
<b>4-Way</b>	<b>DALI XC G3 CWM 30 DA2</b>	28002877	1	99.85	<b>99.85</b>
	<p>DALI-2 certified push-button input module for use with DIMLITE pro and DALI-2 certified application controllers. Integration for up to 4 conventional light switches for e.g. switching, dimming, calling scenes and changing the colour temperature of the luminaires.</p> <p>Degree of protection: IP20 Size: 47.7 x 28.2 x 14.6 (L x W x H, in mm) Weight: 0.09 kg</p> <p>Material group: NM - Zumtobel</p>				

Item no.	Description	Article no	Qty.	Unit price GBP	Total GBP
	<a href="http://www.zumtobel.co.uk/28002877">http://www.zumtobel.co.uk/28002877</a>				
<b>Commission</b>	<b>COMMISSIONING DAY</b>	80005331	1	849.00	<b>849.00</b>
	Daily rate for commissioning, including the flat travel charge. Travel time is calculated according to expenditure for projects at further distances. Possible auxiliary equipment such as work platforms must be provided by the customer or are invoiced separately.  Material group: NM - Zumtobel  <b>Product guarantees are in accordance with our terms at <a href="http://www.zumtobel.com/guarantee">www.zumtobel.com/guarantee</a></b>				
		<b>Value of goods</b>			<b>71,847.22</b>
		<b>Special Surcharge</b>			<b>2,101.94</b>
		<b>Total without VAT</b>			<b>73,949.16</b>

\*\*\*\*\*  
**Logistics surcharge due to constantly rising logistics costs. For questions please contact your customer service.**  
 \*\*\*\*\*

Sales person  
John Gibbs  
07785248626

Blaenau Gwent County Borough Council  
Community Services  
The Energy Centre  
Lime Avenue  
Ebbw Vale NP23 6GL

**ZUMTOBEL Group**

Quotation: 25714845  
Date: 19.04.2023

**Project: 0002283428 Llantarnam 3G Pitch New Build Works Cwmbran, Cwmbran**

**Summary of costs**

Article no	Description	Unit price	Qty.	Value
92905133	IP 48L35-740 EWS BP 3550 CL1 M42 GY-S	214.12	18	3,969.78
59010561	ISARO PRO SPIGOT D76 M76 GY	15.90	18	294.79
96678659	ALG4 432L120-740 PTR AI6AI6AI6 ANT	1,569.88	24	38,807.43
96670169	ALG4 GB 1750W 1.20A 520V 3CH HV DA	749.89	24	18,537.28
96671490	ALTIS G4G5 GB BRACKET 3BRICK STIRRUP AN	51.22	24	1,266.16
96671498	ALTIS G4G5 1 BRICK AJ VISOR	123.90	72	9,188.42
22171127	LITECOM CCD DALI-2	933.45	1	933.45
28002877	DALI XC G3 CWM 30 DA2	99.85	1	102.85
80005331	COMMISSIONING DAY	849.00	1	849.00
<b>Total without VAT</b>				<b>73,949.16</b>

Returns Policy

<http://www.thornlighting.co.uk/en-gb/about-us/return-policy>

<https://www.zumtobel.com/gb-en/returns-policy.html>

Nominated Charity 2022



Sustainability Award

