

# eArc

## SMD310M-6X10DW

# 310 Watt

## 60 Cell Monocrystalline Module



**Ultra-light:** Glass free module weighs 5.8 kg, 70% lighter than conventional glass modules.



**Fast-Installation:** Through "Quick-Bonding" installation, eArc requires no penetration, reduces time on roof by 40% and eliminates the use of mounting hardware.



**Aesthetic:** Seamless integration with underlying installation surface.



**Durable:** eArc is the first glassless module to pass the same durability tests as conventional glass modules, including IEC 61215:2016, IEC61730:2016 and UL1703 (USA). eArc has also passed PID, salt mist and ammonia corrosion tests.

POWER OUTPUT RANGE 305~310 W

POWER TOLERANCE 0-5 W

**10 Year Product Warranty**

**25 Year Linear Power Warranty**




[www.sunman-energy.com](http://www.sunman-energy.com)


### LINEAR PERFORMANCE WARRANTY

CAUTION: Read installation manual before using the product.


©2020 Sunman (zhenjiang) Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.



## DIMENSIONS




## I-V CURVE (310)



## TEMPERATURE CHARACTERISTICS

Nominal Module Operating Temperature(NOMT)	<b>41±2 °C</b>
Temperature Coefficient of $P_{max}$	<b>-0.38 %/°C</b>
Temperature Coefficient of $V_{oc}$	<b>-0.28 %/°C</b>
Temperature Coefficient of $I_{sc}$	<b>0.020 %/°C</b>



SMDDW/IEC EN 2020B

## ELECTRICAL CHARACTERISTICS

STC	SMD305M-6X10DW	SMD310M-6X10DW
Maximum Power ( $P_{max}$ )	305	310
Maximum Power Voltage ( $V_{mp}$ )	33.0	33.3
Maximum Power Current ( $I_{mp}$ )	9.25	9.31
Open-circuit Voltage ( $V_{oc}$ )	40.3	40.5
Short-circuit Current ( $I_{sc}$ )	9.74	9.81
Module Efficiency (%)	17.6	17.9
Operating Temperature	-40 °C to 85 °C	
Maximum System Voltage	1000 V DC (IEC)	
Maximum Series Fuse Rating	20 A	
Application Class	Class A	
Power Tolerance	0/+5 W	

STC: Irradiance 1000W/m<sup>2</sup>, Cell temperature 25°C, AM=1.5. Tolerances of  $P_{max}$ ,  $V_{oc}$  and  $I_{sc}$  are within ±5%

NMOT	SMD305M-6X10DW	SMD310M-6X10DW
Maximum Power ( $P_{max}$ )	229	233
Maximum Power Voltage ( $V_{mp}$ )	30.5	30.7
Maximum Power Current ( $I_{mp}$ )	7.51	7.59
Open-circuit Voltage ( $V_{oc}$ )	37.4	37.6
Short-circuit Current ( $I_{sc}$ )	7.96	8.04

NMOT: Irradiance 800W/m<sup>2</sup>, Ambient temperature 20°C, AM=1.5, Wind speed 1 m/s.

## MECHANICAL CHARACTERISTICS

Solar Cell	Monocrystalline silicon (158.75mm)
No. of Cells	60 (6×10)
Module Dimensions	1682×1029×5.6 mm
Weight	5.8kg
Backsheet	White
Frame	Black Anodized Aluminium Alloy
J-box	IP 68 rated
Output Cables	Photovoltaic technology cable 4.0 mm 2, (+)150 / (-)450 mm
Connector	MC4 compatible

## PACKAGING CONFIGURATION

	20' GP	40' HC
Module per pallet	30+50	50
Pieces per container	480	1200