

TH-200 O2 dispenser (general type) Automatically feeds and cuts Oxygen Absorbents from a continuous strip wound on a Reel or Belt. Fully adjustable from 20cc up to 500cc oxygen absorber. The configuration is easily set up through a Color Touch Screen and Complete Access with a Full View of the Feeding Process. A Portable Adjustable Supporting Base that provides Easy mounting over or Alongside a Production Line is available. The unit can be a master or slave to an existing line. A photoelectric sensor will trigger when to dispense and will stop cutting if detecting possible false cuts to eliminate the danger of opening the sachet into production.

The table below shows some technical specifications of the machine:

MODEL TH-200CE	GENERAL TYPE
Cutting rates (max.)	100 cuts per minute for a 45 mm pouch
Min web width	30 mm / 1.2 in.
Max web width	50 mm / 2 in.
Min. packet length	35 mm / 1.4 in.
Max packet length	85 mm / 3.3 in.
Max web thickness	10 mm / 0.39 in.
Machine dimension ⁽¹⁾ (L x W x H)	830 x 600 x 504 (mm) / 32.7 x 23.6 x 19.8 (in.)
Machine weight	80 -100kgs / 176-220 lbs.
Power consumption	600 w
Power supply	AC 110V 60Hz (Optional 220v 60HZ)
Operating environment	Indoor temperature: 0°C~40°C, without condensate
Materials	Stainless steel and aluminum alloy
Interface language	English
Critical components	PLC Interface screen The servo motor and controller Photoelectric sensor switching device
Alarm system	Alarm lamp and buzzer alarm
Delivery Time	7-10 Days
FOB	San Bernardino, CA 92408
Payment Terms	50% down and balance, 30 days after delivery.



Additional Features:

- Open Exit Chute for versatility and it's Virtually Jam Free
- Color Touch Screen for Easy Operator Setup
- Cantilever Design offers Complete Access and a Full View of the Feeding Process
- Portable Adjustable Height Stand*
- Easy to Mount over or Alongside a Production Line with a Holding Stand for Rolls or Belts
- A sensor to prevent false cuts that may cause a sachet to open and contaminate the production line.
- This unit can be a master or a slave to an existing line. A sensor will trigger when to dispense or can receive a cutting signal from your packing machine.

***Note: A supporting frame supplied with the machine will allow the adjustment of height between 700-1000 mm.**

