



AABBITT®
ADHESIVES, INC.

2403 N. OAKLEY AVENUE • CHICAGO, ILLINOIS 60647 • 773-227-2700

FAX • 773-227-2103

INFO@AABBITT®.COM

PRODUCT SPECIFICATION

852-320-G5

REMOISTENABLE DOWEL ADHESIVE (GREEN)

User must preapprove and prequalify adhesion quality as well as the long-term functionality of product 852-320-G5 before embarking on mass production.

To prevent adhesion failure in the winter months, freshly glued dowels it is mandatory to store immediately in a heated warehouse (65° to 100°F) for a minimum 5 hours before shipped to end user destination in a non-heated trailer. Failure to adhere to this guideline, it will result in a wooden dowel questionable adhesion.

PHYSICAL PROPERTIES:

METHOD OF APPLICATION:	Spray
BASE:	Modified Polyvinyl Acetate Resin Emulsion
COLOR:	Green
ODOR:	Typical sweet when wet, none when dry
SOLVENT:	Water-based
SHELF LIFE:	90 Days
ADHESION:	Excellent to approved surfaces
VISCOSITY:	550-750 cps
GRAVIMETRIC SOLIDS:	45-48%
WATER RESISTANCE:	None
PH:	4.0-6.0
CLEAN UP:	Use warm water
ASH:	None
WEIGHT/GALLON:	8.8-9.0 pounds per gallon

Aabbitt® Adhesives, Inc. cannot, however, undertake to guarantee the quality of finished products incorporating this material.

All components of product 852-320-G5 conform to the following F.D.A. regulations subject to the extraction limitations thereof:

C.F.R. Section 175.105 "Adhesives", logistic support packaging for food, excluding inks.

Storage:

Do not mix with other adhesives. Keep container sealed. Store away from direct sunlight or extreme cold air stream. Store at temperatures between 60-100°F. Rotate material first in, first out. Material solids will settle after prolonged standing For uniform results, stir well before use.

Freeze-Thaw Stability:

Yes:___ NO___ Cycles:___


**AABBITT®
ADHESIVES, INC.**

 2403 N. OAKLEY AVENUE • CHICAGO, ILLINOIS 60647 • 773-227-2700
 FAX • 773-227-2103
 info@aabbitt.com

Safety Data Sheet

852-320-G5**Remoistenable Dowel Adhesive (Green)****SECTION 1: PRODUCT AND COMPANY INFORMATION**

Manufacturer Aabbitt Adhesives, Inc. 2403 N Oakley Ave, Chicago, IL 60647
 1-800-AABBITT® (773) 227-2700 info@aabbitt.com www.aabbitt.com/
Chemical Family Polyrinyl Acetate Resin Emulsion
Trade Name Remoistenable Dowel Adhesive (Green)
Product ID 852-320-G5
Recommended Uses Remoistenable Dowel Adhesive (Green)

SECTION 2: HAZARD IDENTIFICATION

Classification: Not classified as hazardous according to 29 CFR 1910.1200 (2012)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Components: None classified as hazardous according to 29 CFR 1910.1200 (2012)

SECTION 4: FIRST AID MEASURES

Skin Contact: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Thoroughly clean clothing and shoes before reuse.

Eye Contact: If in eyes: Flush eyes with water for 15 minutes lifting upper and lower lids occasionally. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs and persists: Get medical advice/attention.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, Move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Ingestion: If swallowed seek immediate medical attention. Do not induce vomiting unless recommended by physician. If spontaneous vomiting occurs, keep head below hips to avoid aspiration (into lungs).

Delayed or Other Symptoms and Health Effects: Not Classified.

SECTION 5: FIREFIGHTING MEASURES

Basic Firefighting Procedures: Material will not burn. Use Extinguishing Media suitable to surrounding fire. Exposed firefighters should wear MSHA/NIOSH approved self-contained breathing apparatus with full-face mask and full protective equipment if product breakage with dust generation occurs.

Unusual Fire and Explosion Hazards: None known.

SECTION 6: ACCIDENTAL RELEASE MEASURES**Refer to Section 8: Exposure Control and Personal Protection**

Spill Management: Stop leak. Ventilate area and avoid breathing vapor or mist. For large spills, dike far ahead of liquid spill for later disposal. Contain away from surface waters and sewers. Absorb with compatible absorbent material and shovel into closable container for disposal. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Notification: Any spill or release to navigable water that causes a visible sheen upon the water must be reported immediately to the National Response Center (800/424-8802), as required by U.S. federal law.

SECTION 7: HANDLING AND STORAGE**Refer to Section 8: Exposure Control and Personal Protection**

Precautionary Measures: Use in well-ventilated area and avoid breathing vapor or mist.

General Handling Information: Use good personal hygiene. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco products. Clean contaminated clothing, shoes and protective equipment before reuse. Discard contaminated clothing, shoes or protective equipment if they cannot be thoroughly cleaned.

Container Warnings: Keep container tightly closed when not in use and during transport. Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous.

Storage: Store at room temperature, keep from freezing. Keep container sealed and free from dirt.

Other Precautions: Keep out of reach of children

SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

Engineering Controls: Use good ventilation. Local exhaust is acceptable.

Eye, Face and Skin Protection: Use safety glasses with eye guards. Use of rubber gloves is recommended.

Inhalation: Negligible hazard at ambient temperature. Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract. Use NIOSH/MSHA-approved respiratory protective equipment when concentration of vapor or mist is present.

Ingestion: No hazard in normal industrial use.

Other Protective Equipment: Not required.

Safety Data Sheet: 852-320-G5 Remoistenable Dowel Adhesive (Green)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State	Liquid, off white when wet, off white when dry.
Specific Gravity	1.08-1.13
pH	4.0-6.0
Solubility in Water	Miscible
Odor	Typical sweet when wet, odorless when dry.
Odor Threshold	Not Determined
Melting/Freezing Point	Not Determined
Boiling Range	Not Determined
Initial Boiling Point	>212°F
Flash Point (Setaflash Closed Tester)	Not Applicable
Upper/Lower Flammability Limits	Not Applicable
Auto Ignition Temperature	Not Determined
Decomposition Temperature	Not Determined
Vapor Pressure	As Water
Vapor Density	As Water
Partition Coefficient	Not Determined
Viscosity	550-750 cps
Supplemental Information:	
Evaporation Rate:	Not Applicable
Percent Volatility by Weight	52-55%

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Material is stable under normal conditions.

Stability/Incompatibility/ Conditions to Avoid: None known.

Hazardous Reactions/Decomposition Products: Thermal decomposition may produce oxides of carbon.

NFPA Reactivity Hazard Class: 0 (Insignificant)

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes and skin contact, inhalation.

Acute Effects: Eyes: Contact may produce mild eye irritation and redness. Skin: Contact may produce mild skin irritation. No significant skin absorption hazard. Inhalation (Breathing): High concentration of vapor or mist may be irritating to the respiratory tract. Ingestion (Swallowing): Low order of acute oral toxicity. May cause irritation of gastrointestinal tract.

Chronic Effects: Prolonged or repeated skin contact may cause drying or dermatitis. Any acute symptoms may be aggravated. Individuals with pre-existing lung or disorders may have increased susceptibility to the effects of exposure.

Symptoms: May include redness, drying, cracking of the skin, gastrointestinal and respiratory discomfort. Refer to Sections 2 and 4 for recommended actions.

Carcinogenicity: No components of this product are found to be carcinogens by NTP, IARC or OSHA.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

Persistence and Biodegradability: Not available.

Bioaccumulative Potential: Not available.

Mobility in Soil: Not Determined.

SECTION 13: DISPOSAL CONSIDERATION

EMPTY CONTAINER WARNINGS: Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

WASTE DISPOSAL METHODS: Waste disposal should be in accordance with existing federal, state, and local environmental regulations. Use material for its intended purpose or recycle if possible. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: Not regulated

DOT CLASS: Not regulated

DOT ID NUMBER: Not regulated

TDG CLASSIFICATION: Not regulated

Safety Data Sheet: 852-320-G5 Remoistenable Dowel Adhesive (Green)

SECTION 15: REGULATORY INFORMATION

SARA TITLE III: Product does not contain toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372

EPCRA 311/312 CATEGORIES: None

CHEMICAL INVENTORIES: All components comply with the following chemical inventory requirements: DSL (Canada), TSCA (United States).

State Right to Know: Not Listed

California Proposition 65: Not Listed

Canadian Regulatory Information: Canada DSL/NDSL Inventory: This product and/or its components are listed either on the domestic Substances List (DSL) or are exempt.

HMIS Health – 0 Flammability – 0 Reactivity -0 Personal Protection – B

SECTION 16: OTHER INFORMATION

Disclaimer: The information given and the recommendations made herein are based on our research and are believed to be accurate but no guaranty of their accuracy is made. In every case we urge and recommend that purchasers before using any product in full scale production make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the non-existence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.