



**Toyota Hilux/ Revo 2005-Present
Runflat Specifications
Assembly PN# HLXRF-DT**

Web: www.dimensiontek.com

Tel.: 614-638-2854

E-mail : info@dimensiontek.com

406 E Johnstown Rd. Gahanna, OH 43230

Cage: 7HX48

Runflat Assembly Components

- ❑ 16" Runflat, FINABEL 20.A.5
- ❑ 16"x 8", One Piece Steel Wheel, ISO/DOT
- ❑ LT245/75R16 120Q All-Terrain Tire , DOT

Runflat Assembly Specifications

Runflat Specification Met: 16"

- FINABEL 20.A.5, travel a total distance of 31mi/50km on the road (desirable: 46mi/75km), without tires coming off rims or starting to burn, and without its properties of steering maneuverability, stability or speed being seriously affected under the following conditions:
- - 2mi/3km at maximum speed (escape speed),
- - 6mi/10km at uniform speed of 31mph/50km/h,
- - The rest of the distance at a uniform speed of 16mph/25km/h
- - Runflat rated: 3417lbs./1550kgs



Runflat Assembly Specifications

Wheel Specifications:

- 16"x8" Six Lug Toyota Style One Piece Steel Wheel.
- DOT Approved, Conforming to ISO MFG. standards.
- Rated to 3417lbs./1550kgs



Runflat Assembly Specifications

Tire Specifications:

- Kenda Klever All-Terrain Tire - LT245/75R16 120Q
- Approval: DOT
- Ply: 10
- Load Rating: 120 3086lbs./1400kg
- Speed Rating: Q 99 mph 160 km/h
- Optional BFG KO2 LT255/70R16



Runflat Assembly Specifications

Assembly Estimated Size/Weight Each

- Size: 30.5"x 9.6" / 774mm x 244mm
- Weight: 92lbs./42kg



Dimension**tek**

Web: www.dimensiontek.com

Tel.: 614-638-2854

E-mail: info@dimensiontek.com

406 E Johnstown Rd. Gahanna, OH 43230

Cage: 7HX48