

**AUTOMATED CHEMICAL SOLUTIONS** 

**Chemicals and Controllers for PWB Fabrication** 

# **Product Overview**

## **AUTOtreat MP-9230**

**Metal Precipitant** 

### **Product Description**

AUTOtreat MP-9230 is a calcium polysulfide based waste treatment additive for precipitating metal ions. MP-9230 provides a safe, cost effective means for removing heavy metals from chelated and non-chelated waste streams. MP-9230 can be used in batch or continuous treatment processes and will reduce most heavy metal concentrations to below 0.10 ppm. MP-9230 forms a chemically stable sludge that settles rapidly and dewaters easily.

#### **Physical Properties**

Specific gravity:	1.17
pH:	11-13
Appearance:	clear, yellow-green to amber liquid
Flash point:	> 200 °F

#### **Operating Parameters**

MP-9230 can be used in either batch or continuous treatment applications. Adjust waste stream to a pH of 4 – 5 for chelated waste streams or 6 – 8 for non-chelated streams prior to adding MP-9230. Addition rates can be controlled through monitoring waste stream ORP or through empirical determination. When using ORP to control additions, the setpoint will typically be between 0 and –50 mV. The required setpoint will vary with each application and on-site testing is always recommended. The use of an anionic polymer flocculent, such as AUTOtreat PF-9310, will increase settling rates and enhance dewatering of the sludge.

#### Safety

Avoid contact with eyes, skin and clothing. Wear chemical handler's gloves, goggles and protective clothing when handling. Read and understand Material Safety Data Sheet before using this product.

#### Notice

The information and recommendations of Automated Chemical Solutions, Inc., and its representatives, regarding this product are, to the best of our knowledge, true and accurate. We make no guarantee of results because the conditions of actual use are beyond our control. We assume no liability for damages or penalties resulting from the use of this product or following our recommendations. Our recommendations and suggestions for use of this product are not intended to grant license to operate under or infringe any patent.