



# JET-X<sup>®</sup> SUBLIMATION TRANSFER PAPER

JET-X® papers are designed to work optimal with all different types of water based sublimation inks, irrespective of the glycol content. Due to its base paper structure and unique coating JET-X® will give you optimal colours and a perfect runnability on printer and calander.



Worldwide availability



Premium quality



Cost efficient solution



Your sustainable partner

## JET-X<sup>®</sup> SPECIFICATION



### GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for industrial and plotter printers using water-based sublimation inks.

#### **RECOMMENDED PRINT ROOM SETTINGS**

- Ideal printing room temperature is 23°C and 50% relative humidity.
- Maintaining ideal printing room climatic conditions for good dimensional stability, flatness of paper and faster ink drying.

#### **RECOMMENDED TRANSFER SETTINGS**



Temperature: 195-205°C Time: 25-40 seconds

Ideal settings might vary depending on the process, print environment and textiles.

## AVAILABILITY

ТҮРЕ	WIDTH		LENGTH		DIAMETER	
	MM	INCH	М	FT	MM	INCH
plotter	1118	44	200	656	165	6,5
plotter	1320	52	200	656	165	6,5
plotter	1620	64	200	656	165	6,5
plotter	1900	75	200	656	165	6,5
plotter	2570	101	200	656	165	6,5
plotter	3200	126	300	984	190	7,5
mini jumbo	1620	64	500	1640	250	10
mini jumbo	1620	64	1000	3280	350	14
mini jumbo	1620	64	1500	4921	400	16
mini jumbo	1620	64	2000	6562	450	18
mini jumbo	1620	64	2500	8202	500	19.5
mini jumbo	1800	71	2500	8202	500	19.5
mini jumbo	3200	126	1000	3280	350	14
mini jumbo	3200	126	2000	6562	450	18
jumbo	1620	64	8100	26575	900	35.5
jumbo	1620	64	13800	45276	1110	44
jumbo	1900	75	8100	26575	900	35.5
jumbo	3200	126	5000	16404	700	27,5

Standard Core is 76 mm / 3 inches.

Other sizes or special dimensions are available on request. Anyone interested can contact the licensed agent or Neenah Coldenhove sales representative.

SHELF LIFE	This product is covered with a guarantee of 1 year after receiving the product under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.
STORAGE AND	<ul> <li>Store material in original packaging only.</li> <li>Avoid exposure to direct sunlight and extreme weather conditions.</li> <li>Place the roll to be printed in printing room at least 24 hours prior to printing.</li></ul>
HANDLING	Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable. <li>For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, this may in some cases bend the core bar.</li>



Scan the QR code for instructional video or go to the link **www.neenahcoldenhove.com** 

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and pressed with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Neenah Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.



## SUSTAINABILITY



Thanks to our inhouse water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Currently all energy required by the factory comes out of energy released during the production of paper. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

### CERTIFICATIONS



ISO 9001 ISO 14001 BUREAU VERITAS Certification