## SYNTHETIC SHACKLE

## Lockaw

- Stronger than steel yet extremely light
- Wraps around most anchor points
- Lock keeps shackle securely closed





LockJaw® Synthetic Lifting Shackle is the most advanced shackle for your industrial applications. Made from high strength synthetic fibers, LockJaw is as strong as steel shackles but vastly lighter. Its flexible shapeprovides greater versatility than any shackle in the marketplace. LockJaw easily wraps around all kinds of anchor points. The synthetic fibers create less damage while working around delicate components. The fibers are UV, abrasion and will rust resistant. The exclusive lock securely holds the shackle closed when in use. LockJaw's light weight makes it much safer to use and minimizes safety risks. Not rated for lifting. Patent pending. Made in USA



## SYNTHETIC SHACKLE





| LOCKJAW SYNTHETIC SHACKLE SIZES |          |          |                |                    |
|---------------------------------|----------|----------|----------------|--------------------|
| Model #                         | Diameter | Bow With | Product Weight | Working Load (lbs) |
| 15-025004                       | 1/4"     | 4"       | .25 lbs        | 5500               |
| 15-025008                       | 1/4"     | 8"       | .3 lbs         | 5500               |
| 15-031305                       | 5/16"    | 5"       | .3 lbs         | 8800               |
| 15-031310                       | 5/16"    | 10"      | .4 lbs         | 8800               |
| 15-037505                       | 3/8"     | 5"       | .4 lbs         | 11200              |
| 15-037510                       | 3/8"     | 10"      | .5 lbs         | 11200              |
| 15-043805                       | 7/16"    | 5"       | .5 lbs         | 14333              |
| 15-043810                       | 7/16"    | 10"      | .6 lbs         | 14333              |
| 15-050006                       | 1/2"     | 6"       | .8 lbs         | 22000              |
| 15-050012                       | 1/2"     | 12"      | .9 lbs         | 22000              |
| 15-056306                       | 9/16"    | 6"       | 1.1 lbs        | 26667              |
| 15-056312                       | 9/16"    | 12"      | 1.2 lbs        | 26667              |
| 15-062507                       | 5/8"     | 7"       | 1.7 lbs        | 34000              |
| 15-062514                       | 5/8"     | 14"      | 1.8 lbs        | 34000              |