

# Introducing Roam

# Fast, accurate, real-time water testing in the palm of your hand.

#### Water testing done with the push of a button

When we say that Roam<sup>™</sup> is easy to use, we mean it. With the e-sens Roam<sup>™</sup> you can easily...

- Test water without the prep work, just fill the sample vial, insert it into the Roam and it will do the rest.
- Sync with your mobile device's Bluetooth for instant data transmission.
- $\cdot$  Conduct testing in virtually any location or environment.

#### Accuracy is everything

#### If you want testing to be done right, the first time, trust e-sens Roam™ to...

- $\cdot$  Improve testing accuracy through greater user-to-user consistency.
- Generate results from 23 different test parameters in a fraction of the time.
- Provide the central office with greater visibility into what's happening in the field.

#### Cut down on test time and cost

#### We know time and money are important resources. Let Roam<sup>™</sup> save you on both by...

- Eliminating the need for cumbersome reagents and solutions with our simple all-inclusive cartridge.
- Providing multi parameter testing that eliminates the time, cost, and expense of single parameter tests.
- $\cdot$  Uses a recyclable cartridge good for 100 tests (each test measures 23 parameters).

#### Water Quality Data in Real-time

When you want instant access to information, anytime, anywhere, Roam™ delivers by giving you...

- Results that are transmitted to any mobile device and uploaded to your servers for consistent, long-term analytics.
- Instant alerts and notifications in real time with the e-sens mobile app.



Our free mobile app allows you to collect, track and analyze ALL your water quality parameters. Available on iOS or Android. Search: e-sens



# e-sens Roam<sup>™</sup> product specs

## Included in Box:

- e-sens Roam<sup>™</sup>
- USB-C Charging Cable
- Wall charger
- Quick Start Guide

# **Physical Properties:**

- $\cdot\,$  Control button with RGB status indicator
- $\cdot\,$  USB charging port with LED indicator
- $\cdot$  IP66 dust and water resistant
- Sample protecting lid

#### **Other Properties:**

- 1-2 days mixed usage time
- 24.4 Wh (6600 mAh) Li-ion battery
- Supported Operating Systems: iOS, Android
- Bluetooth LE
- $\cdot$  100 tests per cartridge or 30 days of use
- Secure Data uploads

#### \*e-sens also offers a simpler 8-parameter test cartridge.



Proudly distributed in NZ and the Pacific by



Ph: 0800 796 516 Email: sales@connectm2m.co.nz Web: connectm2m.co.nz

	Base	Cartridge	Complete Unit
Material	Aluminum	Plastic	
Height	17/8 in	2 5/8 in	2 5/8 in
Width	3 3/4 in	3 3/4 in	3 3/4 in
Length	6 1/2 in	5 1/2 in	10 in
Weight	1 lb. 10 oz.	12 oz.	2 lb. 6 oz.
Color	Silver	White	

## Measured Chemical Parameters:

Parameter	Operating Range	Accuracy (Whichever is greater)		MDL
*pH	5.00 - 11.00	+/- 0.1 pH	n/a	n/a
*ORP	-1000 - 2000 mV	+/- 10%	n/a	n/a
*Conductivity	50 - 2500 µS/cm	+/- 10%	+/- 20 µS/cm	50 µS/cm
*Total Dissolved Solids	25 - 1250 mg/L	+/- 10%	+/- 10 mg/L	25 mg/L
*Free Chlorine	0.05 - 5.00 mg/L	+/- 10%	+/- 0.10 mg/L	0.05 mg/L
*Monochloramine	0.05 - 5.00 mg/L	+/- 10%	+/- 0.10 mg/L	0.05 mg/L
*Total Chlorine	0.05 - 5.00 mg/L	+/- 10%	+/- 0.10 mg/L	0.05 mg/L
Ammonium	0.05 - 5.00 mg/L	+/- 10%	+/- 0.20 mg/L	0.05 mg/L
Free Ammonia	0.05 - 5.00 mg/L	+/- 10%	+/- 0.20 mg/L	0.05 mg/L
Total Ammonia	0.05 - 5.00 mg/L	+/- 10%	+/- 0.20 mg/L	0.05 mg/L
Chlorine to Ammonia Ratio	0.01 - 100.00 pts	+/- 10%	+/- 0.5 pts	n/a
Nitrification Capacity	0.10 - 10.00	+/- 10%	+/- 5 pts	n/a
Calcium Hardness	5 - 1250 mg/L	+/- 10%	+/- 10 mg/L	5 mg/L
Magnesium Hardness	5 - 1250 mg/L	+/- 10%	+/- 10 mg/L	5 mg/L
Total Hardness	5 - 2000 mg/L	+/- 10%	+/- 10 mg/L	5 mg/L
Ionic Calcium	3 - 500 mg/L	+/- 10%	+/- 5 mg/L	3 mg/L
Ionic Magnesium	3 - 500 mg/L	+/- 10%	+/- 5 mg/L	3 mg/L
*Sample Temperature	2.0 - 45.0	+/- 10 C	+/-1C	2.0 C
Dissolved Carbon Dioxide	0.05 - 50 mg/L	+/- 10%	+/- 1 mg/L	0.05 mg/L
Total Alkalinity	10 - 325 mg/L	+/-10%	+/- 10 mg/L	10 mg/L
Langelier Saturation Index	-10 - 10.00 pts	+/- 10%	n/a	n/a
Ryzner Stability Index	0 - 12.00	+/- 10%	n/a	n/a
Dissolved Inorganic Carbon	1 - 200 mg/L	+/- 10%	+/- 1 mg/L	1 mg/L