

**FLOOD PUMP SERIES – CS 3 / 5**

Model	CS 3	CS 5
* Flow Rate	50-60 GPM	90-100 GPM
Height	52"	
Width	32"	
Depth	24"	
Weight	250 lbs	300 lbs
Input Power	208/230/480 3 Phase 60 Cycle	
Control Power	115 Volt 1 Phase 15 Amp Max	
Primary Pump	3.0 HP	5.0 HP
Full Load Amps	8.5 / 8.0 / 4.0	13.0 / 12.2 / 6.1
Suction Inlet	2" NPT	3" NPT
Filtered Outlet	1.5" NPT	2" NPT

3/5 HP Process Pump  
 Strainer Basket  
 UL Listed Electrical Controls  
 Hydrocyclone 50 Micron Filtration  
 Flow Rates up to 100GPM  
 Stainless and Sch 80 PVC Plumbing  
 Brass Check Valves

\* GPM Ratings may vary due to Piping Layout that may change Pump Head Curve

- High Volume Under Carriage Washer
- Ideal for Flood Applications
- Small Platform

**Available Options:**

- Ballast Pressure Control
- Mass Air Injection
- BIOZONE Pit Treatment
- VFD for 2-Speed Output
- EFO- Emergency Fresh Water Override



**CS 3 Flood Pump  
 w/VFD and BIOZONE**