



SPECIFICATION SHEET

SEBCO 100 - 600^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1
 1022-12-MT (100 Watt)
 120VAC-1A MAX
 12-15VAC - 8.33A MAX
 1X10A
 60Hz
 9.65" x 4.35" x 3.86"
 8 LBS

CLASS 1
 1101-12-MT (300 Watt)
 120VAC-5A MAX
 12-15VAC-25A MAX
 1x25A
 60 Hz
 9.65" x 4.35" x 3.86"
 13 LBS.

CLASS 1
 1102-12-MT (600 Watt)
 120VAC-5.5A MAX
 12-15VAC-50A MAX
 2x25A
 60 Hz
 9.65" x 4.35" x 3.86"
 17 LBS.