



SPECIFICATION SHEET

TRIAC / Phase-Cut DIMMABLE LED POWER SUPPLY



FEATURES

- 3 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE WITH FORWARD AND REVERSE PHASE DIMMERS
- MLV, ELV, TRIAC COMPATIBLE DIMMING
- STANDARD WITH MANDATORY AUTO RESET SECONDARY PROTECTION
- MEET CLASS 2 OUTPUT LIMITS
- 24 VOLT "DC" RATED OUTPUT
- 0-100% DIMMING. POWER FACTOR > 0.95

REQUIREMENTS

- UL LISTED, CLASS 2, CLASS P, FCC, TYPE HL, RoHS
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

192 WATT

KVF-C24192-TDWJ
100-277VAC
24VDC - 8A MAX
2x4A
50/60 Hz
10.2" x 4" x 1.8"
4-1/2 LBS.

288 WATT

KVF-C24288-TDWJ
100-277VAC
24VDC - 12A MAX
3x4A
50/60 Hz
10.9" x 4.25" x 1.8"
5 LBS.