



### RYCO #912 DOUBE WETPUMPS

The most damage free, fastest and most reliable large wetpumps ever constructed.

This is the most efficient pump available for small fish such as herring, sardine, mackerel, and pollock.

The bottom inlet of this pump results in the absolute minimum suction height possible in a wetpump, throughout the suction cycle. The low turbulence and lack of internal impact in bottom entry wetpumps results in less fish damage and prevents air blowback in the suction hose.

This wetpump is constructed of stainless, bronze, and plastic. Our stainless tanks are reliable, and they meet all sanitation and safety requirements.

This system is easily maintained in remote locations by untrained employees, and is the most reliable control system available

#### FEATURES:

- Pump tank capacities over 300 ft<sup>3</sup> (8.5 m<sup>3</sup>)
- Blowers available from 450 to 2100 CFM (to 87.8 m<sup>3</sup>/min)
- Automatic pumps easily operated manually
- Manual quickly converted to automatic
- Suction lifts to 27 feet (8.2 m)
- Discharge lifts exceed 50 feet (15.2 m)
- Horizontal discharge up to 1 mile (1.6km)
- Electric or Diesel drive

#### UTILITIES:

- Water: filtered, fresh or salt, 10 gpm, 30 psi min. (38 liter/min at 2.1 bar)
- Air: filtered and dry, 2 CFM at 100 psi. (0.06m<sup>3</sup> at 6.9 bar)



#### PHOTOS:

Top: #912 Double Tank

Bottom: Electric Power Unit



**#912 DOUBLE WEATPUMP**  
**200MT/HR**

**SPECIFICATIONS MAY CHANGE, CONTACT RYCO FOR SPECIFIC APPLICATIONS**

**OVERLEAF: D4139-A1**

*Address:* **6810 220<sup>th</sup> St. SW**  
**Mountlake Terrace, WA 98043**  
**USA**

*Phone #:* **425-744-0444**  
*Fax #:* **425-673-2666**

*Web:* **rycous.com**  
*E-mail:* **sales@rycous.com**