




#820 INDICATOR

RYCO INDICATOR....

STANDARD FEATURES:

- Weight Display: Six large high contrast red numerals for weight.
- Data Display: White/Blue graphic display.
- Configurable Analog/Digital converter.
- Power for two load cells.
- Readout: g, kg, oz, lb
- NEMA 4X Stainless Washdown Enclosure
- Two RS232 communication ports
- Piezoelectric push-button interface
- Programmable for ticket printing or other control operations
- Easy to use Graphical User Interface
- Ethernet capable with web access for remote monitoring.
- Optional RFID reader
- CERTIFICATIONS: OIML
- COMPATIBLE with any Ryco, Marel, Scanvegt, Rice Lake or similar scale base.
- MOTION COMPENSATION: True reference load cell Motion Compensation with proprietary software.



- OPERATION MODES: Marine Scale, Bench Scale, Grading, Reverse Grading, Manual Batching, and Automatic Batching with belt and hopper control.

SPECIFICATIONS:

POWER:
115/230VAC 50/60HZ

RESOLUTION:
Internal: 24 bits
Display: 20,000 divisions

RESPONSE TIME:
0.25 seconds

WARRANTY:
Two Year limited warranty

CIRCUIT PROTECTION:
ESD, EMI, RFI Protection

SERIAL OUTPUT:
RS232, all common protocols.

STATUS INDICATORS:
Zero center, tare, net, lb, kg, oz, g

OPERATING TEMPERATURE:
-10°C TO 40°C

WEIGHT:
2.9kg (6.4lb)

RATING/MATERIAL:
Enclosure: NEMA 4X
Heavy stainless steel

APPROVALS:
OIML PENDING/UL

SPECIFICATIONS MAY CHANGE, CONTACT RYCO FOR SPECIFIC APPLICATIONS

OVERLEAF: D4139-A1

Address: 6810 220th St. SW
Mountlake Terrace, WA 98043
USA

Phone #: 425-744-0444
Fax #: 425-673-2666

Web: rycous.com
E-mail: sales@rycous.com



#820 INDICATOR

SPECIFICATIONS MAY CHANGE, CONTACT RYCO FOR SPECIFIC APPLICATIONS

OVERLEAF: D4139-A1

Address: 6810 220th St. SW
Mountlake Terrace, WA 98043
USA

Phone #: 425-744-0444
Fax #: 425-673-2666

Web: rycous.com
E-mail: sales@rycous.com