

Model	Voltage (v)	Capacity mAh	Thick mm	Width mm	Length mm	weight grams ≤
423443ARE	3.7	400	4.6	33.9	43.0	14
053034APT	3.7	500	5.3	29.9	34.0	14
354249ARD	3.7	550	3.8	41.9	48.5	19
423048APT	3.7	600	4.5	29.9	47.9	17
483436APT	3.7	600	5.1	33.9	35.9	16
53040APT	3.7	630	5.3	29.9	40.0	16
433536ARG	3.7	650	4.6	34.9	35.7	16
63830ART	3.7	700	6.3	37.9	30.0	17
413446APH	3.7	700	4.4	33.9	46.0	17
433048APH	3.7	700	4.6	29.9	47.8	17
523436APH	3.7	700	5.5	33.9	35.9	17
543136ARG	3.7	700	5.7	30.9	36.0	16
063040APT	3.7	750	6.3	29.9	40.0	19
483048APT	3.7	750	5.1	29.9	48.0	18
573436APT	3.7	750	6.0	33.9	36.0	19
433450ART	3.7	800	4.6	33.8	50.0	20
453447ART	3.7	800	4.8	33.9	46.6	19
513048APT	3.7	800	5.4	29.9	48.0	19
523450ART	3.7	800	5.4	33.9	49.5	20
523450ART	3.7	800	5.5	33.9	49.5	20
533640ART	3.7	800	5.6	35.9	40.0	19
573436APH	3.7	800	5.9	33.9	36.0	19
592742APG	3.7	800	6.2	26.9	41.2	18
633040APT	3.7	800	6.6	29.6	40.0	20
53442ARH	3.7	820	5.3	33.9	41.6	21
523450ARD	3.7	820	5.4	33.9	49.5	21
433450APH	3.7	850	4.6	33.8	49.9	21
453447APH	3.7	850	4.8	33.9	46.6	21
513048APH	3.7	870	5.4	29.9	48.0	20
762836APG	3.7	890	7.9	27.9	36.0	20
53450APE	3.7	900	5.3	33.9	50.0	21
623835ARH	3.7	900	6.5	37.9	35.0	20
72928APG	3.7	900	11.0	28.9	27.5	21
533443ARH	3.7	920	5.6	33.9	42.9	20
63048APT	3.7	950	6.3	29.9	48.0	21
433450ARG	3.7	950	4.6	33.9	50.0	20
533443ARG	3.7	950	5.6	33.9	43.0	20
613048APT	3.7	950	6.4	29.9	48.0	24
663040APG	3.7	950	6.9	29.9	40.0	21
753040APT	3.7	950	7.8	29.9	40.0	23
423857ART	3.7	1000	4.5	37.9	57.0	23
533450ARE	3.7	1000	5.6	33.9	49.9	22
663437APG	3.7	1000	6.9	33.9	37.0	22
523446ARG	3.7	1010	5.4	33.9	45.9	22
883035ARG	3.7	1010	9.1	29.1	35.0	22
633443ART	3.7	1020	6.6	33.9	43.0	22
783236ARG	3.7	1020	8.1	31.9	36.0	22
833038ARE	3.7	1030	8.3	29.9	38.0	22
523450ARH	3.7	1040	5.6	33.9	49.5	23
Model	Voltage (v)	Capacity mAh	Thick mm	Width mm	Length mm	weight grams ≤

Model	Voltage (v)	Capacity mAh	Thick mm	Width mm	Length mm	weight grams ≤
454349ARG	3.7	1050	4.7	42.9	49.2	24
454350ART	3.7	1050	4.8	42.9	50.0	25
424353ARH	3.7	1080	4.5	42.9	53.0	25
543447ARG	3.7	1090	5.7	33.9	46.2	23
862939ARG	3.7	1090	8.9	28.9	38.4	22
424455ART	3.7	1100	4.5	43.7	55.0	26
533450ARH	3.7	1100	5.6	33.9	49.9	23
673141APG	3.7	1100	7.0	30.6	40.7	23
793436ARH	3.7	1100	8.2	33.9	36.0	23
633443ARG	3.7	1140	6.6	33.9	43.0	23
364262ARG	3.7	1150	3.8	41.9	61.7	25
423857ARG	3.7	1180	4.5	37.9	57.0	25
613450ART	3.7	1180	6.4	33.9	49.9	25
044261ARH	3.7	1200	4.3	41.9	61.0	26
384462ARH	3.7	1200	4.1	43.8	62.0	27
424353ARG	3.7	1200	4.5	42.9	53.0	25
454060ART	3.7	1200	4.8	39.9	59.9	27
454350ARG	3.7	1200	4.8	42.9	50.0	25
523855ART	3.7	1200	5.5	37.9	55.0	30
533450ARG	3.7	1200	5.6	33.9	49.9	24
423858ARG	3.7	1220	4.5	37.9	57.3	26
613450ARH	3.7	1230	6.4	33.9	49.9	28
73448APT	3.7	1300	7.3	33.9	48.0	28
454655ART	3.7	1300	4.8	45.9	55.0	29
673447APG	3.7	1300	7.0	33.8	47.0	26
733450APT	3.7	1300	7.6	33.6	50.0	28
464354ARG	3.7	1320	4.9	42.9	53.5	28
63350ARG	3.7	1350	6.3	32.9	50.0	22
454354ARG	3.7	1350	4.8	42.8	54.0	28
484655ARE	3.7	1350	5.1	45.9	55.0	30
454461ART	3.7	1400	4.8	43.9	61.0	30
454655ARH	3.7	1400	4.8	45.9	55.0	30
484655ARH	3.7	1430	5.1	45.9	55.0	31
384473ARH	3.7	1450	4.1	43.8	73.0	31
395065ARE	3.8	1450	4.2	49.9	65.0	32
384865ARG	3.7	1460	4.1	47.9	65.0	31
44466ARG	3.7	1500	4.2	43.9	65.8	31
54656ARE	3.7	1500	5.3	45.9	56.0	32
384672ARH	3.7	1500	4.1	45.9	72.0	33
425159ARH	3.7	1500	4.5	50.9	59.0	30
484461ARE	3.7	1500	5.1	43.9	61.0	32
564462ARE	3.7	1500	5.8	43.9	62.0	34
454463ARG	3.7	1520	4.8	43.9	62.8	31
484553ARG	3.7	1550	5.1	44.8	52.5	29
525153ARE	3.7	1550	5.5	50.9	53.0	34
454461ARG	3.7	1600	4.8	43.9	61.0	32
643960APD	3.7	1600	6.7	38.8	60.0	35
384672ARG	3.7	1650	4.0	45.9	72.0	34
484473ARD	3.7	1700	5.1	43.9	73.0	37
Model	Voltage (v)	Capacity mAh	Thick mm	Width mm	Length mm	weight grams ≤

Model	Voltage (v)	Capacity mAh	Thick mm	Width mm	Length mm	weight grams ≤
525153ARE	3.7	1700	5.5	50.9	53.0	35
584163ARD	3.7	1700	6.0	40.9	62.7	37
613468ARG	3.7	1700	6.3	33.9	68.0	35
643960APE	3.7	1700	6.7	38.8	60.0	35
103447APH	3.7	1750	10.3	33.9	47.0	36
485155ARG	3.7	1750	5.0	50.9	54.9	35
484473ARH	3.7	1750	5.1	43.9	73.0	37
564462ARH	3.7	1750	5.8	43.9	62.0	36
584163ARH	3.7	1750	6.0	40.9	62.7	36
074056APH	3.7	1800	7.3	39.9	56.0	36
103450ART	3.7	1800	10.3	33.9	50.0	38
474861ARG	3.7	1800	4.9	47.9	61.0	35
545148ARG	3.7	1800	5.7	50.9	48.0	35
554461ARG	3.7	1800	5.8	43.9	60.5	36
643960APH	3.7	1800	6.7	38.8	60.0	38
973445ARG	3.7	1800	10.0	33.9	44.5	34
983450ART	3.7	1800	10.1	33.2	50.0	36
454469ARG	3.7	1850	4.7	43.9	68.5	35
366070ARG	3.7	1900	3.9	59.9	70.0	38
543877ARG	3.7	1970	5.7	37.9	76.5	38
46066ARG	3.7	2000	4.3	59.9	66.0	40
103450ARG	3.7	2000	10.3	33.9	50.0	38
375880ARH	3.7	2000	3.9	57.9	79.5	43
385870ARG	3.7	2000	4.1	57.9	70.0	39
564462ARG	3.7	2000	5.9	43.9	62.0	38
624475ARD	3.7	2000	6.4	43.9	74.5	46
764257ARE	3.7	2000	7.9	41.9	52.9	41
445074ARG	3.7	2020	4.7	49.9	73.5	41
464476ARG	3.7	2070	4.9	43.9	75.8	40
555254ARG	3.7	2150	5.8	51.1	53.4	41
396072ARG	3.7	2200	4.2	59.9	71.5	43
415879ARG	3.7	2450	4.4	57.9	78.5	44
624474ARE	3.7	2500	6.5	43.9	74.2	48
624475ARD	3.7	2500	6.4	43.9	74.5	49
625083ARD	3.7	2500	6.5	49.9	83.0	55
754473ARD	3.7	2500	7.8	33.9	73.0	53
595264ARG	3.7	2650	6.1	51.9	64.0	48
754473ARH	3.7	2750	7.8	43.9	73.0	57
794663ARG	3.7	2940	8.1	45.9	62.8	54
625083ARG	3.7	3600	6.5	49.9	83.0	65
Model	Voltage (v)	Capacity mAh	Thick mm	Width mm	Length mm	weight grams ≤

Please use the above information as a guide only, it is subject to change.

Dimensions are for bare cells only, without sleeve or additional protection parts.

The above Lithium Ion ( Li Ion ) prismatic cells can be supplied assembled into single cell or multi-cell packs complete with protection circuit module (PCM). Please contact us for further details.

