



**Visit us on the web.
Share your stories pictures, and
ideas on our Facebook Page.**

PO Box 51027, Greater Sudbury, ON, P3C0A3
info@bakerbag.ca

Set-up instructions:

- 1. Unpack bag and inspect for wear or damages. Best practice is to repair any damages before using BakerBag.**
- 2. Remove platform from your baker scaffold and set aside. It is not used with a BakerBag.**
- 3. Relocate siderails to desired height above the ground. Typical height is approximately three feet.**
- 4. Release one end of one side rail. Slide the BakerBag's side pocket onto the rail completely where the open bag is located within the scaffold. Reattach the rail to its end.**
- 5. Remove the opposite side rail from the baker scaffold. Slide the rail through the remaining side pocket until both ends are free and able to reattach to the baker.**
- 6. Attach the rail to both ends at the same height as the opposite rail. BakerBag can now be adjusted for fit.**
- 7. Inspect assembly. Ensure all connections and components of the scaffold have been assembled (without the platform) and in good working condition.**
- 8. We at BakerBag trust our customer's judgement, but please do not overload BakerBag or use it for a purpose that is not intended. It is neither a people carrier, nor should it be used for liquids.**

We look forward to receiving your feedback! Feel free to send us pics. Write a review!

Our customers are industry professionals and their feedback can only help us to make BakerBag the #1 material truck cart and demolition bin.