

Simon Marketing Group, LLC

dba Parking Lot Safety Solutions 1405 White Oak Dr., Kalamazoo, MI 49008 248-855-6647

Title:	Post Guard	l Flat	Тор	Cover

Recommended Use: Bollard, Post or Pole Cover

Specifications: See Below

POST GUARD FLAT TOP SPECIFICATION SHEET

MATERIAL

Marlex [™] HHM 5502 BN High Density Polyethylene

Microthene™ MP635662 Linear Low Density Polyethylene*

HDPE, hexene copolymer, is tailored for blow molded products that require excellent stiffness, impact strength and UV resistance. HDPE is designed for an optimum balance of density, molecular weight distribution, demonstrating maximum property advantages for large products. Blow molded HDPE products are durable and recyclable for sustainability. Five year UV stabilizer package and Antic-static package are combined with the HDPE.

*Low Density PE, ethylene hexene copolymer. LDPE Resin is tailored for rotationally molded large hollow objects that require impact strength, warp resistance, stress crack resistance and UV stabilization.

** The Yellow color 8-7/8" x 72" Post Guard bollard cover is stocked in HDPE. Other colors may be available in 8-7/8" HDPE as the market demands.

Reflective Stripes: 3 M Scotchlite Reflective Sheeting

Installation Strips: 2 foam strips

INSTALLATION

- 1. Crisscross the two foam strips over the top of the bollard.
- 2. Slide the Post Guard over the foam strips and the bollard.

The manufacturer warrants this product, Post Guard® sleeves, against defects due to workmanship or materials, for a period of one year. **This is a limited warranty and does not cover the following:** Damage to product caused by improper installation; Damage due to normal wear and tear; Damage due to abuse; Finish damage due to normal wear and tear.

	A ID Width/Dia	B Height/Length	C Thickness	D OD Width/Dia	E	F Recess	G	Н	I Reflect Tape
4.5" x 52"	4.72	52	.1406	5	2.875	.875	5.875	41.50	.75w
4.5" x 64"	4.72	64	.1406	5	2.875	.875	5.875	53.50	.75w
7" x 52"	7	52	.1719	7.34	2.875	.875	5.875	41.50	.75w
7" x 60"	7	60	.1719	7.34	2.875	.875	5.875	49.50	.75w
7" x 72"	7	72	.1719	7.34	2.875	.875	5.875	61.50	.75w
8% x 72"**	8.8125	72	.19	9.1857	3.875	.875	5.75	60.62	.75w
10% x 60"*	10.875	60	.22	11.3125	3.0	.875	5.75	49.50	1.0w
12¾ x 60″*	13.00	60	.20	13.4	3.0	.875	5.75	49.50	1.0w

