



NOTES  
Normal pressure is 300PSI.

20	Shaft sleeve	C63000
19	Axle hole sleeve	C63000
18	Plug	SS304
17	Swing arm sleeve	C63000
16	Scutcheon	SS304
15	Radial spindle	SS304
14	Plug the gasket	EPDM
13	Shaft hole plug	SS304
12	Seat	C84400
11	Disc	SS304+Q235+EPDM
10	Split pin	SS304
9	Washer	SS304
8	Hexagonal slot thin nut	SS304
7	Rocker	DI
6	Body	DI
5	O-Ring	EPDM
4	Spring washer	65Mn
3	Washer	C.S
2	Hexagon head bolts	GR.8.8
1	Cover	DI
ITEM	NAME	

DN	INCH	B	C	ØD	L	ØW	F	ASME B16.1 CLASS125	
								PCD	N-ØC
50	2"	117	66	50	203	165	19	Ø120.7	4-Ø19
65	2.5"	128	72	65	254	185	19	Ø139.7	4-Ø19
80	3"	132.5	85	82	279	200	19	Ø152.4	4-Ø19

Manufacture/Supplier:

SHOP DRAWING

FIG NO. 7000

SENTRY SPRINKLERS

						DRAWN		Date		TITLE: SWING CHECK VALVE(II) 2"-3"(DN50-80)
						Checked		Date		
						Approved		Date		
REV.	BY	APP.	Description	Date		Projection		ALL DIM'S IN: mm DO NOT SCALE FROM DRAWING		DRAWING NO. :