

## Minnesota Throwdown

### Youth and Midsize Stock Compact Rules

1. Any 1980 and Newer FWD car. No vans/Suvs
2. All cars must be stripped off all plastic, glass, headlights, taillights and anything else that could fall off onto the track during the show.
3. All cars must remain stock, ABSOLUTY NO WELDING ANYWHERE.
4. Bumpers may be welded on solid. You may add a 6"X6"X1/4" plate to the front side of frame to help weld bumper on (nothing on side of frame). Bumpers may be any 1980 and newer car bumper, or a piece of 4"X4"X1/4" square tube. Absolutely no points added to tube, and it can not stick out past wheels. Nothing may be added to stock bumpers or any seam welding. Nothing can be welded to K Member. NO BUMPER SHOCKS ALLOWED. If car comes factory with bumper shocks, then you may leave it all factory or remove bumper shocks and weld your plate to front of frame. Rear Bumper must remain completely stock or taken off.
5. Batteries must be moved inside vehicle and be held down or have battery box
6. Suspension must be left stock no adding metal or welding
7. If factory gas tank is in front of axle you may leave it there. If its behind the axle, you must move it to the rear seat area. Factory tanks may be moved inside but cannot move. After marker tanks may be used.
8. All doors may be wired or chained in 6 places max per seam. Except drivers door can be welded solid this does not include passenger door in youth.
9. Trunks, hoods, tailgates, all may be wired or chained in 6 places total. Sheet metal to sheet metal only. Nothing to frame, unibody or bumpers. If you remove trunk, hood, or tailgate you lose that wire or chain.
10. Rear seat bar may be added. It may be welded to post. If you have to add something to get it away from seat please call. This is only to stop sides from coming in, not to help any other part of car. You may have a 4 point floating cage no further back than 6" behind drivers seat. If you have a tank protector only can be 24" wide and no taller than speaker deck and must be 4" away from sheet metal. You may add a roll over bar for driver safety attached to the floating cage. This cage is for driver safety only.
11. Must have 1 windshield bar and cannot strengthen car in any way this is only for safety
12. Drivers door only may have a plate welded to the outside or inside. This is for drivers safety.
- 13 These rules are cut and dry, you should not have to call to ask many questions on this class. If it does not say you can do it then that means YOU CANNOT do it. Quick and easy build.
- 14.No aftermarket parts what so ever besides header, bumper, wheels/tires, battery cables, and fuel line.

For questions call: Hunter Shelstad 507-993-6337