



CONTAINER CHASSIS 40

- ✓ 3 years in manufacturing and 1 year in spare parts (Does not apply for misuse of the equipment).
- ✓ High Quality Guarantees*



FICHA TÉCNICA

MEASURES

Length: 479" 15/16" (12.19 meters)
Width: 96" (2.438 meters)
Height: (1.30 meters)
Load capacity: 30,000 KGS

MATERIALS

REINFORCED CONSTRUCTION WITH PERFECT WELDING OF .45 TUBULAR.

Steel with certified code: A-50 high resistance STEEL.

Main cast beams for 40/20. 12" x 4 1/2 "I" Beam. DOUBLE WALL NECK 10 FT. EXTENSION: 6x4 "I" Beam

Screws: Grade 8, which dictates the standard for its resistance.

5th wheel plate: 5/16" gauge brand PERNO REY PREMIER O SAMPA.

Cross members with rib reinforcement: Front ¼ and rear 3/8 added square double crescent reinforcement per cross member.

Mud flaps: Two of high relief.

Towing hook: SAF-TITE 8 holes, with lime pull plate. 5/8" PREMIER OR HOLLAND BRAND.

FLEETMASTER OR ACP padlocks: 4.

SUSPENSION

Suspension: Pneumatic HT-300 brand MAF in laser cuts. MAF imported airbags. SHOCK ABSORBERS (THICK TYPE).

NEW AXLES: FLEETMASTER BRAND Capacity of 30,000 lbs. WARRANTY AGAINST MANUFACTURING DEFECTS 1 YEAR (NOT APPLICABLE FOR USE). 5"

Brakes: HALDEX OR BENDIX AMERICAN ABS: 2 air tanks, double boosters, self-adjusting ratchet, front and rear handles with stopcock, leveling and protective valves.

Landing Gear: Two speed AAR approved, square leg. 62,000 lb. static load capacity.

HOSES, LIGHTS AND PAINT

All are covered with POLIFLEX ANTI-FLAME hose.

All air and light connections are covered with corrugated hose.

Plug: 7-line female. **Ceiling lights:** Slim with 9 and 6 LEDs. **Sides:** 2 Red and 2 Amber on each side. **Rear:** 2 red stop and quarter, 2 amber directional and quarter.

Reflective tape: 16 red and white on all 4 sides. DTM AUE-370 acrylic polyurethane paint with high solids content and high coverage, PPG brand.

