



Lighting-Power-Control

LARGE HALO BULKHEAD

FEATURES

- 525mm round halo effect backlight bulkhead
- Up to 2732 luminaire lumens
- Integral controls and dimming
- Various trim colours available
- Integral 3-hour emergency options including self-test, DALI and DATA2
- Addressable central battery version available for the TM-CBA



TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cW
RDF-C2LW48504K-HE	White Trim	28W 2D	2.8	65	8A 80µs	10	1734	1301	130.1
RDF-C2LC48504K-HE	Chrome Trim	28W 2D	2.8	65	8A 80µs	10	1734	1301	130.1
RDF-C2LS48504K-HE	Brushed Steel Trim	28W 2D	2.8	65	8A 80µs	10	1734	1301	130.1
RDF-C2LW48704K-HE	White Trim	38W 2D	2.8	40	10A 100µs	14	2428	1821	130.1
RDF-C2LC48704K-HE	Chrome Trim	38W 2D	2.8	40	10A 100µs	14	2428	1821	130.1
RDF-C2LS48704K-HE	Brushed Steel Trim	38W 2D	2.8	40	10A 100µs	14	2428	1821	130.1
RDF-C2LW48104K-HE	White Trim	38W 2D	2.8	40	10A 100µs	21	3642	2732	130.1
RDF-C2LC48104K-HE	Chrome Trim	38W 2D	2.8	40	10A 100µs	21	3642	2732	130.1
RDF-C2LS48104K-HE	Brushed Steel Trim	38W 2D	2.8	40	10A 100µs	21	3642	2732	130.1

OPTIONS AND ACCESSORIES

- EM** Integral Emergency (1W)
- EMST** Integral Emergency Self Test (1W)
- EMD2** Integral Emergency DATA2 (1W)
- EMCB** Addressable TM Central Battery
- CF** Corridor Function
- MWP** Remotely Programmable Microwave
- DD** DALI/SwitchDIM
- WL** Wireless Control System
- WLEM** Wireless Monitored Emergency
- 3K** 3000K Colour Temperature
- 5K** 5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

