

SAFETY DATA SHEET
Intimidator Pro Polish

Printed: 05/19/16
Revision: 05/19/16
Supersedes Revision:

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name (Label): Intimidator Pro Polish
Other Identifiers:

Recommended Use: multi-purpose polish for metal, oxidized paint, fiberglass and glass

Restrictions on Use: N / A

Manufacturer/Distributor

name: The Intimidator Micro Diamon Pro Polish
address: 9416 Moody Park Dr. Overland Park, KS 66212

phone #: 701-599-2302

INGREDIENT A – Green Chrome Rouge Buffing Compound

Name: Green Chrome Rouge Buffing Compound
Other Identifiers: 515-6124, 780-6124,J-52, 515-113, GR-639
Synonyms: none
Recommended Use: Abrasive / Buffing Compound
Restrictions on Use: N/A

Details of the supplier of the safety data sheet information:

Supplier Name The Intimidator
Supplier Address 9416 Moody Park Dr.
Overland Park, KS 66212
Supplier Phone 701-599-2302main
Supplier Email intimidatorpolish@gmail.com

INGREDIENT B – Paint Thinner

Name: Paint Thinner
Other Identifiers CKPT94402, GKPT94002B, DKPT94403CA, EKPT94401, GKPT94002, GKPT94002P,
& Synonyms: GKPT94002T, GKPT9400, GPT1KS, PA12779, QKPT94003, QKPT94203, QPT1KS, GKPTDP
Recommended Use: Paint, stain, and varnish thinning
Restrictions on Use: N/A

Details of the supplier of the safety data sheet information:

Details of the supplier of the safety data sheet information:

Supplier Name The Intimidator
Supplier Address 9416 Moody Park Dr.
Overland Park, KS 66212
Supplier Phone 701-599-2302main
Supplier Email intimidatorpolish@gmail.com

2. HAZARD(S) IDENTIFICATION

INGREDIENT A – Green Chrome Rouge Buffing Compound

Classification of Chemical(s) (paragraph [d] §1910.1200)

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

GHS Label elements, including precautionary statements

Signal Word: none

The product contains no substances which at their given concentration, are considered to be hazardous to health.

Appearance: Dark Green

Physical State: Solid

Odor: Fatty Odor

Precautionary Statements – Prevention: Obtain special instructions before use.

Precautionary Statements – Response: None

Precautionary Statements – Storage: None

Precautionary Statements – Disposal: None

Hazards not otherwise classified (HNOC): N/A

Unknown Toxicity: None

Other Information: May cause slight eye irritation
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals: No information available

INGREDIENT B –Paint Thinner

Classification of Chemical(s) (paragraph [d] §1910.1200)

Flammable Liquids, Category 3

Acute Toxicity: Oral, Category 5

Germ Cell Mutagenicity, Category 1B

Carcinogenicity, Category 1B

Target Organ Systemic Toxicity (single exposure), Category 3

Target Organ Systemic Toxicity (repeated exposure), Category 1

Aspiration Toxicity, Category 1

Signal word, hazard statement(s), symbol(s) and precautionary statement(s) [paragraph (f) §1910.1200. (Hazard symbols may be provided as graphical reproductions in black and white or the name of the symbol, e.g. flame, skull & crossbones)



GHS Signal Word: Danger

GHS Hazard Phrases: H226: Flammable liquid and vapor.
H303: May be harmful if swallowed.

SAFETY DATA SHEET

Intimidator Pro Polish

Printed: 05/19/16
Revision: 05/19/16
Supersedes Revision:

GHS Precaution Phrases:

H340: May cause genetic defects.
H350: May cause cancer.
H336: May cause drowsiness or dizziness.
H372: Causes damage to organs through prolonged or repeated exposure.
H304: May be fatal if swallowed and enters airways.
P233: Keep container tightly closed.
P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P280: Wear protective gloves/& protective clothing/eye protection/face protection.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P243: Take precautionary measures against static discharge.
P242: Use only non-sparking tools.
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read & understood.
P281: Use personal protective equipment as required.
P261: Avoid breathing gas/mist/vapors/spray.
P271: Use only outdoors or in a well-ventilated area.
P260: Do not breathe dust/fume/gas/mist/vapors.
P264: Wash hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.

GHS Response Phrases:

P370+378: In case of fire, use dry chemical to extinguish.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P312: Call a POISON CENTER/doctor if you feel unwell.
P308+313: IF exposed or concerned: Get medical attention/advice.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P314: Get medical attention/advice if you feel unwell.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331: do NOT induce vomiting.

GHS Storage and Disposal Phrases:

P403+235: Store in cool/well-ventilated place.
P501: Dispose of contents/container according to local, state and federal regulations.
P405: Store locked up.
P403+233: Store container tightly closed in well-ventilated place – if product is as volatile as to generate hazardous atmosphere.

Hazard Rating System:

HMIS:

HEALTH	*	1
FLAMMABILITY		2
PHYSICAL		0
PPE		



OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects

Inhalation Acute Exposure Effects:

SAFETY DATA SHEET
Intimidator Pro Polish

Page: 4

Printed: 05/19/16

Revision: 05/19/16

Supersedes Revision:

(Acute and Chronic): May cause dizziness; headache; watering of eyes; eye irritation; weakness; nausea; muscle twitches, and depression of central nervous system. Severe overexposure may cause convulsions; unconsciousness; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

May cause irritation; numbness in the fingers and arms; drying of skin; and dermatitis. May cause increased severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may irritate eyes.

Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. May cause nausea; weakness; muscle twitches; gastrointestinal irritation; and diarrhea. Severe overexposure may cause convulsions; unconsciousness; and death.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. May cause jaundice; bone marrow damage; liver damage; anemia and skin irritation.

Medical conditions Generally

Aggravated By Exposure: Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

Additional hazards not otherwise classified that have been identified during the classification process. N/A

3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT A – Green Chrome Rouge Buffing Compound

Except as provided for in paragraph (i) of §1910.1200 on trade secrets:

Chemical Name	CAS No	Weight-%	Trade Secret
Aluminum oxide	1344-28-1	30 - 60	*
Chromium (III) oxide	1308-38-9	15 – 40	*
Stearic acid	57-11-4	5 - 10	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

INGREDIENT B –Paint Thinner

Except as provided for in paragraph (i) of §1910.1200 on trade secrets:

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	0.0 - 100.0%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	0.0 - 100.0%
8052-41-3	Stoddard solvent (Mineral spirits; Aliphatic Petroleum Distillates; White spirits)	0.0 – 95.0%
95-63-6	1,2,4-Trimethylbenzene (Pseudocumene)	0.0 – 5.0%
111-84-2	Nonane	0.0 – 5.0%
25551-13-7	Benzene, Trimethyl-	0.0 – 5.0%
98-82-8	Cumene (Benzene, 1-Methylethyl-Isopropylbenzene)	0.0 – 1.0%
100-41-4	Ethylbenzene (Ethylbenzol; Phenylethane)	0.0 – 1.0%

Additional Chemical Information:

Ingredients vary due to multiple blends and/or raw material suppliers.

4. FIRST-AID MEASURES

INGREDIENT A – Green Chrome Rouge Buffing Compound

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
Skin Contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions, see a physician.
Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Ingestion	Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.
Most important symptoms effects, both acute & delayed	No information available
Indication of any immediate medical attention & needed special treatment	
Note to Physician	Treat symptomatically

INGREDIENT B –Paint Thinner

Eye Contact	Flush with large quantities of water for at least 15 minutes Seek immediate medical attention
Skin Contact	Wash with soap and large quantities of water. Seek medical attention if irritation from contact persists.
Inhalation	If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial medical assistance can be rendered.
Ingestion	Do NOT induce vomiting. Call your local poison control center, hospital emergency room or physician immediately for instructions to induce vomiting. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to a person who is not fully conscious. Do not leave victim unattended. Seek medical attention immediately.

SAFETY DATA SHEET

Intimidator Pro Polish

Page: 7

Printed: 05/19/16
Revision: 05/19/16
Supersedes Revision:

Signs/Symptoms of Exposure: Inhalation, ingestion, and dermal are possible routes of exposure.

Note to Physician: Call your local poison control center for further information.

Inhalation: Inhalation overexposure can produce toxic effects. Monitor respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation as required.

Ingestion: If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

5. FIRE-FIGHTING MEASURES

INGREDIENT A – Green Chrome Rouge Buffing Compound

Suitable (and unsuitable) extinguishing media:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Hazardous Combustion Products: Carbon oxides.

Explosion Data:

Sensitivity to Mechanical Impact: NO

Sensitivity to Static Discharge: NO

Special protective equipment and precautions for fire-fighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

INGREDIENT B –Paint Thinner

Suitable (and unsuitable) extinguishing media:

Use carbon dioxide, dry chemical powder, or foam.

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Combustible Liquid:	NFPA Class II
Flash Point:	>100.00 F
Explosive Limits:	LEL: 0.5 UEL: 6
Autoignition Point:	No data

Special protective equipment and precautions for fire-fighters:

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas.

Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.

Stay away from heads of containers that have been exposed to intense heat or flame.

6. ACCIDENTAL RELEASE MEASURES

INGREDIENT A – Green Chrome Rouge Buffing Compound

Personal precautions, protective equipment & emergency procedures: Avoid contact with eyes

Methods & materials for containment and cleaning up: Prevent further leakage or spillage if safe to do so.
Pick up and transfer to properly labeled containers.

INGREDIENT B –Paint Thinner

Personal precautions, protective equipment & emergency procedures: Keep unnecessary people away.
Isolate hazard area and deny entry.
Stay upwind, out of low areas and ventilate closed spaces before entering.
Shut off ignition sources.
Keep flares, smoking or flames out of hazard area.

Methods & materials for containment and cleaning up: **Small Spills:** Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.
Large Spills: Dike far ahead of spill for later disposal.
Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

INGREDIENT A – Green Chrome Rouge Buffing Compound

Precautions for safe handling: Handle in accordance with good industrial hygiene & safety practice.
Avoid contact with eyes.

Conditions for safe storage, including any incompatibilities: Keep container tightly closed.
No known incompatibilities, based on supplied information

INGREDIENT B –Paint Thinner

Precautions for safe handling: Read carefully all cautions & directions on product label before each use. Since empty container retains residue, follow all label warnings even after container is empty.
Dispose of empty container according to all regulations. Do not reuse this container.

A static electrical charge can accumulate when this material is flowing through pipes, nozzles or filters, and when it is agitated. A static spark discharge can ignite accumulated vapors particularly during dry weather conditions. Always use proper bonding and grounding procedures.

Conditions for safe storage, including any incompatibilities: Keep container tightly closed when not in use. Store in a cool, dry place.
Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENT A – Green Chrome Rouge Buffing Compound

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Aluminum Oxide 1344-28-1	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5mg/m ³ respirable fraction	
Chromium (III) Oxide 1308-38-9	TWA: 0.5 mg/m ³ Cr	TWA: 0.5 mg/m ³ Cr (vacated) TWA: 0.5m/m ³ Cr	IDLH: 25 mb/m ³ Cr(III) TWA: 0.5 mg/m ³ Cr

ACGIH TLV: American Conference of Governmental Industrial Hygienists – Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration – Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v.OSHA, 965 F.2d962 (11th Cir., 1992) See section 15 for national exposure control parameters

Engineering Measures Showers
 Eyewash stations
 Ventilation systems

Individual Protection Measures, such as Personal protective equipment:

Eye/Face Protection For buffing machines, wear safety glasses and/or face shield helmets.
 See OSH 29 CFR 1910.122 (Safety Glasses)

Skin and Body Protection Protective work clothing, heavy duty gloves, body apron or belly pads, safety shoes as needed.

Respiratory Protection Respiratory protection (specify type): OSHA 24 CFR/134 NIOSH/MSHA Approved respirators for particulates from buffing debris.

Hearing Protection Avoid prolonged excessive noise levels created by buffing and polishing operations.
 See: OSHA 29 CFR 1910.215 (Hearing Protection)

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

INGREDIENT B –Paint Thinner

Exposure Guidelines

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	No data	TLV: 200 mg/m ³	No Data
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	No data	No data	No data

SAFETY DATA SHEET
Intimidator Pro Polish

Printed: 05/19/16
Revision: 05/19/16
Supersedes Revision:

8052-41-3	Stoddard solvent (Mineral spirits; Aliphatic Petroleum Distillates; White spirits)	PEL: 500 ppm	TLV: 100 ppm	No data
95-63-6	1,2,4-Trimethylbenzene (Pseudocumene)	No data	No data	No data
111-84-2	Nonane	No data	TLV: 200 ppm	No data
25551-13-7	Benzene, Trimethyl-	No data	TLV: 25 ppm	No data
98-82-8	Cumene (Benzene, 1-Methylethyl-; Isopropylbenzene)	PEL: 50 ppm	TLV: 50 ppm	No data
100-41-4	Ethylbenzene (Ethylbenzol; Phenylethane)	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data

Engineering Measures Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering – Stop – ventilation is inadequate. Leave area immediately.

Individual Protection Measures, such as Personal protective equipment:

Eye/Face Protection Safety glasses, goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury.

Contact lenses should not be worn while working with chemicals.

Respiratory Equipment For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air controls not feasible, se properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Protective Gloves Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

Other Protective Clothing Various application methods can dictate use of additional protective safety equipment such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

Work/Hygienic/Maintenance Practices A source of clean water should be available in the work area or flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use.

SAFETY DATA SHEET
Intimidator Pro Polish

9. PHYSICAL AND CHEMICAL PROPERTIES

INGREDIENT A – Green Chrome Rouge Buffing Compound

Physical and Chemical Properties:

Physical State solid
Appearance pre-molded cake form
Color dark green
Odor fatty odor
Odor Threshold n/a

Property	Values	Remarks / Method
pH	No data available	None known
Melting/freezing point	131F	None known
Boiling point/boiling range	No data available	None known
Flash point	No data available	None known
Evaporation rate	Nil	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

Other Information:

Softening Point No data available
VOC Content (%) No data available
Particle Size No data available
Particle Size Distribution

INGREDIENT B –Paint Thinner

Physical States: [] Gas [X] Liquid [] Solid
Appearance: Water White / Free and Clear
Melting Point: No data
Boiling Point: 318.00F – 385.00 F
Autoignition Point: No data
Flash Point: >100.00 F
Explosive Limits: LEL: 0.5 UEL: 6
Specific Gravity (Water=1): 0.78

SAFETY DATA SHEET
Intimidator Pro Polish

Vapor Pressure
(vs. Air or mm Hg): 0.3 MM HG at 68.0 F
Vapor Density (vs.Air=1) 5 Air = 1
Evaporation Rate: No data
Solubility in Water: No data
Solubility Notes: Very slightly soluble in cold water.
Percent Volatile: 100.0% by weight.
VOC / Volume: 778.0000 G/L

10. STABILITY AND REACTIVITY

INGREDIENT A – Green Chrome Rouge Buffing Compound

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid (e.g. static discharge, shock, or vibration)

Using under conditions of insufficient dust collecting systems or ventilation.

Incompatible materials

Strong Oxidizers or Reducing Agents.

Hazardous decomposition byproducts

Carbon Oxides.

INGREDIENT B –Paint Thinner

Reactivity

No data available

Chemical stability

Unstable [] Stable [X]

Possibility of hazardous reactions

Will occur [] Will not occur [X]

Conditions to avoid (e.g. static discharge, shock, or vibration)

No data available

Incompatible materials

Incompatible with strong acids, alkalis, and oxidizers such as liquid chlorine and oxygen.

Hazardous decomposition byproducts

Decomposition may produce carbon monoxide and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

INGREDIENT A – Green Chrome Rouge Buffing Compound

Information on likely routes of exposure:

Product Information Product does not present an acute toxicity hazard based on known or supplied information.
Inhalation Specific test data for the substance or mixture is not available.
Eye Contact Specific test data for the substance or mixture is not available.
Skin Contact Specific test data for the substance or mixture is not available.
Ingestion Specific test data for the substance or mixture is not available.

Component Information

Chemical Name Aluminum Oxide 1344-28-1
Oral LD50 >5000mg/kg (Rat)
Decimal LD50 ---
Inhalation LC50 ---

Information on Toxicological Effects:

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Sensitization No information available
Mutagenic Effects No information available
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Chromium (III) Oxide 1308-38-9		Group 3		

IARC (International Agency for Research on Cancer)

Group 3 – Not Classifiable as to Carcinogenicity in Humans

Reproductive Toxicity No information available
STOT – single exposure No information available
STOT – repeated exposure No information available
Chronic Toxicity No known effect based on information supplied. Carcinogenic potential is unknown.
Target Organ Effects eyes, respiratory system, skin, lungs
Aspiration Hazard No information available

Numerical measures of toxicity Product Information

INGREDIENT B –Paint Thinner

Toxicological Information: **CAS# 111-84-2:**
 Open irritation test., Skin, Rat, 300.0L, 4 D, Moderate.
Result:
 Sense organs and special senses (nose, eye, ear, and taste): Ear: Changes in cochlear structure or function.

SAFETY DATA SHEET
Intimidator Pro Polish

Printed: 05/19/16
Revision: 05/19/16
Supersedes Revision:

Behavioral: Alteration of operant conditioning.
- Toxicology and Industrial Health., Princeton Scientific Pub. Co., POB 2155,
Princeton, NJ 08540, Vol/p/yr: 20,109,2004

CAS# 25551-13-7:

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.

Result:

Kidney, Ureter, Bladder: Changes in liver weight.

Endocrine: Changes in thymus weight.

Immunological Including Allergic: Decreased immune response.

- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24,1972

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, 24 H, Mild.

Result:

Kidney, Ureter, Bladder: Changes in liver weight.

Kidney, Ureter, Bladder: Changes in bladder weight.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24,1972

CAS# 100-41-4:

Tumorigenic Effects:, TClO, Inhalation, Rat, 750.0 ppm.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillates (petroleum)	n.a.	n.a.	A4	n.a.
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	n.a.	n.a.	n.a.	n.a.
8052-41-3	Stoddard solvent (Mineral spirits; Aliphatic Petroleum Distillates; White spirits)	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene (Pseudocumene)	n.a.	n.a.	n.a.	n.a.
111-84-2	Nonane	n.a.	n.a.	n.a.	n.a.
25551-13-7	Benzene, trimethyl-	n.a.	n.a.	n.a.	n.a.
98-82-8	Cumene (Benzene, 1-Methylethyl-; Isopropylbenzene)	n.a.	2B	n.a.	n.a.
100-41-4	Ethylbenzene (Ethylbenzol; Phenylethane)	n.a.	2B	A3	n.a.

12. ECOLOGICAL INFORMATION (non-mandatory)

INGREDIENT A – Green Chrome Rouge Buffing Compound

Ecotoxicity The environmental impact of this product has not been fully investigated.
Persistence and Degradability No information available.
Bioaccumulation No information available.
Other Adverse Effects No information available.

INGREDIENT B –Paint Thinner

No data available

13. DISPOSAL CONSIDERATIONS (non-mandatory)

INGREDIENT A – Green Chrome Rouge Buffing Compound

Waste Treatment Methods

Disposal Methods This material, as supplied is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

Chemical Name	RCRA	RCRA – Basis for Listing	RCRA – D Series Wastes	RCRA – U Series Wastes
Chromium (III) Oxide 1308-38-9			D007	

This

Chemical Name	California Hazardous Waste
Chromium (III) Oxide 1308-38-9	Toxic Corrosive Ignitable

product contains one or more substances that are listed

with the State of California as a hazardous waste.

INGREDIENT B –Paint Thinner

Waste Disposal Method Dispose in accordance with federal, state, and local regulations.

SAFETY DATA SHEET
Intimidator Pro Polish

Printed: 05/19/16
Revision: 05/19/16
Supersedes Revision:

14. TRANSPORT INFORMATION (non-mandatory)

INGREDIENT A – Green Chrome Rouge Buffing Compound

DOT	NOT REGULATED
Proper Shipping Name	NMFC-48580 Scouring Compound (Cake, Paste or Liquid form N.O.I.)
Hazard Class	N/A
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated
IATA	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
IMDG/IMO	Not regulated
Hazard Class	N/A
RID	Not regulated
ADR	Not regulated
ADN	Not regulated

INGREDIENT B –Paint Thinner

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material, Not Regulated
DOT Hazard Class:
UN/NA Number:

Additional Transport Information: For D.O.T.

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

SAFETY DATA SHEET
Intimidator Pro Polish

15. REGULATORY INFORMATION (non-mandatory)

INGREDIENT A – Green Chrome Rouge Buffing Compound

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.
TSCA – United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL – Canadian Domestic Substances List/Non-Domestic Substance List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS No	Weight-%	SARA 313 – Threshold Values %
Aluminum Oxide 1344-28-1	1344-28-1	30 – 60	1.0
Chromium (III) Oxide – 1308-38-9	1308-38-9	15 – 40	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA – Reportable Quantities	CWA – Toxic Pollutants	CWA – Priority Pollutants	CWA – Hazardous Substances
Chromium (III) Oxide 1308-38-9		X		

CERCLA

This material, as supplied, does not contain any substances regulate as hazardous substances under the Comprehensive Environment Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of the material.

SAFETY DATA SHEET

Intimidator Pro Polish

Printed: 05/19/16
Revision: 05/19/16
Supersedes Revision:

U.S. State Regulations:

California Proposition 65 - This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Aluminum Oxide 1344-28-1	x	x	x	x	
Chromium (III) Oxide 1308-38-9	x	x	x	x	x
Supplier Trade Secret			x		

International Regulations:

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Aluminum Oxide 1344-28-1 (30 – 60)		Mexico: TWA = 10 mg/m ³
Chromium (III) Oxide 1308-38-9 (15 – 40)		Mexico: TWA 0.5 mg/m ³

Mexico – Occupational Exposure Limits – Carcinogens

Canada

WHMIS Hazard Class Non-controlled

INGREDIENT B –Paint Thinner

This material meets the EPA “Hazard Categories” defined for SARA Title III Sections 311/312 as indicated:

<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Acute (immediate) Health Hazard
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Chronic (delayed) Health Hazard
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Fire Hazard
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Sudden Release of Pressure Hazard
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP, ODC: No; CWA NPDES: No; TSCA: Yes – Inventory; CA PROP.65: No
64742-82-1	Naphtha (petroleum, hydrodesulfurized heavy	CAA HAP, ODC: No; CWA NPDES: NO; TSCA: Yes – Inventory; CA PROP.65: No
8052-41-3	Stoddard solvent (Mineral spirits; Aliphatic Petroleum Distillates; White spirits)	CAA HAP, ODC: No; CWA NPDES: NO; TSCA: Yes – Inventory; CA PROP.65: No
95-63-6	1,2,4- Trimethylbenzene (Pseudocumene)	CAA HAP, ODC: No; CWA NPDES: NO; TSCA: Yes – Inventory; CA PROP.65: No
111-84-2	Nonane	CAA HAP, ODC: No; CWA NPDES: No; TSCA: Yes – Inventory, 4 Test, BA PAIR; CA PROP.65: No
25551-13-7	Benzene, Trimethyl-	CAA HAP, ODC: No; CWA NPDES: No; TSCA: Yes – Inventory; CA PROP. 65: No
98-82-8	Cumene (Benzene, 1-Methylethyl-; Isopropylbenzene)	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP. 65: Yes
100-41-4	Ethylbenzene (Ethylbenzol; Phenylethane)	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes – Inventory, 4 Test; CA PROP. 65: Yes

Regulatory Information Statement: All components of this material are listed on the TSCA inventory or are exempt.

16. OTHER INFORMATION

INGREDIENT A – Green Chrome Rouge Buffing Compound

NFPA	Health Hazards 1	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 1	Flammability 0	Physical Hazard 0	Personal Protection X

Revision Date

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

INGREDIENT B –Paint Thinner

Revision Date 7-14-2023
Preparer Name The Intimidator

Additional Information
About this product: No data available

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.