



**XTREMEPRO SERIES**

**PRO SERIES**

**PALLETPRO SERIES**

**SEMIPRO SERIES**

**COMPRESSORS,  
KITS &  
ACCESSORIES**

**CORDLESS**

**FASTENERS**

**DURASPIN**

**SMART SERIES**

**HIGH LOAD TOOLS**



## SENCO INTRODUCTION

Senco is one of the most recognised brands in the world of pneumatic fastening systems and produces a wide range of pneumatic, electric, gas and battery powered fastening tools.

Senco fastening tools are divided into series ranges: XtremePro, Pro, Semi-Pro, PalletPro and the unique DuraSpin collated fastening system. Every tool delivers top level performance.

In additionally, there is the cordless range of nailers and pinners based on the unique Fusion technology and a gas powered tools. Senco also offer a complete range of high quality compressors, pneumatic screwdrivers and drills.

Senco Tools support a wide range of high quality fasteners designed to meet all industry standards and application requirements.



## INDEX

CHAPTER	PAGE
Senco Introduction	2
Icons	4
Product lines for each application	5
XtremePro series	6 - 19
Pro series	20 - 39
PalletPro series	40 - 45
SemiPro series	46 - 51
Compressors, kits & accessories	52 - 63
Cordless	64 - 71
Fasteners	72 - 85
Coding chart	86 - 91
DuraSpin	92 - 103
Smart series	104 - 109
High load tools	110 - 113
Senco distributors	114 - 115
Application / tool index	116 - 120
Index	122 - 123



MAKING HARD WORK  
**EASIER**

## ICONS



### WOOD CONSTRUCTION

Carpentry, timber frame construction, remodeler solutions such as battens, mouldings, constructive connections, thermal insulation systems, frame connections, steel sheets, shingles, flooring.



### DRYWALL

Screw connections in the static and nonstatic applications such as gypsum board to metal or wood, gypsum fibre boards on wood substructure, sound insulation.



### GENERAL JOINERY

Carpentry, assembly, stair construction, windows, doors, interior design, furniture boards, panelling, profile boards, panels, tongue & groove, furniture, flooring, ceiling, wall fittings, decking, glazing bead.



### DISPLAY

Exhibition construction, point of sale items, packaging, display boxes, upholstery work, fixing fabrics, leather.



### FURNITURE

Furniture frames, drawer assembly, cabinets, upholstery.



### PALLET INDUSTRY

Manufacture and repair of boxes, box parts, stalls, single and multiple-way pallets, product and shipping packaging.



### ROOFING/SHEATHING

Substructures, panels, facade and roof production, roof and facade shingles, slides, roof panels.



### AUTOMOTIVE

Seat manufacture, upholstery.



### UPHOLSTERY

For the fixing of foam and textiles to each other or on other substrates.



### PACKAGING

Packaging, boxes, crates, cardboard packaging.



### BEDDING

Divan, mattress and headboard manufacturing



### STEEL

Steel applications



### CONCRETE

Concrete applications



All Senco EMEA. Tools are marked with the CE-mark, and therefore meet the strict European CE regulations. On request we can provide you with specific sound and vibration information of specific tools.



**1 year limited warranty** after date of purchase and applies to defects in material and production, excluding wearing parts, problems due to lack of maintenance, overload and usage of non-Senco parts and/or fasteners.



**2 year limited warranty** after date of purchase and applies to defects in material and production, excluding wearing parts, problems due to lack of maintenance, overload and usage of non-Senco parts and/or fasteners.



**5 year limited warranty** after date of purchase and applies to defects in material and production, excluding wearing parts, problems due to lack of maintenance, overload and usage of non-Senco parts and/or fasteners.



**The tool will be delivered in a case**



**The tool is also available in a case**



**Oil free**



**The tool is powered by a fuel cell**



## PRODUCTLINE FOR EVERY APPLICATION



### XTREMEPRO SERIES

Xtreme quality for industrial applications. Elite tools built with the highest quality for 24/7 use in the toughest industrial environments. Features of these top of the line tools are: internal design of highest quality materials for maximum durability and performance.



### PRO SERIES

Professional tools designed for professional end-users. Designed without compromise for professional every day use. The tools in the Pro Series reflect Senco's 60 year reputation in reliability and performance.



### PALLETPRO SERIES

Specifically designed for long-term usage in the pallet and packaging industry. The tools in the PalletPro Series are perfectly balanced and very powerful, which enables long-term use. Features of the PalletPro Series are: rapid fire with a superb reliability and low maintenance.



### SEMIPRO SERIES

Senco quality for the professional home and garden user. The SemiPro Series is specifically designed for professional use where tools are used less frequent.



### SENCO COMPRESSORS

For every application there's a Senco compressor. In addition to high quality professional tools, Senco also has a complete range of high quality compressors. There are oil-less and oil lube versions available for a wide range of applications. Senco compressors are designed to run at least 3.000 hours, leaving the competition behind.



### CORDLESS

Cordless convenience, pneumatic power. Senco nailers with Fusion Technology use compressed air that is permanently sealed in the tool's self-contained, built-in cylinder to unleash a shot of pure, portable pneumatic power every time you pull the trigger. There's no ramp up time and virtually no cleaning or servicing costs.



### FASTENERS

Senco fasteners guarantee a fault-free use of Senco tools and a perfect finish. All Senco fasteners are produced according to international standards, like CE.



### DURASPIN

Collated screw fastening systems. The DuraSpin Collated Screw Fastening System Family is the professionals' choice for demanding drywall and wood fastening applications. The perfect solution for high productivity screwing as well as a single man operation. Senco DuraSpin will dramatically increase your productivity.



### SMART SERIES

The Senco Smart solutions are ergonomic designed for increased product quality and a safer work environment.



### HIGH LOAD TOOLS

The Senco High Load tools are designed for high volume, consistent and accurate fastening capable of repetitive stapling for improved productivity.

# MAKING HARD WORK EASIER

# XTREMEPRO SERIES



XTREME QUALITY

RED CAP, GREY ACCENT



CAST & GROUND  
SENCO LOGO



24/7 USAGE

Xtreme quality for industrial applications. Elite tools built with the highest quality for 24/7 use in the toughest industrial environments. Features of these top of the line tools are: internal design of highest quality materials for maximum durability and performance.







**SENCO®**

**WELL-BALANCED,  
ERGONOMIC DESIGN**

## **XTREMEPRO SERIES**

Xtreme quality for  
24/7 use

**TRIGGER FUNCTION VISIBLE  
WITH COLOUR**

**ROTATABLE BELT HOOK**



**COMFORTABLE GRIP,  
REDUCES FATIGUE**

**FOR INDUSTRIAL  
APPLICATIONS**

**5** YEAR  
LIMITED  
WARRANTY



**MAKING HARD WORK  
EASIER**

# STAPLERS

## LIGHT WIRE STAPLER SFT10XP



### TECHNICAL INFORMATION

Length	218 mm
Width	42 mm
Height	167 mm
Weight	1,0 kg
Actuation	TF/Automatic
Air inlet	1/4" NPT
Operating pressure	4,1-6,5 bar
Air consumption	19,8 l/min
Magazine capacity	180


### APPLICATIONS

Upholstering operations, furniture assembly, cabinets, interior trim, bedding manufacture, picture frames, molding and roofing felt

### FEATURES

- One-handed magazine opening
- Rear exhaust
- Comfort grip
- Short trigger stroke

DESCRIPTION	ART. NR.
SFT10XP A/D TF	6S2001N
SFT10XP B TF	6S2011N
SFT10XP B Auto	6S2111N
SFT10XP C TF	6S2021N
SFT10XP C Auto	6S2121N
SFT10XP E TF	6S2031N
SFT10XP F TF	6S2041N
SFT10XP G TF	6S2051N
SFT10XP AT TF	6S2061N
SFT10XP AT Auto	6S2161N



## LIGHT WIRE STAPLER SFT10XP-DL



### TECHNICAL INFORMATION

Length	375 mm
Width	42 mm
Height	167 mm
Weight	1,0 kg
Actuation	TF/Automatic
Air inlet	1/4" NPT
Operating pressure	4,1-6,5 bar
Air consumption	19,8 l/min
Magazine capacity	390


### APPLICATIONS

Upholstering operations, furniture assembly, cabinets, interior trim, bedding manufacture, picture frames, molding and roofing felt

### FEATURES

- One-handed magazine opening
- Rear exhaust
- Comfort grip
- Short trigger stroke
- Double length magazine

DESCRIPTION	ART. NR.
SFT10XP B TF D/L Magazine	6S2211N
SFT10XP C TF D/L Magazine	6S2221N
SFT10XP C Auto D/L Magazine	6S2321N
SFT10XP F Auto D/L Magazine	6S2341N
SFT10XP G Auto D/L Magazine	6S2351N
SFT10XP AT Auto D/L Magazine	6S2361N







# SENCO®

## LIGHT WIRE STAPLER SFT10XP-LN



## MEDIUM WIRE STAPLER SLS20XP



## MEDIUM WIRE STAPLER SLS25XP



### TECHNICAL INFORMATION

Length	305 mm
Width	51 mm
Height	218 mm
Weight	1,0 kg
Actuation	TF/Automatic
Air inlet	1/4" NPT
Operating pressure	4,1-6,5 bar
Air consumption	19,8 l/min
Magazine capacity	180

### APPLICATIONS

Upholstering operations, furniture assembly, cabinets, interior trim, bedding manufacture, picture frames, molding and roofing felt

### FEATURES

- One-handed magazine opening
- Rear exhaust
- Comfort grip
- Short trigger stroke
- For deep reach applications

### DESCRIPTION

DESCRIPTION	ART. NR.
SFT10XP C - long nose	6S2421N
SFT10XP AT - long nose	6S2461N



### TECHNICAL INFORMATION

Length	305 mm
Width	51 mm
Height	216 mm
Weight	1,1 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	54 l/min
Magazine capacity	168

### APPLICATIONS


Furniture, cabinets, paneling, upholstery, siding, fencing

### FEATURES

- Oil free
- Lightweight
- Ergonomic design
- No-Mar pad
- Depth adjustment
- Comfort Grip

### DESCRIPTION

DESCRIPTION	ART. NR.
SLS20XP-K BF(TF)	492026N
SLS20XP-L BF(TF) + Case	492023N
SLS20XP-M BF(TF) + Case	492024N
SLS20XP-M BF/Auto	492009N
M SENCOMATIC	490009N
L SENCOMATIC	MD0023



### TECHNICAL INFORMATION

Length	305 mm
Width	51 mm
Height	229 mm
Weight	1,2 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	54 l/min
Magazine capacity	168

### APPLICATIONS


Furniture, cabinets, paneling, upholstery, siding, fencing

### FEATURES

- Oil free
- Lightweight
- Ergonomic design
- Suitable for high volume production environments
- Depth adjustable

### DESCRIPTION

DESCRIPTION	ART. NR.
SLS25XP-L BF(TF)	822009N
SLS25XP-M BF(TF)	822010N



# STAPLERS

## MEDIUM WIRE STAPLER SKSXP



### TECHNICAL INFORMATION

Length	314 mm
Width	51 mm
Height	238 mm
Weight	1,9 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	61 l/min
Magazine capacity	160


### APPLICATIONS

Furniture, cabinets, paneling, upholstery, sidings, doors & window casings

### FEATURES

- Oil free
- Lightweight
- Low maintenance
- Only 2 moving O-rings
- Long 25mm lip to get into tight spots

DESCRIPTION	ART. NR.
SKSXP-L BF/TF	302020N
SKSXP-L TF	302028N
SKSXP-M BF/TF	302052N
SKSXP-M TF	302060N
SKSXP-N BF/TF	302084N



## HEAVY WIRE STAPLER SHS50XP



### TECHNICAL INFORMATION

Length	381 mm
Width	89 mm
Height	279 mm
Weight	2,3 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8 - 8,3 bar
Air consumption	90 l/min
Magazine capacity	160


### APPLICATIONS

Sheathing, furniture framing, subflooring, crate & box assembly, pallets, shingles

### FEATURES

- 15% more powerful than all other construction staplers in its class
- Adjustable depth of drive
- Better balance
- All metal magazine
- 25mm lip length for access into tight corners

DESCRIPTION	ART. NR.
SHS50XP-N(O) TF/BF	7B2001N



## HEAVY WIRE STAPLER SHS51XP



### TECHNICAL INFORMATION

Length	381 mm
Width	102 mm
Height	279 mm
Weight	2,4 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8 - 8,3 bar
Air consumption	90 l/min
Magazine capacity	160


### APPLICATIONS

Sheathing, furniture framing, subflooring, crate & box assembly, pallets, shingles

### FEATURES

- 20% more powerful than the SHS50XP
- Adjustable depth of drive
- Better balance
- All metal magazine
- 25mm lip length for access into tight corners

DESCRIPTION	ART. NR.
SHS51XP-N(O) TF/BF	7C2001N







# SENCO®

## HEAVY WIRE STAPLER SNS50XP



## HEAVY WIRE STAPLER SQS55XP



### TECHNICAL INFORMATION

Length	365 mm
Width	92 mm
Height	305 mm
Weight	2,7 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	185 l/min
Magazine capacity	160

### APPLICATIONS

Framework, sub-floors, sheathing, furniture framing, pallets, cedar shingles, crates, fascia & soffits

### FEATURES

- Robust design for intensive use
- Adjustable power
- Adjustable depth of drive
- Up to 15 shots per sec.
- Reload indicator

### DESCRIPTION

DESCRIPTION	ART. NR.
SNS50XP BF/TF-63mm	XL3057
SNS50XP TF-63mm	XL3057R



### TECHNICAL INFORMATION

Length	365 mm
Width	92 mm
Height	305 mm
Weight	2,7 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	185 l/min
Magazine capacity	130

### APPLICATIONS


Framework, sub-floors, lathing, plate material, furniture hulls, pallets, crates, decking

### FEATURES

- Rugged dependability
- Adjustable exhaust
- Adjustable depth of drive
- Up to 15 shots per sec.
- EZ-Clear Nose

### DESCRIPTION

DESCRIPTION	ART. NR.
SQS55XP BF/TF	662001N
SQS55XP TF	662002N
SQS55XP Automatic	EJ00300
SQS55XP-S BF/TF-90mm	XL3089
SQS55XP-S TF-90mm	XL3089R



# STAPLERS / STRIPNAILERS

## WIDE CROWN STAPLER WC150XP



## WIDE CROWN STAPLER WC200XP



## BRAD NAILER 1,2MM SLP20XP



### TECHNICAL INFORMATION

Length	387 mm
Width	89 mm
Height	225 mm
Weight	2,3 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	90 l/min
Magazine capacity	160


### APPLICATIONS

Lathing, roof and wall felt, furniture, frames, cardboard onto pallets, packaging, insulation board, butt joints

### FEATURES

- Rugged design
- Lightweight
- Adjustable depth of drive
- Large staple capacity
- EZ-Clear Nose

DESCRIPTION	ART. NR.
WC150XP BF/TF	4W2001N
Block out kit for short staples (P08-P11)	YK0786
Pogostick	VC0371



### TECHNICAL INFORMATION

Length	387 mm
Width	89 mm
Height	254 mm
Weight	2,4 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	97 l/min
Magazine capacity	160


### APPLICATIONS

Lathing, roof and wall felt, furniture, frames, cardboard onto pallets, packaging, insulation board, butt joints

### FEATURES

- Rugged design
- Lightweight
- Adjustable depth of drive
- Large Staple capacity
- EZ-Clear Nose

DESCRIPTION	ART. NR.
WC200XP BF/TF	4Y2001N
Pogostick	VC0371



### TECHNICAL INFORMATION

Length	241 mm
Width	50 mm
Height	210 mm
Weight	1,0 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	54 l/min
Magazine capacity	110


### APPLICATIONS

Mouldings, furniture decoration, glass slats, cabinets and drawer cabinets, rattan furniture, finishing

### FEATURES

- Oil free
- Lightest on the market in its class
- Easy to maintain
- EZ-Clear Nose

DESCRIPTION	ART. NR.
SLP20XP TF	432001N





# SENCO®

## BRAD NAILER 1,2MM SLP20XP GLN



## BRAD NAILER 1,2MM SBN10XP



## HEADLESS BRAD NAILER LS1XP



### TECHNICAL INFORMATION

Length	241 mm
Width	50 mm
Height	210 mm
Weight	1,0 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	54 l/min
Magazine capacity	110

### APPLICATIONS

Window beading, secret nailing


### FEATURES

- Oil free
- Lightest on the market in its class
- Easy to maintain
- EZ-Clear Nose

### DESCRIPTION

DESCRIPTION	ART. NR.
SLP20XP GLN 4mm	WCE0472
SLP20XP GLN 7mm	WCE0485

AX 16-42 x 1,2



### TECHNICAL INFORMATION

Length	255 mm
Width	42 mm
Height	167 mm
Weight	0,9 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,5-7,0 bar
Air consumption	19 l/min
Magazine capacity	105

### APPLICATIONS

Mouldings, furniture decoration, trim, beading, cabinets and drawers, rattan furniture, finishing

### FEATURES

- Compact design- use in tight spaces
- Superior balance with minimal recoil
- One handed magazine opening
- Short trigger stroke

### DESCRIPTION

DESCRIPTION	ART. NR.
SBN10XP mini AX brad nailer	8K2001N

AX 12-25 x 1,2



### TECHNICAL INFORMATION

Length	229 mm
Width	51 mm
Height	210 mm
Weight	1,3 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	19 l/min
Magazine capacity	100

### APPLICATIONS

Panels, molding, finish and trim, rattan furniture, window beading, nailable plastic parts, cabinets and drawers, mirror and picture frames

### FEATURES

- Muffler ensures quieter operation
- Comfort grip
- Bottom loading magazine for quick loading
- Oil free
- Tapered nose

### DESCRIPTION

DESCRIPTION	ART. NR.
LS1XP AZ brad nailer	8N2001N

AZ 13-25 x 1,2



# STRIPNAILERS

## BRAD NAILER 1,2MM FINISHPRO25XP



### TECHNICAL INFORMATION

Length	249 mm
Width	56 mm
Height	251 mm
Weight	1,2 kg
Actuation	Restrictive
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	54 l/min
Magazine capacity	110



### APPLICATIONS

Mouldings, furniture decoration, trim, beading, cabinets and drawers, rattan furniture, finishing

### FEATURES

- Oil free
- Adjustable depth of drive
- Comfort grip
- Belt hook
- Drives both slight & medium head brads

DESCRIPTION	ART. NR.
FinishPro25XP TF	762002N



## FINISH NAILER FINISHPRO42XP



### TECHNICAL INFORMATION

Length	330 mm
Width	89 mm
Height	292 mm
Weight	2,1 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	110 l/min
Magazine capacity	104


### APPLICATIONS

Baseboards, cabinets, frames, door & window frames, skirting boards, exterior trim, furniture manufacture, dado & architrave

### FEATURES

- Oil free
- Adjustable depth of drive
- EZ-Clear Nose
- Comfort grip
- Belt hook

DESCRIPTION	ART. NR.
FinishPro42XP BF/TF	4G2003N



## CLIPPED HEAD NAILER SN90CXP



### TECHNICAL INFORMATION

Length	384 mm
Width	106 mm
Height	337 mm
Weight	3,62 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	283 l/min
Magazine capacity	70




### APPLICATIONS

Framing, truss building, subflooring, sheathing, decking, siding, fencing, pallets and crate assembly

### FEATURES

- Fixed firing valve improves tool life and speed
- Overmold grip and trigger
- 360° adjustable exhaust
- Aggressive sawtooth safety
- Selectable trigger

DESCRIPTION	ART. NR.
SN90CXP BF/TF	2H2001N





# SENCO®

## FULL ROUND HEAD NAILER SN90FXP



∠ 20°



## FULL ROUND HEAD NAILER SN90FXP+



∠ 20°



### TECHNICAL INFORMATION

Length	508 mm
Width	106 mm
Height	337 mm
Weight	3,8 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	283 l/min
Magazine capacity	60

### APPLICATIONS

Timber frame construction, sub-floors, framing, sheathing, pallets and crates, decking, furniture frame assembly

### FEATURES


- 20° in-line magazine provides excellent maneuverability and line of sight
- Simple two-step loading
- Aggressive toenail safety
- Fits easily between studs and joists

### DESCRIPTION

SN90FXP BF/TF

### ART. NR.

2K2001N



### TECHNICAL INFORMATION

Length	508 mm
Width	106 mm
Height	362 mm
Weight	3,97 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	311 l/min
Magazine capacity	60

### APPLICATIONS

Timber frame construction, sub-floors, framing, sheathing, pallets and crates, decking, furniture frame assembly

### FEATURES


- 20° in-line magazine provides excellent maneuverability and line of sight
- Simple two-step loading
- Aggressive toenail safety
- Fits easily between studs and joists

### DESCRIPTION

SN90FXP+ BF/TF

### ART. NR.

2F2001N



# COILNAILERS / SPECIALTY TOOLS

## COILNAILER SCN49XP



∠ 15-16°

## COILNAILER SCN65XP



∠ 16°

## COILNAILER ROOFPRO455XP



∠ 16°



### TECHNICAL INFORMATION

Length	305 mm
Width	128 mm
Height	285 mm
Weight	2,3 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	111 l/min
Magazine capacity	250-375


### APPLICATIONS

Cladding, underlayment, garden products, pallets and crates, gate and fence construction

### FEATURES

- Selectable trigger
- Adjustable depth of drive
- Well balanced and lightweight
- Drives wire and plastic collated flat coilnails

DESCRIPTION	ART. NR.
SCN49XP coilnailer	5J2001N



### TECHNICAL INFORMATION

Length	327 mm
Width	137 mm
Height	359 mm
Weight	3,6 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	270 l/min
Magazine capacity	225-275


### APPLICATIONS

Timber frame constructions, framing, sheathing, decking, sub-floors, pallets and crates

### FEATURES

- Highest power to weight ratio in its class
- Adjustable depth of drive
- High firing rate-high productivity
- EZ-load design saves time

DESCRIPTION	ART. NR.
SCN65XP BF/TF	542001N



### TECHNICAL INFORMATION

Length	260 mm
Width	114 mm
Height	267 mm
Weight	2,5 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	185 l/min
Magazine capacity	120


### APPLICATIONS

Asphalt shingles, tar paper, waterproof metal drip edges, paneling, cement board

### FEATURES

- Manual depth setting
- Adjustable shingle guidance
- Aluminium mainbody & cap
- Steel wearplates reduce shingle abrasion
- Jaws for nail guidance

DESCRIPTION	ART. NR.
RoofPro455XP	3D2011N







# SENCO®

## CONCRETE NAILER SAP40XP



## SENCLAMP FASTENER SC1XP



### TECHNICAL INFORMATION

Length	463 mm
Width	114 mm
Height	310 mm
Weight	3,2 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	147 l/min
Magazine capacity	42

### APPLICATIONS

Nailing into concrete, masonry & steel

### FEATURES


- Well balanced, rugged design
- Magnesium body
- Uses up to 15% less air than competitor tools
- Functions with a "low pressure" compressor

### DESCRIPTION

SAP40XP BF/TF

### ART. NR.

5V9201N



### TECHNICAL INFORMATION

Length	322 mm
Width	82 mm
Height	249 mm
Weight	2,8 kg
Actuation	TF
Air inlet	3/8" NPT
Operating pressure	5,5-7,5 bar
Air consumption	108 l/min
Magazine capacity	120

### APPLICATIONS

Butt joints, cabinets, door and window frames, picture frames, furniture

### FEATURES

- Pulls joints together while the adhesive cures
- Replaces expensive, time consuming solutions such as screws or clamps
- Provide twice the joint strength of ordinary fasteners

### DESCRIPTION

SC1XP TF

### ART. NR.

220101N



# SPECIALTY TOOLS

## PLIER TOOL DFPXP



## PLIER TOOL F75LXP



## PLIER TOOL F75SXP



### TECHNICAL INFORMATION

Length	380 mm
Width	75 mm
Height	327 mm
Weight	2,2 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,5-7,0 bar
Air consumption	26 l/min
Magazine capacity	230

### APPLICATIONS

Corrugated box fabrication, packaging, displays, light assembly

### FEATURES

- High capacity (230 staples) magazine
- Comfort grip
- 175mm throat allows for extended reach into cartons
- Tool-free adjustable anvil opening

### DESCRIPTION

DFPXP TF

### ART. NR.

8H2001N



### TECHNICAL INFORMATION

Length	380 mm
Width	75 mm
Height	327 mm
Weight	2,2 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,5-7,0 bar
Air consumption	33 l/min
Magazine capacity	230

### APPLICATIONS

Corrugated box fabrication, bed manufacturing, packaging

### FEATURES

- High capacity (152 staples) magazine
- Comfort grip
- 175mm throat allows for extended reach into cartons
- Tool-free adjustable anvil opening

### DESCRIPTION

F75LXP TF

### ART. NR.

8J2002N



### TECHNICAL INFORMATION

Length	380 mm
Width	75 mm
Height	327 mm
Weight	2,2 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,5-7,0 bar
Air consumption	33 l/min
Magazine capacity	230

### APPLICATIONS

Corrugated box fabrication, bed manufacturing, packaging

### FEATURES


- High capacity (152 staples) magazine
- Comfort grip
- Tool-free adjustable anvil opening

### DESCRIPTION

F75SXP TF

### ART. NR.

8J2001N





**SENCO®**

## PLIER TOOL FAT25



### TECHNICAL INFORMATION

Length	380 mm
Width	75 mm
Height	320 mm
Weight	2,1 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,5-7,0 bar
Air consumption	33 l/min
Magazine capacity	170

### APPLICATIONS

Mattress plastic and cloth stapling, Upholstered, Furniture, Plastic tanks (paint bins etc.), Cardboard packaging

### FEATURES


- The jaw opening is adjustable by simply turning the screw on the top of the tool
- Comfort grip
- Rear exhaust
- Bottom load double length magazine
- Jaw openings are both wide and deep

### DESCRIPTION

FAT25 TF

### ART. NR.

FAT25





# PRO SERIES



GREY CAP



PROFESSIONAL USE



Designed without compromise for professional every day use The tools in the Pro Series reflect Senco's 60 year reputation in reliability and performance.





**SENCO®**

**TRIGGER FUNCTION VISIBLE  
WITH COLOUR**

## PRO SERIES

Professional tools  
designed for every day use



**REDUCES FATIGUE**

**LIGHT WEIGHT  
MAGNESIUM BODY**

**WIDEST RANGE  
OF SENCO TOOLS**

**1 YEAR  
LIMITED  
WARRANTY**

**PRO  
SERIES**

MAKING HARD WORK  
**EASIER**

# STAPLERS

## LIGHT WIRE STAPLER SFW09



### TECHNICAL INFORMATION

Length	241 mm
Width	49 mm
Height	151 mm
Weight	0,9 kg
Actuation	TF/Automatic
Air inlet	1/4" NPT
Operating pressure	4,1-6,5 bar
Air consumption	23 l/min
Magazine capacity	110-185

### APPLICATIONS

Upholstering operations, furniture assembly, cabinets, automotive vinyl roofs and interior trim, bedding manufacture, picture frames, shoemaking, molding, roofing felt

### FEATURES

- Long 25mm lip
- Rounded steel cap
- Rear exhaust
- Rear magazine bumper
- Comfort grip

DESCRIPTION	ART. NR.
SFW09 AT	4C2021N
SFW09 AT Automatic	4C2051N
SFW09 A	4C2031N
SFW09 B	4C2012N
SFW09 B Automatic	4C2061N
SFW09 C	4C2001N
SFW09 C Automatic	4C2071N
SFW09 F	4C2041N
SFW09 AT leather grip	4C2021N-1
SFW09 A leather grip	4C2031N-1



## MEDIUM WIRE STAPLER SLS18MG



### TECHNICAL INFORMATION

Length	260 mm
Width	64 mm
Height	241 mm
Weight	1,2 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	68 l/min
Magazine capacity	110



### APPLICATIONS

Cabinets, furniture, drawer assembly, case backs, picture frames

### FEATURES

- Magnesium body
- Oil free
- Adjustable depth of drive
- Selectable trigger
- Comfort grip

DESCRIPTION	ART. NR.
SLS18-L Mg BF/TF	1W2025N
SLS18-M Mg BF/TF	1W2026N
SLS18-92 Mg BF/TF	1W2027N







# SENCO®

## MEDIUM WIRE STAPLER SMS92



## HEAVY WIRE STAPLER SNS41



## WIDE CROWN STAPLER WC330-SP



### TECHNICAL INFORMATION

Length	310 mm
Width	78 mm
Height	274 mm
Weight	1,9 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	55 l/min
Magazine capacity	160

### APPLICATIONS

Furniture frames, drawer assembly, upholstery

### FEATURES

- Magnesium body
- Special developed guiding mechanism
- 360° adjustable exhaust
- Selectable trigger
- Quick release mechanism

### DESCRIPTION

SMS92 BF/TF

### ART. NR.

1VS2003N



### TECHNICAL INFORMATION

Length	381 mm
Width	75 mm
Height	273 mm
Weight	2,1 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	153 l/min
Magazine capacity	160

### APPLICATIONS

Framework, sub-floors, sheathing, furniture framing, pallets, ramps and gates, crates, fascia & soffits

### FEATURES

- Durable design
- Adjustable depth of drive
- 360° adjustable exhaust
- EZ-Clear Nose
- Comfort grip
- Reload indicator


### DESCRIPTION

SNS41 BF/TF

### ART. NR.

3L2003N

SNS41 TF 3L2004N



### TECHNICAL INFORMATION

Length	397 mm
Width	133 mm
Height	400 mm
Weight	5,9 kg
Actuation	TF
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	176 l/min
Magazine capacity	120

### APPLICATIONS

To fasten (thermowall) insulating materials. Planking wooden outside frames with wood fibre board and wood wool sandwich board.

### FEATURES


- Ergonomic design
- Adjustable depth of drive
- Available with extra handle for higher user convenience

### DESCRIPTION

WC330-SP TF

### ART. NR.

6P2001N



# STRIPNAILERS

## WIDE CROWN STAPLER WC360-SP



## MICROPINNER 0,6MM FINISHPRO10



## BRAD NAILER 1,2MM FINISHPRO18MG



### TECHNICAL INFORMATION

Length	400 mm
Width	138 mm
Height	470 mm
Weight	6,3 kg
Actuation	TF
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	261 l/min
Magazine capacity	120

### APPLICATIONS

To fasten (thermowall) insulating materials. Planking wooden outside frames with wood fibre board and wood wool sandwich board.

### FEATURES


- Ergonomic design
- Adjustable depth of drive
- Available with extra handle for higher user convenience

### DESCRIPTION

WC360-SP TF

### ART. NR.

7E2001N



### TECHNICAL INFORMATION

Length	225 mm
Width	41 mm
Height	171 mm
Weight	1,1 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	22 l/min
Magazine capacity	110

### APPLICATIONS

Mouldings, glazing beads, furniture decoration, cabinets and drawers, rattan furniture

### FEATURES


- Rear exhaust
- Adjustable depth of drive
- Reload indicator
- Extra powerful
- Magazine bumper pad

### DESCRIPTION

FinishPro10 TF

### ART. NR.

2C2001N



### TECHNICAL INFORMATION

Length	267 mm
Width	64 mm
Height	248 mm
Weight	1,1 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	68 l/min
Magazine capacity	110

### APPLICATIONS

Mouldings, furniture decoration, trim, beading, cabinets and drawers, rattan furniture, finishing

### FEATURES


- Magnesium body
- Oil free
- Adjustable depth of drive
- Selectable trigger
- Comfort grip

### DESCRIPTION

FinishPro18Mg BF/TF

### ART. NR.

1U2025N





# SENCO®

## BRAD NAILER 1,6MM FINISHPRO32



## FINISH NAILER FINISHPRO35MG



∠ 34°



## FINISH NAILER SFN30



∠ 34°



### TECHNICAL INFORMATION

Length	307 mm
Width	76 mm
Height	267 mm
Weight	1,9 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	62 l/min
Magazine capacity	110


### APPLICATIONS

Baseboards, frames, skirting boards, trim, architrave, dado, moldings

### FEATURES

- Adjustable depth of drive
- EZ-Clear Nose
- 360° adjustable exhaust
- Comfort grip

DESCRIPTION	ART. NR.
FinishPro32 TF + Case	1X2201N
FinishPro32 BF/TF	1X2202N



### TECHNICAL INFORMATION

Length	330 mm
Width	86 mm
Height	311 mm
Weight	2,1 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	128 l/min
Magazine capacity	104


### APPLICATIONS

Baseboards, cabinets, frames, door & window frames, skirting boards, exterior trim, furniture manufacture, dado & architrave

### FEATURES

- Adjustable depth of drive
- EZ-Clear Nose
- 360° adjustable exhaust
- Comfort grip

DESCRIPTION	ART. NR.
FinishPro35Mg BF/TF	6G2001N



### TECHNICAL INFORMATION

Length	305 mm
Width	83 mm
Height	244 mm
Weight	1,6 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	61 l/min
Magazine capacity	104


### APPLICATIONS

Baseboards, cabinets, frames, door & window frames, skirting boards, exterior trim, furniture manufacture, dado & architrave

### FEATURES

- Oil-free
- Lightweight
- Adjustable depth of drive
- No-Mar pad

DESCRIPTION	ART. NR.
SFN30 BF/TF	622002N
SFN30 TF	622003N





# STRIPNAILERS

## CLIPPED HEAD NAILER SIDINGPRO40



∠ 34°



## CLIPPED HEAD NAILER FRAMEPRO601



∠ 34°



## CLIPPED HEAD NAILER FRAMEPRO651



∠ 34°



### TECHNICAL INFORMATION

Length	351 mm
Width	86 mm
Height	322 mm
Weight	2,1 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	173 l/min
Magazine capacity	70

### APPLICATIONS



Siding, sub-floors, pallets and crates

### FEATURES

- Lightweight
- EZ-Clear Nose
- Adjustable depth of drive
- Powerful

### DESCRIPTION

DESCRIPTION	ART. NR.
SidingPro40 BF/TF	2Y2001N
SidingPro40 TF	2Y2002N



### TECHNICAL INFORMATION

Length	384 mm
Width	106 mm
Height	343 mm
Weight	3,6 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	283 l/min
Magazine capacity	70

### APPLICATIONS




Timber frame constructions, framing, sub-floors, pallets and crates, decking, roofs, fencing, door and window frames

### FEATURES

- Lightweight and powerful
- Toolless depth of drive
- 360° adjustable exhaust
- Nose with sawtooth for more grip
- Shorter straight-line magazine
- Adjustable trigger

### DESCRIPTION

DESCRIPTION	ART. NR.
FramePro601 BF/TF	1G2101N



### TECHNICAL INFORMATION

Length	384 mm
Width	106 mm
Height	363 mm
Weight	3,8 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	312 l/min
Magazine capacity	65-70

### APPLICATIONS




Timber frame constructions, framing, sub-floors, pallets and crates, decking, roofs, fencing, door and window frames

### FEATURES

- Extra powerful
- Adjustable depth of drive
- 360° adjustable exhaust
- Nose with sawtooth for more grip
- Shorter straight-line magazine
- Comfort grip

### DESCRIPTION

DESCRIPTION	ART. NR.
FramePro651 BF/TF	2G2111N
FramePro651 100mm BF/TF	2G2121N



## FULL ROUND HEAD NAILER FRAMEPRO602



∠ 20°



## FULL ROUND HEAD NAILER FRAMEPRO652\*



∠ 20°



### TECHNICAL INFORMATION

Length	508 mm
Width	106 mm
Height	337 mm
Weight	3,9 kg
Actuation	TF
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	283 l/min
Magazine capacity	60


### APPLICATIONS

Timber frame constructions, framing, sub-floors, pallets and crates, decking, roofs, fencing, door and window frames

### FEATURES

- Lightweight and powerful
- Adjustable depth of drive
- 360° adjustable exhaust
- Nose with sawtooth for more grip
- Comfort grip

DESCRIPTION	ART. NR.
FramePro602 BF/TF	1E2001N
FramePro602 BF/TF 17°	1E2101N



### TECHNICAL INFORMATION

Length	511 mm
Width	106 mm
Height	343 mm
Weight	3,9 kg
Actuation	TF
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	283 l/min
Magazine capacity	60


### APPLICATIONS

Timber frame constructions, framing, sub-floors, pallets and crates, decking, roofs, fencing, door and window frames

### FEATURES

- Lightweight and powerful
- Adjustable depth of drive
- 360° adjustable exhaust
- Nose with sawtooth for more grip
- Comfort grip

DESCRIPTION	ART. NR.
FramePro652 BF/TF	2E2001N



\*only available in grey



# STRIPNAILERS / COILNAILERS

## FULL ROUND HEAD NAILER SN1302



∠ 20°



### TECHNICAL INFORMATION

Length	533 mm
Width	144 mm
Height	478 mm
Weight	6,2 kg
Actuation	TF
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	255 l/min
Magazine capacity	50-56


### APPLICATIONS

Prefab, roofs, timber frame construction, sub-floors

### FEATURES

- Robust design for intensive use
- Available with extra handle for higher user convenience
- Adjustable depth of drive
- Reload indicator

DESCRIPTION	ART. NR.
SN1302 20° TF	6L2001N
SN1302 24° TF	6L2001NX



## FULL ROUND HEAD NAILER SN1602



∠ 20°



### TECHNICAL INFORMATION

Length	550 mm
Width	150 mm
Height	495 mm
Weight	7,0 kg
Actuation	TF
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	297 l/min
Magazine capacity	48-56


### APPLICATIONS

Prefab, roofs, timber frame construction, sub-floors

### FEATURES

- Compact size comparing with other 160mm nailers
- Dry-fire lockout
- Cushioned grip provides greater comfort and less fatigue

DESCRIPTION	ART. NR.
SN1602 20° TF	7D2001N



## COILNAILER SCN30



∠ 0°



### TECHNICAL INFORMATION

Length	277 mm
Width	98 mm
Height	203 mm
Weight	1,1 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	43 l/min
Magazine capacity	150-188



### APPLICATIONS

Furniture, floors, fences, garden products

### FEATURES

- Special nose for short nails
- Lightweight and compact design
- Selectable trigger
- For plastic collated coils

DESCRIPTION	ART. NR.
SCN30 BF/TF	SCN30







# SENCO®

## COILNAILER SCN34



∠ 15-16°



## COILNAILER COILPRO32



∠ 0°

## COILNAILER COILPRO50



∠ 15-16°



### TECHNICAL INFORMATION

Length	260 mm
Width	108 mm
Height	302 mm
Weight	1,6 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	44 l/min
Magazine capacity	400

### APPLICATIONS

Furniture, floors, fences, garden products, pallets and crates

### FEATURES



- Selectable trigger
- Lightweight and compact design
- Adjustable depth of drive

### DESCRIPTION

SCN34 BF/TF

### ART. NR.

SCN34



### TECHNICAL INFORMATION

Length	212 mm
Width	110 mm
Height	257 mm
Weight	1,4 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	5,0-7,5 bar
Air consumption	40,2 l/min
Magazine capacity	100

### APPLICATIONS

Pallets and crates, gate and fence construction

### FEATURES


- Selectable trigger
- Adjustable depth of drive
- Well balanced and lightweight
- 360° turnable exhaust

### DESCRIPTION

CoilPro32

### ART. NR.

8Z2001N



### TECHNICAL INFORMATION

Length	305 mm
Width	128 mm
Height	285 mm
Weight	2,0 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	83 l/min
Magazine capacity	250-375

### APPLICATIONS

Pallets and crates, gate and fence construction, underlay, garden products, cladding

### FEATURES



- Well balanced and lightweight
- Selectable trigger
- Adjustable depth of drive
- Highest power/weight ratio in its class

### DESCRIPTION

CoilPro50 BF/TF

### ART. NR.

4U2001N



# COILNAILERS

## COILNAILER SCN58A



∠ 15-16°



## COILNAILER SCN650



∠ 0°

## COILNAILER SCN75



∠ 15-16°



### TECHNICAL INFORMATION

Length	300 mm
Width	89 mm
Height	310 mm
Weight	2,6 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	113 l/min
Magazine capacity	200-300

### APPLICATIONS

Construction, pallets and crates, fencing, packaging

### FEATURES


- Well balanced and lightweight
- Powerful
- Adjustable depth of drive
- Robust design

### DESCRIPTION

SCN58A BF/TF

### ART. NR.

2S9011N



### TECHNICAL INFORMATION

Length	316 mm
Width	145 mm
Height	300 mm
Weight	2,3 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	106 l/min
Magazine capacity	300

### APPLICATIONS

Wall sheathing/Siding, packaging (boxes, crates), fencing, sub-flooring, boarding and other wooden assembly work

### FEATURES


- Ergonomically magnesium housing
- Excellent power to weight ratio
- User friendly depth of drive adjustment
- High capacity easy to load magazine

### DESCRIPTION

SCN650 BF/TF

### ART. NR.

7P2001N



### TECHNICAL INFORMATION

Length	292 mm
Width	132 mm
Height	315 mm
Weight	2,9 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	168 l/min
Magazine capacity	150-250

### APPLICATIONS

Framing, sheathing/ Siding, decking, sub-flooring, exterior decks, pallets and crates

### FEATURES


- Nose with sawtooth for more grip
- Depth of drive
- Adjustable trigger
- Runs both wire welded and plastic collated nails without any adjustment

### DESCRIPTION

SCN75 BF/TF

### ART. NR.

SCN75







# SENCO®

## COILNAILER COILPRO90



∠ 15-16°



### TECHNICAL INFORMATION

Length	306 mm
Width	128 mm
Height	317 mm
Weight	3,3 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	157 l/min
Magazine capacity	150-300

### APPLICATIONS

Timber frame constructions, sub-floors, pallets and crates, decking, roofs, cladding

### FEATURES


- Well balanced and lightweight
- Nose with sawtooth for more grip
- Selectable trigger
- Adjustable depth of drive

### DESCRIPTION

CoilPro90 BF/TF

### ART. NR.

1VS2001N





# SPECIALTY TOOLS

## METAL CONNECTOR MC60-34



∠ 34°



### TECHNICAL INFORMATION

Length	350 mm
Width	110 mm
Height	359 mm
Weight	2,7 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	118 l/min
Magazine capacity	20

### APPLICATIONS

Shaft pre-drilled (metal) plates, shaft pre-drilled metal strips, bar carriers, anchor plates, corner anchors

### FEATURES


- Magnesium body
- Adjustable depth of drive
- Special nose for good visibility and more precision
- Reload indicator

### DESCRIPTION

MC60-34 TF

### ART. NR.

6K2001N



## CORRUGATED FASTENER SC15



### TECHNICAL INFORMATION

Length	300 mm
Width	82 mm
Height	282 mm
Weight	2,4 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	99 l/min
Magazine capacity	73

### APPLICATIONS

Timber frame constructions, sub-floors, pallets and crates, decking, roofs, cladding

### FEATURES


- Magnesium body
- Adjustable depth of drive
- Selectable trigger
- Sharp angled nosepiece to fit into corners

### DESCRIPTION

SC15 BF/TF

### ART. NR.

6N2001N



## CORRUGATED FASTENER SC25



### TECHNICAL INFORMATION

Length	350 mm
Width	112 mm
Height	370 mm
Weight	3,9 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	99 l/min
Magazine capacity	80

### APPLICATIONS

Timber frame constructions, sub-floors, pallets and crates, decking, roofs, cladding

### FEATURES

- Robust design for industrial usage
- Well balanced
- Easy to load

### DESCRIPTION

SC25 TF

### ART. NR.

E612000





# SENCO®

## T-NAILER TPR065



NEW

INCLUDES  
CASE

## BUTTON CAP STAPLER BC58



### TECHNICAL INFORMATION

Length	283 mm
Width	98 mm
Height	305 mm
Weight	2,7 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	88 l/min
Magazine capacity	80

### APPLICATIONS

Trackless carpet strip, wood furring, floor underlayment, installation of metal drywall track

### FEATURES


- Strong and lightweight body
- Special hardened driver blade
- 360° adjustable exhaust
- Drives into concrete, steel & wood

### DESCRIPTION

TPR065 BF/TF

### ART. NR.

1VS2002N



### TECHNICAL INFORMATION

Length	211 mm
Width	52 mm
Height	197 mm
Weight	1,2 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	23 l/min
Magazine capacity	100

### APPLICATIONS

House wrap installation, roofing felt, packaging

### FEATURES


- Easy load system for staples and caps
- Light weight aluminium housing
- Comfort grip
- Balanced and fast for high production

### DESCRIPTION

Senco BC58

### ART. NR.

4A0001N



# SPECIALTY TOOLS

## PALM HAND NAILER A20



## HAMMERTACKER SHT-F



## MANUAL CARTON CLOSER SCCM



### TECHNICAL INFORMATION

Length	101 mm
Width	83 mm
Height	122 mm
Weight	1,1 kg
Air inlet	3/8" NPT
Operating pressure	3,5-8,3 bar
Air consumption	57-113 l/min

### APPLICATIONS

Nailing in places with limited motion space and fixing anchor plates and corner anchors

### FEATURES


- Drives loose nails 50-90mm
- Magnetic nail guide
- Soft rubber grip

### DESCRIPTION

A20 Palm nailer

### ART. NR.

PC0781



### TECHNICAL INFORMATION

Length	300 mm
Width	30 mm
Height	85 mm
Weight	1,1 kg
Magazine capacity	168

### APPLICATIONS

Upholstery, installing insulation, carpet and underlayment, plastic

### FEATURES

- Durable construction
- Comfortable anti-slip
- Quick loading

### DESCRIPTION

SHT-F Hammertacker

### ART. NR.

6R2001N



### TECHNICAL INFORMATION

Length	455 mm
Width	104 mm
Height	320 mm
Weight	1,7 kg
Magazine capacity	120

### APPLICATIONS

Packaging, carton closing

### FEATURES

- Toolless depth of drive
- Staple clinch adjustment
- Hard-wearing steel magazine
- High capacity and quick load magazine
- Durable and lightweight

### DESCRIPTION

SCCM18P-35 for 1 staple

### ART. NR.

7M2001N

SCCM22P-35 for 1 staple


7M2002N

SCCM18P-32 for U staple

7M2003N

SCCM22P-32 for U staple

7M2004N







# SENCO®

## CARTON CLOSER SCCP



## CARTON CLOSER SRCC



### TECHNICAL INFORMATION

Length	406 mm
Width	103 mm
Height	210 mm
Weight	1,9 kg
Operating pressure	4,8-6,3 bar
Air consumption	58 l/min
Magazine capacity	120

### APPLICATIONS

Packaging, carton closing

### FEATURES

- Toolless depth of drive
- Staple clinch adjustment
- Hard-wearing steel magazine
- High capacity and quick load magazine
- Durable and lightweight

### DESCRIPTION

	ART. NR.
SCCP18P-35 for 1 staple	7M2011N
SCCP22P-35 for 1 staple	7M2012N
SCCP18P-32 for U staple	7M2013N
SCCP22P-32 for U staple	7M2014N



### TECHNICAL INFORMATION

Length	235 mm
Width	104 mm
Height	205 mm
Weight	1,8 kg
Air inlet	1/4" NPT
Operating pressure	4,9-6,3 bar
Air consumption	59 l/min
Magazine capacity	1.000

### APPLICATIONS


Packaging, carton closing

### FEATURES

- Toolless depth of drive
- Staple clinch adjustment
- Hard-wearing steel magazine
- High capacity and quick load magazine
- Durable and lightweight

### DESCRIPTION

	ART. NR.
SRCC18P-32 for U staple	7M2015N



# DRILLS AND SCREWDRIVERS

## PNEUMATIC DRILL SEN510C



## PNEUMATIC DRILL SEN511C



### TECHNICAL INFORMATION

Length	215 mm
Width	42 mm
Height	137 mm
Weight	1,3 kg
Torque	10,8 Nm
RPM	800
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	226 l/min

### APPLICATIONS

Drilling

### FEATURES

- Composite housing
- Comfort grip
- Low noise - 83 dB(A)
- Direct drive
- Reversible motor
- Low maintenance cost

### DESCRIPTION

SEN510C Drill

### ART. NR.

SEN510C



### TECHNICAL INFORMATION

Length	188 mm
Width	42 mm
Height	137 mm
Weight	1,1 kg
Torque	5,1 Nm
RPM	1800
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	212 l/min

### APPLICATIONS

Drilling

### FEATURES

- Composite housing
- Comfort grip
- Low noise - 83 dB(A)
- Direct drive
- Reversible motor
- Low maintenance cost

### DESCRIPTION

SEN511C Drill

### ART. NR.

SEN511C





# SENCO®



## PNEUMATIC SCREWDRIVER SEN600C



### TECHNICAL INFORMATION

Length	187 mm
Width	42 mm
Height	137 mm
Weight	0,9 kg
Torque	5,7 Nm
RPM	1800
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	424 l/min
Torque control	Direct
Start	Direct

### APPLICATIONS

For screwdriving where torque is not critical

### FEATURES

- Composite housing
- Low noise - 83 dB(A)
- Direct torque control
- Push-in start
- Low maintenance cost

DESCRIPTION	ART. NR.
SEN600C Screwdriver	SEN600C

## PNEUMATIC SCREWDRIVER SEN602C



### TECHNICAL INFORMATION

Length	205 mm
Width	42 mm
Height	137 mm
Weight	1,1 kg
Torque	14,7 Nm
RPM	800
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	453 l/min
Torque control	Direct
Start	Direct

### APPLICATIONS

For screwdriving where torque is not critical

### FEATURES

- Composite housing
- Low noise - 83 dB(A)
- Direct torque control
- Reversible motor
- Low maintenance cost

DESCRIPTION	ART. NR.
SEN602C Screwdriver	SEN602C



# SCREWDRIVERS

## PNEUMATIC SCREWDRIVER SEN610C



## PNEUMATIC SCREWDRIVER SEN611C



## PNEUMATIC SCREWDRIVER SEN612C



### TECHNICAL INFORMATION

Length	210 mm
Width	42 mm
Height	137 mm
Weight	1,1 kg
Torque	1,0-10,0 Nm
RPM	1800
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	424 l/min
Torque control	Adjustable
Start	Push-in

### APPLICATIONS

Screwdriving with adjustable torque

### FEATURES

- Composite housing
- Low noise - 83 dB(A)
- Adjustable torque
- Push-in start
- Low maintenance cost

DESCRIPTION	ART. NR.
SEN610C Screwdriver	SEN610C



### TECHNICAL INFORMATION

Length	230 mm
Width	42 mm
Height	137 mm
Weight	1,2 kg
Torque	3,0-13 Nm
RPM	800
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	453 l/min
Torque control	Adjustable
Start	Push-in

### APPLICATIONS

Screwdriving with adjustable torque

### FEATURES

- Composite housing
- Low noise - 83 dB(A)
- Adjustable torque
- Push-in start
- Low maintenance cost

DESCRIPTION	ART. NR.
SEN611C Screwdriver	SEN611C



### TECHNICAL INFORMATION

Length	202 mm
Width	43 mm
Height	137 mm
Weight	1,2 kg
Torque	10,0 Nm
RPM	800
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	453 l/min
Torque control	Direct
Start	Push-in

### APPLICATIONS

For screwdriving where torque is not critical

### FEATURES

- Composite housing
- Low noise - 83 dB(A)
- Reversible motor
- Low maintenance cost

DESCRIPTION	ART. NR.
SEN612C Screwdriver	SEN612C



# SENCO®

## PNEUMATIC IMPACT DRIVER SEN700C



### TECHNICAL INFORMATION

Length	164 mm
Width	48 mm
Height	168 mm
Weight	0,98 kg
Torque	325 Nm
RPM	8900
Air inlet	1/4" NPT
Operating pressure	6,2 bar
Air consumption	96 l/min
Torque control	Adjustable
Start	Push-in

### APPLICATIONS

Screwdriving application that need high torque

### FEATURES

- Composite housing
- Twin-hammer mechanism provides more power
- Feather trigger for precise speed control
- Left and right turning
- Energy efficient motor

### DESCRIPTION

SEN700C

### ART. NR.

SEN700C



# PALLETPRO SERIES



**STRENGTHENED DRIVER  
AND BUMPER**



**WELL BALANCED**

**HIGH VOLUME  
LOW MAINTENANCE**



**FLEXIBLE COLLATION DEFLEC-  
TOR AND DUST GUARD**

The tools in the PalletPro Series are perfectly balanced and very powerful, which enables long-term use. Features of the PalletPro Series are: rapid fire with a superb reliability and low maintenance.







**SENCO®**

**DUAL ACTION TRIGGER**

## **PALLETPRO SERIES**

Specially designed for 24/7  
use in the pallet and packaging  
industry

**COMFORTABLE GRIP,  
REDUCES FATIGUE**

**FOCUS ON HIGH  
PRODUCTIVITY**

**1 YEAR**  
**LIMITED**  
**WARRANTY**

**PALLET  
PRO  
SERIES**

**MAKING HARD WORK  
EASIER**

# COILNAILERS

## COILNAILER PAL50



∠ 16°

## COILNAILER PAL57F



∠ 16°

## COILNAILER PAL57F 2 HAND SAFETY



∠ 16°



### TECHNICAL INFORMATION

Length	305 mm
Width	128 mm
Height	285 mm
Weight	2,0 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	102 l/min
Magazine capacity	350-400

### APPLICATIONS

Furniture, floors, fences, garden products, pallets and crates

### FEATURES



- Robust design for intensive use in the pallet industry
- Well balanced and powerful
- Strong and easy to load magazine

### DESCRIPTION

PAL50 BF/TF

### ART. NR.

PAL50



### TECHNICAL INFORMATION

Length	302 mm
Width	133 mm
Height	286 mm
Weight	2,7 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	87 l/min
Magazine capacity	300-350

### APPLICATIONS

Pallets and crates, floors, roofs, garden products, cladding

### FEATURES



- Robust design for intensive use in the pallet industry
- Side steel wearplates reduce tool abrasion
- Strong and easy to load magazine
- Well balanced and powerful

### DESCRIPTION

PAL57F BF/TF

### ART. NR.

PAL57F



### TECHNICAL INFORMATION

Length	302 mm
Width	133 mm
Height	286 mm
Weight	2,7 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	87 l/min
Magazine capacity	300-350

### APPLICATIONS

A lightweight and versatile tool for boxes and crates, carton-to-skid and pallets

### FEATURES



- Special double handed safety design
- Robust design for intensive use in the pallet industry
- Side steel wearplates reduce tool abrasion
- Strong and easy to load magazine

### DESCRIPTION

PAL57F 2h safety

### ART. NR.

PAL57F-2H





# SENCO®

## COILNAILER PAL70



∠ 16°

## COILNAILER PAL70 DUPLEX



∠ 16°

## COILNAILER PAL83



∠ 16°



### TECHNICAL INFORMATION

Length	339 mm
Width	129 mm
Height	319 mm
Weight	3,6 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	136 l/min
Magazine capacity	250-300

### APPLICATIONS

Pallets and crates, timber, sub-floors, shuttering, roof, battens, cladding

### FEATURES


- Robust design for intensive use in the pallet industry
- Well balanced and powerful
- Strong and easy to load magazine
- High durability driver and piston

### DESCRIPTION

PAL70 BF/TF

### ART. NR.

PAL70



### TECHNICAL INFORMATION

Length	339 mm
Width	129 mm
Height	319 mm
Weight	3,6 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	136 l/min
Magazine capacity	250-300

### APPLICATIONS

Pallets and crates

### FEATURES


- Robust design for intensive use in the pallet industry
- Well balanced and powerful
- Strong and easy to load magazine
- High durability driver and piston

### DESCRIPTION

PAL70 Duplex BF/TF

### ART. NR.

XL3035



### TECHNICAL INFORMATION

Length	341 mm
Width	132 mm
Height	365 mm
Weight	3,8 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	164 l/min
Magazine capacity	225-300

### APPLICATIONS

Pallets and crates, timber, sub-floors, shuttering, roof, battens, cladding

### FEATURES

- Robust design for intensive use in the pallet industry
- Well balanced and powerful
- Strong and easy to load magazine

### DESCRIPTION

PAL83 BF/TF

### ART. NR.

PAL83





# COILNAILERS

## COILNAILER PAL90



∠ 16°

## COILNAILER PAL100



∠ 16°

## COILNAILER PAL100 2 HAND SAFETY



∠ 16°



### TECHNICAL INFORMATION

Length	385 mm
Width	145 mm
Height	370 mm
Weight	3,5 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	193 l/min
Magazine capacity	200-300

### APPLICATIONS

Pallets and crates, timber, sub-floors shuttering, roof, battens, cladding

### FEATURES


- Robust design for intensive use in the pallet industry
- Side steel wearplates reduce tool abrasion
- Strong and easy to load magazine
- Well balanced and powerful

### DESCRIPTION

PAL90 BF/TF

### ART. NR.

PAL90



### TECHNICAL INFORMATION

Length	338 mm
Width	153 mm
Height	417 mm
Weight	5,2 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	322 l/min
Magazine capacity	225-300

### APPLICATIONS

Pallets and crates, timber, sub-floors shuttering, roof, battens, cladding

### FEATURES


- Robust design for intensive use in the pallet industry
- Aluminium body
- Strong and easy to load magazine
- Includes removable handle

### DESCRIPTION

PAL100 BF/TF

### ART. NR.

PAL100



### TECHNICAL INFORMATION

Length	338 mm
Width	153 mm
Height	417 mm
Weight	5,2 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	323 l/min
Magazine capacity	225-300

### APPLICATIONS

Pallets and crates, timber, sub-floors shuttering, roof, battens, cladding

### FEATURES


- Special double handed safety design
- Robust design for intensive use in the pallet industry
- Aluminium body
- Strong and easy to load magazine

### DESCRIPTION

PAL100 2h safety

### ART. NR.

5L0021N





# SENCO®

## COILNAILER PAL130



∠ 16°

## COILNAILER PAL100 EPAL



∠ 16°

## COILNAILER EPAL MARKING NAIL



∠ 16°



### TECHNICAL INFORMATION

Length	330 mm
Width	168 mm
Height	457 mm
Weight	5,9 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	323 l/min
Magazine capacity	120-225


### APPLICATIONS

Pallets and crates, timber, sub-floors shuttering, roof, battens, cladding

### FEATURES

- Robust design for intensive use in the pallet industry
- For use in the toughest environments
- Includes removable handle
- Strong and easy to load magazine

DESCRIPTION	ART. NR.
PAL130 BF/TF	5M2001N



### TECHNICAL INFORMATION

Length	338 mm
Width	153 mm
Height	417 mm
Weight	5,2 kg
Actuation	BF (TF)
Air inlet	3/8" NPT
Operating pressure	4,8-8,3 bar
Air consumption	322 l/min
Magazine capacity	225-300


### APPLICATIONS

Pallets and crates, timber, sub-floors shuttering, roof, battens, cladding

### FEATURES

- Robust design for intensive use in the pallet industry
- Aluminium body
- Strong and easy to load magazine
- Includes removable handle

DESCRIPTION	ART. NR.
PAL100EPAL BF/TF	PAL100-EPAL



### TECHNICAL INFORMATION

Length	260 mm
Width	114 mm
Height	267 mm
Weight	2,5 kg
Actuation	BF (TF)
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	185 l/min
Magazine capacity	120


### APPLICATIONS

Pallet repairing

### FEATURES

- Manual depth setting
- Aluminium mainbody & cap
- Jaws for nail guidance

DESCRIPTION	ART. NR.
EPAL marking nail coilnailer	3D2011N-EPAL



# SEMIPRO SERIES



**MULTI-DIRECTIONAL  
EXHAUST DEFLECTOR**

**SENCO STAMP  
OF QUALITY**



**ERGONOMICALLY  
MAGNESIUM HOUSING**



Senco quality for the professional home and garden user. The SemiPro Series is specifically designed for professional use where tools are used less frequent.







**SENCO®**

**COMFORTABLE  
RUBBER GRIP**

**RESTRICTIVE TRIGGER**

**SEMIPRO  
SERIES**

Senco quality for every  
now and then use

**GREAT VALUE  
FOR MONEY**



**FOR EVERY NOW  
AND THEN USER**

**1 YEAR**  
LIMITED  
WARRANTY

SEMI  
**PRO**  
SERIES

MAKING HARD WORK  
**EASIER**

# STAPLERS / STRIPNAILERS

## LIGHT WIRE STAPLER SFW05



## MEDIUM WIRE STAPLER S150LS



## BRAD NAILER S200BN



### TECHNICAL INFORMATION

Length	229 mm
Width	45 mm
Height	163 mm
Weight	0,9 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	5,2-6,9 bar
Air consumption	27 l/min
Magazine capacity	100


### APPLICATIONS

Upholstering operations, furniture assembly, cabinets, automotive vinyl roofs and interior trim, bedding manufacture, TV and stereo grille cloth, picture frames, shoemaking, molding and roofing felt

### FEATURES

- Slim, compact design for use in small spaces
- Adjustable exhaust
- Lightweight

DESCRIPTION	ART. NR.
SFW05-B	SFW05-B
SFW05-C	SFW05-C
SFW05-AT	SFW05-AT



### TECHNICAL INFORMATION

Length	249 mm
Width	45 mm
Height	227 mm
Weight	1,5 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	54 l/min
Magazine capacity	100-110

### APPLICATIONS

Cabinets, furniture, drawer assembly, case backs, picture frames

### FEATURES

- Adjustable depth of drive
- Comfort grip
- Reload indicator

DESCRIPTION	ART. NR.
S150LS TF	952008N



### TECHNICAL INFORMATION

Length	251 mm
Width	68 mm
Height	232 mm
Weight	1,4 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	5,0-8,3 bar
Air consumption	22 l/min
Magazine capacity	107-110


### APPLICATIONS

Mouldings, trim, furniture decoration, glazing beads, cupboards and drawers, general finishing

### FEATURES

- Adjustable depth of drive
- EZ-Clear Nose
- Comfort grip
- Adjustable exhaust
- Reload indicator

DESCRIPTION	ART. NR.
S200BN TF	922008N



## BRAD NAILER S200SM



## BRAD NAILER S250FN



∠ 34°



### TECHNICAL INFORMATION

Length	254 mm
Width	68 mm
Height	230 mm
Weight	1,4 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	5,0-8,3 bar
Air consumption	113 l/min
Magazine capacity	100

### APPLICATIONS

Mouldings, trim, furniture decoration, glazing beads, cupboards and drawers, general finishing

### FEATURES


- Adjustable depth of drive
- Reload indicator
- EZ-Clear Nose
- Comfort grip
- Adjustable exhaust

### DESCRIPTION

S200SM TF

### ART. NR.

942008N



### TECHNICAL INFORMATION

Length	303 mm
Width	85 mm
Height	346 mm
Weight	2,3 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	5,0-7,0 bar
Air consumption	128 l/min
Magazine capacity	100

### APPLICATIONS

Baseboards, cabinets, frames, door & window frames, skirting boards, exterior trim, furniture manufacture, dado & architrave

### FEATURES


- Adjustable depth of drive
- EZ-Clear Nose
- Comfort grip
- Adjustable exhaust

### DESCRIPTION

S250FN TF

### ART. NR.

932008N





# STRIPNAILERS

## CH FRAMING NAILER A900FN



∠ 34°



## ROOFING COILNAILER S45CNR



∠ 16°



## COILNAILER S65CNP



∠ 16°



### TECHNICAL INFORMATION

Length	530 mm
Width	90 mm
Height	290 mm
Weight	3,8 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4,8-8,3 bar
Air consumption	274 l/min
Magazine capacity	100


### APPLICATIONS

Baseboards, cabinets, frames, door & window frames, skirting boards, exterior trim, furniture manufacture, dado & architrave

### FEATURES

- Adjustable depth of drive
- EZ-Clear Nose
- Comfort grip
- Adjustable exhaust

DESCRIPTION	ART. NR.
A900FN TF	4F0311N



### TECHNICAL INFORMATION

Length	300 mm
Width	110 mm
Height	310 mm
Weight	2,75 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4.8 – 8.3 bar
Air consumption	68 l/min
Magazine capacity	120


### APPLICATIONS

For asphalt and fiberglass shingle nailing, for both new roofs and reroofing. Also for attaching waterproof tar paper, metal drip edges and insulation board.

### FEATURES

- Aluminum body
- Comfort grip
- Tool-free adjustable depth of drive
- 360 adjustable exhaust

DESCRIPTION	ART. NR.
S45CNR	1VS2004N



### TECHNICAL INFORMATION

Length	304 mm
Width	128 mm
Height	300 mm
Weight	2,49 kg
Actuation	TF
Air inlet	1/4" NPT
Operating pressure	4.9 – 8.3 bar
Air consumption	220 l/min
Magazine capacity	250-275


### APPLICATIONS

Wall sheathing/Siding, Timber frame constructions, Fencing, Sub-flooring, Boarding and other wooden assembly work.

### FEATURES

- Magnesium body
- Comfort grip
- Multi-directional exhaust deflector
- Adjustable depth of drive
- Runs both wire and plastic collated nails

DESCRIPTION	ART. NR.
S65CNP TF	8G2001N





**SENCO®**



# COMPRESSORS & KITS



**COMFORTABLE  
CUSHIONED GRIP**

**DIRECT DRIVE MOTOR/  
PUMP**



**REGULATOR**



**ALUMINUM CYLINDER**

Senco compressors from small to large: for every application there's a Senco compressor. In addition to high quality professional tools, Senco also has a complete range of high quality compressors. There are oil free and oil lube versions available for a wide range of applications.







**SENCO®**



**AIR FILTER**

**1 OR 2 1/4" UNIVERSAL  
COUPLER**

**OIL-LUBE OR  
OILLESS MODELS**

## **COMPRESSORS, KITS & ACCESSORIES**

For every application,  
a Senco compressor.

**PRESSURE GAUGES**

**1 YEAR**  
LIMITED  
WARRANTY

**COM**  
PRESSOR

**MAKING HARD WORK  
EASIER**

# COMPRESSORS

## MINI COMPRESSOR PC1010



### TECHNICAL INFORMATION

Length	360 mm
Width	330 mm
Height	250 mm
Weight	9,1 kg
Power	230V / 0,3kW (0,5 hp)
RPM	2850
Tank capacity	3,8 l
Maximum pressure	8 bar
Displacement	34 l/min
Airflow (6-6,2 bar)	20 l/min
Noise level	68 db(A)

### APPLICATIONS

Primarily finish, trim and upholstery

### FEATURES

- Oil free
- Ultra light, hand carry
- Comfort grip
- Aluminium cylinder
- Silent and durable (3000 hours)

DESCRIPTION	ART. NR.
0,3kW (0,5 hp) compressor (230V)	PC1010EU
0,3kW (0,5 hp) compressor (110V)	PC1010UK1
0,3kW (0,5 hp) compressor (230V)	PC1010UK2

## MINI COMPRESSOR PC1010N



### TECHNICAL INFORMATION

Length	365 mm
Width	300 mm
Height	310 mm
Weight	9,7 kg
Power	230V / 0,3kW (0,5 hp)
RPM	2850
Tank capacity	3,8 l
Maximum pressure	9 bar
Displacement	34 l/min
Airflow (6-6,2 bar)	20 l/min
Noise level	68 db(A)

### APPLICATIONS

Upholstery, finish and trim

### FEATURES

- Highly visible gauges
- Integrated control panel
- Oil free
- Efficient, long life operation induction motor

DESCRIPTION	ART. NR.
0,3kW (0,5 hp) compressor (230V)	PC1010NEU

## MINI COMPRESSOR PC1248



### TECHNICAL INFORMATION

Length	160 mm
Width	490 mm
Height	460 mm
Weight	16,8 kg
Power	230V / 1,1 kW (1,5 hp)
RPM	2850
Tank capacity	8,0 l
Maximum pressure	9 bar
Displacement	139 l/min
Airflow (6-6,2 bar)	79 l/min
Noise level	83 db(A)

### APPLICATIONS

Finish, trim, upholstery, roofing, siding and sheathing

### FEATURES

- Maintenance free
- Oil free
- Sturdy, lightweight
- Thermal overload protection
- Fully automated control

DESCRIPTION	ART. NR.
1,1 kW (1,5 hp) compressor (230V)	PC1248EU
1,1 kW (1,5 hp) compressor (110V)	PC1248UK1
1,1 kW (1,5 hp) compressor (230V)	PC1248UK2



# SENCO®

## MINI COMPRESSOR PC0968



### TECHNICAL INFORMATION

Length	400 mm
Width	380 mm
Height	340 mm
Weight	17 kg
Power	230V / 1,1 kW (1,5 hp)
RPM	2850
Tank capacity	10,0 l
Maximum pressure	9 bar
Displacement	113 l/min
Airflow (6-6,2 bar)	51 l/min
Noise level	81 db(A)

### APPLICATIONS

Finish, trim, upholstery, roofing and siding

### FEATURES

- Hand carry
- Ultra light
- Comfort grip
- Oil free
- Silent and durable (3000 hours)

### DESCRIPTION

### ART. NR.

1,1 kW (1,5 hp) compressor (230V) PC0968EU

## MIDI COMPRESSOR PC1252



### TECHNICAL INFORMATION

Length	540 mm
Width	310 mm
Height	430 mm
Weight	23 kg
Power	230V / 1,5 kW (2 hp)
RPM	2850
Tank capacity	3,0 l
Maximum pressure	9 bar
Displacement	201 l/min
Airflow (6-6,2 bar)	122 l/min
Noise level	84 db(A)

### APPLICATIONS

Finish, trim, roofing, siding, decking, subflooring, sheathing and framing

### FEATURES

- Hand carry
- Sturdy, very compact and mobile
- Pressure switch with start-up valve
- Fully automated control
- Excellent for pneumatic caulk guns

### DESCRIPTION

### ART. NR.

1,5 kW (2 hp) compressor (230V) PC1252EU

## MIDI COMPRESSOR PC1249



### TECHNICAL INFORMATION

Length	320 mm
Width	360 mm
Height	660 mm
Weight	30 kg
Power	230V / 1,5 kW (2 hp)
RPM	2850
Tank capacity	10,0 l
Maximum pressure	9 bar
Displacement	201 l/min
Airflow (6-6,2 bar)	133 l/min
Noise level	93 db(A)

### APPLICATIONS

Finish, trim, upholstery, roofing, siding, decking, subflooring, sheathing, pallets and framing

### FEATURES

- Sturdy mobile compressor
- Thermal overload protection
- Pressure regulator for controlled working pressure

### DESCRIPTION

### ART. NR.

1,5 kW (2 hp) compressor (230V) PC1249EU



# COMPRESSORS

## MIDI COMPRESSOR PC1250



### TECHNICAL INFORMATION

Length	880 mm
Width	320 mm
Height	670 mm
Weight	42 kg
Power	230V / 1,5 kW (2 hp)
RPM	2850
Tank capacity	46,0 l
Maximum pressure	10 bar
Displacement	277 l/min
Airflow (6-6,2 bar)	164 l/min
Noise level	87 db(A)

### APPLICATIONS

Finish, trim, roofing, siding, decking, subflooring, sheathing, pallets, framing, packaging

### FEATURES

- Sturdy, high performance compressor
- Thermal overload protection
- Fully automated control
- Oil free

### DESCRIPTION ART. NR.

1,5 kW (2 hp) compressor (230V) PC1250EU

1,5 kW (2 hp) compressor (110V) PC1250UK1

## MAXI COMPRESSOR PC2225



### TECHNICAL INFORMATION

Length	650 mm
Width	560 mm
Height	530 mm
Weight	39 kg
Power	230V / 1,9 kW (2,5 hp)
RPM	2850
Tank capacity	16,0 l
Maximum pressure	9 bar
Displacement	268 l/min
Airflow (6-6,2 bar)	192 l/min
Noise level	82 db(A)

### APPLICATIONS

Finish, trim, roofing, siding, decking, subflooring, sheathing, pallets and framing

### FEATURES

- Big wheels, stable and easy to move
- Die cast aluminium
- Compact design and strong frame
- Pump with cast iron sleeve

### DESCRIPTION ART. NR.

1,9 kW (2,5 hp) compressor (230V) PC2225EU

## MAXI COMPRESSOR PC1251



### TECHNICAL INFORMATION

Length	550 mm
Width	520 mm
Height	760 mm
Weight	37,5 kg
Power	230V / 1,9 kW (2,5 hp)
RPM	2850
Tank capacity	20,0 l
Maximum pressure	9 bar
Displacement	271 l/min
Airflow (6-6,2 bar)	164 l/min
Noise level	83 db(A)

### APPLICATIONS

Finish, trim, upholstery, roofing, siding, decking, subflooring, sheathing, pallets and framing

### FEATURES

- Sturdy mobile compressor
- Thermal overload protection
- Fully automated control
- Large non-inflatable rubber wheels

### DESCRIPTION ART. NR.

1,9 kW (2,5 hp) compressor (230V) PC1251EU

1,9 kW (2,5 hp) compressor (110V) PC1251UK1



# SENCO®

## MAXI COMPRESSOR PC1246



## KIT COMPRESSOR PC1287EU



## HP COMPRESSOR PC1286EU



### TECHNICAL INFORMATION

Length	650 mm
Width	530 mm
Height	850 mm
Weight	57 kg
Power	230V / 2,6 kW (3,5 hp)
RPM	2850
Tank capacity	16,0 l
Maximum pressure	10 bar
Displacement	350 l/min
Airflow (6-6,2 bar)	224 l/min
Noise level	89 db(A)

### APPLICATIONS

Finish, trim, roofing, siding, decking, subflooring, sheathing, pallets and framing

### FEATURES

- Compact design
- Thermal overload protection
- Pressure switch with start-up valve
- Instrument panel enables easy operation

### DESCRIPTION

### ART. NR.

2,6 kW (3,5 hp) compresor(230V) PC1246EU

2,6 kW (3,5 hp) compresor (110V) PC1246UK1

2,6 kW (3,5 hp) compresor (230V) PC1246UK2

### TECHNICAL INFORMATION

Length	540 mm
Width	310 mm
Height	430 mm
Weight	28,5 kg
Power	230 V / 0,75 kW (1 hp)
RPM	1450
Tank capacity	3,0 l
Maximum pressure	15 bar
Displacement	131 l/min
Airflow (6-6,2 bar)	74 l/min
Noise level	77 db(A)

### APPLICATIONS

Caulking, finish & trim, siding, decking

### FEATURES

- Excellent for pneumatic caulk guns
- Sturdy, very compact and mobile
- Comfort grip
- Fully automated control
- Thermal overload protection

### DESCRIPTION

### ART. NR.

Senco kit compressor

PC1287EU

### TECHNICAL INFORMATION

Length	620 mm
Width	425 mm
Height	320 mm
Weight	25 kg
Power	230V / 1,5 kW (2 hp)
RPM	2400
Tank capacity	10,0 l
Maximum pressure	27,5 bar
Displacement	70 l/min
Airflow (6-6,2 bar)	40 l/min
Noise level	80 db(A)

### APPLICATIONS

30 bar application, features also a 8 bar connection, multiple machines at 8 bar

### FEATURES

- Oil free
- Light weight, easy to move
- Dual safety valves
- Thermal overload protection

### DESCRIPTION

### ART. NR.

High Pressure Compressor

PC1286EU

# KITS AND ACCESSORIES

## COMPRESSOR KIT PC1010EU & 3 IN 1 SET



## STARTER KIT PC1010EU/SLS18MG



## STARTER KIT PC1010EU/FINISHPRO18MG



### APPLICATIONS

Easy to transport. Fits on every systainer and protects tools or compressor.

### CONTENT

- PC1010

### CONTENTS 3 IN 1

- SLS18Mg, page 22
- FIP18Mg, page 24
- FIP35Mg, page 25

DESCRIPTION	ART. NR.
Systainerset PC1010EU	3PR2014N
Systainer 3 in 1	3PR2012N

Systainerset PC1010 (110V) 3PR2014N-UK



### APPLICATIONS

Cabinets, furniture, drawer assembly, case backs, picture frames

### CONTENTS

- PC1010 Compressor
- SLS18-L Mg Medium wire stapler
- Including hose
- Including safety glasses
- Including blisterpack L staples

DESCRIPTION	ART. NR.
PC1010EU/SLS18Mg	PC0972EUPU
PC1010EU/SLS18Mg (Systainer)	PC0972EUPS

PC1010/SLS18Mg (110V) PC0972UKPU1  
PC1010/SLS18Mg (110V) (Systainer) PC0972UKPS1



### APPLICATIONS

Mouldings, furniture, decoration, trim, beading, cabinets and drawers, rattan furniture, finishing

### CONTENTS

- PC1010 Compressor
- FinishPro18Mg Brad nailer
- Including hose
- Including safety glasses
- Including blisterpack AX brads

DESCRIPTION	ART. NR.
PC1010EU/FinishPro18Mg	PC0964EUPU
PC1010EU/FinishPro18Mg (Systainer)	PC0964EUPS

PC1010/FinishPro18Mg (110V) PC0964UKPU1  
PC1010/FinishPro18Mg (230V) PC0964UKPU2  
PC1010/FinishPro18Mg (110V) (Systainer) PC0964UKPS1  
PC1010/FinishPro18Mg (230V) (Systainer) PC0964UKPS2





# SENCO®

## AIR ACCESSORY KIT



DESCRIPTION	ART. NR.
Air accessory kit;	400050
Washing pistol, tire inflating gun with pressure gauge, paint spray gun, air blow gun, hose	

## AIRBLOW GUN



DESCRIPTION	ART. NR.
Airblow gun metal with Cejn coupling	400030
Airblow gun metal with Orion coupling	400031
Airblow gun blue with Orion coupling	400032

## HOSE REEL



DESCRIPTION	ART. NR.
Hose reel universal auto PU	
320 comp. 12m x 6,5mm	4000720
320 comp. 10m x 8,0mm	4000721

## HOSE REEL



DESCRIPTION	ART. NR.
Hose reel universal PU	
320 comp. 30m x 8mm	4000730

## PREMIUM HOSE REEL



DESCRIPTION	ART. NR.
Hose reel premium hybrid PVC	
320 comp. 30m x 10mm	4000731

## PLUG 320 MALE



DESCRIPTION	ART. NR.
Universal 320 comp. NPT 1/4" 2 pcs.	4000100
Universal 320 comp. NPT 3/8" 2 pcs.	4000110
Universal 320 comp. NPT 1/2" 2 pcs.	4000120
Universal 320 comp. NPT 1/4" 10 pcs.	4000101
Universal 320 comp. NPT 3/8" 10 pcs.	4000111

## PLUG 300 MALE



DESCRIPTION	ART. NR.
Plug 300 comp. NPT 1/4" 2 pcs.	4000060
Plug 300 comp. NPT 1/4" 10 pcs.	4000061
Plug 300 comp. NPT 1/4" 1000 pcs.	4000062
Plug 300 comp. NPT 3/8" 2 pcs.	4000070
Plug 300 comp. NPT 3/8" 10 pcs.	4000071
Plug 300 comp. NPT 3/8" 1000 pcs.	4000072

## PLUG 310 MALE



DESCRIPTION	ART. NR.
Plug 310 comp. NPT 1/4" 2 pcs.	4000080
Plug 310 comp. NPT 1/4" 10 pcs.	4000081
Plug 310 comp. NPT 1/4" 1000 pcs.	4000082
Plug 310 comp. NPT 3/8" 2 pcs.	4000090
Plug 310 comp. NPT 3/8" 10 pcs.	4000091
Plug 310 comp. NPT 3/8" 1000 pcs.	4000092

## HOSE PLUG



DESCRIPTION	ART. NR.
Universal hose 320 comp. 6,5mm blist. 2 pcs.	4000200
Universal hose 320 comp. 8mm blist. 2 pcs.	4000210
Universal hose 320 comp. 10mm blist. 2 pcs.	4000220
Universal hose 320 comp. 12,7mm blist. 2 pcs.	4000230
Universal hose 310 comp. 8mm blist. 2 pcs.	4000211

# ACCESSORIES

## PLUG FEMALE



DESCRIPTION	ART. NR.
Universal 320 comp. NPT 1/4" 2 pcs.	4000150
Universal 320 comp. NPT 3/8" 2 pcs.	4000160
Universal 320 comp. NPT 1/2" 2 pcs.	4000170
Universal 320 comp. NPT 1/4" 10 pcs.	4000151
Universal 320 comp. NPT 3/8" 10 pcs.	4000161

## HOSE REPAIR PLUG



DESCRIPTION	ART. NR.
6mm blist. 2 pcs.	4000480
8mm blist. 2 pcs.	4000490
9,5mm blist. 2 pcs.	4000500

## HOSE CLAMP



DESCRIPTION	ART. NR.
10-16mm blist. 5 pcs.	4000520

## COUPLER MALE



DESCRIPTION	ART. NR.
Universal 320 comp. NPT 1/4" blist. 1 pcs.	4000300
Universal 320 comp. NPT 3/8" blist. 1 pcs.	4000310
Universal 320 comp. NPT 1/2" blist. 1 pcs.	4000320
Universal 310 comp. NPT 1/4" blist. 1 pcs.	4000302
Universal 310 comp. NPT 3/8" blist. 1 pcs.	4000312

## COUPLER FEMALE



DESCRIPTION	ART. NR.
Universal 320 comp. NPT 1/4" blist. 1 pcs.	4000370
Universal 320 comp. NPT 3/8" blist. 1 pcs.	4000380
Universal 320 comp. NPT 1/2" blist. 1 pcs.	4000390
Universal 310 comp. NPT 1/4" blist. 1 pcs.	4000372
Universal 310 comp. NPT 3/8" blist. 1 pcs.	4000382

## HOSE COUPLER



DESCRIPTION	ART. NR.
Universal 320 comp. 6,5mm blist. 1 pcs.	4000400
Universal 320 comp. 8mm blist. 1 pcs.	4000410
Universal 320 comp. 10mm blist. 1 pcs.	4000420
Universal 320 comp. 12,7mm blist. 1 pcs.	4000430
Universal 310 comp. 8mm blist. 1 pcs.	4000412

## SPIRAL HOSE



DESCRIPTION	ART. NR.
Kit universal PU 320 comp. 6m x 6,5mm (i.d.)	4000600
Kit universal PU 320 comp. 6m x 8mm (i.d.)	4000610
Kit universal PU 320 comp. 6m x 10mm (i.d.)	4000620

## AIR HOSE KIT



DESCRIPTION	ART. NR.
Kit universal PU 320 comp. 10m x 6,5mm (i.d.)	4000650
Kit universal PU 320 comp. 10m x 8mm (i.d.)	4000660
Kit universal PU 320 comp. 10m x 10mm (i.d.)	4000670

## AIR HOSE KIT PREMIUM



DESCRIPTION	ART. NR.
Kit premium PVC 320 comp. 10m x 6,5mm (i.d.)	4000651
Kit premium PVC 320 comp. 10m x 10mm (i.d.)	4000671
Kit premium PVC 310 comp. 10m x 10mm (i.d.)	4000661



# SENCO®

## AIR HOSE



DESCRIPTION	ART. NR.
PU 50m x 6,5mm (i.d.)	4000680
PU 50m x 8mm (i.d.)	4000690
PU 50m x 10mm (i.d.)	4000700
PU 150m x 6,5mm (i.d.)	4000681
PU 150m x 8mm (i.d.)	4000691
PU 150m x 10mm (i.d.)	4000701

## AIR HOSE PREMIUM



DESCRIPTION	ART. NR.
Premium hybrid PVC 50m x 6,5mm (i.d.)	4000682
Premium hybrid PVC 50m x 8mm (i.d.)	4000692*
Premium hybrid PVC 50m x 10mm (i.d.)	4000702
Premium hybrid PVC 150m x 6,5mm (i.d.)	4000683
Premium hybrid PVC 150m x 10mm (i.d.)	4000703

\*Coming soon

## HIGH PRESSURE HOSE



DESCRIPTION	ART. NR.
High pressure hose 15m	960400

## TEFLON TAPE



DESCRIPTION	ART. NR.
10m blist. 1 pcs.	4000540

## SPRING BALANCER



DESCRIPTION	ART. NR.
Spring balancer cap. 1,5-3,0 kg.	4001000
Spring balancer cap. 3,0-5,0 kg.	4001001

## LUBRICANTS



DESCRIPTION	ART. NR.
Tool lubricant 115 g	YB0123

COMPATIBILITY MATRIX	SENCO 300 SERIES	SENCO 310 SERIES	SENCO 320 SERIES
ARO 210	X		
ATLAS COPCO		X	
QIC8			
CEJN 300	X		
CEJN 310		X	
CEJN 320			X
FOSTER 3003		X	
GROMMELLE 600		X	
HANSEN 210	X		
HANSEN 3000		X	
HANSEN AUTO-FLO 24			X
JWL520			X
JWL521		X	
JWL531		X	
JWL532	X		
JWL552	X		
OETIKER B1		X	
OETIKER SC C			X
ORION 44510	X		
ORION 44515	X		
PARKER 20 1/4"		X	
PARKER 30 1/4"		X	
PARKER 50	X		
PREVOST ASI06	X		
PREVOST ERC07			X
PREVOST ESC07			X
PREVOST ESI07			X
PREVOST ESI08			X
PREVOST ISC06		X	
PREVOST ISI06		X	
RECTUS 14	X		
RECTUS 22	X		
RECTUS 23		X	
RECTUS 24		X	
RECTUS 25			X
RECTUS 26			X
TEMA 1400		X	
TEMA 1423		X	
TEMA 1600			X
TEMA 1625			X



# ACCESSORIES

## LUBRICANTS



DESCRIPTION	ART. NR.
Tool lubrication	PC1295
945 ml	
Lubrication Senco tools	PC0101
235 ml	
Lubrication Senco tools	PC0102
945 ml	
Lubrication Senco tools	PC0103
3,78 l	

## COMPRESSOR OIL



DESCRIPTION	ART. NR.
Compressor oil 945 ml	PC0344

## SAFETY GLASSES



DESCRIPTION	ART. NR.
Senco safety glasses CE	PC1166
Senco safety glasses, tinted CE	PC1167

## SERVICE REPAIR KITS



DESCRIPTION	ART. NR.
Firing/Trigger system kit SNS45XP	YK0230
Piston stop kit SNS45XP	YK0231
Firing system/trigger kit FrameProXP	YK0243
Piston stop kit FrameProXP	YK0244
Piston stop kit FinishPro25XP	YK0282
Piston stop kit SLS25XP	YK0291
Seal kit FramePro652	YK0353
Firing/trigger system kit SLS25XP	YK0359
Repair kit FramePro601/	YK0360
602/651/652	
Firing/Trigger system kit FiP41XP,42	YK0361
Repair kit FinishPro35	YK0365
Repair kit SCN60/65N	YK0366
Repair kit SFN40	YK0367
Repair kit SFN30	YK0368
Repair kit SFN40R	YK0369
Repair kit SLS20	YK0372
Repair kit SLP20	YK0373
Repair kit SNS40	YK0374
Repair kit SNS50XP/SQS55XP	YK0375
Repair kit SFN1, SKS, SPS	YK0376
Repair kit PW 2"	YK0378
Repair kit SLS15/18 FiP15/18/2N1	YK0393

## STAPLE REMOVER



DESCRIPTION	ART. NR.
Senco staple remover	960037
Spare blade Senco staple remover	960038

DESCRIPTION	ART. NR.
Repair kit FiP10 new main body	YK0397
Repair kit PW150-200	YK0402
T-Driver kit SCN90CXP	YK0414
Piston/driver kit FramePro702XP	YK0418
Firing/trigger system kit SNS44XP	YK0421
Piston stop kit SNS44XP	YK0422
Repair kit RP450	YK0426
Firing system kit	YK0444EU
SN901XP/902 951XP/952	
Piston stop kit	YK0445EU
SN901XP/902 SN951XP/952	
Repair kit PAL57	YK0446
Repair kit PAL70	YK0447
Piston stop kit SN951XP/952XP	YK0768EU
Repair kit SCN48	YK0769
Repair kit SCN75	YK0770
Repair kit SCN49	YK0771
Repair kit PAL50	YK0772
Repair kit PAL90	YK0774
Repair kit SFW09-C	YK0775EU
Repair kit PAL83	YK0779
Repair kit FinishPro18Mg	YK0780
Repair kit WC150XP/WC200XP	YK0783EU
Repair kit WC150XP/WC200XP	YK0784EU
Repair kit SCN34	YK0785
Repair kit SN1302	YK0789EU
Repair kit SC15	YK0790EU
Driver/back plate upgrade kit SNS44	YK0793
Driver/back plate upgrade kit SNS41	YK0794
Drive assembly Fusion FN65DA	YK0798EU
Cylinder assembly Fusion FN55AX	YK0799EU
Drive assembly Fusion FN65RHS	YK0801EU
Repair kit SFT10XP	YK0802EU
Repair kit SFT10XP	YK0803EU
Repair kit SFT10XP	YK0804EU
Cap assembly upgraded WC150XP	YK0818
Drive assembly Fusion FN65RHA	YK0822EU
Long Magazine kit SGP40-S	YK0837EU
Trigger valve system kit SHS51XP	YK0838EU
Piston stop kit SHS51XP	YK0839EU
Trigger valve system kit SHS50XP	YK0840EU
Piston stop kit SHS50XP	YK0841EU



**SENCO®**

### CABLE CLIP VARIABLE



DESCRIPTION	ART. NR.
Cable clip, variable, 14-18mm	918ABT
Cable clip, variable, 20-25mm	925ABT

### P CABLE CLIP, DOUBLE



DESCRIPTION	ART. NR.
P cable clip, double, 16mm	916FPD
P cable clip, double, 20mm	920FPD
P cable clip, double, 25mm	925FPD

### MULTICLIP



DESCRIPTION	ART. NR.
Multiclip, 16mm	916UT

### P CABLE CLIP



DESCRIPTION	ART. NR.
P cable clip, 16mm	916FP
P cable clip, 18mm	918FP
P cable clip, 20mm	920FP
P cable clip, 22mm	922FP
P cable clip, 25mm	925FP
P cable clip, 28mm	928FP

### P CABLE CLIP, METAL



DESCRIPTION	ART. NR.
P cable clip, metal, 16mm	916FT
P cable clip, metal, 18mm	918FT
P cable clip, metal, 20mm	920FT
P cable clip, metal, 22mm	922FT
P cable clip, metal, 25mm	925FT
P cable clip, metal, 28mm	928FT

### METAL WASHER



DESCRIPTION	ART. NR.
Metal washer 25,4x1,1mm	SWM025B

### MAGNETIC NOSE PIECE



DESCRIPTION	ART. NR.
For SGP40S/SGP40L	HC0697
For SGP40/SAP40	HC0690



# CORDLESS



**RESISTANT TO DAMAGE**

**PATENTED REFLEX-SHOT  
DESIGN**

**INNOVATIVE EZ-CLEAR  
FEATURE**

**THUMBWHEEL  
DEPTH-OF-DRIVE**

**NOSE MOUNTED  
LED LIGHT**



Senco nailers with Fusion Technology use compressed air that is permanently sealed in the tool's self-contained, built-in cylinder to unleash a shot of pure, portable pneumatic power every time you pull the trigger. You don't need to buy costly gas cells. There's no smelly exhaust, no ramp up time and virtually no cleaning or servicing costs.

Senco Gas tools have proven their cordless convenience in a variety of applications, ranging from wood construction to 2nd fix applications.







**SENCO®**



**HIGH PERFORMANCE  
BATTERY**

**LEFT/RIGHT USABLE  
BELT HOOK**

**SELECTABLE DRIVE  
SWITCH**

**CORDLESS**

Cordless convenience  
pneumatic power

**2** YEAR  
LIMITED  
WARRANTY

**CORD  
LESS**

MAKING HARD WORK  
**EASIER**

# STRIPNAILERS

## FINISH NAILER 1,8MM F-15 FUSION



∠ 34°



## FINISH NAILER 1,6MM F-16A FUSION



∠ 20°



## FINISH NAILER 1,6MM F-16S FUSION



### TECHNICAL INFORMATION

Length	330 mm
Width	76 mm
Height	348 mm
Weight	2,8 kg
Actuation	BF (TF)
Battery	18V Li-ion
Recharge time	45 min
Magazine capacity	110


### APPLICATIONS

Finish and trim, baseboard, cabinets and caskets, chair rail, decorative trim, door & window, casing, furniture trim, paneling

### FEATURES

- Fusion cordless pneumatic technology
- Adjustable depth of drive
- 18V Li-ion battery
- Selectable trigger

DESCRIPTION	ART. NR.
Fusion FN65DA BF/TF	5N2001N
Fusion FN65DA BF/TF+ 1 extra battery	5N2501N
Fusion FN65DA BF/TF UK	5N7001N
Fusion FN65DA BF/TF UK + 1 extra battery	5N7501N



### TECHNICAL INFORMATION

Length	279 mm
Width	76 mm
Height	330 mm
Weight	2,7 kg
Actuation	BF (TF)
Battery	18V Li-ion
Recharge time	45 min
Magazine capacity	100


### APPLICATIONS

All 2nd-fix applications including architrave, dado, skirting, casings, baseboards, frames

### FEATURES

- Fusion cordless pneumatic technology
- Adjustable depth of drive
- 18V Li-ion battery
- Selectable trigger

DESCRIPTION	ART. NR.
Fusion FN65RHA BF/TF	5P2001N
Fusion FN65RHA BF/TF + 1 extra battery	5P2501N
Fusion FN65RHA BF/TF UK	5P7001N
Fusion FN65RHA BF/TF UK + 1 extra battery	5P7501N



### TECHNICAL INFORMATION

Length	330 mm
Width	76 mm
Height	330 mm
Weight	2,7 kg
Actuation	BF (TF)
Battery	18V Li-ion
Recharge time	45 min
Magazine capacity	100


### APPLICATIONS

All 2nd-fix applications including architrave, dado, skirting, casings, baseboards, frames

### FEATURES

- Fusion cordless pneumatic technology
- Adjustable depth of drive
- 18V Li-ion battery
- Selectable trigger

DESCRIPTION	ART. NR.
Fusion FN65RHS BF/TF	6U2001N
Fusion FN65RHS BF/TF + 1 extra battery	6U2501N
Fusion FN65RHS BF/TF UK	6U7001N
Fusion FN65RHS BF/TF UK + 1 extra battery	6U7501N





**SENCO®**

## BRAD NAILER 1,2MM F-18 FUSION



### TECHNICAL INFORMATION

Length	279 mm
Width	76 mm
Height	343 mm
Weight	2,7 kg
Actuation	BF (TF)
Battery	18V Li-ion
Recharge time	45 min
Magazine capacity	110

### APPLICATIONS

Molding and decorative trim, furniture trim, window beading, blind pinning of upholstered and trim panels, rattan, scribe molding, cabinets, drawers and picture frame assembly

### FEATURES


- Fusion cordless pneumatic technology
- Adjustable depth of drive
- 18V Li-ion battery
- Selectable trigger

### DESCRIPTION

### ART. NR.

Fusion FN55AX BF/TF	6E2001N
Fusion FN55AX BF/TF + 1 extra battery	6E2501N

Fusion FN55AX BF/TF UK	6E7001N
Fusion FN55AX BF/TF UK + 1 extra battery	6E7501N





# STRIPNAILERS

## BRAD NAILER 1,2MM GT50AX



## FINISH NAILER 1,6MM GT65RHA



∠ 20°



## FINISH NAILER 1,6MM GT65RHS



### TECHNICAL INFORMATION

Length	320 mm
Width	86 mm
Height	285 mm
Weight	2,3 kg
Actuation	TF
Battery	6V Ni-MH
Recharge time	2 hours
Fuel cell	18g (31,5x80 mm)
Magazine capacity	100


### APPLICATIONS

Molding and decorative trim, furniture trim, window beading, blind pinning of upholstered and trim panels, rattan, scribe molding, cabinets, drawers and picture frame assembly

### FEATURES

- High voltage ignition
- Adjustable depth of drive
- EZ-Clear Nose
- Works in all weather conditions

DESCRIPTION	ART. NR.
GT50AX TF	7R2001N
GT50AX Restr. UK	7R7001N



### TECHNICAL INFORMATION

Length	340 mm
Width	86 mm
Height	340 mm
Weight	2,1 kg
Actuation	TF
Battery	6V Ni-MH
Recharge time	2 hours
Fuel cell	18g (31,5x80 mm)
Magazine capacity	100


### APPLICATIONS

All 2nd-fix applications including architrave, dado, skirting, casings, baseboards, frames

### FEATURES

- High voltage ignition
- Works in all weather conditions
- Adjustable depth of drive
- EZ-Clear Nose

DESCRIPTION	ART. NR.
GT65RHA TF	5S2001N
GT65RHA Restr. UK	5S7001N



### TECHNICAL INFORMATION

Length	312 mm
Width	86 mm
Height	300 mm
Weight	2,3 kg
Actuation	TF
Battery	6V 1,5 Ah Ni-MH
Recharge time	2 hours
Fuel cell	18g (31,5x80 mm)
Magazine capacity	100


### APPLICATIONS

All 2nd-fix applications including architrave, dado, skirting, casings, baseboards, frames

### FEATURES

- High voltage ignition
- Works in all weather conditions
- Adjustable depth of drive
- EZ-Clear Nose

DESCRIPTION	ART. NR.
GT65RHS TF	6D2001N
GT65RHS Restr. UK	6D7001N





# SENCO®

## HAFTEN NAILER GT35HN



## FINISH NAILER 1,8MM GT65DA



## CH FRAMING NAILER GT90CH



### TECHNICAL INFORMATION

Length	326 mm
Width	136 mm
Height	309 mm
Weight	2,26 kg
Actuation	TF
Battery	6V 1,5 Ah Ni-MH
Recharge time	2 hours
Fuel cell	18g (31,5x80 mm)
Magazine capacity	36

### APPLICATIONS

Fastening haften onto wood on roofs, tin roofs, zinc sheathing and covering. Great for any application where cordless convenience would be a benefit.


### FEATURES

- Cordless convenience
- Powerful motor
- Durable metal magazine
- Works in all weather conditions

### DESCRIPTION

### ART. NR.

GT35HN	3VS2001N
GT35HN Restr. UK	3VS7001N



### TECHNICAL INFORMATION

Length	318 mm
Width	91 mm
Height	362 mm
Weight	2,4 kg
Actuation	TF
Battery	6V 1,5 Ah Ni-MH
Recharge time	2 hours
Fuel cell	18g (31,5x80 mm)
Magazine capacity	110

### APPLICATIONS

Finish and trim, baseboard, cabinets and caskets, chair rail, decorative trim, door & window, casing, furniture trim, paneling


### FEATURES

- High voltage ignition
- Adjustable depth of drive
- EZ-Clear Nose
- Works in all weather conditions

### DESCRIPTION

### ART. NR.

GT65DA TF	5R2001N
GT65DA Restr. UK	5R7001N



### TECHNICAL INFORMATION

Length	371 mm
Width	107 mm
Height	376 mm
Weight	3,6 kg
Actuation	TF
Battery	6V 1,5 Ah Ni-MH
Recharge time	2 hours
Fuel cell	40g (31,5x165 mm)
Magazine capacity	70

### APPLICATIONS

Timber frame, subfloors, pallets and crates, decking, shuttering, frames


### FEATURES

- High voltage ignition
- Adjustable depth of drive
- Durable metal magazine
- Comfort grip
- Works in all weather conditions

### DESCRIPTION

### ART. NR.

GT90CH TF	5F2001N
GT90CH Restr. UK	5F7001N



# STRIPNAILERS / ACCESSORIES

## FRH FRAMING NAILER GT90FRH



## CONCRETE NAILER SGP40S



## METAL CONNECTOR GT60NN



### TECHNICAL INFORMATION

Length	371 mm
Width	107 mm
Height	376 mm
Weight	3,6 kg
Actuation	TF
Battery	6V 1,5 Ah Ni-MH
Recharge time	2 hours
Fuel cell	40g (31,5x165 mm)
Magazine capacity	70



### APPLICATIONS

Timber frame, subfloors, pallets and crates, decking, shuttering, frames

### FEATURES

- High voltage ignition
- Adjustable depth of drive
- Durable metal magazine
- Comfort grip
- Works in all weather conditions

DESCRIPTION	ART. NR.
GT90FRH TF	5G2001N
GT90FRH Restr. UK	5G7001N



### TECHNICAL INFORMATION

Length	340 mm
Width	107 mm
Height	380 mm
Weight	4,0 kg
Actuation	TF
Battery	6V 1,5 Ah Ni-MH
Recharge time	2 hours
Fuel cell	40g (31,5x165 mm)
Magazine capacity	22


### APPLICATIONS

Ceiling grid to concrete, fastening of drywall track

### FEATURES

- High voltage ignition
- Adjustable depth of drive
- Interchangeable short and long magazine
- Comfort grip
- Rear loading

DESCRIPTION	ART. NR.
SGP40S Restr.	5H9211N
SGP40L with long Magazine	5H9211N-L
SGP40S Restr. (UK)	5H9711N



### TECHNICAL INFORMATION

Length	355 mm
Width	108 mm
Height	393 mm
Weight	3,6 kg
Actuation	TF
Battery	6V 1,4 Ah Ni-MH
Recharge time	2 hours
Fuel cell	40g (31,5x165 mm)
Magazine capacity	20

### APPLICATIONS

Pre-drilled metal plates, pre-drilled metal strips, joist hanger

### FEATURES

- High voltage ignition
- Adjustable depth of drive
- Rear loading
- Overhanging nail tip for locates pre-punched holes

DESCRIPTION	ART. NR.
GT60NN TF	7N2001N
GT60NN Restr. UK	7N7001N







# SENCO®

## GAS TOOL LUBRICATION



DESCRIPTION	ART. NR.
Gas tool lubrication 100 ml	PC1236

## FUEL CELLS



DESCRIPTION	ART. NR.
Polar fuel cell 40 gr. (12pcs.)	PC1308P
Polar fuel cell 18 gr. (12pcs.)	PC1309P
Polar fuel cells 2 x 40 gr. (blis)	PC1307P
Polar fuel cells 2 x 18 gr. (blis)	PC1310P

## GAS TOOL CLEANER



DESCRIPTION	ART. NR.
Tool cleaner for gas tools 100 ml	PC1235

## GAS TOOL CLEANING KIT



DESCRIPTION	ART. NR.
Gas tool cleaning kit	PC1239

## GAS TOOL BATTERIES



DESCRIPTION	ART. NR.
Gas tools battery 6V	VB0109EU

## GAS TOOL BATTERY CHARGER



DESCRIPTION	ART. NR.
Gas tools battery charger	VA0058EU
Adapter 220V	VB0115EU

## FUSION BATTERIES



DESCRIPTION	ART. NR.
Fusion battery 18V Li-ion 1,5 Ah	VB0160EU
Fusion battery 18V Li-ion 3,0 Ah	VB0162EU

## FUSION BATTERY CHARGER




DESCRIPTION	ART. NR.
Fusion tools battery charger 18V Li-ion EU	VB0157EU
Fusion tools battery charger 18V Li-ion UK	VB0159EU

## CAR ADAPTOR FOR GAS TOOL BATTERIES



DESCRIPTION	ART. NR.
Gas tool battery car adaptor (12V)	PC1196

Senco fasteners guarantee a fault-free use of Senco tools and a perfect finish. All Senco fasteners are produced according to international standards, like CE.





**SENCO®**



**FASTENERS**

•USE•  
GENUINE  
**SENCO®**  
FASTENERS™

**FAST  
ENER**  
—

MAKING HARD WORK  
**EASIER**




# FASTENERS


## INDEX

Senco offers a wide range of fasteners. For every application, data sheets are available with different specifications, such as point geometry, material and surface coating. For advice contact your Senco dealer.

### STAPLE POINTS



### NAIL POINTS



## MATERIAL / FINISH



Bright Basic



Electrolytic galvanized <12μ



Electrolytic galvanized 12μ



Mechanical galvanized 30μ



Hot dip galvanized



Stainless Steel



Stainless Steel



Aluminum

## CE MARKING ON FASTENERS

Many building products used for on-site construction and factory manufacture throughout the EU require the CE mark. This logo shows that the product has been tested with the appropriate European harmonised test method. This ensures that the products are safe to use and provides important information about the essential characteristics for use in the intended application. The rules for CE marking were tightened on July 1st, 2013 with the introduction of the new Construction Products Regulation (305/2011).

With the introduction new Construction Products Regulation (CPR) you are required to show the Declaration of Performance of the product next to the CE marking. The aim of the declaration is to inform architects, structural engineers and contractors about the essential performance characteristics of the product, thereby providing the necessary information to ensure the product is suitable for use in a building or any part of it in order to meet the design requirements package.

Senco fasteners intended for use in structural timber applications are manufactured in accordance with the requirements outlined in EN14592. In the Declaration of Performance product details are listed with the relevant flexural strength, pull-out and pull-through values, tensile strength and climatic resistance classification indicated.

Fasteners for the mechanical fixing of plasterboard meet the standards of EN14566 which is tested for exposure to fire class A1 according to and flexibility without breakage phenomena.




Performance statements for Senco fasteners manufactured in accordance with the Construction Products Regulation can be found on the following website: [www.senco.eu](http://www.senco.eu)






**SENCO®**

## SERVICE CLASS

	<b>SERVICE CLASS 1</b>  indoor use	<b>SERVICE CLASS 2</b>  outdoor protected	<b>SERVICE CLASS 3</b>  outdoor use
For nails & screws $\varnothing \leq 4\text{mm}$	None	1) 12 $\mu\text{m}$ electrolytic galvanized	1) 25 $\mu\text{m}$ electrolytic galvanized 2) 30 $\mu\text{m}$ mechanical galvanized 3) 55 $\mu\text{m}$ hot dip galvanized
	Bright Basic Electrolytic galvanized <12 $\mu$ Electrolytic galvanized 12 $\mu$ Electrolytic galvanized 25 $\mu$ Mechanical galvanized 30 $\mu$ Hot dip galvanized 55 $\mu$		
Staples	1) 12 $\mu\text{m}$ electrolytic galvanized	1) 12 $\mu\text{m}$ electrolytic galvanized	Stainless Steel
	Electrolytic galvanized 12 $\mu$ Stainless Steel		


## WHEN DOES MY FASTENER NEED CE MARKING?



MAKING HARD WORK  
**EASIER**

# STAPLES

## LIGHT STAPLE A STAPLE



### TECHNICAL INFORMATION

Crown size	4,8 mm
Length	4-16 mm

## LIGHT STAPLE AT (80) STAPLE



### TECHNICAL INFORMATION

Crown size	12,7 mm
Length	6-16 mm

## LIGHT STAPLE B STAPLE



### TECHNICAL INFORMATION

Crown size	12,7 mm
Length	4-16 mm

## LIGHT STAPLE C STAPLE



### TECHNICAL INFORMATION

Crown size	9,5 mm
Length	2-16 mm

## LIGHT STAPLE E STAPLE



### TECHNICAL INFORMATION

Crown size	4,8 mm
Length	6-16 mm

## LIGHT STAPLE F STAPLE



### TECHNICAL INFORMATION

Crown size	12,7 mm
Length	6-16 mm

## LIGHT STAPLE G STAPLE



### TECHNICAL INFORMATION

Crown size	9,5 mm
Length	6-16 mm


## LIGHT STAPLE H STAPLE



### TECHNICAL INFORMATION

Crown size	11,1 mm
Length	8-14 mm

## LIGHT STAPLE J STAPLE



### TECHNICAL INFORMATION

Crown size	11,9 mm
Length	10-16 mm





**SENCO®**


### MEDIUM STAPLE 92 STAPLE



#### TECHNICAL INFORMATION

Crown size 8,5 mm  
Length 18-40 mm


### MEDIUM STAPLE K STAPLE



#### TECHNICAL INFORMATION

Crown size 6,4 mm  
Length 12-25 mm


### MEDIUM STAPLE L STAPLE



#### TECHNICAL INFORMATION

Crown size 6,4 mm  
Length 12-38 mm


### MEDIUM STAPLE M STAPLE



#### TECHNICAL INFORMATION

Crown size 9,5 mm  
Length 12-38 mm


### HEAVY STAPLE N STAPLE



#### TECHNICAL INFORMATION

Crown size 11,1 mm  
Length 16-63 mm


### HEAVY STAPLE O (14) STAPLE



#### TECHNICAL INFORMATION

Crown size 11,1 mm  
Length 25-50 mm


### HEAVY STAPLE P STAPLE



#### TECHNICAL INFORMATION

Crown size 25,4 mm  
Length 12-50 mm


### HEAVY STAPLE Q STAPLE



#### TECHNICAL INFORMATION

Crown size 11,2 mm  
Length 38-63 mm

### HEAVY STAPLE S STAPLE




#### TECHNICAL INFORMATION

Crown size 11,7 mm  
Length 70-90 mm

MAKING HARD WORK  
**EASIER**

# STAPLES / STRIPNAILS


## HEAVY STAPLE SP STAPLE



### TECHNICAL INFORMATION

Crown size	27,0 mm
Length	75-160 mm


## PACKAGING STAPLE 1 STAPLE



### TECHNICAL INFORMATION

Crown size	35 mm
Length	15-22 mm


## PACKAGING STAPLE U STAPLE



### TECHNICAL INFORMATION

Crown size	32 mm
Length	15-22 mm


## 1,8 MM SMOOTH (DA)



### TECHNICAL INFORMATION

Head type	Brad head
Length	25-63 mm
Angle	34°


## 2,3 MM SMOOTH (EC)



### TECHNICAL INFORMATION

Head type	Clipped head
Length	45-60 mm
Angle	34°


## 2,9 MM BARBED (GB)



### TECHNICAL INFORMATION

Head type	Full round head
Length	50-75 mm
Angle	17°/ 20°


## 2,9 MM SMOOTH (GC)



### TECHNICAL INFORMATION

Head type	Clipped head
Length	50-85 mm
Angle	34°


## 2,9 MM RING (GE)



### TECHNICAL INFORMATION

Head type	Clipped head
Length	50-80 mm
Angle	34°

## 3,1 MM BARBED (HB)




### TECHNICAL INFORMATION

Head type	Full round head
Length	90 mm
Angle	17°/20°



**SENCO®**


### 3,1 MM SMOOTH (HC)



#### TECHNICAL INFORMATION

Head type	Clipped head
Length	70-100 mm
Angle	34°


### 3,1 MM RING (HE)



#### TECHNICAL INFORMATION

Head type	Clipped head
Length	80-90 mm
Angle	34°


### 3,3 MM SMOOTH (KC)



#### TECHNICAL INFORMATION

Head type	Clipped head
Length	90-100 mm
Angle	34°


### 3,8 MM SMOOTH (MD)



#### TECHNICAL INFORMATION

Head type	Full round head
Length	100-130 mm
Angle	20°/ 24°


### 4,2 MM SMOOTH (OD)



#### TECHNICAL INFORMATION

Head type	Full round head
Length	130-160 mm
Angle	20°/ 24°


### 4,6 MM SMOOTH (TD)



#### TECHNICAL INFORMATION

Head type	Full round head
Length	145-160 mm
Angle	20°/ 24°


### 1,6 MM BARBED (RW) FLOORING CLEAT



#### TECHNICAL INFORMATION

Head type	L cleat head
Length	38-50 mm
Angle	0°


### 2,8 MM RING (1L) HAFTEN NAIL



#### TECHNICAL INFORMATION

Head type	Full round head
Length	22-35 mm
Angle	20°/ 21°

### 4,1 MM RING (NN) METAL CONNECTOR



#### TECHNICAL INFORMATION


Head type	Full round head
Length	40-60 mm
Angle	34°

MAKING HARD WORK  
**EASIER**



# COILNAILS

## 2,1 MM SMOOTH (SC)



### TECHNICAL INFORMATION

Head type	Flat head
Length	32-50 mm
Angle	16°
Collation	Wire collation
Winding	Conical wound


## 2,1 MM RING (SE)



### TECHNICAL INFORMATION

Head type	Flat head
Length	32-50 mm
Angle	16°
Collation	Wire collation
Winding	Conical wound


## 2,1 MM RING (SG)



### TECHNICAL INFORMATION

Head type	Cupped head
Length	35-50 mm
Angle	16°
Collation	Wire collation
	Plastic collation
Winding	Flat wound


## 2,1 MM SMOOTH (SS)



### TECHNICAL INFORMATION

Head type	Dome head
Length	35-50 mm
Angle	16°
Collation	Wire collation
	Plastic collation
Winding	Conical wound
	Flat wound


## 1,6 MM SMOOTH (RC)



### TECHNICAL INFORMATION

Head type	Flat head
Length	25-32 mm
Angle	16°
Collation	Wire collation
	Plastic collation
Winding	Conical wound

## 1,6 MM SMOOTH (RD)



### TECHNICAL INFORMATION

Head type	Flat head
Length	19 mm
Angle	0°
Collation	Plastic collation
Winding	Flat wound



**SENCO®**


### 1,8 MM RING (DL)



#### TECHNICAL INFORMATION

Head type	Flat head
Length	19-25 mm
Angle	0°
Collation	Plastic collation
Winding	Flat wound


### 2,3 MM SMOOTH (ED)



#### TECHNICAL INFORMATION

Head type	Flat head
Length	50-65 mm
Angle	0°/16°
Collation	Wire collation
Winding	Flat wound


### 2,3 MM RING (EL)



#### TECHNICAL INFORMATION

Head type	Flat head
Length	38-65 mm
Angle	0°/16°
Collation	Wire collation
Winding	Flat wound


### 2,5 MM RING (BG)



#### TECHNICAL INFORMATION

Head type	Cupped head
Length	35 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound


### 2,5 MM SMOOTH (BJ)



#### TECHNICAL INFORMATION

Head type	Flat head
Length	50-70 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound

### 2,5 MM RING (BL)




#### TECHNICAL INFORMATION

Head type	Flat head
Length	50-75 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound

MAKING HARD WORK  
**EASIER**

# COILNAILS


## 2,5 MM RING (BS)



### TECHNICAL INFORMATION

Head type	Dome head
Length	35-65 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound


## 2,5 MM SCREW (BX)



### TECHNICAL INFORMATION

Head type	Flat head
Length	32-38 mm
Angle	0°/16°
Collation	Plastic collation
Winding	Flat wound

## 2,9 MM SMOOTH (GD)



### TECHNICAL INFORMATION

Head type	Flat head
Length	65-90 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound

## 2,9 MM RING (GL)



### TECHNICAL INFORMATION

Head type	Flat head
Length	50-90 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound


## 2,9 MM SCREW (GK)



### TECHNICAL INFORMATION

Head type	Full round head
Length	50-90 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound

## 2,9 MM RING (GS)



### TECHNICAL INFORMATION


Head type	Dome head
Length	70-80 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound





**SENCO®**


### 3,1 MM BARBED (HB)



#### TECHNICAL INFORMATION

Head type	Flat head
Length	90 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound

### 3,1 MM SMOOTH (HD)



#### TECHNICAL INFORMATION

Head type	Flat head
Length	80-90 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound


### 3,1 MM SMOOTH (HJ)



#### TECHNICAL INFORMATION

Head type	Large flat head
Length	19-38 mm
Angle	16°/20°
Collation	Wire collation
Winding	Conical wound


### 3,1 MM RING (HL)



#### TECHNICAL INFORMATION

Head type	Flat head
Length	65-90 mm
Angle	16°/20°
Collation	Wire collation
Winding	Flat wound

### 3,3 MM SMOOTH (KR)



#### TECHNICAL INFORMATION

Head type	Duplex head
Length	55-75 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound

### 3,8 MM SMOOTH (MD)




#### TECHNICAL INFORMATION

Head type	Flat head
Length	120 mm
Angle	16°
Collation	Wire collation
Winding	Flat wound

MAKING HARD WORK  
**EASIER**

# PINS AND BRADS / OTHERS

## 1,2 MM BRAD (AX)



### TECHNICAL INFORMATION

Diameter	18 ga, 1,2 mm
Shank type	Smooth
Head type	Medium head
Length	15-55 mm
Angle	0°


## 1,2 MM BRAD (AY)



### TECHNICAL INFORMATION

Diameter	18 ga, 1,2 mm
Shank type	Smooth
Head type	Slight head
Length	15-42 mm
Angle	0°

## 1,2 MM BRAD (AZ)



### TECHNICAL INFORMATION

Diameter	18 ga, 1,2 mm
Shank type	Smooth
Head type	Headless
Length	12-25 mm
Angle	0°


## 0,6 MM PIN (CZ)



### TECHNICAL INFORMATION

Shank type	Smooth
Head type	Headless
Length	12-25 mm
Angle	0°


## 1,6 MM BRAD (RH)



### TECHNICAL INFORMATION

Diameter	16 ga, 1,6 mm
Shank type	Smooth
Head type	T head
Length	32-65 mm
Angle	20°

## 1,6 MM BRAD (RX)



### TECHNICAL INFORMATION

Diameter	16 ga, 1,6 mm
Shank type	Smooth
Head type	T head
Length	25-65 mm
Angle	0°



**SENCO®**


### PREMIUM CONCRETE PINS (SCP)



#### TECHNICAL INFORMATION

Diameter	2,7 mm 3,1 mm
Head type	Full round head
Length	15-40 mm

### REGULAR CONCRETE PINS (SCP)



#### TECHNICAL INFORMATION

Diameter	2,7 mm 3,1 mm
Head type	Full round head
Length	15-40 mm


### 2,2 MM T-NAIL (PH)



#### TECHNICAL INFORMATION

Diameter	2,2 mm 2,5 mm
Shank type	Smooth
Head type	T head
Length	18-64 mm


### 33,6 MM CORRUGATED (WM)



#### TECHNICAL INFORMATION

Length	25 mm
--------	-------


### 25,4 MM CORRUGATED (X)



#### TECHNICAL INFORMATION

Length	9-15 mm
--------	---------

### 11,6 MM SENCLAMP (Y)



#### TECHNICAL INFORMATION

Length	8-14 mm
--------	---------

MAKING HARD WORK  
**EASIER**



# STAPLE CODING CHART

1ST DIGIT CROWN & WIDTH & THICK MM			
Carton close (crown35mm)			
1(XB)	35,00	2,27	0,90
A	4,76	0,75	0,54
B	12,70	0,75	0,54
C	9,53	0,75	0,54
E	4,76	1,25	0,51
F	12,70	1,25	0,51
G	9,53	1,13	0,61
H	11,11	1,25	0,51
J	11,90	1,89	0,55
K	6,35	1,14	0,78
L	6,35	1,23	1,04
M	9,53	1,23	1,04
N	10,60	1,58	1,40
O	10,40	1,45	1,29
P	25,40	1,58	1,40
Q	11,20	1,88	1,70
R	4,76	1,14	0,76
RS	11,11	2,08	1,92
S	11,70	2,08	1,92
Carton close (crown32mm)			
U	32,00	1,87	0,94
Corrugated (crown25mm)			
WW			
W	4,76	0,81	0,64
X	25,40	2,18	0,51
Y	11,11	2,08	0,51
Z	Special fastener		
AT	12,70	0,91	0,69
SP	27,00	2,08	1,80
31	12,20	3,30	2,70
P88	12,70	1,20	0,50
92	8,47	1,25	1,00
100	11,11	1,57	1,40

2ND & 3RD DIGITS LENGTH	
01	3mm
02	4mm
03	5mm
04	6mm
05	8mm
06	10mm
07	11mm
08	12mm
09	14mm
10	16mm
11	19mm
12	22mm
13	25mm
14	28mm
15	32mm
16	35mm
17	38mm
18	41mm
19	44mm
20	48mm
21	50mm
22	54mm
23	56mm
24	60mm
25	63mm
26	70mm
27	76mm
28	82mm
29	90mm
30	100mm
36	110mm
41	120mm
45	130mm
48	140mm
54	150mm

4TH DIGIT POINT	
A	Blunt
B	Chisel
C	Inside chisel
D	Outside chisel
E	Easy clinch
F	Divergent
G	Outside chisel divergent
H	Cross cut chisel
J	Cross cut chisel divergent
L	Chisel divergent
M	Self clinch
N	Sharp chisel

5TH DIGIT WIRE CHEMISTRY & FINISH	
A	Regular galvanized std tensile
B	Regular galvanized high tensile
C	Liquor finish, standard tensile
D	Liquor finish, ultra high tensile
E	Liquor finish, low tensile
F	Senclamp
G	Stainless steel, AISI 304 (A2)
H	Stainless steel, high tensile, AISI 304
K	Steel core aluminum
L	Steel core bronze
M	Aluminium
N	Bronze
P	Regular galvanized (flash 0 or greater)
Q	Class 1 galvanized, standard tensile
R	Bright basic, standard tensile
S	Special hardened steel
U	Stainless steel, AISI 316 (A4)
X	Xtra heavy electro galvanized 12 micron

6TH DIGIT FINISH	
A	Plain
B	Sencoted
C	Painted
D	Painted / Sencoted
E	Coated



EXAMPLE: C 0 6 B A A P

1 2 3 4 5 6 7

1	C	9,53	0,75	0,54	2 3	06	10mm	4	B	Chisel	5	A	Regular galvanized std tensile	6	A	Plain
---	---	------	------	------	-----	----	------	---	---	--------	---	---	--------------------------------	---	---	-------




**SENCO®**

#### 7TH DIGIT FEATURES

<b>B</b>	Band production for heavy staples
<b>L</b>	Special leg length
<b>N</b>	Carton / label / count change
<b>P</b>	Bulk pack
<b>S</b>	Special strong glue
<b>T</b>	Taped strips
<b>V</b>	Angular strips
<b>Z</b>	Coiled staple

#### 8TH DIGIT SOURCE ETC.

<b>HL</b>	Strong adhesive
<b>123</b>	Number represents RAL code/color of staple back
<b>9005</b>	Completely black band production




7

**P** Bulk pack

MAKING HARD WORK  
**EASIER**

# STRIPNAIL CODING CHART

1ST DIGIT GAUGE & DIA (MM)		2ND DIGIT HEAD/SHANK CONFIGURATION		3RD & 4TH DIGITS LENGTH			5TH DIGIT POINT		6TH DIGIT WIRE CHEMISTRY & FINISH	
				mm	US					
A	18 Gauge	A	Brad head	46	35mm	16	A	Diamond	A	Regular galvanized std tensile
B	2,5 mm	B	Barbed, full round head	47	40mm	18	B	Blunt dia	C	Liquor finish
C	23 Gauge, 0,68 mm	C	Flat head, smooth for clipped head stripnails	49	45mm	19	C	Blunt	D	"Wheatherex II" galvanized
D	15 Gauge, 1,8 mm	D	Flat head, smooth shank, plastic collated, full round head	51	50mm	21	D	Blunt chisel	G	Stainless steel, AISI 304 (A2)
E	2,3 mm	E	Flat head, ring for clipped head stripnails	52	55mm	22	E	Sharp chisel	H	Bright basic, heat-treated
F	2,46 mm	F	Flat head, screw for clipped head stripnails	54	60mm	24	F	Chisel	I	Regular galvanized, heat-treated
G	2,87 mm	H	"T" head, smooth shank, full round head stripnails	55	65mm	25	G	Semi-blunt	J	Hot-dipped galvanized - corrosivity class 2
H	3,1 mm	K	Flat head, screw shank, plastic collated stripnails, full round head	56	70mm	26	H	Clinch point	K	Hot-dipped galvanized - corrosivity class 4
K	3,3 mm	L	Flat head, ring shank, plastic collated stripnails, full round head	57	75mm	27			M	Aluminium
M	3,8 mm	N	Full round head metal connector nail, aggressive ring DIN1052	58	80mm	28			P	Bright basic, std tensile
N	4,1 mm	P	Full round head metal connector nail, aggressive ring	85	85mm	85			R	Regular galvanized, yellow chromated
O	4,2 mm	Q	Flat head, 1/3rd ring, for full round head nails	59	90mm	29			S	Hot-dipped galvanized - corrosivity class 3
P	2,2 mm	S	Flat, ring, dome full round head	95	95mm	30			T	"Flash" galvanized or greater
Q	3,4 mm	V	Bugle head, metal connector, ring shank, 34 degree	60	100mm	31			U	Stainless steel, AISI 316 (A4)
R	1,6 mm	W	L cleat head, barded shank	61	110mm	32			X	Xtra heavy electro galvanized 12 micron
T	4,6 mm	X	Medium head pin	62	115mm	33			Z	Bronze
U	2,0 mm	Y	Slight head pin	63	120mm	34				
V	2,6 mm	Z	Headless pin	64	125mm	35				
1	2,8 mm	5	Offset full round head, smooth	65	130mm	36				
2	4,5mm	6	Offset full round head, ring	66	135mm	37				
				67	140mm	38				
				68	145mm	39				
				69	150mm	40				
				70	160mm	41				



EXAMPLE: **GC51ASBK R**

1 2 3 4 5 6 7 8 9

1	G	2,87 mm	2	C	Flat head, smooth for clipped head stripnails
---	---	---------	---	---	---

3 4	51	50mm	21
-----	----	------	----

5	A	Diamond
---	---	---------

6	S	Hot-dipped galvanized - corrosivity class 3
---	---	---






**SENCO®**

7TH DIGIT FINISH	
<b>A</b>	Plain
<b>B</b>	Sencoted
<b>C</b>	Painted
<b>D</b>	Painted / sencoted
<b>E</b>	Coated by vendor
<b>S</b>	New glue

8TH DIGIT FEATURES	
<b>D</b>	Full round head nail, paper collated 34 degree
<b>E</b>	24 Degree strip angle
<b>K</b>	Short strip
<b>L</b>	Plastic collation strip with 7,5mm pitch
<b>M</b>	Full round head nail, plastic collated 34 degree
<b>N</b>	Carton / label / count change
<b>P</b>	Bulk pack
<b>R</b>	Retail packaging
<b>S</b>	Full round head, plastic collated 20 degree angled
<b>T</b>	Full round head nail, paper collated 20 degree angled metal connector
<b>X</b>	Half strips - retail packaging
<b>4</b>	17 Degree strip angle

9TH DIGIT SOURCE AND SPECIAL FEATURES	
<b>G</b>	Stainless steel welding wire
<b>K</b>	Short strip
<b>R</b>	Retail packaging
<b>W</b>	Waterproof packaging

10TH DIGIT OTHER	
<b>-FC</b>	Fuel cell
<b>R</b>	Retail packaging



<b>7</b>	<b>B</b>	Sencoted
----------	----------	----------


<b>8</b>	<b>K</b>	Short strip
----------	----------	-------------

<b>9</b>	<b>R</b>	Retail packaging
----------	----------	------------------

MAKING HARD WORK  
**EASIER**

# COILNAIL CODING CHART

1ST DIGIT GAUGE & DIA (MM)		2ND DIGIT HEAD/SHANK CONFIGURATION		3RD & 4TH DIGITS LENGTH		5TH DIGIT POINT		6TH DIGIT WIRE CHEMISTRY & FINISH	
B	2,5 mm	B	Flat head, barbed for conical and flat coils	02	27mm	A	Diamond	A	Regular galvanized std tensile
D	1,8 mm	C	Flat head, smooth for conical coils	03	30mm	B	Blunt dia	C	Liquor finish
E	2,3 mm	D	Flat head, smooth for flat coils	10	16mm	C	Blunt	D	"Wheatherex II" galvanized
F	2,46 mm	E	Flat head, ring for conical coils	11	19mm	D	Blunt chisel	G	Stainless steel, AISI 304 (A2)
G	2,87 mm	F	Flat head, screw for conical nails	12	22mm	E	Sharp chisel	H	Bright basic, heat-treated
H	3,1 mm	G	Cupped head, ring shank, drywall for flat coils	13	25mm	F	Chisel	I	Regular galvanized, heat-treated
K	3,3 mm	J	Flat head, smooth for flat coils (only for 2,5 regular nails and 3,1 roofing nails)	14	28mm	G	Semi-blunt	J	Hot-dipped galvanized - corrosivity class 2
M	3,8 mm	K	Flat head, screw for flat coils	15	32mm	H	Clinch point	K	Hot-dipped galvanized - corrosivity class 4
P	2,2 mm	L	Flat head, ring for flat coils	16	35mm			L	Mechanical galvanized
Q	3,4 mm	M	Flat head, ring for flat coils, conical coil wire positions	17	38mm			M	Aluminium
R	1,6 mm	R	Duplex head	18	40mm			P	Bright basic, std tensile
S	2,1 mm	S	Dome head, ring for conical and flat coils	19	45mm			R	Regular galvanized, yellow chromated
T	4,6 mm	SD	Dome head, smooth for conical and flat coils	21	50mm			S	Hot-dipped galvanized
U	2,03 mm	SK	Dome head, screw for conical and flat coils	22	55mm			T	"Flash" galvanized or greater
V	2,6 mm	X	Knurled	24	60mm			U	Stainless steel, AISI 316 (A4)
1	2,8 mm			25	65mm			X	Xtra heavy electro galvanized 12 micron
				26	70mm			Z	Bronze
				27	75mm				
				28	80mm				
				85	85mm				
				29	90mm				
				30	95mm				
				31	100mm				
				32	110mm				
				33	115mm				
				34	120mm				
				35	125mm				
				36	130mm				
				37	135mm				
				38	140mm				
				39	145mm				
				40	150mm				
				41	160mm				



EXAMPLE: **SE21AABV**

1 2 3 4 5 6 7 8

1	S	2,1 mm	2	E	Flat head, ring for conical coils	3 4	21	50mm	5	A	Diamond	6	A	Regular galvanised std tensile
---	---	--------	---	---	-----------------------------------	-----	----	------	---	---	---------	---	---	--------------------------------



**SENCO®**

#### 7TH DIGIT FINISH

<b>A</b>	Plain
<b>B</b>	Sencoted
<b>C</b>	Painted
<b>D</b>	Painted / sencoted
<b>E</b>	Coated by Verdor

#### 8TH DIGIT FEATURES

<b>A</b>	Coil, flat wound, angular collation, wire, 6,0mm nail spacing
<b>B</b>	Coil, flat wound, straight collation plastic carrier strip (normal 16mm wide)
<b>C</b>	Coil, flat wound, angular collation, plastic carrier strip (normal 16mm wide)
<b>E</b>	Coil, flat wound, angular collation, wire, 10.5mm nail spacing
<b>F</b>	Coil, flat wound, angular collation, wire, 8,2mm nail spacing
<b>G</b>	Coil, flat wound, straight collation, wire
<b>H</b>	Coil, flat wound, angular collation, wire, 7,0 mm nail spacing
<b>R</b>	Retail packaging
<b>V</b>	Coil, conical wound, angular collation, wire, 6,0mm nailspacing (8mm for HJ-nails)
<b>W</b>	Coil, conical wound, straight collation, wire, 8,2mm nail spacing
<b>Z</b>	Coil, conical wound, straight collation, wire, 5,5mm & 6,5 mm nail spacing
<b>9</b>	Coil, flat wound, straight collation, plastic carrier strip (small 9mm)

#### 9TH DIGIT SOURCE

<b>G</b>	Stainless steel welding wire
<b>I</b>	Special leg feature
<b>J</b>	Jumbo coil 1000 nails
<b>N</b>	Carton / label / count change
<b>P</b>	High load
<b>R</b>	Retail packaging
<b>S</b>	Small plastic carrier strip, 9mm wide
<b>D/F</b>	Plastic collation 0 degree
<b>9</b>	Coil, flat wound, straight collation, plastic carrier strip (small 9mm)

#### 10TH DIGIT SOURCE

<b>J</b>	Jumbo coil 1000 nails
<b>N</b>	Carton / label / count change
<b>P</b>	High load
<b>R</b>	Retail packaging
<b>S</b>	Small plastic carrier strip, 9mm wide



7

**B** Sencoted

8

**V** Coil, conical wound, angular collation, wire, 6,0mm nailspacing (8mm for HJ-nails)

MAKING HARD WORK  
**EASIER**



# DURASPIN



**TOOL FREE ADJUSTABLE  
NOSE PIECE**

**QUICK SLIDE BIT RELEASE**



**CORNER FIT ACCESS**



**ADJUSTABLE DEPTH-OF-  
DRIVE WITH LOCK**

**EASY LOAD SYSTEM**



**LANDING STRIP**

The DuraSpin Collated Screw Fastening System Family is the professionals choice for demanding steel framing, drywall and wood fastening applications. The perfect solution for high productivity crews as well as a single man operation. Like having an extra hand, Senco DuraSpin will dramatically increase your productivity.



**SENCO®**

REVERSE SWITCH

PATENTED CLUTCH DESIGN

HIGH TORQUE MOTOR



COMFORTABLE GRIP

TRIGGER LOCK

BELT HOOK

VARIABLE SPEED TRIGGER

**DURASPIN**

Collated screw  
fastening systems



MAKING HARD WORK  
**EASIER**

# COLLATED SCREW SYSTEMS

## HEAVY DUTY MACHINE DS5525-18V



### TECHNICAL INFORMATION

LxWxH	381x86x241 mm
Weight	2,6 kg
RPM	2500
Torque	8Nm
Magazine capacity	50
Max. screw length	55mm
Battery	18V 3Ah Li-ion
Screw per charge	up to 1400
Recharge time	1 hour


### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION	ART. NR
DS5525-18V EU	7X2001N
DS5525-18V UK	7X7001N



\* 13-25 mm screws require special nosepiece

## HEAVY DUTY MACHINE DS5525-AC



### TECHNICAL INFORMATION

LxWxH	425x70x233 mm
Weight	2,1 kg
RPM	2500
Torque	11Nm
Magazine capacity	50
Max. screw length	55mm


### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION	ART. NR
DS5525-AC EU	7U2001N
DS5525-AC UK (230V)	7U7001N
DS5525-AC UK (110V)	7U7002N



\* 13-25 mm screws require special nosepiece

## HIGH SPEED MACHINE DS5550-18V



### TECHNICAL INFORMATION

LxWxH	381x86x241 mm
Weight	2,6 kg
RPM	5000
Torque	5Nm
Magazine capacity	50
Max. screw length	55mm
Battery	18V 3Ah Li-ion
Screw per charge	up to 1400
Recharge time	1 hour


### APPLICATIONS

Drywall to wood or steel studs, subfloor, sheathing, cement board, underlayment

### FEATURES

- 5000 RPM high speed motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION	ART. NR
DS5550-18V EU	7W2001N
DS5550-18V UK	7W7001N



\* 13-25 mm screws require special nosepiece





# SENCO®

## HIGH SPEED MACHINE DS5550-AC

## MULTI PURPOSE MACHINE DS7525-18V

## MULTI PURPOSE MACHINE DS7525-AC



### TECHNICAL INFORMATION

LxWxH	425x70x233 mm
Weight	2,1 kg
RPM	5000
Torque	7Nm
Magazine capacity	50
Max. screw length	55mm

### APPLICATIONS

Drywall to wood or steel studs, subfloor, sheathing, cement board, underlayment

### FEATURES

- 5000 RPM high speed motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION	ART.NR
DS5550-AC EU	7T2001N
DS5550-AC UK (230V)	7T7001N
DS5550-AC UK (110V)	7T7002N



\* 13-25 mm screws require special nosepiece



### TECHNICAL INFORMATION

LxWxH	394x86x241 mm
Weight	2,7 kg
RPM	2500
Torque	8Nm
Magazine capacity	50
Max. screw length	75mm
Battery	18V 3Ah Li-ion
Screw per charge	up to 1400
Recharge time	1 hour

### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Patented sliding screw guide
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock

DESCRIPTION	ART.NR
DS7525-18V EU	7Y2001N
DS7525-18V UK	7Y7001N



### TECHNICAL INFORMATION

LxWxH	438x70x233 mm
Weight	2,2 kg
RPM	2500
Torque	11Nm
Magazine capacity	50
Max. screw length	75mm


### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Patented sliding screw guide
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock

DESCRIPTION	ART.NR
DS7525-AC EU	7V2001N
DS7525-AC UK (230V)	7V7001N
DS7525-AC UK (110V)	7V7002N



# COLLATED SCREW SYSTEMS & ACCESSORIES

## SCREW FASTENING ATTACHMENT DS50

NEW



## SCREW FASTENING ATTACHMENT DS75

NEW



## ADAPTERS DS50, DS75



### TECHNICAL INFORMATION

LxWxH	521x70x89 mm
Weight	0,68 kg
Magazine capacity	50
Max. screw length	55mm

### APPLICATIONS

Metal framing, gypsum sheathing, structural steel decking, drywall to wood and steel, underlayment and flooring, sheathing to wood and steel


### FEATURES

- Easy load rail
- Patented sliding rail
- Tool free adjustable nose piece
- Patent pending corner-fit system
- Precise depth-of-drive adjustment with depth lock

### DESCRIPTION

DESCRIPTION	ART. NR.
DuraSpin attachment DS50	6W2001N

**Please note:** The DS50 is an attachment and requires assembly to a screwdriver.



\* 13-25mm require special metal framing nosepiece FC0948EU.



### TECHNICAL INFORMATION

LxWxH	521x70x89 mm
Weight	1,6 kg
Magazine capacity	50
Max. screw length	75mm

### APPLICATIONS

Metal framing, gypsum sheathing, rigid foam insulation, structural steel decking, drywall to wood and steel underlayment and flooring


### FEATURES

- Easy load rail
- Patented sliding rail
- Tool free adjustable nose piece
- Patent pending corner-fit system
- Precise depth-of-drive adjustment with depth lock

### DESCRIPTION

DESCRIPTION	ART. NR.
DuraSpin attachment DS75	6W2003N

**Please note:** The DS75 is an attachment and requires assembly to a screwdriver.



### BRAND TOOL MODEL

### ART.NR.

#### ADAPTERS FOR DS50, DS75

DeWalt	DW252, DW253, DW255, DW257, DW266, DW272, DW276	ADP009
Makita	FS2200, FS2500, FS4200, FS6200	ADP019
Makita	FS2701	MB0174
Makita	6820, 6821, 6823, 6824, 6825, 6826	ADP011
Makita	6805BV, 6827	ADP020
Hitachi	W6V4, W6VA4, W6VB3, W6VM, W8VB2	ADP010
Hitachi	WH14DM	ADP017



# SENCO®

## DURASPIN BATTERIES



DESCRIPTION	ART. NR.
DuraSpin battery 18V Li-ion 1,5 Ah	VB0160EU
DuraSpin battery 18V Li-ion 3,0 Ah	VB0162EU

## DURASPIN CHARGERS



DESCRIPTION	ART. NR.
Battery charger 18V EU	VB0157EU
Battery charger 18V UK	VB0159EU

## NOSE PIECES



DESCRIPTION	ART.NR.
<i>Nose piece for drywall</i>	
DS5525/DS5550/DS50	FC0886EU
DS7525/DS75	FC0906EU



DESCRIPTION	ART.NR.
<i>Nose piece for wood</i>	
DS5525/DS5550/DS50	FB0162EU
DS7525/DS75	FB0160EU

## DRIVE BITS IN BLISTERPACK



DESCRIPTION	ART.NR.
-------------	---------

### BITS FOR DS5525, DS5550

Screw bit PH2	EA0326B
Screw bit SQ2	EA0327B
Screw bit PZ2	EA0335B*
Screw bit TX20	EA0336B*
Screw bit Senco drive	EA0333B*

### BITS FOR DS7525

Screw bit PH2	EA0329B
Screw bit SQ2	EA0330B
Screw bit PZ2	EA0337B*
Screw bit TX20	EA0338B*
Screw bit Senco drive	EA0334B*

### BITS FOR DS50

#### adaptor ADP019 and MB0174

Screw bit tapered PH2 204mm	EA0365TB
Screw bit tapered SQ2 204mm	EA0364TB
Screw bit Senco 204mm	EA0313B

#### adaptor ADP011 and ADP020

Screw bit tapered PH2 193mm	EA0369TB
Screw bit tapered SQ2 193mm	EA0368TB
Screw bit Senco 193mm	EA0319B

### BITS FOR DS75


#### adaptor ADP019 and MB0174

Screw bit tapered PH2 225mm	EA0363TB
Screw bit tapered SQ2 225mm	EA0362TB
Screw bit Senco 225mm	EA0316B

#### adaptor ADP011, ADP020 and AD0020

Screw bit tapered PH2 214mm	EA0367TB
Screw bit tapered SQ2 214mm	EA0366TB
Screw bit Senco 214mm	EA0322B

\* article could have longer delivery time







# COLLATED SCREWS

## INDEX


### SCREW HEAD




### SCREW POINT



### RECESS



### SCREW THREAD




### MATERIAL/ FINISH

- Phosphate
- Clear zinc
- Yellow zinc
- Green ruspert II
- Stainless Steel
- Weatherex II

Items marked \* could have a longer lead time.



## DRYWALL TO WOOD








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
3,9 x 25mm	Phosphate	8,00-8,50	39A25MP
3,9 x 30mm	Phosphate	8,00-8,50	39A30MP
3,9 x 35mm	Phosphate	8,00-8,50	39A35MP
3,9 x 41mm	Phosphate	8,00-8,50	39A41MP *
3,9 x 45mm	Phosphate	8,00-8,50	39A45MP
3,9 x 50mm	Phosphate	8,00-8,50	39A50MP
3,9 x 55mm	Phosphate	8,00-8,50	39A55MP
4,5 x 75mm	Phosphate	8,00-8,50	45A75MP
3,9 x 32mm	Clear Zinc	8,00-8,50	39A32MC-5
3,9 x 35mm	Clear Zinc	8,00-8,50	39A35MC-5 *
3,9 x 42mm	Clear Zinc	8,00-8,50	39A42MC-5
3,9 x 55mm	Clear Zinc	8,00-8,50	39A55MC-5 *







**SENCO®**

### DRYWALL TO WOOD








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 3,9 x 30mm	Clear Zinc	8,00-8,50	39N30MC-5
○ 3,9 x 42mm	Clear Zinc	8,00-8,50	39N42MC-5 *
○ 3,9 x 55mm	Clear Zinc	8,00-8,50	39N55MC-5 *

### DRYWALL TO WOOD OR LIGHT STEEL (UP TO 1MM)








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 3,9 x 30mm	Clear Zinc	6,00-6,50	39T30MC-5 *
○ 3,9 x 40mm	Clear Zinc	6,00-6,50	39T40MC-5 *
○ 3,9 x 50mm	Clear Zinc	6,00-6,50	39T50MC-5 *

### DRYWALL TO LIGHT STEEL (UP TO 1MM)






SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 3,5 x 25mm	Clear Zinc	8,00-8,50	35P25MC-5 *
○ 3,5 x 40mm	Clear Zinc	8,00-8,50	35P40MC-5

### DRYWALL TO LIGHT STEEL (UP TO 1MM)



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 3,5 x 35mm	Phosphate	8,00-8,50	35B35MP
○ 3,5 x 45mm	Phosphate	8,00-8,50	35B45MP
○ 3,9 x 25mm	Phosphate	8,00-8,50	39B25MP
○ 3,9 x 35mm	Phosphate	8,00-8,50	39B35MP
○ 3,9 x 45mm	Phosphate	8,00-8,50	39B45MP
○ 3,9 x 55mm	Phosphate	8,00-8,50	39B55MP *

### DRYWALL TO HEAVY STEEL (UP TO 3MM)








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 3,5 x 25mm	Phosphate	8,00-8,47	35Q25MP *
○ 3,5 x 35mm	Phosphate	8,00-8,48	35Q35MP *
○ 3,5 x 40mm	Phosphate	8,00-8,49	35Q40MP *
○ 3,5 x 45mm	Phosphate	8,00-8,50	35Q45MP *
○ 3,5 x 25mm	Clear Zinc	8,00-8,50	35Q25MC-5
○ 3,5 x 35mm	Clear Zinc	8,00-8,50	35Q35MC-5
○ 3,5 x 40mm	Clear Zinc	8,00-8,50	35Q40MC-5 *
○ 3,5 x 45mm	Clear Zinc	8,00-8,50	35Q45MC-5

MAKING HARD WORK  
**EASIER**





# COLLATED SCREWS

## DRYWALL TO WOOD OR LIGHT STEEL (UP TO 1MM)







SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
● 3,9 x 25mm	Phosphate	8,00-8,45	39S25MP *
● 3,9 x 35mm	Phosphate	8,00-8,50	39S35MP *
● 3,9 x 40mm	Phosphate	8,00-8,47	39S40MP *
● 3,9 x 45mm	Phosphate	8,00-8,48	39S45MP *
● 3,9 x 55mm	Phosphate	8,00-8,48	39S55MP *
○ 3,9 x 25mm	Clear Zinc	8,00-8,50	39S25MC-5 *
○ 3,9 x 30mm	Clear Zinc	8,00-8,50	39S30MC-5 *
○ 3,9 x 32mm	Clear Zinc	8,00-8,50	39S32MC-5
○ 3,9 x 35mm	Clear Zinc	8,00-8,50	39S35MC-5
○ 3,9 x 40mm	Clear Zinc	8,00-8,50	39S40MC-5 *
○ 3,9 x 42mm	Clear Zinc	8,00-8,50	39S42MC-5
○ 3,9 x 50mm	Clear Zinc	8,00-8,50	39S50MC-5 *

## GYPSUM FIBER BOARD TO LIGHT STEEL (UP TO 1MM)







SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
● 3,9 x 30mm	Phosphate	6,70-7,00	39J30MP
● 3,9 x 45mm	Phosphate	6,70-7,00	39J45MP

## GYPSUM FIBER BOARD TO WOOD OR LIGHT STEEL (UP TO 1MM)







SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 3,9 x 30mm	Clear Zinc	6,00-6,50	39U30MC-5 *
○ 3,9 x 40mm	Clear Zinc	6,00-6,50	39U40MC-5 *
○ 3,9 x 50mm	Clear Zinc	6,00-6,50	39U50MC-5 *

## HARD FIBER TO WOOD OR LIGHT STEEL (UP TO 1MM)



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 3,9 x 30mm	Clear Zinc	6,70-7,00	39JS30MC *
○ 3,9 x 45mm	Clear Zinc	6,70-7,00	39JS45MC *






## HARD FIBER BOARD TO LIGHT STEEL (UP TO 1MM)



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
● 4,2 x 35mm	Phosphate	7,40-7,80	42UM35MP *
● 4,2 x 38mm	Phosphate	7,40-7,80	42UM38MP







## GENERAL WOOD TO WOOD








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,0 x 25mm	Clear Zinc	8,00-8,50	40K25MC *
○ 4,0 x 30mm	Clear Zinc	8,00-8,50	40K30MC *
○ 4,0 x 35mm	Clear Zinc	8,00-8,50	40K35MC *
○ 4,0 x 40mm	Clear Zinc	8,00-8,50	40K40MC *
○ 4,0 x 45mm	Clear Zinc	8,00-8,50	40K45MC *
○ 4,0 x 50mm	Clear Zinc	8,00-8,50	40K50MC *
○ 4,0 x 55mm	Clear Zinc	8,00-8,50	40K55MC *
○ 4,0 x 60mm	Clear Zinc	8,00-8,50	40K60MC *
○ 4,2 x 25mm	Yellow Zinc	8,00-8,50	42K25MY
○ 4,2 x 30mm	Yellow Zinc	8,00-8,50	42K30MY
○ 4,2 x 35mm	Yellow Zinc	8,00-8,50	42K35MY
○ 4,2 x 45mm	Yellow Zinc	8,00-8,50	42K45MY

## FLOORING WOOD TO WOOD (CHIPBOARD)








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,0 x 25mm	Clear Zinc	8,00-8,50	40H25MC *
○ 4,0 x 30mm	Clear Zinc	8,00-8,50	40H30MC *
○ 4,0 x 35mm	Clear Zinc	8,00-8,50	40H35MC
○ 4,0 x 40mm	Clear Zinc	8,00-8,50	40H40MC
○ 4,0 x 45mm	Clear Zinc	8,00-8,50	40H45MC *
○ 4,0 x 50mm	Clear Zinc	8,00-8,50	40H50MC *
○ 4,0 x 55mm	Clear Zinc	8,00-8,50	40H55MC *
○ 4,0 x 60mm	Clear Zinc	8,00-8,50	40H60MC *
○ 4,2 x 25mm	Yellow Zinc	8,00-8,50	42H25MY *
○ 4,2 x 30mm	Yellow Zinc	8,00-8,50	42H30MY *
○ 4,2 x 35mm	Yellow Zinc	8,00-8,50	42H35MY *
○ 4,2 x 45mm	Yellow Zinc	8,00-8,50	42H45MY *

## WOOD TO WOOD (CHIPBOARD)



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,2 x 35mm	Yellow Zinc	8,00-8,50	42KS35MY *
○ 4,2 x 40mm	Yellow Zinc	8,00-8,50	42KS40MY *
○ 4,2 x 45mm	Yellow Zinc	8,00-8,50	42KS45MY *
○ 4,2 x 50mm	Yellow Zinc	8,00-8,50	42KS50MY *






## FLOORING WOOD TO WOOD



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,5 x 75mm	Yellow Zinc	8,00-8,50	45F75MY





# COLLATED SCREWS

## FLOORING WOOD TO WOOD








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
4,5 x 60mm	Yellow Zinc	8,00-8,50	45X60MY
4,5 x 65mm	Yellow Zinc	8,00-8,50	45X65MY *
4,5 x 70mm	Yellow Zinc	8,00-8,50	45X70MY *

## FLOORING WOOD TO WOOD








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
4,2 x 35mm	Yellow Zinc	7,00-7,50	42Z35MY *
4,2 x 45mm	Yellow Zinc	7,00-7,50	42Z45MY *
4,2 x 55mm	Yellow Zinc	7,00-7,50	42Z55MY

## FLOORING WOOD TO WOOD (MEDIUM)



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
4,2 x 25mm	Yellow Zinc	7,00-7,50	42R25MY *
4,2 x 35mm	Yellow Zinc	7,00-7,50	42R35MY *
4,2 x 40mm	Yellow Zinc	7,00-7,50	42R40MY *
4,2 x 45mm	Yellow Zinc	7,00-7,50	42R45MY
4,2 x 50mm	Yellow Zinc	7,00-7,50	42R50MY
4,2 x 55mm	Yellow Zinc	7,00-7,50	42R55MY *
4,5 x 75mm	Yellow Zinc	7,00-7,50	45R75MY *
4,2 x 40mm	Ruspurt II	7,00-7,50	42R40MR *
4,2 x 50mm	Ruspurt II	7,00-7,50	42R50MR *
4,2 x 55mm	Ruspurt II	7,00-7,50	42R55MR *
4,5 x 50mm	Ruspurt II	7,00-7,50	45R50MR *
4,5 x 55mm	Ruspurt II	7,00-7,50	45R55MR *
4,2 x 50mm	Stainless Steel	7,00-7,50	42R50MS *
4,2 x 55mm	Stainless Steel	7,00-7,50	42R55MS *
4,2 x 45mm	Weatherex II	7,00-7,50	42R45MW *
4,5 x 65mm	Weatherex II	7,00-7,50	45R65MW *

## FLOORING WOOD TO WOOD








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
4,2 x 35mm	Yellow Zinc	7,00-7,50	42RH35MY *
4,2 x 40mm	Yellow Zinc	7,00-7,50	42RH40MY *
4,2 x 45mm	Yellow Zinc	7,00-7,50	42RH45MY
4,2 x 50mm	Yellow Zinc	7,00-7,50	42RH50MY *
4,2 x 55mm	Yellow Zinc	7,00-7,50	42RH55MY *
4,5 x 65mm	Yellow Zinc	7,00-7,50	45RH65MY *
4,5 x 75mm	Yellow Zinc	7,00-7,50	45RH75MY *
4,2 x 40mm	Ruspurt II	7,00-7,50	42RH40MR *
4,2 x 50mm	Ruspurt II	7,00-7,50	42RH50MR *
4,2 x 55mm	Ruspurt II	7,00-7,50	42RH55MR *
4,5 x 65mm	Ruspurt II	7,00-7,50	45RH65MR *
4,5 x 75mm	Ruspurt II	7,00-7,50	45RH75MR *
4,2 x 35mm	Stainless Steel	7,00-7,50	42RH35MS *
4,2 x 40mm	Stainless Steel	7,00-7,50	42RH40MS *
4,2 x 45mm	Stainless Steel	7,00-7,50	42RH45MS *
4,2 x 50mm	Stainless Steel	7,00-7,50	42RH50MS *
4,2 x 55mm	Stainless Steel	7,00-7,50	42RH55MS
4,5 x 75mm	Stainless Steel	7,00-7,50	45RH75MS *








# SENCO®

## DECKING WOOD TO WOOD





SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,5 x 50mm	Stainless Steel	8,00-8,50	45D50MSA *
○ 4,5 x 65mm	Stainless Steel	8,00-8,50	45D65MSA
○ 4,5 x 75mm	Stainless Steel	8,00-8,50	45D75MSA *

## FLOORING/DECKING WOOD TO WOOD (SOFT)








SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
● 4,2 x 50mm	Weatherex II	8,00-8,50	42W50MW
● 4,2 x 55mm	Weatherex II	8,00-8,50	42W55MW
● 4,5 x 65mm	Weatherex II	8,00-8,50	45W65MW
● 4,5 x 75mm	Weatherex II	8,00-8,50	45W75MW
○ 4,2 x 50mm	Yellow Zinc	8,00-8,50	42W50MY
○ 4,2 x 55mm	Yellow Zinc	8,00-8,50	42W55MY
○ 4,5 x 65mm	Yellow Zinc	8,00-8,50	45W65MY
○ 4,5 x 75mm	Yellow Zinc	8,00-8,50	45W75MY

## STEEL TO STEEL (UP TO 3MM)








SIZE	MATERIAL/FINISH	RECESS	HEAD Ø	ART.NR.
○ 5,5 x 19mm	Clear Zinc	PH2	7,68-8,18	55WP19MC
○ 5,5 x 19mm	Clear Zinc	SQ2	7,68-8,18	55WS19MC
○ 5,5 x 19mm	Clear Zinc	TX20	7,68-8,18	55WT19MC *

## FLOORING/DECKING WOOD TO WOOD (SOFT)







SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,2 x 35mm	Yellow Zinc	8,00-8,50	42Y35MY *
○ 4,2 x 40mm	Yellow Zinc	8,00-8,50	42Y40MY *
○ 4,2 x 50mm	Yellow Zinc	8,00-8,50	42Y50MY *
○ 4,2 x 55mm	Yellow Zinc	8,00-8,50	42Y55MY

## STEEL TO STEEL (UP TO 3 OR 4,4MM)



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,2 x 13mm	Clear Zinc	7,77-8,18	42OP13MC
○ 4,2 x 16mm	Clear Zinc	7,77-8,18	42OP16MC
○ 4,2 x 19mm	Clear Zinc	7,77-8,18	42OP19MC *

## WOOD TO HEAVY STEEL (UP TO 3MM)



SIZE	MATERIAL/FINISH	HEAD Ø	ART.NR.
○ 4,2 x 35mm	Clear Zinc	8,00-8,50	42GS35MC *
○ 4,2 x 41mm	Clear Zinc	8,00-8,50	42GS41MC
○ 4,2 x 65mm	Clear Zinc	8,00-8,50	42GS65MC *

# MAKING HARD WORK EASIER



# SMART SERIES

FOR ALL SORTS OF PREFAB  
PANELS AND ELEMENTS

EASY INSTALLATION



Tools in Smart Serie are the solution to improve productivity. The **Smart Bridge** has been developed for entry level automation of nailing, stapling and screwing of wooden prefabricated panel assembly. **Senco wegmatic stapler** drives staples into panel-shaped building materials such as chipboard, gypsum fibreboards, OSB boards etc. for assembly on wooden frames. The **Smart Board Fixer** is a smart way to improve the production quality of larger panels by a single operator. The tool can be set on every wanted distances and you no longer need to climb on to the panels to fix it.






# SENCO®

## SMART SERIES

The Senco Smart solutions are designed for increased product quality, ergonomic use and a safer work environment.



HIGH CAPACITY  
MAGAZINE

DESIGNED FOR INCREASED  
PRODUCT QUALITY

ERGONOMIC DESIGN

HIGHER PRODUCTIVITY



## MAKING HARD WORK EASIER

# SMART BRIDGE TOOLS

## SENCO SMART BRIDGE

Senco Introduces the Senco Smart Bridge. The Senco Smart Bridge has been developed for entry level automation of nailing, stapling and screwing of wooden prefabricated panel assembly. This highly flexible Smart Bridge will help manufacturers to increase capacity and quality without adding manpower and has a high return on investment (ROI) of mostly less than a year.

The modular design of the Senco Smart Bridge is easy to install into any production line and will be up and running within hours. The Senco Smart Bridge provides practical fastening solutions for any small or medium sized manufacturer.

The wide range of Senco XP tools, which are renowned for their performance, high quality and durability, provides fastening solutions for every application and are adaptable to be fitted to the Senco Smart Bridge in minutes. Besides the standard Senco XP tools, there are also Smart alternatives such as the Smart-Load SHS51XP & the Smart coilnailer SCN49XP. With their high capacity magazines reloading time is reduced.

Remote firing of the Smart Bridge tools provides a safer working environment and creates less operator strain as the need to stretch over the panel is eliminated.



## SPECIFICATIONS

### The standard configuration of the Senco Smart Bridge consist of:

- Bridge
- 2 tool holders
- Guiding rail
- PLC
- Control sensor to detect material under each tool

### Maximum dimensions product (standard):

Length up to 10 meters  
Width 4 meters  
Height 30 cm

Other dimensions on request  
(excludes table)





# SENCO®

## SMART LOAD STAPLER SHS51XP



### TECHNICAL INFORMATION

Length	444 mm
Width	123 mm
Height	280 mm
Weight	10 kg
Actuation	Remote trigger
Operating Pressure	6-8,3 bar
Air inlet	3/8" NPT
Air consumption	136,5 l/min
Magazine capacity	1400


### APPLICATIONS

Wall panels, wood, floor and roofing elements, fences, crates

### FEATURES

- Designed for high volume stapling applications
- High capacity magazine 1400 staples
- Based on high quality and proven Senco technology

DESCRIPTION	ART. NR
Smartload SHS51XP-N stapler	1SB15001N



## SMART SERIES COILNAILER SCN49XP



### TECHNICAL INFORMATION

Length	314 mm
Width	342 mm
Height	304 mm
Weight	6,3 kg
Actuation	Remote trigger
Operating Pressure	4,8-8,3 bar
Air inlet	3/8" NPT
Air consumption	111 l/min
Magazine capacity	1000


### APPLICATIONS

Wall panels, wood, floor and roofing elements, fences, crates

### FEATURES

- Designed for high volume nailing applications
- High capacity magazine 1000 nails
- Based on high quality and proven Senco technology

DESCRIPTION	ART. NR
Smartload SCN49XP jumbo magazine	1SB15002N



## SMART SERIES DURASPIN DS7525-18V



### TECHNICAL INFORMATION

Length	220 mm
Width	100 mm
Height	(depends on screw length) 600 mm
Weight	11 kg
Actuation	Remote trigger
Operating Pressure	5-7 bar
Air inlet	1/4" NPT
Air consumption	30 l/min
Magazine capacity	500


### APPLICATIONS

Wall panels, wood, floor and roofing elements, fences, crates

### FEATURES

- Designed for high volume screwing applications
- High capacity magazine 500 screws
- Based on high quality and proven Senco technology
- Quick slide button bit change

DESCRIPTION	ART. NR
Smartload DS7525-18V screwdriver	1SB15003N



# SMART SERIES


## WEGMATIC SNS50XP



## WEGMATIC SQS55XP



## BOARD FIXER SKSXP



### TECHNICAL INFORMATION

Length	430 mm
Width	340 mm
Height	310 mm
Weight	10,5 kg
Actuation	Semi automatic
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	185 l/min
Magazine capacity	130


### APPLICATIONS

Fast and precise technology for framing/sheathing

### FEATURES

- Exact staple distance
- Edge according to DIN 1052
- User friendly
- 2 handles
- For semi-automation applications

DESCRIPTION	ART. NR.
SNS50XP two handles	EJ02000
Wegmatic guide rail 3 meter	MDM0217



### TECHNICAL INFORMATION

Length	430 mm
Width	340 mm
Height	310 mm
Weight	10,5 kg
Actuation	Semi automatic
Air inlet	3/8" NPT
Operating pressure	5,5-8,3 bar
Air consumption	185 l/min
Magazine capacity	130


### APPLICATIONS

Fast and precise technology for framing

### FEATURES

- Exact staple distance
- Edge according to DIN 1052
- User friendly
- 2 handles
- For semi-automation applications

DESCRIPTION	ART. NR.
SQS55XP two handles	EJ01900
Wegmatic guide rail 3 meter	MDM0217



### TECHNICAL INFORMATION

Length	2100 mm
Width	500 mm
Height	450 mm
Weight	15 kg
Operating Pressure	4,8-8,3 bar
Air inlet	1/4" NPT
Air consumption	61 l/min
Magazine capacity	160


### APPLICATIONS

Stitching board material to wooden frames

### FEATURES

- Set fastener distance of 85/170mm
- Increased productivity and quality
- No need to climb on the panels to fix them
- Wide fastener range using different Senco tools
- Perfectly aligned fasteners due to side guidance

DESCRIPTION	ART. NR.
Smart Board Fixer SKSXP	9VS99001N






# SENCO®

## BOARD FIXER SQS55XP

## BOARD FIXER COILPRO50

## BOARD FIXER SCN49XP



### TECHNICAL INFORMATION

Length	2100 mm
Width	500 mm
Height	450 mm
Weight	15 kg
Operating Pressure	5,5-8,3 bar
Air inlet	3/8" NPT
Air consumption	185 l/min
Magazine capacity	130


### APPLICATIONS

Stitching board material to wooden frames

### FEATURES

- Set fastener distance of 85/170mm
- Increased productivity and quality
- No need to climb on the panels to fix them
- Wide fastener range using different Senco tools
- Perfectly aligned fasteners due to side guidance

DESCRIPTION	ART. NR
Smart Board Fixer SQS55XP	9VS99002N



### TECHNICAL INFORMATION

Length	2100 mm
Width	500 mm
Height	450 mm
Weight	15 kg
Operating Pressure	4,8-8,3 bar
Air inlet	3/8" NPT
Air consumption	83 l/min
Magazine capacity	250-375


### APPLICATIONS

Stitching board material to wooden frames

### FEATURES

- Set fastener distance of 85/170mm
- Increased productivity and quality
- No need to climb on the panels to fix them
- Wide fastener range using different Senco tools
- Perfectly aligned fasteners due to side guidance

DESCRIPTION	ART. NR
Smart Board Fixer CoilPro50	9VS99003N



### TECHNICAL INFORMATION

Length	2100 mm
Width	500 mm
Height	450 mm
Weight	15 kg
Operating Pressure	4,8-8,3 bar
Air inlet	3/8" NPT
Air consumption	111 l/min
Magazine capacity	250-375

### APPLICATIONS

Stitching board material to wooden frames

### FEATURES

- Set fastener distance of 85/170mm
- Increased productivity and quality
- No need to climb on the panels to fix them
- Wide fastener range using different Senco tools
- Perfectly aligned fasteners due to side guidance

DESCRIPTION	ART. NR
Smart Board Fixer SCN49XP	9VS99004N





# HIGH LOAD TOOLS



RE-LOAD SENSOR



MISS FIRE SENSOR

Highload tools are a range of nails and staple machines with high capability to meet the changing demands of modern, automated timber framing technology. Higher productivity, less refilling, less down time and more profit.





# SENCO®

**LESS REFILLING**


## HIGH LOAD TOOLS

The Senco High Load tools are designed for high volume, consistent and accurate fastening for improved productivity.

**HIGHER PRODUCTION**

**LESS DOWN TIME**

**CENTRAL CONNECTION AIR AND POWER**



**5 YEAR  
LIMITED  
WARRANTY**

**HIGH  
LOAD**

MAKING HARD WORK  
**EASIER**

# HIGH LOAD TOOLS

## HIGH LOAD N STAPLER SHLS80-N



## HIGH LOAD Q STAPLER SHLS80-Q



## HIGH LOAD S STAPLER SHLS90-S



### TECHNICAL INFORMATION

Length	475 mm
Width	115 mm
Height	613 mm
Weight	10,0 kg
Operating Pressure	6,0-8,3 bar
Air inlet	12 mm
Air consumption	2.000 l/min
Magazine capacity	3080

### APPLICATIONS


Sheating, pallets, garden products

### FEATURES

- Re-load sensor
- Miss fired sensor
- Central connection air and power

### DESCRIPTION

DESCRIPTION	ART. NR
SHLS80-N13 magazine	EM04000
SHLS80-N14 magazine	EM04100
SHLS80-N17 magazine	EM04200
SHLS80-N19 magazine	EM02900
SHLS80-N21 magazine	EM04300
SHLS80-N23 magazine	EM04400
SHLS80-N25 magazine	EM04500



### TECHNICAL INFORMATION

Length	475 mm
Width	100 mm
Height	613 mm
Weight	10,0 kg
Operating Pressure	6,0-8,3 bar
Air inlet	12 mm
Air consumption	2.000 l/min
Magazine capacity	2400

### APPLICATIONS

Sheating, pallets, garden products

### FEATURES

- Modular compact design
- Left or right hand loading
- Central connection air and power

### DESCRIPTION

DESCRIPTION	ART. NR
SHLS80-Q17 magazine	EM03100
SHLS80-Q19 magazine	EM03200
SHLS80-Q21 magazine	EM02800
SHLS80-Q23 magazine	EM03300
SHLS80-Q25 magazine	EM03400



### TECHNICAL INFORMATION

Length	475 mm
Width	140 mm
Height	623 mm
Weight	10,0 kg
Operating Pressure	6,0-8,3 bar
Air inlet	12 mm
Air consumption	2.000 l/min
Magazine capacity	2000

### APPLICATIONS


Sheating, pallets, garden products

### FEATURES

- Modular compact design
- Left or right hand loading
- Central connection air and power

### DESCRIPTION

DESCRIPTION	ART. NR
SHLS90-S19 magazine	EM03600
SHLS90-S23 magazine	EM03500
SHLS90-S28 magazine	EM05000
SHLS90-S29 magazine	EM03000







# SENCO®

## HIGH LOAD SP STAPLER SHLS130-SP/SHLS160-SP



## HIGH LOAD COILNAILER SHLCN90



### TECHNICAL INFORMATION

Length	550 mm
Width	220/250 mm
Height	593/653 mm
Weight	22,9/24,3 kg
Operating Pressure	5,0-7,0 bar
Air inlet	12 mm
Air consumption	1.280/1.600 l/min
Magazine capacity	1500

### APPLICATIONS


Insulation panel fastening up to 100mm/130mm

### FEATURES

- Slim profile
- Removable magazine
- Modular compact design
- No need to un-nest staples can be loaded straight from the box

### DESCRIPTION

DESCRIPTION	ART. NR
SHLS130-SP	EM07000
SHLS160-SP	EM07100



\* for staple lengths below 100mm spacer is required



### TECHNICAL INFORMATION

Length	687 mm
Width	179 mm
Height	453 mm
Weight	10 kg
Operating Pressure	5,0-7,0 bar
Air inlet	12 mm
Air consumption	1.260 l/min
Magazine capacity	3000

### APPLICATIONS


Framing, pallets, garden products

### FEATURES

- Up to 10 shots per second
- Left or right hand loading
- Fully compatible with factory automation lines of international suppliers

### DESCRIPTION

DESCRIPTION	ART. NR
SHLCN90 hi-load coilnailer	EM07200



# SENCO DISTRIBUTORS

EUROPE | MIDDLE EAST | AFRICA | RUSSIA





**SENCO®**

- |                               |                                  |
|-------------------------------|----------------------------------|
| 1 Aerfast                     | 15 Ottensten Lithuania           |
| 2 Afcom Group                 | 16 Ottensten Polska              |
| 3 Affut PreciS Maroc          | 17 Ottensten Ukraine             |
| 4 Betis Distribution          | 18 Poppers Senco Deutschland     |
| 5 Cerclindus                  | 19 Poppers Senco Ireland         |
| 6 Fortune Emirates            | 20 Poppers Senco Makine          |
| 7 H. Clausen                  | 21 Poppers Senco Nederland       |
| 8 Heinz Bühnen                | 22 Poppers Senco UK              |
| 9 J.P. Müller                 | 23 Romeo Maestri & Figli         |
| 10 Kedmi                      | 24 Sofragraf Senco               |
| 11 Mechelin                   | 25 Technical Supplies & Services |
| 12 Ottensten Denmark          | 26 Vamvacas                      |
| 13 Miraflores (Trading agent) | 27 Y.Kawoosh                     |
| 14 Ottensten Latvia           | 28 Yalco                         |


**FOR MORE INFORMATION:**

**WWW.SENCO.EU**



# APPLICATION / TOOL INDEX

## FINISH & WOODWORKING

<b>SLS20XP</b> MEDIUM WIRE STAPLER	<b>SLS25XP</b> MEDIUM WIRE STAPLER	<b>SLS18MG</b> MEDIUM WIRE STAPLER	<b>SMS92</b> MEDIUM WIRE STAPLER	<b>SKSXP</b> MEDIUM WIRE STAPLER	<b>SC1XP</b> SENCAMP FASTENER
					
P 9	P 9	P 22	P 23	P 10	P 17
<b>FINISHPRO10</b> MICROPINNER 0,6MM	<b>LS1XP</b> HEADLESS BRAD NAILER	<b>SBN10XP</b> BRAD NAILER 1,2MM	<b>SLP20XP</b> BRAD NAILER 1,2MM	<b>SLP20XP GLN</b> BRAD NAILER 1,2MM	<b>FINISHPRO18MG</b> BRAD NAILER 1,2MM
					
P 24	P 13	P 13	P 12	P 13	P 24
<b>FINISHPRO25XP</b> BRAD NAILER 1,2MM	<b>FINISHPRO32</b> BRAD NAILER 1,6MM	<b>FINISHPRO42XP</b> FINISH NAILER	<b>FINISHPRO35MG</b> FINISH NAILER	<b>SFN30</b> FINISH NAILER	<b>S200BN</b> BRAD NAILER
					
P 14	P 25	P 14	P 25	P 25	P 48
<b>S200SM</b> BRAD NAILER	<b>S250FN</b> BRAD NAILER				
					
P 49	P 49				

## FRAMING, SHEETING & SUBFLOORS

<b>SNS50XP</b> HEAVY WIRE STAPLER	<b>SHS50XP</b> HEAVY WIRE STAPLER	<b>SNS41</b> HEAVY WIRE STAPLER	<b>SQS55XP</b> HEAVY WIRE STAPLER	<b>WC150XP</b> WIDE CROWN STAPLER	<b>WC200XP</b> WIDE CROWN STAPLER
					
P 11	P 10	P 23	P 11	P 12	P 12
<b>WC330-SP</b> WIDE CROWN STAPLER	<b>WC360-SP</b> WIDE CROWN STAPLER	<b>SN90CXP</b> CLIPPED HEAD NAILER	<b>SN90FXP</b> FULL ROUND HEAD NAILER	<b>SN90FXP+</b> FULL ROUND HEAD NAILER	<b>FRAMEPRO601</b> CLIPPED HEAD NAILER
					
P 23	P 24	P 14	P 15	P 15	P 26



**SENCO®**

<b>FRAMEPRO602</b> FULL ROUND HEAD NAILER	<b>FRAMEPRO651</b> CLIPPED HEAD NAILER	<b>FRAMEPRO652</b> FULL ROUND HEAD NAILER	<b>SN1302</b> FULL ROUND HEAD NAILER	<b>SN1602</b> FULL ROUND HEAD NAILER	<b>SAP40XP</b> CONCRETE NAILER
					
P 27	P 26	P 27	P 28	P 28	P 17
<b>MC60-34</b> METAL CONNECTOR	<b>SCN65XP</b> COILNAILER	<b>COILPRO90</b> COILNAILER	<b>SCN58A</b> COILNAILER	<b>A20</b> PALM HAND NAILER	<b>A900FN</b> CH FRAMING NAILER
					
P 32	P 16	P 31	P 30	P 34	P 50

## PALLETS, CRATING & PACKAGING

<b>DFPXP</b> PLIER TOOL	<b>F75LXP</b> PLIER TOOL	<b>F75SXP</b> PLIER TOOL	<b>FAT25</b> PLIER TOOL	<b>COILPRO32</b> COILNAILER	<b>COILPRO50</b> COILNAILER
					
P 18	P 18	P 18	P 19	P 29	P 29
<b>PAL50</b> COILNAILER	<b>PAL57F</b> COILNAILER	<b>PAL57F 2 HAND SAFETY</b> COILNAILER	<b>PAL70</b> COILNAILER	<b>PAL70 DUPLEX</b> COILNAILER	<b>PAL83</b> COILNAILER
					
P 42	P 42	P 42	P 43	P 43	P 43
<b>PAL90</b> COILNAILER	<b>PAL100</b> COILNAILER	<b>PAL100 2 HAND SAFETY</b> COILNAILER	<b>PAL130</b> COILNAILER	<b>SCN34</b> COILNAILER	<b>SCCM</b> MANUAL CARTON CLOSER
					
P 44	P 44	P 44	P 45	P 29	P 34
<b>SCCP</b> CARTON CLOSER	<b>SRCC</b> CARTON CLOSER				
					
P 35	P 35				

# APPLICATION / TOOL INDEX

## ROOFING & SIDING

<b>BC58</b> BUTTON CAP STAPLER	<b>ROOFPRO455XP</b> COILNAILER	<b>SCN49XP</b> COILNAILER	<b>SCN650</b> COILNAILER	<b>SCN75</b> COILNAILER	<b>SIDINGPRO40</b> CLIPPED HEAD NAILER
					
P 33	P 16	P 16	P 30	P 30	P 26
<b>TPR065</b> T-NAILER	<b>SHT-F</b> HAMMERTACKER	<b>S45CNR</b> ROOFING COILNAILER	<b>S65CNP</b> COILNAILER		
					
P 33	P 34	COMING SOON P 50	P 50		

## UPHOLSTERY & FURNITURE

<b>SFT10XP</b> LIGHT WIRE STAPLER	<b>SFT10XP-DL</b> LIGHT WIRE STAPLER	<b>SFT10XP-LN</b> LIGHT WIRE STAPLER	<b>SFW09</b> LIGHT WIRE STAPLER	<b>SHS51XP</b> HEAVY WIRE STAPLER	<b>SC25</b> CORRUGATED FASTENER
					
P 8	P 8	P 8	P 22	P 51	P 32
<b>SC15</b> CORRUGATED FASTENER	<b>SCN30</b> COILNAILER	<b>SFW05</b> LIGHT WIRE STAPLER	<b>S150LS</b> MEDIUM WIRE STAPLER		
					
P 32	P 28	P 48	P 48		

## COMPRESSORS

<b>PC0968</b> MINI COMPRESSOR	<b>PC1010</b> MINI COMPRESSOR	<b>PC1010N</b> MINI COMPRESSOR	<b>PC1246</b> MAXI COMPRESSOR	<b>PC1248</b> MINI COMPRESSOR	<b>PC1249</b> MIDI COMPRESSOR
					
P 55	P 54	P 54	P 57	P 54	P 55
<b>PC1250</b> MIDI COMPRESSOR	<b>PC1251</b> MAXI COMPRESSOR	<b>PC1252</b> MIDI COMPRESSOR	<b>PC1286EU</b> HP COMPRESSOR	<b>PC1287EU</b> KIT COMPRESSOR	<b>PC2225</b> MAXI COMPRESSOR
					
P 56	P 56	P 55	P 57	P 57	P 56



## DRILLS & SCREWDRIVERS

DS5525-18V HEAVY DUTY MACHINE	DS5525-AC HEAVY DUTY MACHINE	DS5550-18V HIGH SPEED MACHINE	DS5550-AC HIGH SPEED MACHINE	DS7525-18V MULTI PURPOSE MACHINE	DS7525-AC MULTI PURPOSE MACHINE
					
P 94	P 94	P 94	P 95	P 95	P 95
ATTACHMENT DS50 SCREW FASTENING	ATTACHMENT DS75 SCREW FASTENING	SEN510C PNEUMATIC DRILL	SEN511C PNEUMATIC DRILL	SEN600C PNEUMATIC SCREWDRIVER	SEN602C PNEUMATIC SCREWDRIVER
					
P 96	P 96	P 36	P 36	P 37	P 37
SEN610C PNEUMATIC SCREWDRIVER	SEN611C PNEUMATIC SCREWDRIVER	SEN612C PNEUMATIC SCREWDRIVER	SEN700C PNEUMATIC IMPACT DRIVER		
					
P 38	P 38	P 38	P 39		

## FUSION

F-15 FUSION FINISH NAILER 1,8MM	F-16A FUSION FINISH NAILER 1,6MM	F-16S FUSION FINISH NAILER 1,6MM	F-18 FUSION BRAD NAILER 1,2MM
			
P 66	P 66	P 66	P 67

## GAS TECHNOLOGY

GT35HN HAFTEN NAILER	GT50AX BRAD NAILER 1,2MM	GT60NN METAL CONNECTOR	GT65DA FINISH NAILER 1,8MM	GT65RHA FINISH NAILER 1,6MM	GT65RHS FINISH NAILER 1,6MM
					
P 69	P 68	P 70	P 69	P 68	P 68
GT90CH CH FRAMING NAILER	GT90FRH FRH FRAMING NAILER	SGP40S CONCRETE NAILER			
					
P 69	P 70	P 70			

# APPLICATION / TOOL INDEX



## SMART SOLUTIONS

**STAPLER SHS51XP**  
SMART LOAD



P 107

**COILNAILER SCN49XP**  
SMART SERIES



P 107

**DURASPIN DS7525-18V**  
SMART SERIES



P 107

**SNS50XP**  
WEGMATIC



P 108

**SQS55XP**  
WEGMATIC




P 108

**SKSXP**  
BOARD FIXER



P 108

**SQS55XP**  
BOARD FIXER



P 109

**COILPRO50**  
BOARD FIXER



P 109

**SCN49XP**  
BOARD FIXER



P 109

## HIGH LOAD TOOLS

**SHLS80-N**  
HIGH LOAD N STAPLER



P 112

**SHLS80-Q**  
HIGH LOAD Q STAPLER



P 112

**SHLS90-S**  
HIGH LOAD S STAPLER



P 112

**SHLS130-SP/SHLS160-SP**  
HIGH LOAD SP STAPLER



P 113

**SHLCN90**  
HIGH LOAD COILNAILER



P 113



[illegible]



## INDEX

DESCRIPTION	PAGE	DESCRIPTION	PAGE	DESCRIPTION	PAGE
<b>ACCESSORIES</b>					
Air accessory kit	59	SCN65XP Coilnailer	16	GT60NN Metal connector	70
Airblow gun	59	SCN75 Coilnailer	30	GT65DA Finish nailer 1,8mm	69
Collated screw system accessories	96-97	<b>COLLATED SCREW SYSTEM</b>		GT65HN Haften nailer	69
Compressor oil	62	DS50 Screw fastening attachment	96	GT65RHA Finish nailer 1,6mm	68
Concrete accessories	63	DS75 Screw fastening attachment	96	GT65RHS Finish nailer 1,6mm	68
Couplings	60	DS5525-18V Heavy duty machine	94	GT90CH CH Framing nailer	69
Gas tool accessories	71	DS5525-AC Heavy duty machine	94	GT90FRH FRH Framing nailer	70
Hose clamp	60	DS5550-18V High speed machine	94	SGP40S Concrete nailer	70
Hoses	59-61	DS5550-AC High speed machine	95		
Lubricants	61-62	DS7525-18V Multi purpose machine	95	<b>DRILLS AND SCREWDRIVERS</b>	
Plugs	59-60	DS7525-AC Multi purpose machine	95	SEN510C Drill	36
Safety glasses	62			SEN511C Drill	36
Service repair kits	62	<b>COMPRESSORS</b>		SEN600C Screwdriver	37
Spring balancer	61	Compressor kit 3 in 1 set	58	SEN602C Screwdriver	37
Staple remover	62	Compressor kit PC1010	58	SEN610C Screwdriver	38
Teflon tape	61	Compressor kit PC1010 /SLS18Mg	58	SEN611C Screwdriver	38
		Compressor kit PC1010/FinishPro18Mg	58	SEN612C Screwdriver	38
<b>COILNAILERS</b>		PC0968 Mini compressor	55	SEN700C Impact driver	39
CoilPro32 Coilnailer	29	PC1010 Mini compressor	54		
CoilPro50 Coilnailer	29	PC1010N Mini compressor	54	<b>FASTENERS</b>	
CoilPro90 Coilnailer	31	PC1246 Maxi compressor	57	CE/Index	74-75
EPAL Marking nail coilnailer	45	PC1248 Mini compressor	54	Coding chart	86-91
PAL50 Coilnailer	42	PC1249 Midi compressor	55	Coilnails	80-83
PAL57F Coilnailer	42	PC1250 Midi compressor	56	Collated screws	98-103
PAL57F 2h Safety coilnailer	42	PC1251 Maxi compressor	56	Pins and brads / others	84-85
PAL70 Coilnailer	43	PC1252 Midi compressor	55	Staples	76-78
PAL70 Duplex coilnailer	43	PC1286EU High pressure compressor	57	Stripnails	78-79
PAL83 Coilnailer	43	PC1287EU Kit compressor	57		
PAL90 Coilnailer	44	PC2225 Maxi compressor	56	<b>HIGH LOAD TOOLS</b>	
PAL100 Coilnailer	44			SHLCN90 High load coilnailer	113
PAL100 2h Safety coilnailer	44	<b>CONCRETE NAILERS</b>		SHLS130-SP High load SP stapler 130mm	113
PAL100EPAL Coilnailer	45	SAP40XP Concrete nailer	17	SHLS160-SP High load SP stapler 160mm	113
PAL130 Coilnailer	45	SGP40S Concrete nailer	70	SHLS80-N High load N stapler	112
Roofing Coilnailer S45CNR	50			SHLS80-Q High load Q stapler	112
RoofPro455XP Coilnailer	16	<b>CORDLESS</b>		SHLS90-S High load S stapler	112
S65CNP Coilnailer	50	F-15 Fusion Finish nailer 1,8mm	66		
SCN30 Coilnailer	28	F-16A Fusion Finish nailer 1,6mm	66	<b>SMART SOLUTIONS</b>	
SCN34 Coilnailer	29	F-16S Fusion Finish nailer 1,6mm	66	CoilPro50 Board fixer	109
SCN49XP Coilnailer	16	F-18 Fusion Brad nailer 1,2mm	67	DS7525-18V Smart series DuraSpin	107
SCN58A Coilnailer	30	GT35HN Haften nailer	69	SCN49XP Board fixer	109
SCN650 Coilnailer	30	GT50AX Brad nailer 1,2mm	68	SCN49XP Smart series coilnailer	107



## INDEX

DESCRIPTION	PAGE	DESCRIPTION	PAGE
SHS51XP Smart load stapler	107	SHT-F Hammertacker	34
SKSXP Board fixer	108	SRCC Carton closer	35
SQS55XP Board fixer	109	TPRO65 T-nailer	33
SNS50XP Wegmatic	108		
SQS55XP Wegmatic	108		
<b>STAPLERS</b>		<b>STRIPNAILERS</b>	
S150LS Medium wire stapler	48	A900FN Clipped head framing nailer	50
SFT10XP Light wire stapler	8	FinishPro10 Micropinner 0,6mm	24
SFT10XP-DL Light wire stapler	8	FinishPro18 Mg Brad nailer 1,2mm	24
SFT10XP-LN Light wire stapler	9	FinishPro25XP Brad nailer 1,2mm	14
SFW05 Light wire stapler	48	FinishPro32 Brad nailer 1,6mm	25
SFW09 Light wire stapler	22	FinishPro35Mg Finish nailer	25
SHS50XP Heavy wire stapler	10	FinishPro42XP Finish nailer	14
SHS51XP Heavy wire stapler	10	FramePro601 Clipped head nailer	26
SKSXP Medium wire stapler	10	FramePro602 Full round head nailer	27
SLS18Mg Medium wire stapler	22	FramePro651 Clipped head nailer	26
SLS20XP Medium wire stapler	9	FramePro652 Full round head nailer	27
SLS25XP Medium wire stapler	9	LS1XP Headless brad nailer	13
SMS92 Medium wire stapler	23	S200BN Brad nailer	48
SNS41 Heavy wire stapler	23	S200SM Brad nailer	49
SNS50XP Heavy wire stapler	11	S250FN Brad nailer	49
SQS55XP Heavy wire stapler	11	SBN10XP Brad nailer 1,2mm	13
WC150XP Wide crown stapler	12	SFN30 Finish nailer	25
WC200XP Wide crown stapler	12	SidingPro40 Clipped head nailer	26
WC330-SP Wide crown stapler	23	SLP20XP Brad nailer 1,2mm	12
WC360-SP Wide crown stapler	24	SLP20XP GLN Brad nailer 1,2mm	13
		SN1302 Full round head nailer 130mm	28
		SN1602 Full round head nailer 160mm	28
		SN90CXP Clipped head nailer	14
		SN90FXP Clipped head nailer	15
		SN90FXP+ Clipped head nailer	15
<b>SPECIALITY TOOLS</b>			
A20 Palm hand nailer	34		
BC58 Button cap stapler	33		
DFPXP Plier tool	18		
FAT25 Plier tool	19		
F75LXP Plier tool	18		
F75SXP Plier tool	18		
MC60-34 Metal connector	32		
SC1XP Senclamp fastener	17		
SC15 Corrugated fastener 15mm	32		
SC25 Corrugated fastener 20mm	32		
SCCM Manual carton closer	34		
SCCP Carton closer	35		

© Copyright Verpa Senco BV 2016-2.  
All rights reserved; No rights may be  
derived from the information in this  
publication.

R.S. Johnston Industrial Fastening Systems  
16 Diamond Road, Dromore, Co Down, BT25 1FD  
Tel: +44 (0) 28 92699644 Fax: +44 (0) 28 92693498  
Email General: [info@rsjohnston.co.uk](mailto:info@rsjohnston.co.uk)  
Web: [www.rsjohnston.co.uk](http://www.rsjohnston.co.uk)