



## METHANOL (CH<sub>3</sub>OH) SPECIFICATIONS ASTM D1152

<b>SPECIFICATION</b>	<b>VALUE</b>
SPECIFIC GRAVITY, 20°/20°C (E-346)	0.791 - 0.793
DISTILLATION AT 760 MM HG, °C (D-1078)	1.0 RANGE (TO INCLUDE 64.6 ± 0.1)
PURITY, % BY WT	99.85 MIN
NONVOLATILES, MG/100 ML (D-1353)	5 MAX
ACIDITY, % BY WT, AS ACETIC ACID (D-1613)	0.003 MAX
ACETONE, % BY WT (D-1612)	0.003 MAX
ALKALINITY, % BY WT	0.003 MAX
CARBONIZABLE SUBSTANCES, PT-CO (E-346)	30 MAX
PERMANGANATE TEST AT 15°C, MINUTES (D-1363)	60 MIN
WATER, % BY WT (E-346)	0.10 MAX
COLOR, PT-CO (D-1209)	5 MAX
HYDROCARBONS (D-1722)	PASS TEST

### **SHIPPING DATA:**

POUNDS PER GALLON, 20°C	6.59
KG PER LITER, 20°C	0.79
FLASH POINT, °F (T.C.C.)	54
DOT LABEL REQUIRED	FLAMMABLE LIQUID
DOT IDENTIFICATION NO.	UN 1230

NOTICE: ARTEXON GROUP MAKES NO WARRANTY OR REPRESENTATION AS TO THE SUITABILITY OF THE PRODUCT AS SPECIFIED HEREIN FOR ANY PARTICULAR APPLICATION. THE DETERMINATION OF THE SUITABILITY OF THE ABOVE SPECIFICATION FOR ANY PARTICULAR USE IS SOLELY THE RESPONSIBILITY OF THE USER.