

SCHRIOCK'S LAWN & TRAIL 1000 20th Ave. S.W. Minot, N. Dak. 58701

Your Dealer Is:

Manufactured by Adventure Vehicles, Inc. Monroe, Louisiana 71203



MODEL 300

HEELERS



NWO SIH HTIW MAKE A KID HAPPY

The ADJUSTABLE HANDLEBARS fit the shortest or the longest DESIGNED FOR THE LITTLE RIDER IN MIND!

The AUTOMATIC VARIABLE SPEED CLUTCHES allow the novice trol and easily set to limit the top speed to suit the riders ability. The THROTTLE LEVER can be turned for thumb or fingertip con-

shifting gears with his toes. rider to ride with ease without the bother of



Automatic Clutch

DRIVE SYSTEM

8 × 11 × 17

SPECIFICATIONS

* Weight - 163 lbs.

★ Overall Length — 611/2"

* Width - 40"

¥ Wheel Base - 45%"

* Seat Height - 29"

Under Engine ★ Ground Clearance — 61/2"

* Turning Radius - 6 ft. * Load Capacity - 150 lbs.

SPECIFICATIONS SUBJECT TO CHANGE



MADE TO RIDE Sporty and Responsive Sleek yet Rugged



- ★ 305 cc Cast Iron Electric Start KOHLER Engine
- ★ Fiberglass Body
- ★ 1" 11 Gauge Tubular Steel Frame—Double Cradled
- ★ Hand Controls: Throttle — Thumb or Fingertip Brake + Lock Park Position
- ★ 1½" Tubular Front Fork
- ★ 400 Lb. Weight Capacity
- ★ Adjustable Handlebars
- ★ 12 Volt Headlight

- ★ Fully Enclosed Drive System Primary — Automatic Varible Speed Clutches Final — Transaxle where chains and sprockets run in oil in a sealed case.
- ★ 30 AMP Heavy Duty Battery
- ★ 15 AMP Charging System
- ★ Goodyear Demountable 21 x 11 x 8 Knobby Tires
- ★ Brush Guard Foot Platform
- ★ Wider stance affords ease in handling

SPECIFICATIONS

Weight — 287 Lbs.

Overall Length — 65½"

Width — 41"

Wheel Base — 45½"

Handle Bar Height —
Adjustable

Seat Height -31%''Ground Clearance -9''Under Engine Load Capacity -400 Lbs.

Turning Radius — 3 Ft. Top Speed — 30 MPH Max.

SPECIFICATIONS SUBJECT TO CHANGE

OPTIONAL ACCESSORIES

Forward/Neutral/Reverse Transaxle
Gun Rack
Magnum Cargo Rack
Electric Broadcaster
Spot Spraying System
Control Droplet Applicator Spray Boom
Front Rack

>>>>>>>>>>>>>> MAKE TRACKS WITH A

SPECIFICATIONS

DIMENSIONS

Weight - 325 lbs. Overall Length - 68" Width - 421/2" Wheel Base - 451/2" Handle Bar Height - Adjustable Seat Height - 33" Ground Clearance - 10" Under Engine

PERFORMANCE

Load Capacity - 400 lbs. Turning Radius - 3 ft. Top Speed - 35 MPH Max.

OPTIONAL ACCESSORIES

Gun Rack Magnum Cargo Rack Electric Broadcaster Spot Spraying System Control Droplet Applicator Spray Boom Front Rack

SPECIFICATIONS SUBJECT TO CHANGE



BIG FOOT GIVES YOU MORE:

★ Tires — 26" x 12" x 12" **★ Engine** — 305 cc **★ Battery** 30 AMP ★ Seating — 2 Passenger ★ Load Capacity — 400 Lbs.

BIG ON STANDARD FEATURES!

HANDLEBARS: Adjustable

FRONT FORK: 1½" Tubular Steel

HAND OPERATED CONTROLS:

Throttle: Your Choice!

Thumb or Fingertip Control with a turn of a

screw.

Brake: Flip a pin for a lock position for

parking

BODY: Fiberglass

COLOR: Brown or Blue with

optional Metal Flake

BRUSH GUARD & FOOT PLATFORM

SEATING: 2 passenger

TIRES: GOODYEAR — Demountable

Front: 21 x 11 x 8 Rear: 26 x 12 x 12

FRAME: 1" 11 gauge Tubular Steel

DOUBLE CRADLE

HEADLIGHT: 12 Volt Sealed Beam

TRAILER HITCH

ENGINE: 305 cc - 4 Cycle - Electric Start

CAST IRON KOHLER

PRIMARY DRIVE: FULLY ENCLOSED

AUTOMATIC CLUTCHES

FINAL DRIVE: Forward/Neutral/Reverse positions in a Maintenance Free Fully Enclosed

Transaxle Drive where the chains and

sprockets run in oil.

The AVENGER BIG FOOT is built for the big job!

The Multi-Purpose AVENGER







This AVENGER Big Foot is featured with a 12 volt ELECTRIC BROADCASTER. The BROADCASTER contains a 1.2 bushel hopper, stainless steel agitator, centering pivot plate (for directional broadcasting) and an adjustable flow gate.



This self-contained MICRON BOOM SPRAY SYSTEM features an 11 gallon Poly tank and 12 volt electric fluid pump. The Controlled Droplet Applicator (CDA) nozzles produce uniform micron sized droplets. Boom sizes range from 3'-10' with adjustable heights of 8"-20". The booms articulate to prevent damage to the heads.





50 GALLON POLY TANK AND TRAILER
The trailer is equipped with high speed bearings, spindles, high flotation tires and a 12 volt electric, 2 gal. per minute liquid transfer pump. Where added quantities of chemical are needed, this trailer is easily pulled behind an AVENGER and can be used as the primary tank. The trailer can be easily disconnected and left in a field to be used as a nurse tank.



This AVENGER 300 is shown with a canvas "buggy top" CANOPY which can be easily adjusted to shade the driver. The self-contained SPOT SPRAYING SYSTEM uses an 11 gallon Poly tank, 12 volt electric fluid pump, and an 18" hand operated wand with an adjustable tip.

FRONT SKI affords the rider three-wheeling fun in the snow.





This AVENGER Big Foot is equipped with a carryall MAGNUM CARGO RACK. The FRONT RACK attaches easily to the front fork for extra carrying capacity.

ACCESSORIES NOT SHOWN
★Gun Rack