The "BIG EIGHT"

By GESTAD

Ride the "Bulldog Eight" and you'll recognize the combination of power, comfort and WOW! what a ride. The big foam padded seat, husky tubular frame and BIG 21x12-8" tires, front and rear, give you that real pleasure while rollin' through the fields, trails and snow-covered woods. A slight twist of the handle sends you off to a new experience on every ride. The peppy 8 HP Tecumseh engine produces good speed through the torque converter which automatically seeks the right position for gearing down and up.

A 12-volt alternator produces power for the head and tail lights, all of which are standard on the "Bulldog Eight." All controls are at your fingertips, literally; twist-grip throttle and individual hand levers control the speed and dual external band type brake on each wheel. If you want the "Bulldog Eight" and beauty, too, get the deluxe fiberglass body and seat.



CS-123 ROLL BAR

Black roll bar, afford protection for engine and passenger.





CS-122 FIBERGLASS BODY

The "BULLDOG EIGHT"

Model CS-9081A

SPECIFICATIONS

ENGINE:

Manufacturer—Tecumseh Power Products
HP @ RPM—8 HP at 3850 RPM, 1 cylinder, 4 cycle
Starter Type—manual, recoil type. As an extra—Electric-Start.
Fuel Capacity—1 gallon
Estimated Running Time—2 hours
Fuel Requirement—regular gas

TRANSMISSION: (DRIVE TRAIN)

Type—torque converter

Primary Drive—V-belt, symmetric

Clutch—centrifugal pulley

Final Drive—#40 chain

Drive Ratios—19.17 low—7.39 high

Axle—automotive type differential w/steel sprocket and bevel gears—

1" dia. axles

CHASSIS:

Frame Type—single backbone tubular reinforced sideframe superstructure Wheel Base—65" Width—45" overall; $34^{1}/_{2}$ " tread width Overall Length—86" Suspension—provided by the low pressure ATV tires Wheels—8" dia. x 7" wide pressed steel Overall Height— $38^{1}/_{2}$ " (handle bar) Seat—two-piece, vinyl covered, foam padded, plywood reinforced Tires—21-12x8" low pressure, knobby tread Brakes—dual, independently operated, band type, non-reversing Ground Clearance— $5^{1}/_{2}$ " Seat Height— $15^{1}/_{2}$ " Handle Bar Height— $38^{1}/_{2}$ " Lighting System—12-volt alternator in engine, headlight and taillight Trailer Hitch—equipped with tongue-type hitch

ATTACHMENTS AVAILABLE (ACCESSORIES):

Emergency/Parking Brake mounted on Jackshaft.

WEIGHTS AND DIMENSIONS:

Dry Weight—220 lbs.
Shipping Weight—245 lbs.
Carton Dimensions—26" high x 38" wide x 63" long, w/skid 28" high



