# 7½ Or 9 H.P.-They Don't Come Any Tougher Than Our Engines!



# Pacesetter III




heavy cast-in cast iron cylinder liner; ball main bearings on both ends of crankshaft; forged aluminum connecting rod and encap-

Takes you wherever you want to go and

sulated ignition system.

takes you there in a hurry!


**GALLON!** 







IT'S A SNOWMOBILE!









IT'S A FARM IMPLEMENT!

It's Whatever You Want It To Be-In Any Terrain-Any Season!



**WINDSHIELD** 

**FRONT-MOUNT** 

LUGGAGE RACK

**INSULATED JACKET** 

## **DIMENSIONS**

PTO KIT

Weight - 225 lbs. Length (overall) - 66" Width (overall) - 391/2" Wheel Base - 45" Handle Bar Height - 401/2" Seat Height - 30" Ground Clearance - 9" Fuel Tank Capacity - 11/2 gals. Crankcase Capacity - 11/2 pts.

# **PERFORMANCE**

Maximum Speed — Approx. 40 mph Climbing Ability — 40° grade Load Capacity — 400 lbs. Braking Distance - 22 ft. at 20 mph

#### FRAME

Type — Tubular, double cradle Suspension: Front - Flotation Tire Rear — Swing Arm Tire Size — 21 x 11:00 - 8

### **ENGINES**

**UTILITY TRAILER** 

**OPTIONS AND** 

**ACCESSORIES** 


Make - Wisconsin Robin Type — 4 cycle, single-cylinder Model EY25W: 7.5 HP at 4500 RPM Displacement — 250 C.C. Model EY27W: 9.0 HP at 4500 RPM Displacement — 265 C.C.

# **TRANSMISSION**

Type — Torque Converter (torque sensing) Clutch — Automatic Ratio - 3 to 1 in low, to 8 to 1 in high

#### STANDARD EXTRAS

High-Low Headlight Tail and Brake Light **Brush-deflecting Foot Platform** Mud Guard Rear Shock Absorbers Heavy-duty Trailer Hitch **Engine Kill-Button** 



**MIRRORS** 

SPEEDOMETER KIT

**REAR CARGO** 

CARRIER RACK

**ELECTRIC HORN** 

**WINDBREAKER**