



SUSTAINABLE BUILDING SOLUTIONS

SPARTA365

PRODUCT DESCRIPTION

SPARTA365 SINGLE COMPONENT POLYASPARTIC eliminates many of the associated issues with traditional two-component polyaspartic systems by removing the pot-life concerns and by providing 50 minutes of working time. SPARTA365 has exceptional physical properties, excellent self-leveling capabilities, strong chemical resistance, along with excellent adhesion.

CURING

At 75°F (24°C) and 50% relative humidity, allow to cure for 6-12 hours prior to permitting light foot traffic and 24-48 hours before permitting heavy traffic. Allow 48-72 hours of curing prior to permitting wheel traffic and parking on the surface.

MIXING INSTRUCTIONS

Pre-Mix SPARTA365 prior to use. Pigment color packs should be mixed by hand or a low speed mechanical mixer making sure not to mix air into the coating.

SURFACE PREPARATION

Surface preparation is the key element for long term success. The concrete surface must allow the coating to soak into the surface of the concrete to create a strong mechanical bond. The concrete must be prepared to industry standards in accordance with NACE and SSPC guidelines.

WASTE DISPOSAL

Hazardous waste under RCRA 40 CFR 261. Disposal must be in compliance with all local, state and federal laws and regulations regarding treatment.

WARRANTY

Product free from material defects only.

PRECAUTIONS

Moisture vapor emission in the concrete (MVE) to be less than 3 pounds per 1000 sq.ft. for 24-hour period. Calcium Chloride test ASTM F1869-98 recommended. Moisture vapor drive can cause adhesion failure. Should not be applied in direct sunlight or on elevated surface temperatures. Clear coat applications may turn opaque or cloudy in exterior application due to moisture vapor penetration.

SPARTA365

Classified: Industrial Maintenance Non-compliant SCAQMD areas
VOC: 250 gm/liter. Check local VOC regulations prior to use.

STORAGE

Shelf life is 8-12 months from the date of manufacturing. Store in climate controlled area at 75°F (24°C).

COVERAGE RATES

Subject to substrate condition (estimate) 4-5 Mil=200-225 square feet per gallon.

SAFETY DATA SHEET

Read prior to opening and applying the product. Product for professional use only.

PERSONAL PROTECTIVE EQUIPMENT

Eye protection, gloves, respirator and proper clothing for protection when mixing and applying the product.

EMERGENCY CONTACT:

**INFOTRAC at 1-800-535-5053
USA & CANADA**

**Outside USA & CANADA
1-352-323-3500**



**TRANSPORTATION INFORMATION BY D.O.T. OR T.D.G.
NOT REGULATED WHEN SHIPPED DOMESTICALLY**

www.BuildWithSBS.com