



MIXING INSTRUCTIONS

Pre-Mix prior to use. Pigment color packs should be mixed by hand or a low speed mechanical mixer making sure not to mix air into the coating. Add – 2.0 pounds of pigment per gallon of clear. Quart packaging consistent of 2.0 pounds per can in Grey, Tan and Black. Other colors (Yellow, White and Blue) contain 3.0 pounds per quart.

PRODUCT DESCRIPTION

*See SPARTA365 Product Data Sheet.

CURING

At 75°F (24°C) and 50% relative humidity, allow to cure for 6-12 hours prior to permitting light foot traffic and 24-48 hours before permitting heavy traffic. Allow 48-72 hours of curing prior to permitting wheel traffic and parking on the surface.

USDA/FDA APPROVAL

Acceptable for use in floors subject to USDA/FDA inspections and regulations. USDA prohibits the use of any chemicals where existing food or food packaging can become contaminated.

WASTE DISPOSAL

Hazardous waste under RCRA 40 CFR 261. Disposal must be in compliance with all local, state and federal laws and regulations regarding treatment.

WARRANTY

Product free from material defects only.

**TRANSPORTATION INFORMATION BY D.O.T. OR T.D.G.
NOT REGULATED WHEN SHIPPED DOMESTICALLY**

PRECAUTIONS

Moisture vapor emission in the concrete (MVE) to be less than 3 pounds per 1000 sq.ft. for 24-hour period. Calcium Chloride test ASTM F1869-98 recommended. Older concrete exposed to the elements is susceptible to greater contamination and should be evaluated thoroughly prior to any application. Should not be applied in direct sunlight or on elevated surface temperatures. Clear coating may turn opaque or cloudy in exterior application due to moisture penetration. Recommended for indoor use only. Coated surface may be slippery when wet.

PACKAGING

Quart cans, 1-gallon cans, 5-gallon cans

COVERAGE RATES

Subject to substrate condition (estimate)
4-6 Mills = 200-225 square feet per gallon.

STORAGE

Shelf life: 1 year from the date of manufacturing.

MATERIAL DATA SHEET

Read prior to opening and applying the product, wear goggles, gloves, respirator and proper clothing for protection when mixing and applying the product.

