EuropeLIFT

optimize reaching

MODEL: 45 25A



- Working Height: 52 ftPlatform Height: 45 ft
- Horizontal Reach: 26 ft 5 in (485 lbs)
- Articulated telescopic boom
- Flyjib: 4 ft
- Standard Platform Rotator
- Auto chassis level
- Upper control box with LCDdisplay, plus wifi remote live service diagnostic (standard)
- Auto home function (standard)
- Gasoline engine (Honda/Briggs) power source (standard)
- Compact transport dimensions (Transport length 20 ft)










TRAILER MOUNTED BOOM LIFT

Specifications Daten	45 25A
Working Height	51 ft 8 in
Platform Height	45 ft
Horizontal Reach (485 lbs)	26 ft 7in
Max. Platform capacity	485 lbs
Slewing	355°
Flyjib	4 ft 3 in
Platform dimensions	4 ft 7 in x 2 ft 3 in x 3 ft 3in
Platform rotator	2x45°
Transport Lenght	ca. 19 ft 6 in
Transport width	5 ft 6 in
Transport Height	6 ft 8 in
Total weight (230V, Honda, wheel assist, Flyjib)	4078 lbs
Total weight 24VDC (battery, wheel assist)	4188 lbs
Outrigger footprint	12 ft 7 in
Gradeability	6,5°
Max. towing speed	62 mph
Brake	overrun brakes
Wheel	215R 14C
Energychain	Inside telescope



Manufacturer: Europe**LIFT**


9 Gepallomas 8992 Bagod

www.europelift.com

Made in EU

EuropeLIFT

MODEL: 45 25A



STANDARD FEATURES

- Articulated boom with telescope
- Autohome and Platform rotator 2x45°
- Flyjib 4 ft 3 in
- Hydraulic platform leveling with auto correction at 3°
- Chassis level sensor 1° with accoustic alarm
- Alu basket with wide tool tray, safety handrail and dual harness points
- Proportional electro-hydraulic controls by fingertip joysticks
- Ground pressure sensors on all outrigger plates with audible and visible alarms
- 230V outlet in the basket
- Hourmeter
- Ground and upper controls with tarp cover
- Manual recovery with hand pump
- Automatic reverse and overrun brakes
- Ground pressure monitoring on outrigger plates with accoustic and visual warning signal
- Protective cover on upper control box
- Rear LED light support frame
- Platform controls with LCD function display, plus Wifi remote live service diagnostics

OPTIONS

- Custom colour
- Auto chassis level
- Battery power 24V 225 Ah
- G.R.P. basket with tool tray (2 person)
- Outrigger plate pads
- 230V & Honda power source
- Wheel assist

Distributed by: National Equipment Wholesales

1725 Spectrum Dr. Ste A Lawrenceville, GA 30043

sales@nationalequip-us.com

+1 800-771-0908