

4-STROKE ENGINE OIL SAE 10W40

(Fully Synthetic 4-T Motor Oil)



DESCRIPTION

This oil is specially designed for automatic scooters and gearless 2-wheelers. Its exclusive and unique formulation does not let the oil film break easily, thereby providing superior protection even in heavy traffic 'stop-n-go' conditions.

This leads to a distinctly superior performance, which can be felt from the first use itself! This oil is designed specifically for motorcycles to meet the requirements that automotive oils are not designed to handle.

Premium base oils and advanced additives are used to meet special properties for proper performance and protection of dry clutch system.

APPLICATIONS

PATROL 4T Special motor oils are primarily intended for general use in all types of four-stroke motorcycles and engines. It is suitable for all makes of 4-stroke bikes, both carburetor and fuel injected and this product is compliance with the API SN and JASO MB international standards.

It is perfectly compatible with catalytic converters. The oil-change intervals recommended by the constructors and the minimum required viscosities must be complied with

PROPERTIES

PATROL 4T Special motor oils combine highly refined, quality synthetic oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection.

Specially formulated to provide outstanding, durable protection under severe high-torque, high-stress conditions when motorcycle engines operate at extremely high temperatures, causing viscosity and thermal breakdown of motor oil. PATROL 4T motor oils are engineered to provide maximum protection against viscosity and thermal breakdown.

PRODUCT BENEFITS

- Shear Stability Film Strength
- Excellent Corrosion Protection
- Provides exceptional protection for ATVs For use in 4-Stroke Motorcycles
- High RPM, High Temperature Performance Maximum Horsepower
- Good wear protection Advanced Cleaning
- Helps extend engine life Broad viscosity range
- Year round engine protection and performance

RECOMMENDATIONS / SPECIFICATIONS

MEETS OR EXCEEDS

API SN, JASO MB

TYPICAL TECHNICAL PROPERTIES

Density at 15°C, g/ml, ASTM D4052	0.87
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	6500@-25°C
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	100
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	14.5
Viscosity Index, ASTM D2270	150
Flash Point(COC), °C, ASTM D92	222
Pour Point, °C, ASTM D97	-30
Total Base Number, mg KOH/g, ASTM D2896	9.5
Sulphated Ash, %wt, ASTM D874, max	0.8

Note: These characteristics are typical of current production. While future production will conform to PATROL's specification, variations in these characteristics may occur.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment

