

CALCIUM GREASE NLGI 3



DESCRIPTION & APPLICATIONS

This is good quality, smooth-textured, calcium base general purpose grease, formulated with highly refined base stocks, calcium soap thickener and balanced additive package. Suitable for the lubrication of vehicle chassis, water pump, workshop and construction site machineries.

PRODUCT BENEFITS

- Multi-purpose
- Excellent thermal and mechanical stability
- Water resistant
- Long service life.
- High extreme pressure and anti-wear properties.
- Good pumpability.
- Extraordinary resistance to wash –off by water
- Excellent anti-oxidation and anti-corrosion properties
- No harmful substances

RECOMMENDATIONS / SPECIFICATIONS

MEETS OR EXCEEDS

DIN 51502 K1C, K2C, K3C, K4C

DIN 51825 K1B, K2B, K3B, K4C

ISO L-XBADA1, L-XBADA2, L-XBADA3, L-XBADA4

TYPICAL TECHNICAL PROPERTIES

Thickener Type	Calcium
Color	Amber
NLGI Classification	3
Texture	Smooth
Base oil type	Mineral
Dropping Point, °C, DIN ISO 2176	>90°C (>194°F)
Penetration DIN 2137 60 STORKES 10-1mm	220-250
Penetration DIN 2137 100000 STORKES 10-1mm	250 max
Anti-rust performance SKF- EMCOR, DIN 51 802, rating	0-0
Operating temperature range, °C	- 10 to +60

Note: These characteristics are typical of current production. While future production will conform to PATROL's specification, variations in these characteristics may occur. **Health and Safety:** Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.