



MULTI-VEHICLE ATF *(Full Synthetic ATF)*

DESCRIPTION

PATROL MULTI-VEHICLE ATF is a technologically advanced, low viscosity, full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing maximum fuel efficiency for modern automatic transmissions and meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

PATROL MULTI-VEHICLE ATF is suitable for use in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs. Meets or exceeds the requirements of the JASO-1A performance standard and the latest ATF specifications of Ford and GM for use in vehicles.

PROPERTIES

PATROL MULTI-VEHICLE ATF is high quality ATF fluid ensuring superior low temperature performance, easy pump ability and improved cold start. It has excellent frictional properties and performs exceptionally well in reducing sludge and preventing the formation of deposits.

PRODUCT BENEFITS

- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions.
- Anti-wear protection: significantly extended transmission life.
- Extended oil life: excellent thermal and oxidation stability.
- Enhanced friction durability for smooth transmission performance.
- Superior high temperature protection to effectively resist oxidation.
- Unsurpassed protection against copper corrosion.

RECOMMENDATIONS / SPECIFICATIONS

Meets or exceeds

HONDA DW-1, **AISIN-WARNER**-JWS 3324, AW-1, **HYUNDAI** NWS-9638 T5, SP -IV, SP H-IV, **LAND ROVER** LR 023288, **BMW**- M-1375.4, 83222152426, **CHRYSLER** 68157995AA, **FIAT** 9.55550-AV2, 9.55550-AV5, **MB** 236.12, **JAGUAR** 02JDE26444, **MITSUBISHI** ATF J3, **MAZDA** FZ, **TOYOTA** AUTO FL UID WS, **FORD** MERCON SP, MERCON LV, WSS -M2C924-A, **NISSAN** MATIC -S , **VW** G 055 162, G 060 162, G 055 005, G 055 540

TYPICAL TECHNICAL PROPERTIES

Color, VISUAL	RED
Density at 15°C, g/ml, ASTM D4052	0.846
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	29.4
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	6.1
Viscosity Index, ASTM D2270	162
Flash Point(COC), °C, ASTM D92	210
Pour Point, °C, ASTM D97	-54
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	9500

Note: These characteristics are typical of current production. While future production will conform to PATROL's specification, variations in these characteristics may occur.
Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.

