

ENGINE OIL SAE 5W40

(Engine Oils Formulated with 100% Synthetic Oil)



DESCRIPTION

PATROL Fully Synthetic Oil series are premium performance synthetic motor oils delivering ultimate performance and protection. It provides exceptional cleaning power, wear protection and overall performance keeping your engine running like new in all driving conditions.

APPLICATIONS

PATROL Fully Synthetic Oil series are top-tier motor oils recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions.

Extensive cooperative development work with major manufacturers and the application of the latest lubrication technology make them suitable for the latest engine technologies including Turbo-chargers, Direct Injection, Diesels (without DPF) and Hybrids, High performance engines under most operating conditions, from mild to extreme

PROPERTIES

PATROL Fully Synthetic Oil series are high performance engine oils specifically developed to provide the highest fuel economy and lowest CO2 emissions.

These result from laboratory synthesis of precisely controlled ingredients created by oil engineers, scientists and chemists.

When combined with a high-performance additive package, this results in an oil with the highest levels of lubrication and engine protection, generally offering better protection at startup, better cleansing qualities, enhanced durability and better protection against heat buildup.

PRODUCT BENEFITS

- Maximizes engine life.
- Low oil consumption.
- Excellent engine cleanliness and protection.
- Guaranteed protection from oil-related engine failure.
- High resistance to 'shear' and viscosity loss in high stress areas.
- Maximizes power and performance.
- Lower impact emissions.

- Exceptional resistance to oxidation.
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures.
- Outstanding cold flow properties for reduced wear at start up.

RECOMMENDATIONS / SPECIFICATIONS

MEETS OR EXCEEDS

API SL/CF-4

ILSAC GF-5

TYPICAL TECHNICAL PROPERTIES

Density at 15°C, g/ml, ASTM D4052	0.855
Cold Cranking Viscosity(CCS),mPas,ASTMD5293	6250@-30°C
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	102
Kinematic Viscosity at 100°C, mm ² /s, ASTMD445	14.8
Viscosity Index, ASTM D2270	151
Flash Point(COC), °C, ASTM D92	228
Pour Point, °C, ASTM D97	-45
Total Base Number, mg KOH/g, ASTM D2896	9.5
Sulphated Ash, %wt., ASTM D874, max	1.25

Note: These characteristics are typical of current production. While future production will conform to PATROL's specification, variations in these characteristics may occur.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment

