

COMPLETE PRODUCT RANGE


Vacuum Pumps and Systems, Compressors
and Pressure/Vacuum Pumps

MAKE IT BECKER.



FUNCTIONAL PRINCIPLES


DISPLACEMENT PUMPS



ROTARY VANE PUMPS


The robustly constructed rotary vane pumps are also suitable for higher pressure differences in vacuum and/or pressure applications. An eccentrically mounted rotor with slots rotates in a cylindrical housing and the precisely fitting sliding vanes move in the slots and separate the individual working chambers. Compared to dry-

running rotary vane pumps, oil-lubricated pumps additionally seal the working chambers with the oil that is also transported. The pumps are thus able to generate a fine vacuum and are therefore suitable for applications that require a high vacuum.




SCREW PUMPS

Thanks to the direct drive via an integrated frequency inverter, a drive gear is no longer required. The rotors with screw profile rotate in opposite directions and contactless. The working chamber of the machines is 100% oil-free. The integrated speed control enables energy-optimized operation of the devices.



CLAW PUMPS


Claw vacuum pumps are 100% free of oil and contact during operation. To achieve this, the claw-like rotors rotate within the compression chamber in opposite directions and are contactless. This makes the pump particularly low-maintenance. The claw technology ensures a high degree of efficiency and low energy consumption.



ROOTS BOOSTER PUMPS (PUMPING STATIONS)


In the case of contactless and oil-free compressing Roots booster pumps, two symmetrical lobes rotate in the working chamber. In combination with a displacement pump (e.g. rotary vane pump), Roots blowers are often used in pumping stations in order to achieve a very high volume flow with a high final vacuum.

TURBO DYNAMIC PUMPS



SIDE CHANNEL BLOWERS

Side channel blowers generate suction or blowing air for a wide variety of industrial applications. They contain a contactless, fast rotating impeller and are therefore wear and maintenance free. On both sides of the impeller there are two ring-shaped separate side channels along with the housing. This means that a single-stage device with a high volume flow or a two-stage device with higher pressure differences is possible.



RADIAL BLOWERS

Radial blowers are designed for high delivery volumes. The volume flow can be precisely adapted to customer requirements using the frequency inverter integrated on the motor. Radial blowers contain a very fast and contactless rotating impeller and are therefore wear and maintenance free.

Vacuum pumps.....	4	Compressors.....	14
Rotary vane, oil-free	4	Rotary vane, oil-free	14
VT 4.2 – VT 4.40		DT 4.2 – DT 4.40	
KVT 3.60 – KVT 3.140		KDT 3.60 – KDT 3.140	
VTLF 2.200 – VTLF 2.500		DTLF 2.200 – DTLF 2.500	
VARIAIR		VARIAIR	
Series X: VX/KVX/VXLF.....	5	Screw	16
Rotary vane, oil-lubricated	6	VADS 1500	
O 5.4 – O 5.21		Claw	17
U 4.20 – U 4.40		BCP 100 – BCP 300	
U 5.71 – U 5.301		Side channel	18
U 4.400 – U 4.630		SV 1.50 – SV 5.90	
VARIAIR		SV 130 – SV 1100	
Screw	8	VARIAIR	20
VADS 250 – VADS 1500		VARIAIR SV	
Claw	9	VARIAIR Speed Flow (VASF)	
BCV 100 – BCV 300		Radial	21
VARIAIR		VARIAIR RV 2.1944	
Side channel	10	VATP 1600	
SV 1.50 – SV 5.90		Pressure/vacuum pumps.....	22
SV 130 – SV 1100		Rotary vane, oil-free	22
VARIAIR	12	T 4.10 DV – T 4.40 DSK	
VARIAIR SV		DVT 3.60 – DVT 3.140	
VARIAIR Speed Flow (VASF)		Systems	23
Radial	13	Roots Booster Packages	23
VARIAIR RV 2.1944		Vacuum systems with vacuum vessel	24
VATP 1600		Becker worldwide	26

VARIAIR
UNIT

VARIAIR
DIRECT SCREW

VARIAIR
SPEED FLOW

VARIAIR
TURBO PACKAGE

VARIAIR

The frequency inverter integrated in the VARIAIR UNIT significantly enhances the performance data of each pumps. It matches pump delivery exactly to customer requirements. Energy consumption is optimized and constant vacuum or pressure is guaranteed even where demand is subject to Variation or severe fluctuation. As no unnecessary blast or suction air is generated,

(air discharge) noise is kept to a minimum. Dirt from the surrounding environment is kept out of the pumps via inlet filtration. "Gentle" pump start-up reduces strain on mechanical components and reliably extends their useful life. Variable Output ranges minimize the number of different types required, thus also providing logistical advantages.

VT • KVT • VTLF

ROTARY VANE VACUUM PUMPS

- Oil-free
- Air-cooled
- Integrated suction filter and blow off valve
- VT/KVT with vacuum regulating valve
- VTLF with vacuum safety valve
- Version /O-400 with VARIAIR frequency inverter



VT 4.40



		CFM – Refers to intake pressure ¹⁾										
	in. Hg V	0	3	6	9	12	15	18	21	24	25.4	27
VT 4.2	50 Hz	1.1	1.1	0.9	0.8	0.6	0.5	0.4				
	60 Hz	1.4	1.3	1.2	1.1	0.9	0.8	0.6				
VT 4.4	50 Hz	2.4	2.4	2.2	2.1	2.0	1.9	1.8	1.4	0.9	0.4	
	60 Hz	2.8	2.7	2.6	2.5	2.4	2.2	2.1	1.8	1.5	1.2	
VT 4.8	50 Hz	4.7	4.6	4.6	4.5	4.3	4.1	3.8	3.5	2.9	2.4	
	60 Hz	5.4	5.2	5.2	5.1	5.0	4.8	4.4	4.0	3.1	2.4	
VT 4.10	50 Hz	5.9	5.8	5.6	5.4	5.2	4.8	4.4	3.5	1.7	0.1	
	60 Hz	7.1	6.9	6.8	6.5	6.2	5.8	5.2	4.2	2.1	0.1	
VT 4.16	50 Hz	9.4	9.2	9.0	8.8	8.4	7.8	6.9	5.5	2.8	0.1	
	60 Hz	11.2	10.9	10.7	10.4	9.9	9.2	8.2	6.6	3.3	0.1	
VT 4.25	50 Hz	14.7	14.4	14.1	13.6	13.0	12.1	10.8	8.6	4.4	0.1	
	60 Hz	17.6	17.3	16.9	16.3	15.6	14.5	13.0	10.4	5.2	0.1	
VT 4.40	50 Hz	23.5	23.1	22.5	21.8	20.8	19.3	17.3	13.8	6.9	0.1	
	60 Hz	28.2	27.7	27.0	26.1	24.9	23.2	20.8	16.6	8.3	0.1	
KVT 3.60	50 Hz	32	32	32	31	31	29	28	26	22	12	0.1
	60 Hz	39	38	38	37	36	35	32	29	22	15	0.1
KVT 3.80	50 Hz	39	39	38	37	36	35	32	29	22	14	0.1
	60 Hz	46	45	45	44	43	41	38	34	26	17	0.1
KVT 3.100	50 Hz	58	57	56	55	53	51	47	42	33	21	0.1
	60 Hz	66	65	64	63	61	59	55	49	36	24	0.1
KVT 3.140	50 Hz	76	75	74	72	71	68	64	56	44	28	0.1
	60 Hz	91	89	88	86	84	81	76	69	53		
VTLF 2.200	50 Hz	105	102	100	97	93	89	82	68	50		
	60 Hz	128	126	124	120	116	111	105	94	74		
VTLF 2.250	50 Hz	144	142	140	138	135	131	124	116	97		
	60 Hz	168	167	165	162	159	154	146	135	115		
VTLF 2.250 SK	50 Hz	145	142	139	135	129	125	120	111	94	82	52
	60 Hz	173	172	170	167	162	158	151	141	122	112	84
VTLF 2.360	50 Hz	206	206	206	204	202	196	191	178	166 @ 22.4 in.Hg V		
	60 Hz	236	237	236	235	230	225	218	212	207 @ 22.4 in.Hg V		
VTLF 2.400	50 Hz	229	223	218	212	206	191	181	161	143		
	60 Hz	271	268	265	261	256	249	238	219	182		
VTLF 2.500	50 Hz	291	286	282	278	273	265	249	233	221 @ 22.4 in.Hg V		
	60 Hz	335	332	329	325	318	309	296	272	262 @ 22.4 in.Hg V		
KVT 3.100/O-400	60 Hz	66	65	64	63	61	58	55	49	40	33	21
KVT 3.140/O-400	60 Hz	85	82	81	79	77	75	71	65	56	49	36
VTLF 2.250/O-400	60 Hz	165	164	164	160	156	151	143	131	105		
VTLF 2.360/O-400	60 Hz	238	238	238	233	226	218	206	205	205 @ 22.4 in.Hg V		
VTLF 2.500/O-400	60 Hz	329	325	321	316	310	301	288	267	250 @ 22.4 in.Hg V		

¹⁾ Reference (atmosphere): 0 in. Hg V 68°F / tolerance: ±5%

²⁾ Alternatively available as DC variant

³⁾ Power of the VARIAIR frequency inverter



KVT 3.140



VTLF 2.250

Technical data											
	hp 3~		hp 1~		db(A)		lbs	Length	Inch		Connection
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz			Width	Height	
VT 4.2	–	–	0.12	0.14	56.0	58.0	15.4	8.7	6.1	6.5	1/4"
VT 4.4	0.24 ²⁾	0.28 ²⁾	0.24 ²⁾	0.28 ²⁾	59.0	61.0	15.4	8.7	6.1	6.5	1/4"
VT 4.8	0.5 ²⁾	0.6 ²⁾	0.5 ²⁾	0.6 ²⁾	58.0	61.0	25.4	9.1 (3~) 9.9 (1~)	6.1	6.8	3/8"
VT 4.10	0.5	0.6	0.5	0.6	60.0	62.0	35.3	16.9	8.1	7.6	1/2"
VT 4.16	0.7	0.9	0.7	0.9	61.0	64.0	49.6	17.8	9.1	8.2	1/2"
VT 4.25	1.0	1.2	1.1	1.3	62.0	67.0	57.3	19.9	10.2	11.5	3/4"
VT 4.40	1.7	2.0	1.5	1.5	67.0	72.0	84.9	22.5	11.0	11.5	3/4"
KVT 3.60	3.0	3.5			71.0	73.0	185.2	29.4	13.9	12.9	1"
KVT 3.80	3.0	3.5			72.0	75.0	189.6	29.4	13.9	12.9	1"
KVT 3.100	4.0	4.8			75.0	77.0	238.1	33.5	18.5	13.2	1 1/2"
KVT 3.140	5.4	6.4			76.0	79.0	314.2	38.1	18.5	13.2	1 1/2"
VTLF 2.200	5.4	6.4			75.0	77.0	584.3	46.3	25.4	20.8	2 1/2"
VTLF 2.250	7.4	8.9			77.0	79.0	568.9	45.1	25.4	20.8	2 1/2"
VTLF 2.250 SK	10.1	12.1			77.0	79.0	590.9	46.5	25.4	22.0	2 1/2"
VTLF 2.360	14.8	17.7			80.5	82.5	579.9	46.3	25.4	20.8	2 1/2"
VTLF 2.400	10.1	12.1			77.0	79.0	937.1	58.2	29.4	22.8	4"
VTLF 2.500	14.8	17.7			79.0	80.0	906.3	58.2	29.4	22.8	4"
KVT 3.100/0-400	5.4 ³⁾					77.0	241.4	32.7	18.5	15.8	1 1/2"
KVT 3.140/0-400	5.4 ³⁾					77.9	254.7	32.7	18.5	15.8	1 1/2"
VTLF 2.250/0-400	10.1 ³⁾					79.0	595.4	49.3	25.4	22.9	2 1/2"
VTLF 2.360/0-400	14.8–29.5 ³⁾					79.0	639.5	46.5	25.4	25.0	2 1/2"
VTLF 2.500/0-400	14.8–29.5 ³⁾					80.0	981.2	57.5	29.4	28.1	4"

SERIES X: BECKER INNOVATION WITH TOP WARRANTY

Equipped with specially developed vanes, these oil-free rotary vane pumps distinguish themselves by high abrasion resistance, and with that extremely long service lives. Due to the low wear there is also minimal dust, so the series X pumps are perfectly suited for precision processes under clean room conditions.

This innovation branded by Becker is outstanding not only because of its 100 percent oil-free operation, excellent degree of efficiency and low power consumption.

In the area of sensitive vacuum, series X also guarantees precise low-pulsation air conduction.

Becker guarantees for these pumps a vane life-time of 20,000 operating hours or a maximum of 3 years. The enhanced longevity of X series pumps also extends service life intervals, and can cut out the need for frequent service visits with costly pump failures now no longer an issue.

Available as

- VX 4.10 – VX 4.40 (27 in. Hg V)
- K VX 3.60 – K VX 3.140
- V XLF 2.200, 2.250, 2.400 & 2.500



ADVANTAGES

- Quick, clean and quiet
- Oil-free
- Wear resistant
- Energy saving
- Long-life reliability



ROTARY VANE VACUUM PUMPS

- Oil-lubricated
- Air-cooled
- Non return valve and oil separator
- U 5.71 – U 5.301 additionally with gas ballast valve and oil filter
- VARIAIR pumps including frequency inverter



O 5.8



		CFM – Nominal air flow refers to intake pressure ¹⁾													CFM ¹⁾	
Torr		750	675	600	525	450	375	300	225	150	75	37.5	18.75	7.5	@ max. Torr	
O 5.4²⁾	50 Hz	2.4	2.3	2.2	2.2	2.2	2.1	2.1	2.0	2.0	1.9	1.5	1.4	1.1	0.1	1.5
	60 Hz	2.8	2.8	2.7	2.7	2.6	2.6	2.5	2.5	2.4	2.3	1.9	1.8	1.4	0.1	1.5
O 5.6	50 Hz	3.8	3.8	3.7	3.7	3.7	3.6	3.6	3.6	3.6	3.4	1.9	1.8	1.4	0.1	2.3
	60 Hz	4.4	4.4	4.3	4.3	4.3	4.2	4.2	4.2	4.2	3.9	3.6	3.5	3.1	0.1	2.3
O 5.8²⁾	50 Hz	4.7	4.4	4.4	4.4	4.4	4.4	4.3	4.3	4.3	4.2	3.6	3.5	3.1	0.1	1.5
	60 Hz	5.6	5.4	5.4	5.4	5.3	5.3	5.2	5.2	5.2	5.1	4.9	4.7	4.1	0.1	1.5
O 5.10	50 Hz	6.2	5.9	5.9	5.9	5.9	5.6	5.6	5.6	5.3	5.3	5.0	4.7	3.8	0.1	1.5
	60 Hz	7.4	7.1	7.1	7.1	7.1	7.1	6.8	6.8	6.8	6.2	5.6	5.0	4.4	0.1	1.5
O 5.16	50 Hz	9.4	9.4	9.1	9.1	9.1	8.8	8.8	8.5	8.2	7.9	7.4	7.1	5.6	0.1	1.5
	60 Hz	11.2	11.2	9.7	10.9	10.6	10.3	10.3	10.0	9.7	9.1	8.5	7.9	6.5	0.1	1.5
O 5.21	50 Hz	13.8	13.5	13.2	13.2	12.9	12.9	12.9	12.9	12.9	12.9	12.9	12.4	12.4	0.1	1.5
	60 Hz	15.9	15.6	15.6	15.3	15.3	14.7	14.4	14.4	14.4	14.4	14.4	14.1	12.9	0.1	1.5
U 4.20	50 Hz	11	10.5	10.4	10.2	10.0	9.8	9.5	9.3	8.8	8.8	8.7	8.5	7.9	0.1	<0.75
	60 Hz	12	12.3	12.1	11.9	11.7	11.4	10.9	10.6	10.0	9.9	9.9	9.6	9.1	0.1	<1.125
U 4.40	50 Hz	24	23.6	23.2	22.7	22.1	21.6	21.0	20.4	19.8	18.8	18.2	17.6	17.1	0.1	0.375
	60 Hz	28	28.2	28.0	27.6	27.1	26.3	25.6	24.7	23.8	22.3	21.2	20.6	19.4	0.1	0.375
U 5.71	50 Hz	41	41	40	39	39	38	38	37	36	36	34	33	31	0.1	<0.075
	60 Hz	49	49	48	48	47	46	45	45	44	44	39	38	34	0.1	<0.075
U 5.101	50 Hz	59	58	56	55	54	54	52	51	50	49	48	45	43	0.1	<0.075
	60 Hz	71	69	68	66	64	63	61	59	58	56	55	54	47	0.1	<0.075
U 5.166	50 Hz	97	95	94	92	91	89	87	85	83	80	78	71	62	0.1	<0.075
	60 Hz	116	115	112	111	108	106	104	102	100	96	94	83	75	0.1	<0.075
U 5.201	50 Hz	118	115	114	111	109	107	105	102	101	99	96	88	81	0.1	<0.075
	60 Hz	141	138	135	133	130	127	124	121	119	114	111	98	91	0.1	<0.075
U 5.301	50 Hz	176	173	171	167	164	161	157	154	151	148	144	139	128	0.1	<0.075
	60 Hz	212	208	203	199	195	191	186	182	179	171	167	155	146	0.1	<0.075
U 4.400 SA/K U 4.400 F/K	50 Hz	256	256	256	256	256	256	256	255	255	255	253	252	243	0.1	2.3/0.4
	60 Hz	299	299	299	299	299	299	299	299	298	298	298	296	293	0.1	2.3/0.4
U 4.630 SA/K U 4.630 F/K	50 Hz	367	367	367	367	367	367	367	366	366	365	363	360	348	0.1	2.3/0.4
	60 Hz	431	431	431	431	431	431	431	430	430	429	426	422	409	0.1	2.3/0.4
VARIAIR U 5.101	60 Hz	82	73	71	70	69	9	66	65	64	62	59	55	52	0.3	0.075
VARIAIR U 5.201	60 Hz	141	137	134	129	124	119	114	114	122	132	124	115	104	18.8	0.075
VARIAIR U 5.301	60 Hz	194	195	195	196	197	198	198	197	196	195	193	188	176	0.3	0.075



O 5.21



U 5.201

Technical data													
	max. Torr		hp 3~		hp 1~		db(A)		lbs	Length	Inch		Connection
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz			Width	Height	
O 5.4 ²⁾	1.5	1.5	0.13	0.16	0.13	0.13	56.9	57.2	12.1	9.7	4.5 (3~) 5.2 (1~)	5.7 (3~) 4.8 (1~)	Ø 0.47 Inch
O 5.6	2.3	2.3	0.40	0.48	0.40	0.48	54.5	56.1	39.7	13.2 (3~) 14.0 (1~)	7	8	Ø 0.55 Inch
O 5.8 ²⁾	1.5	1.5	0.47	0.60	0.47	0.60	59.6	62.5	22.1	13.1	6.2 (3~) 6.5 (1~)	7.0 (3~) 6.6 (1~)	Ø 0.67 Inch
O 5.10	1.5	1.5			0.50	0.60	58.5	64.0	37.5	12.6	10.3	6.2	½"
O 5.16	1.5	1.5			0.74	0.89	60.5	67.0	39.7	12.6	10.3	6.2	½"
O 5.21	1.5	1.5			1.01	1.21	64.0	69.0	47.4	13.9	11.6	6.4	½"
U 4.20	<0.75	<1.125	0.74	0.89	0.80	0.97	63.0	67.0	44.1	13.2	9.9 (3~) 12.1 (1~)	8.8	½"
U 4.40	0.375	0.375	2.0	2.4	2.0	2.4	69.0	71.0	83.8	18.3	10.9 (3~) 13.4 (1~)	11.0	1"
U 5.71	<0.075-75	<0.075-75	2.0	2.4			64.0	67.0	133.4	27.4	15.0	13.0	1 ¼"
U 5.101	<0.075-300	<0.075-300	3.0	3.5			65.0	68.0	169.8	29.2	15.0	13.0	1 ¼"
U 5.166	<0.075-75	<0.075-75	4.0	4.8			70	72	235.9	33.2	20.1	15.7	2"
	<0.075-300	<0.075-300	5.4	6.4			70	72	229.3	32.3	20.1	15.7	2"
U 5.201	<0.075-75	<0.075-75	5.4	6.4			72	75	224.9	32.3	20.1	15.7	2"
	<0.075-300	<0.075-300	7.4	8.9			72	75	266.8	34.8	20.1	15.7	2"
U 5.301	<0.075-75	<0.075-75	7.4	8.9			73	76	356.1	38.4	21.6	16.1	2"
	<0.075-300	<0.075-300	10.1	12.1			73	76	356.1	38.4	21.6	16.1	2"
U 4.400 SA/K	2.3	2.3	14.8	17.7			78	81	882.0	53.9	26.5	19.9	3"
U 4.400 F/K	0.4	0.4	14.8	17.7			78	81	882.0	53.9	26.5	19.9	3"
U 4.630 SA/K	2.3	2.3	20.1	24.1			80	83	1201.7	60.6	27.4	19.9	3"
U 4.630 F/K	0.4	0.4	20.1	24.1			80	83	1201.7	60.6	27.4	19.9	3"
VARIAIR U 5.101	0.075	0.075	5.4 ³⁾				65	68	157.7	29.0	15.0	14.7	1 ¼"
VARIAIR U 5.201	0.075	0.075	5.4 ³⁾				72	74	235.9	32.3	20.1	16.2	2"
VARIAIR U 5.301	0.075	0.075	10.1 ³⁾				73	76	374.9	38.6	21.6	18.4	2"

¹⁾ Reference (atmosphere): 750 Torr, 68°F / tolerance: ±5% (U 4.) / ±10% (U 5.)

²⁾ For short-time operation

³⁾ Power of the VARIAIR frequency inverter

VADS

SCREW VACUUM PUMPS


- Non-contact compression
- Air-cooled
- Direct drive
- VARIAIR frequency inverter



VADS 250



VADS 1500+



		CFM – Refers to intake pressure ¹⁾														
Torr		750	675	600	525	450	375	300	225	150	75	37.5	18.75	7.5	3.75	≤0.075
VADS 250	340 Hz	141	142	142	143	144	145	145	146	147	155	169	172	174	171	0.1
VADS 1500+	200 Hz	812	815	818	809	800	782	765	723	682						

Technical data							
	Frequency inverter	db(A)	lbs	Length	Inch Width	Height	Connection
VADS 250	10.1 hp • 400/480 V ±10% • 50/60 Hz	68	617.4	47.0	20.5	35.7	2 ½"
VADS 1500+	40.2 hp • 400/480 V ±10% • 50/60 Hz	80	2646	63.0	57.5	71.2	DN 150

¹⁾ Reference (atmosphere): 750 Torr, 68°F / tolerance: ±5%

BCV

CLAW VACUUM PUMPS

- Non-contact compression
- Air-cooled
- Integrated suction filter
- VARIAIR BCV with VARIAIR frequency inverter



BCV 300



VARIAIR BCV 150



		CFM – Nominal air flow refers to intake pressure ¹⁾											
	Torr	750	675	600	525	450	375	300	225	150	112.5	75	37.5
BCV 100	50 Hz	59	52	51	49	48	45	43	39	34	22	11	0.1
	60 Hz	71	64	62	61	59	57	55	52	44	29	15	0.1
BCV 150	50 Hz	88	81	78	76	73	71	67	62	56	45	29	
	60 Hz	106	95	93	91	88	85	82	78	77	65	51	
BCV 300	50 Hz	162	151	149	147	145	143	141	135	112	91		
	60 Hz	191	179	178	176	172	169	166	159	147	120		
VARIAIR BCV 100	60 Hz	71	60	59	58	58	56	55	53	48	43	35	6
VARIAIR BCV 150	60 Hz	106	88	88	86	85	84	82	76	65	54	35	
VARIAIR BCV 300	60 Hz	191	170	168	168	170	171	170	153	115	86		

Technical data										
	hp 3~		db(A)		lbs	Length	Inch Width	Height	Connection	
	50 Hz	60 Hz	50 Hz	60 Hz						
BCV 100	3.0–4.0	3.0–4.0	67	71	266.8–293.3	30.3–31.7	21.2	21.0	2 ½"	
BCV 150	4.0–5.4	4.0–5.4	67	71	419.0–443.2	31.7–33.4	21.2	22.8	2 ½"	
BCV 300	7.4–10.1	7.4–10.1	59	72	712.2–729.9	36.2	22.9	24.6	2 ½"	
VARIAIR BCV 100	5.4 ²⁾		70		392.5	33.4	21.2	21.0	2 ½"	
VARIAIR BCV 150	5.4 ²⁾		71		458.6	32.4	21.2	22.8	2 ½"	
VARIAIR BCV 300	10.1 ²⁾		74		749.7	37.7	22.9	24.6	2 ½"	

¹⁾ Reference (atmosphere): 750 Torr, 68°F / tolerance: ±10%

²⁾ Power of the VARIAIR frequency inverter

SV

SIDE CHANNEL VACUUM PUMPS


- Non-contact compression
- Single or double stage
- Air-cooled



SV 300



SV 1100



		CFM – Refers to intake pressure ¹⁾										CFM ¹⁾	
in. H ₂ O		0	20.1	40.2	60.3	80.4	100.5	120.6	140.7	160.8	@ max.		
in. Hg V		0	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0	in. H ₂ O		
Single stage													
SV 1.50/3	50 Hz	24	12	0.1							0.1	40.2	
	60 Hz	28	19	4							4	40.2	
SV 5.90/1	50 Hz	44	26	7							5	42.2	
	60 Hz	54	37								26	32.2	
SV 130/1	50 Hz	76	61	45	30	14					2	96.5	
	60 Hz	94	80	65	49	34	21				13	108.5	
SV 200/1	50 Hz	106	81	61	40	15					7	86.4	
	60 Hz	135	106	84	64	42					28	92.5	
SV 201/1	50 Hz	112	94	77	61	45	30				22	110.6	
	60 Hz	135	116	100	84	68	52				42	114.6	
SV 300/1	50 Hz	191	167	142	119	94	71				51	116.6	
	60 Hz	229	206	183	159	134	109	79			75	124.6	
SV 400/1	50 Hz	229	208	185	161	136	109	81			72	126.6	
	60 Hz	276	256	233	209	183	156	127			102	136.7	
SV 500/1	50 Hz	300	278	251	226	202	176	148			112	142.7	
	60 Hz	359	341	318	293	268	241	212			168	148.7	
SV 700/1	50 Hz	441	402	361	322	279	239	192			152	136.7	
	60 Hz	529	489	449	410	371	329	284			249	136.7	
SV 1100/1	50 Hz	618	566	516	463	412	355	293			267	128.6	
	60 Hz	735	687	642	592	540	485	427			402	128.6	
Double stage													
SV 5.90/2	50 Hz	25	20	14	8	3					0.1	92.5	
	60 Hz	29	25	20	16	11					5	96.5	
SV 130/2	50 Hz	41	34	28	23	18	14	10	5		2	152.8	
	60 Hz	50	44	38	33	28	24	19	15	11	11	160.8	
SV 200/2	50 Hz	53	44	35	28	23	16	8			4	132.7	
	60 Hz	65	56	48	42	35	29	22	14		14	140.7	
SV 201/2	50 Hz	53	48	42	38	32	28	23	16	10	10	160.8	
	60 Hz	65	59	54	49	44	38	33	27	21	21	160.8	
SV 300/2	50 Hz	94	85	77	70	62	54	45	37	27	26	162.8	
	60 Hz	112	104	96	90	82	74	65	57	47	46	164.8	
SV 400/2	50 Hz	115	106	98	89	80	71	63	54	45	38	176.9	
	60 Hz	138	131	122	114	106	98	89	80	71	63	176.9	
SV 500/2	50 Hz	153	141	128	117	104	93	82	72	61	59	164.8	
	60 Hz	179	172	161	151	140	129	119	108	96	96	160.8	
SV 700/2	50 Hz	218	206	195	183	172	161	149	136	122	118	168.8	
	60 Hz	259	248	236	226	215	204	192	181	169	164	168.8	
SV 1100/2	50 Hz	306	295	282	269	253	238	222	203		187	156.8	
	60 Hz	359	349	339	326	313	299	284	266		251	156.8	

¹⁾ Reference (atmosphere): 0 in. Hg V, 68°F / tolerance: ±10%

Technical data														
	max. in. H ₂ O		hp 3~		hp 1~		db(A)		lbs	Length	Inch		Connection	
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	Width		Height			
Single stage														
SV 1.50/3	40.2	40.2	0.2	0.3	0.2		62.0	63.0	17.6	8.9	8.7	9.3	1"	
SV 5.90/1	42.2	32.2	0.5	0.6	0.5	0.6	63.0	64.0	28.7	10.3	9.1	12.8	1 ¼"	
SV 130/1	30.2	26.1	0.7	0.9	0.7	0.9	60.9	63.6	46.3	15.7	10.4	12.2	1 ½"	
	50.3	46.2	1.0	1.2	1.0	1.2	60.9	63.6	48.5	15.1	10.4	12.2	1 ½"	
	84.4	80.4	1.5	1.7	1.5	1.7	63.4	64.8	49.6	15.2	10.4	12.2	1 ½"	
SV 200/1	96.5	98.5	1.7	2.0			63.4	64.8	54.0	16.0	10.4	12.2	1 ½"	
	96.5	108.5	2.0	2.4	2.0	2.4	64.0	65.4	57.3	16.8	10.4	12.2	1 ½"	
	60.3	56.3	1.5	1.7	1.5	1.7	63.9	69.2	56.2	16.6	12.1	14.1	2"	
SV 201/1	86.4	92.5	2.0	2.4	2.0	2.4	63.9	69.2	62.8	17.0	12.1	14.1	2"	
	56.3	50.3	1.5	1.7	1.5	1.7	65.2	68.3	56.2	16.6	12.1	14.1	2"	
	88.4	84.4	2.0	2.4	2.0	2.4	66.5	68.2	62.8	17.0	12.1	14.1	2"	
SV 300/1	110.6	114.6	3.0	3.6			66.3		71.7	17.8	12.1	14.1	2"	
	68.3	62.3	3.0	3.6			67.3	68.3	88.2	18.5	14.6	16.8	2 ½"	
	106.5	98.5	4.0	4.8			70.1	71.0	93.7	19.5	14.6	16.8	2 ½"	
SV 400/1	116.6	124.6	5.4	6.4			71.4	72.7	120.2	21.2	14.6	16.8	2 ½"	
	84.4	76.4	4.0	4.8			72.5	74.4	115.8	19.3	15.4	17.9	3"	
	126.6	116.6	5.4	6.4			72.5	74.4	116.9	19.8	15.4	17.9	3"	
SV 500/1	126.6	136.7	7.4	8.9			74.5	74.0	120.2	21.1	15.4	17.9	3"	
	80.4	70.4	5.4	6.4			75.5	76.7	135.6	19.5	18.7	20.6	3"	
	126.6	116.6	7.4	8.9			75.5	76.7	146.6	20.9	18.7	20.6	3"	
SV 700/1	142.7	148.7	10.1	12.1			75.5	76.7	166.5	23.6	18.7	20.6	3"	
	80.4	68.3	7.4	8.9			69.0	71.0	196.2	22.5	19.5	23.5	4"	
	120.6	112.6	10.1	12.1			72.0	73.0	247.0	24.2	19.5	23.5	4"	
SV 1100/1	136.7	136.7	14.8	17.7			73.0	74.0	262.4	25.0	19.5	23.5	4"	
	64.3	52.3	10.1	12.1			73.0	77.0	260.2	24.5	20.7	24.1	4"	
	116.6	108.5	14.8	17.7			75.0	79.0	275.6	25.3	20.7	24.1	4"	
SV 1100/1	128.6	128.6	20.1	24.1			75.0	79.0	346.2	26.8	20.7	24.1	4"	
	Double stage													
	SV 5.90/2	92.5	96.5	0.5	0.6	0.5	0.6	62.0	64.0	28.7	10.4	9.7	11.9	1 ¼"
SV 130/2	68.3	60.3	0.7	0.9	0.7	0.9	57.3	59.0	47.4	15.7	10.4	12.2	1 ½"	
	108.5	100.5	1.0	1.2	1.0	1.2	60.4	59.6	48.5	15.1	10.4	12.2	1 ½"	
	152.8	160.8	1.5	1.7	1.5	1.7	59.8	62.7	50.7	15.2	10.4	12.2	1 ½"	
SV 200/2	132.7	120.6	1.5	1.7	1.5	1.7	63.7	68.4	56.2	16.8	12.1	14.1	2"	
	132.7	140.7	2.0	2.4	2.0	2.4	63.7	68.4	62.8	17.0	12.1	14.1	2"	
SV 201/2	112.6	100.5	1.5	1.7	1.5	1.7	65.6	68.7	56.2	16.8	12.1	14.1	2"	
	160.8	160.8	2.0	2.4	2.0	2.4	65.6	68.7	62.8	17.0	12.1	14.1	2"	
SV 300/2	140.7	126.6	3.0	3.6			67.8	67.5	89.3	18.5	14.6	16.8	2 ½"	
	162.8	164.8	4.0	4.8			69.9	69.7	94.8	19.5	14.6	16.8	2 ½"	
SV 400/2	176.9	160.8	4.0	4.8			71.1	73.0	118.0	19.3	15.4	17.9	3"	
	176.9	176.9	5.4	6.4			71.1	73.0	119.1	19.8	15.4	17.9	3"	
SV 500/2	112.6	96.5	4.0	4.8			68.9	71.7	127.9	19.1	18.7	20.6	3"	
	164.8	160.8	5.4	6.4			68.9	71.7	137.8	19.5	18.7	20.6	3"	
SV 700/2	156.8	144.7	7.4	8.9			70.0	74.0	196.2	22.5	19.5	23.5	4"	
	168.8	168.8	10.1	12.1			72.0	76.0	247.0	24.2	19.5	23.5	4"	
SV 1100/2	140.7	104.5	10.1	12.1			72.0	75.0	260.2	24.5	20.7	24.1	4"	
	156.8	156.8	14.8	17.7			74.0	78.0	275.6	25.3	20.7	24.1	4"	


VARIAIR SV • VARIAIR Speed Flow

SIDE CHANNEL VACUUM PUMPS

- Non-contact compression
- Single or double stage
- Air-cooled
- VARIAIR frequency inverter



VARIAIR SV 300

VASF 2.80²⁾

		CFM – Refers to intake pressure ¹⁾									CFM ¹⁾	
		0	20.1	40.2	60.3	80.4	100.5	120.6	140.7	160.8	@ max.	
	in. H ₂ O	0	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0		in. H ₂ O
Single stage												
VARIAIR SV 130/1	100 Hz	168	146	126	106	87	69	51			49	122.6
VARIAIR SV 201/1	100 Hz	206	206	195	179	160	140	71			52	124.6
VARIAIR SV 300/1	87 Hz	329	313	293	271	206	99	0			71	102.5
VARIAIR SV 300/1	100 Hz	376	365	353	332	307	239	171			129	122.6
VARIAIR SV 400/1	100 Hz	509	496	473	446	415	379	320			217	136.7
VARIAIR SV 500/1	100 Hz	588	579	560	538	510	477	436	388		343	148.7
VARIAIR SV 700/1	80 Hz	694	675	645	605	558	510	464			432	135.1
VASF 2.50/1	300 Hz	28	25	24	22	20	16 AC 12 DC				0.1	116.6 AC 112.6 DC
VASF 2.80/1	250 Hz	53	46	42	39	36	30				0.1	112.6 AC 116.6 DC
VASF 2.120/1	200 Hz	84	74	68	64	55					0.1	92.5 AC
Double stage												
VARIAIR SV 130/2	100 Hz	82	74	66	59	52	45	38	32	26	25	164.8
VARIAIR SV 201/2	100 Hz	103	101	98	94	89	85	79	74	66	62	168.8
VARIAIR SV 300/2	100 Hz	188	182	178	172	167	158	152	144	135	114	164.8
VASF 2.50/2	300 Hz	14	13	12	11	11	10	10	9	8	0.1	225.1 AC 221.1 DC
VASF 2.80/2	250 Hz	26	25	22	21	19	18	16	14	11	0.1	201.0 AC 229.1 DC
VASF 2.120/2	200 Hz	42	38	35	32	30	28	26	24	20	0.1	184.9 AC

Technical data									
	Frequency inverter	db(A)	lbs	Inch			Connection		
				Length	Width	Height			
VARIAIR SV 130/X	5.4 hp • 400/480 V ±10% • 50/60 Hz	70.0	67.3	16.7	10.4	15.0	1 ½"		
VARIAIR SV 201/X	5.4 hp • 400/480 V ±10% • 50/60 Hz	77.2	70.6	16.9	12.1	16.0	2"		
VARIAIR SV 300/1 87 Hz	5.4 hp • 400/480 V ±10% • 50/60 Hz	70.2	101.4	19.4	14.6	18.0	2 ½"		
VARIAIR SV 300/X 100 Hz	10.1 hp • 400/480 V ±10% • 50/60 Hz	75.0	109.1	20.2	14.6	19.7	2 ½"		
VARIAIR SV 400/1	14.8–29.5 hp • 400/480 V ±10% • 50/60 Hz	76.8	165.4	22.5	15.4	23.2	3"		
VARIAIR SV 500/1	14.8–29.5 hp • 400/480 V ±10% • 50/60 Hz	80.6	215.0	23.6	18.7	24.5	3"		
VARIAIR SV 700/1	14.8–29.5 hp • 400/480 V ±10% • 50/60 Hz	74.5	264.6	24.9	19.5	14.9	4"		
VASF 2.50/X	0.87 hp • AC~ • 200 V -10% ... 230 V +10% • 50/60 Hz	61.0	27.1	13.9	6.9	10.1	1"		
	0.80 hp • AC~ • 100 V -10% ... 115 V +10% • 50/60 Hz	61.0	27.1	13.9	6.9	10.1	1"		
	1.0 hp • DC~ • 24 V ±20%	65.0	25.4	13.9	6.8	9.2	1"		
VASF 2.80/X	1.48 hp • AC~ • 200 V -10% ... 230 V +10% • 50/60 Hz	61.0	33.1	15.4	6.9	11.5	1 ¼"		
	1.48 hp • DC~ • 48 V ±20%	65.0	32.4	15.4	6.8	10.6	1 ¼"		
VASF 2.120/X	1.88 hp • AC~ • 200 V -10% ... 230 V +10% • 50/60 Hz	63.0	41.5	17.0	7.9	12.6	1 ½"		

¹⁾ Reference (atmosphere): 0 in. Hg V, 68°F / tolerance: ±10%

²⁾ Optionally with integrated VARIAIR frequency inverter, fan and silencers

VARIAIR RV • VATP

RADIAL VACUUM PUMPS


- Non-contact compression
- Air-cooled
- VARIAIR RV with external VARIAIR frequency inverter
- VATP (VARIAIR Turbo Package) consisting of RV 2.1944/10, VARIAIR frequency inverter, intake filter and sound enclosure



RV 2.1944/10



VATP 1600



		CFM – Refers to intake pressure ¹⁾						
	in. H ₂ O	0	20.1	40.2	60.3	80.4	100.5	116.6
	in. Hg V	0	1.5	3.0	4.5	6.0	7.5	8.7
RV 2.1944/10	400 Hz	923	950	887	817	738	623	286
VATP 1600	400 Hz	923	950	887	817	738	623	286

Technical data									
	Frequency inverter	db(A)	lbs	Length	Inch Width	Height	Connection		
RV 2.1944/10	14.8–29.5 hp ²⁾ • 400/480 V ±10% • 50/60 Hz	75	178.6	21.7 ³⁾	17.7 ³⁾	20.5 ³⁾	Ø 5.91 Inch		
VATP 1600	14.8–29.5 hp ²⁾ • 400/480 V ±10% • 50/60 Hz	64	357.2	32.1	22.6	44.7		⁴⁾	

¹⁾ Reference (atmosphere): 0 in. Hg V, 68°F / tolerance: ±5%

²⁾ Alternatively available as 10.1 hp version (see pump data sheet)

³⁾ Without frequency inverter

⁴⁾ Flange for hose connector

DT • KDT • DTLF

ROTARY VANE COMPRESSORS

- Oil-free
- Air-cooled
- Integrated suction filter
- DT/KDT with pressure regulating valve
- DTLF with pressure safety valve
- Version /0-400 with VARIAIR frequency inverter



DT 4.16



		CFM ¹⁾										CFM ¹⁾	
		PSIA	14.5	17.4	20.3	23.2	26.1	29	31.9	34.8	37.7		@ max.
	PSIG	0	2.9	5.8	8.7	11.6	14.5	17.4	20.3	23.2		PSIG	
DT 4.2	50 Hz	1.1	1.0	0.9	0.9							0.9	8.7
	60 Hz	1.4	1.2	1.2	1.1							1.1	8.7
DT 4.4	50 Hz	2.5	2.4	2.2	2.1	2.0	1.9					1.9	14.5
	60 Hz	2.9	2.8	2.6	2.5	2.4	2.2					2.2	14.5
DT 4.6/0-61	50 Hz	3.4	3.1	2.9								2.9	5.8
	60 Hz	3.8	3.5	3.2								3.2	5.8
DT 4.8	50 Hz	4.7	4.6	4.4	4.2	4.0	3.8					3.8	14.5
	60 Hz	5.6	5.4	5.1	4.9	4.6	4.4					4.4	14.5
DT 4.10	50 Hz	5.9	5.6	5.2	4.8	4.5	4.1					4.1	14.5
	60 Hz	7.1	6.9	6.5	6.1	5.8	5.4					5.4	14.5
DT 4.16	50 Hz	9.4	9.0	8.6	8.2	7.8	7.4					7.4	14.5
	60 Hz	11.2	10.9	10.5	10.1	9.6	9.3					9.3	14.5
DT 4.25 K	50 Hz	14.7	14.4	14.0	13.6	13.3	12.9					12.9	14.5
	60 Hz	17.6	17.3	17.1	16.8	16.5	16.2					16.2	14.5
DT 4.40 K	50 Hz	23.5	22.2	21.5	20.8	20.1	19.3					19.3	14.5
	60 Hz	28.2	26.9	26.2	25.5	24.8	24.1					24.1	14.5
KDT 3.60	50 Hz	32	31	30	29	28	26	26	25			24	21.8
	60 Hz	37	36	35	35	34	32	32	31			30	21.8
KDT 3.80	50 Hz	39	38	36	36	35	34	32	31			31	21.8
	60 Hz	45	44	43	42	41	40	39	38			37	21.8
KDT 3.100	50 Hz	58	57	55	54	53	52	51	49			49	21.8
	60 Hz	69	68	67	65	64	62	61	60			59	21.8
KDT 3.140	50 Hz	76	75	74	72	71	70	68	66			66	21.8
	60 Hz	90	89	88	86	85	84	82	81			81	21.8
DTLF 2.200	50 Hz	102	99	96	93	89	86	83	80	76		74	26.1
	60 Hz	127	125	122	118	115	112	109	106	103		100	26.1
DTLF 2.250	50 Hz	145	143	141	138	135	131	129	126	123		121	26.1
	60 Hz	173	171	168	165	162	159	156	153	150		146	26.1
DTLF 2.250 K	50 Hz	141	139	136	134	131	128	126	124	121		119	26.1
	60 Hz	167	164	162	159	156	153	151	148	145		142	26.1
DTLF 2.360	50 Hz	212	210	208	206	203						202	13.1
DTLF 2.400	50 Hz	215	208	202	197	193	192	191	189	189		188	26.1
	60 Hz	259	254	248	245	243	241	239	236	235		232	26.1
DTLF 2.500	50 Hz	303	290	283	277	271	265	259	253	248		242	26.1
	60 Hz	353	345	338	331	325	319	313	307	300		291	26.1
KDT 3.80/0-400	60 Hz	45	44	42	41	40	39	38	36			36	21.8
KDT 3.100/0-400	60 Hz	69	68	67	65	64	62	61	58			58	21.8
KDT 3.140/0-400	60 Hz	88	88	86	85	84	84	76	70			67	21.8
DTLF 2.250/0-400	60 Hz	171	169	166	164	161	157	154	151	88		69	24.7
DTLF 2.500/0-400	60 Hz	343	337	331	325	319	315	300	271			253	21.8



KDT 3.80



DTLF 2.500

Technical data										
	max. PSIG 50 & 60 Hz	hp 3~		db(A)		lbs	Length	Inch Width	Height	Connection
		50 Hz	60 Hz	50 Hz	60 Hz					
DT 4.2	8.7	0.12 (1~)	0.14 (1~)	53.0	55.0	15.4	8.7	6.1	6.5	¼"
DT 4.4	14.5	0.24 ^{2,3)}	0.28 ^{2,3)}	60.0	60.5	15.4	8.7	6.1	6.5	¼"
DT 4.6/0-61	5.8	0.24 ³⁾	0.28 ³⁾	67.0	69.0	15.4	9.1	6.1	6.8	⅜"
DT 4.8	14.5	0.5 ³⁾	0.6 ³⁾	58.0	61.5	25.4	9.1 (3~) 9.9 (1~)	6.1	6.8	⅜"
DT 4.10	14.5	0.5 ³⁾	0.6 ³⁾	60.0	62.0	35.3	16.9	8.1	7.7	½"
DT 4.16	14.5	0.7 ³⁾	0.9 ³⁾	62.0	64.0	51.8	17.8	9.1	8.3	½"
DT 4.25 K	14.5	1.5 ³⁾	1.7	65.0	67.0	80.5	21.5	12.9	11.4	¾"
DT 4.40 K	14.5	2.5 ³⁾	3.0	67.0	70.0	101.4	24.6	12.9	11.4	¾"
KDT 3.60	7.3/14.5/21.8	3.0/3.0/4.0	3.5/3.5/4.8	≤72	≤74	185.2	29.4	13.9	12.9	1"
KDT 3.80	7.3/14.5/21.8	3.0/4.0/5.4	3.5/4.8/6.4	≤74	≤76	250.3	34.0	13.9	12.9	1"
KDT 3.100	7.3/14.5/21.8	5.4/7.4/7.4	6.4/8.9/8.9	≤76	≤78	298.8	38.1	18.5	14.3	1 ½"
KDT 3.140	7.3/14.5/21.8	7.4/10.1/10.1	8.9/12.1/12.1	≤82	≤84	321.9	37.5	18.5	14.3	1 ½"
DTLF 2.200	11.6/14.5/26.1	7.4/10.1/14.8	8.9/12.1/17.7	≤82	≤83	804.8	53.7	25.4	20.8	2 ½"
DTLF 2.250	11.6/14.5/26.1	10.1/14.8/20.1	12.1/14.5/24.1	≤84	≤85	749.7	51.2	25.4	21.9	2 ½"
DTLF 2.250 K	11.6/14.5/26.1	10.1/14.8/20.1	12.1/14.5/24.1	≤84	≤85	796.0	51.2	27.9	20.8	2 ½"
DTLF 2.360	7.3/13.1 (50 Hz)	14.8/20.1	–	≤84	–	630.6	46.5	25.4	20.8	2 ½"
DTLF 2.400	13.1/18.1/26.1	14.8/20.1/24.8	17.7/24.1/29.5	≤80	≤82	1058.4	60.5	29.4	22.8	4"
DTLF 2.500	11.6/16/21.8/26.1	20.1/24.8/29.5/40.2	24.1/29.5/34.9/48.3	≤81	≤82	1080.5	60.5	29.4	22.8	4"
KDT 3.80/0-400	21.8	5.4 ⁴⁾		71.2		192.9	28.6	13.9	15.8	1"
KDT 3.100/0-400	21.8	10.1 ⁴⁾		76.0		328.5	36.5	18.6	17.9	1 ½"
KDT 3.140/0-400	21.8	10.1 ⁴⁾		82.0		328.5	36.5	18.6	17.9	1 ½"
DTLF 2.250/0-400	21.8	14.8–29.5 ⁴⁾		76.7		683.6	50.9	25.5	26.9	2 ½"
DTLF 2.500/0-400	21.8	14.8–29.5 ⁴⁾		80.6		1080.5	56.7	29.4	28.1	4"

¹⁾ Reference (atmosphere): 0 PSIG, 68°F / tolerance: ±5%

²⁾ Alternatively available as DC variant


³⁾ Alternatively available as 1~ variant

⁴⁾ Power of the VARIAIR frequency inverter

VADS

SCREW COMPRESSORS

- Non-contact compression
- Air-cooled
- Direct drive
- VARIAIR frequency inverter



VADS 1500

		CFM ¹⁾							
PSIG		0	2.9	5.8	8.7	10.2	11.6	13.1	14.5
VADS 1500	167 Hz	705	705	705	705	691	663	609	530

Technical data								
	Frequency inverter	db(A)	lbs	Length	Inch Width	Height	Connection	
VADS 1500	60.3 hp • 400/480 V ±10% • 50/60 Hz	80	2646	63	57.5	71.2	DN 150	

¹⁾ Reference (atmosphere): 0 PSIG, 68°F / tolerance: ±5%

BCP

CLAW COMPRESSORS

- Non-contact compression
- Air-cooled
- Integrated suction filter



BCP 300



	PSIG	CFM ¹⁾										
		0	2.9	5.8	8.7	11.6	14.5	17.4	20.3	23.2	26.1	29.0
BCP 100	50 Hz	100	82	78	74	70	66	61	56	52	48	44
	60 Hz	120	96	92	88	84	80	76	72	68	66	64
BCP 150	50 Hz	150	124	119	114	110	105	100	95	90	85	81
	60 Hz	180	149	144	140	136	131	127	123	119	115	111
BCP 300	50 Hz	275	241	233	226	219	211	205	198	191	184	177
	60 Hz	325	292	283	274	267	258	250	242	234	227	219

Technical data										
	max. bar rel. 50 & 60 Hz	hp 3~		db(A)		lbs	inch			Connection
		50 Hz	60 Hz	50 Hz	60 Hz		Length	Width	Height	
BCP 100	11.6/18.85/ 21.75/29.0	4.0-5.4/5.4/ 7.4/7.4-10.1	4.0-5.4/5.4-6.4/ 7.4/7.4-10.1	75	77	237.0-391.4	31.7-35.3	21.3	20.0	1 ½"
BCP 150	14.5/18.85/ 24.65/29.0	7.4/10.1/ 10.1/12.3-14.8	7.4-8.9/10.1/ 10.1-12.0/12.3-17.7	77	78	402.4-517.1	35.3-40.5	21.3	20.0	1 ½"
BCP 300	18.85/ 23.2/29.0	14.8/ 20.1/20.1-24.8	14.8-17.7/ 20.1/20.1-24.8	82	86	702.3-794.9	42.8-44.8	23.0	21.4	2"

¹⁾ Reference (atmosphere): 0 PSIG, 68°F / tolerance: ±10%

SV

SIDE CHANNEL BLOWERS


- Non-contact compression
- Single or double stage
- Air-cooled



SV 300



SV 1100



		CFM ¹⁾											CFM ¹⁾	
		0	0.725	1.45	2.175	2.9	3.625	4.35	5.075	5.8	6.525	7.25	@ max.	
	PSIG	0	0.725	1.45	2.175	2.9	3.625	4.35	5.075	5.8	6.525	7.25		
	in. H ₂ O	0	20.1	40.2	60.3	80.4	100.5	120.6	140.7	160.8	180.9	201	in. H ₂ O	
Single stage														
SV 1.50/3	50 Hz	24	13	2									2	40.2
	60 Hz	28	18	5									5	40.2
SV 5.90/1	50 Hz	45	28										13	38.2
	60 Hz	51	36										29	28.1
SV 130/1	50 Hz	76	61	48	35	22	15						8	112.6
	60 Hz	94	79	68	55	45	34	25					25	120.6
SV 200/1	50 Hz	106	81	62	47	31							22	90.5
	60 Hz	135	107	88	72	57							51	88.4
SV 201/1	50 Hz	112	93	78	65	53	43	34					26	136.7
	60 Hz	135	117	102	88	76	65	55					50	132.7
SV 300/1	50 Hz	191	169	148	128	109	93	78	65				60	148.7
	60 Hz	229	210	191	172	154	137	119					106	136.7
SV 400/1	50 Hz	229	208	188	168	149	131	114	97	82			75	170.9
	60 Hz	276	256	235	215	195	177	160	144	128			125	164.8
SV 500/1	50 Hz	300	276	253	232	212	192	176	158	142			132	174.9
	60 Hz	359	336	318	298	279	259	240	221	201			198	162.8
SV 700/1	50 Hz	441	404	369	339	310	281	251	221	191			191	160.8
	60 Hz	529	490	456	423	393	362	332	299	268			268	160.8
SV 1100/1	50 Hz	618	575	536	497	459	479	383	346				317	156.8
	60 Hz	735	692	652	611	572	532	494	456				456	140.7
Double stage														
SV 5.90/2	50 Hz	25	19	14	9	5							1	96.5
	60 Hz	29	24	19	14	9							6	90.5
SV 130/2	50 Hz	41	34	29	25	20	16	14	11	8			8	160.8
	60 Hz	50	45	39	35	31	26	24	20				18	156.8
SV 200/2	50 Hz	53	44	36	31	26	22	18	12	8			6	164.8
	60 Hz	65	56	49	43	38	33	29	25	21			18	172.9
SV 201/2	50 Hz	53	49	44	39	35	31	26	23	19			18	168.8
	60 Hz	65	60	55	51	46	42	39	35	32			32	160.8
SV 300/2	50 Hz	94	85	78	72	65	59	53	47	41	36		29	207.0
	60 Hz	112	104	98	91	84	79	74	68	63	53		53	180.9
SV 400/2	50 Hz	115	106	99	92	84	78	71	65	59	55	49	47	213.1
	60 Hz	138	131	124	118	112	105	99	94	89	84	79	79	201.0
SV 500/2	50 Hz	153	140	129	119	109	101	92	85	77	71		66	193.0
	60 Hz	179	171	161	152	144	136	128	123	115	108	101	97	213.1
SV 700/2	50 Hz	218	209	201	192	183	176	168	162	155	149	144	144	201.0
	60 Hz	259	245	243	235	226	219	212	206	199	192		189	188.9
SV 1100/2	50 Hz	306	295	285	274	263	253	243	234	225	215	206	206	201.0
	60 Hz	359	349	340	331	321	312	302	293	283			282	164.8

¹⁾ Reference (atmosphere): 0 PSIG, 68°F / tolerance: ±10%

Technical data														
	max. in. H ₂ O		hp 3~		hp 1~		db(A)		lbs	Length	Inch		Connection	
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	Width		Height			
Single stage														
SV 1.50/3	40.2	40.2	0.2	0.3	0.2		62.0	63.0	17.6	8.9	8.7	9.3	1"	
SV 5.90/1	38.2	28.1	0.5	0.6	0.5	0.6	63.0	64.0	28.7	10.3	9.1	12.8	1 ¼"	
SV 130/1	30.2	24.1	0.7	0.9	0.7	0.9	61.2	64.0	46.3	15.7	10.4	12.2	1 ½"	
	50.3	44.2	1.0	1.2	1.0	1.2	61.2	64.0	48.5	15.1	10.4	12.2	1 ½"	
	84.4	78.4	1.5	1.7	1.5	1.7	63.9	64.7	49.6	15.2	10.4	12.2	1 ½"	
	96.5	94.5	1.7	2.0			64.2	65.3	54.0	16.0	10.4	12.2	1 ½"	
SV 200/1	112.6	120.6	2.0	2.4	2.0	2.4	64.2	65.3	57.3	16.8	10.4	12.2	1 ½"	
	58.3	52.3	1.5	1.7	1.5	1.7	64.6	68.2	56.2	16.6	12.1	14.1	2"	
SV 201/1	90.5	88.4	2.0	2.4	2.0	2.4	64.6	68.2	62.8	17.0	12.1	14.1	2"	
	54.3	48.2	1.5	1.7	1.5	1.7	63.9	68.0	56.2	16.6	12.1	14.1	2"	
	84.4	80.4	2.0	2.4	2.0	2.4	65.0	68.0	62.8	17.0	12.1	14.1	2"	
SV 300/1	136.7	132.7	3.0	3.6			68.3		71.7	17.8	12.1	14.1	2"	
	66.3	56.3	3.0	3.6			66.9	68.9	88.2	18.5	14.6	16.8	2 ½"	
	100.5	92.5	4.0	4.8			71.1	69.4	93.7	19.5	14.6	16.8	2 ½"	
SV 400/1	148.7	136.7	5.4	6.4			72.8	73.4	120.2	21.2	14.6	16.8	2 ½"	
	80.4	72.4	4.0	4.8			71.6	74.2	115.8	19.3	15.4	17.9	3"	
	116.6	108.5	5.4	6.4			71.6	74.2	116.9	19.8	15.4	17.9	3"	
SV 500/1	170.9	164.8	7.4	8.9			76.8	76.1	120.2	21.1	15.4	17.9	3"	
	76.4	70.4	5.4	6.4			71.6	74.1	135.6	19.5	18.7	20.6	3"	
	118.6	110.6	7.4	8.9			71.6	74.1	146.6	20.9	18.7	20.6	3"	
SV 700/1	174.9	162.8	10.1	12.1			75.4	77.4	166.5	23.6	18.7	20.6	3"	
	74.4	60.3	7.4	8.9			71.0	72.0	196.2	22.5	19.5	23.5	4"	
	114.6	100.5	10.1	12.1			72.0	74.0	247.0	24.2	19.5	23.5	4"	
SV 1100/1	160.8	160.8	14.8	17.7			73.0	75.0	262.4	25.0	19.5	23.5	4"	
	56.3	44.2	10.1	12.1			74.0	76.0	260.2	24.5	20.7	24.1	4"	
	104.5	88.4	14.8	17.7			74.0	76.0	275.6	25.3	20.7	24.1	4"	
SV 1100/1	156.8	140.7	20.1	24.1			76.0	79.0	346.2	26.8	20.7	24.1	4"	
	Double stage													
	SV 5.90/2	96.5	90.5	0.5	0.6	0.5	0.6	62.0	64.0	28.7	10.4	9.7	11.9	1 ¼"
SV 130/2	64.3	56.3	0.7	0.9	0.7	0.9	59.9	59.4	47.4	15.7	10.4	12.2	1 ½"	
	100.5	92.5	1.0	1.2	1.0	1.2	60.4	60.0	49.6	15.1	10.4	12.2	1 ½"	
	160.8	156.8	1.5	1.7	1.5	1.7	59.8	62.7	50.7	15.2	10.4	12.2	1 ½"	
SV 200/2	120.6	104.5	1.5	1.7	1.5	1.7	64.5	67.6	56.2	16.8	12.1	14.1	2"	
	164.8	172.9	2.0	2.4	2.0	2.4	64.5	67.6	62.8	17.0	12.1	14.1	2"	
SV 201/2	104.5	92.5	1.5	1.7	1.5	1.7	66.9	70.0	56.2	16.8	12.1	14.1	2"	
	168.8	160.8	2.0	2.4	2.0	2.4	66.9	70.0	62.8	17.0	12.1	14.1	2"	
SV 300/2	132.7	112.6	3.0	3.6			68.3	68.5	89.3	18.5	14.6	16.8	2 ½"	
	207.0	180.9	4.0	4.8			71.7	74.5	94.8	19.5	14.6	16.8	2 ½"	
SV 400/2	156.8	140.7	4.0	4.8			73.1	75.1	118.0	19.3	15.4	17.9	3"	
	213.1	201.0	5.4	6.4			73.1	75.1	119.1	19.8	15.4	17.9	3"	
SV 500/2	148.7	136.7	5.4	6.4			69.9	71.6	137.8	19.5	18.7	20.6	3"	
	193.0	213.1	7.4	8.9			69.8	72.2	148.8	20.9	18.7	20.6	3"	
SV 700/2	132.7	108.5	7.4	8.9			71.0	72.0	196.2	22.5	19.5	23.5	4"	
	201.0	188.9	10.1	12.1			72.0	75.0	247.0	24.2	19.5	23.5	4"	
SV 1100/2	104.5	72.4	10.1	12.1			72.0	76.0	260.2	24.5	20.7	24.1	4"	
	201.0	164.8	14.8	17.7			74.0	80.0	275.6	25.3	20.7	24.1	4"	


VARIAIR SV • VARIAIR Speed Flow

SIDE CHANNEL BLOWERS

- Non-contact compression
- Single or double stage
- Air-cooled
- VARIAIR frequency inverter



VARIAR SV 300

VASF 2.80²⁾

	PSIG in. H ₂ O	CFM ¹⁾												CFM ¹⁾		
		0	0.725	1.45	2.175	2.9	3.625	4.35	5.075	5.8	6.525	7.25	7.975	@ max.	in. H ₂ O	
Single stage																
VARIAIR SV 130/1	100 Hz	168	156	145	133	122	111	100	89	61					56	162.8
VARIAIR SV 201/1	100 Hz	206	197	185	172	161	131	81						24	136.7	
VARIAIR SV 300/1	87 Hz	329	304	287	247	196	74							45	102.5	
VARIAIR SV 300/1	100 Hz	376	361	344	328	312	231	151	87					70	142.7	
VARIAIR SV 400/1	100 Hz	509	481	462	442	423	377	307	210					126	152.8	
VARIAIR SV 500/1	100 Hz	588	579	562	544	525	505	485	465	446	399	354		302	213.1	
VARIAIR SV 700/1	80 Hz	694	663	633	605	575	545	512	430	261				230	164.8	
VASF 2.50/1	300 Hz	28	25	24	22	21	19							0.1	116.9 AC 112.6 DC	
VASF 2.80/1	250 Hz	53	47	44	42	39	35							0.1	112.6 AC 116.6 DC	
VASF 2.120/1	200 Hz	84	73	69	66	55								0.1	92.5 AC	
Double stage																
VARIAIR SV 130/2	100 Hz	82	78	74	70	66	63	59	56	54	50	48	45	45	221.1	
VARIAIR SV 201/2	100 Hz	103	99	96	93	89	86	84	81	76	68	59	48	44	225.1	
VARIAIR SV 300/2	100 Hz	188	183	178	172	166	161	156	150	141	121	101	81	72	229.1	
VASF 2.50/2	300 Hz	14	13	12	11	11	10	10	9	9	9	8	2	0.1	225.1 AC	
VASF 2.80/2	250 Hz	26	24	22	21	20	19	18	18	17	16	10	3	0.1	229.1 AC 229.1 DC	
VASF 2.120/2	200 Hz	42	38	35	34	32	31	30	29	27	6			0.1	184.9 AC	

Technical data							
	Frequency inverter	db(A)	lbs	Inch			Connection
				Length	Width	Height	
VARIAIR SV 130/X	5.4 hp • 400/480 V ±10% • 50/60 Hz	71.0	67.3	16.7	10.4	15.0	1 ½"
VARIAIR SV 201/X	5.4 hp • 400/480 V ±10% • 50/60 Hz	77.7	70.6	16.9	12.1	16.0	2"
VARIAIR SV 300/1 87 Hz	5.4 hp • 400/480 V ±10% • 50/60 Hz	69.6	101.4	19.4	14.6	18.0	2 ½"
VARIAIR SV 300/X 100 Hz	10.1 hp • 400/480 V ±10% • 50/60 Hz	77.7	109.1	20.2	14.6	19.7	2 ½"
VARIAIR SV 400/1	14.8–29.5 hp • 400/480 V ±10% • 50/60 Hz	77.8	165.4	22.5	15.4	23.2	3"
VARIAIR SV 500/1	14.8–29.5 hp • 400/480 V ±10% • 50/60 Hz	80.9	215.0	23.6	18.7	24.5	3"
VARIAIR SV 700/1	14.8–29.5 hp • 400/480 V ±10% • 50/60 Hz	75.1	264.6	24.9	19.5	14.9	4"
VASF 2.50/X	0.87 hp • AC~ • 200 V -10% ... 230 V +10% • 50/60 Hz	61.0	27.1	13.9	6.9	10.1	1"
	0.80 hp • AC~ • 100 V -10% ... 115 V +10% • 50/60 Hz	61.0	27.1	13.9	6.9	10.1	1"
	1.0 hp • DC~ • 24 V ±20%	65.0	25.4	13.9	6.8	9.2	1"
VASF 2.80/X	1.48 hp • AC~ • 200 V -10% ... 230 V +10% • 50/60 Hz	61.0	33.1	15.4	6.9	11.5	1 ¼"
	1.48 hp • DC~ • 48 V ±20%	65.0	32.4	15.4	6.8	10.6	1 ¼"
VASF 2.120/X	1.88 hp • AC~ • 200 V -10% ... 230 V +10% • 50/60 Hz	63.0	41.5	17.0	7.9	12.6	1 ½"

¹⁾ Reference (atmosphere): 0 PSIG, 68°F / tolerance: ±10%

²⁾ Optionally with integrated VARIAIR frequency inverter, fan and silencers

VARIAIR RV • VATP

RADIAL BLOWERS


- Non-contact compression
- Air-cooled
- VARIAIR RV with external VARIAIR frequency inverter
- VATP (VARIAIR Turbo Package) consisting of RV 2.1944/10, VARIAIR frequency inverter, intake filter and sound enclosure



RV 2.1944/10



VATP 1600



		CFM ¹⁾									
		0	0.725	1.45	2.175	2.9	3.625	4.35	5.075	5.8	5.945
		in. H ₂ O	20.1	40.2	60.3	80.4	100.5	120.6	140.7	160.8	164.8
RV 2.1944/10	400 Hz	923	923	865	790	717	643	569	496	339	268
VATP 1600	400 Hz	923	923	865	790	717	643	511	496	339	268

Technical data								
Frequency inverter		db(A)	lbs	Length	Inch Width	Height	Connection	
RV 2.1944/10	14.8–29.5 hp ²⁾ • 400/480 V ±10% • 50/60 Hz	75	178.6	21.7 ³⁾	17.7 ³⁾	20.5 ³⁾	Ø 5.91 Inch	
VATP 1600	14.8–29.5 hp • 400/480 V ±10% • 50/60 Hz	64	357.2	32.1	22.6	44.7	⁴⁾	

¹⁾ Reference (atmosphere): 0 PSIG, 68°F / tolerance: ±5%

²⁾ Alternatively available as 10.1 hp version (see pump data sheet)

³⁾ Without frequency inverter

⁴⁾ Flange for hose connector

T • DVT

ROTARY VANE PRESSURE/VACUUM PUMPS

- Oil-free
- Air-cooled
- Integrated suction filter
- Pressure and vacuum regulating valve



T 4.40 DSK



DVT 3.80



		CFM – Suction Blast air rate ¹⁾					
		50 Hz			60 Hz		
		0 in. Hg	-7.4 in. Hg	-14.8 in. Hg	0 in. Hg	-7.4 in. Hg	-14.8 in. Hg
T 4.10 DV	3.63 PSIG	5.6 5.6	4.2 4.2	2.4 2.4	6.9 6.9	4.8 4.8	2.9 4.9
	7.25 PSIG	5.5 5.5	3.8 3.8	2.1 2.1	6.5 6.5	4.1 4.1	2.6 4.5
T 4.16 DV	3.63 PSIG	9.1 9.1	6.5 6.5	3.8 3.8	10.6 10.6	7.8 7.8	4.7 8.0
	7.25 PSIG	8.8 8.8	5.9 5.9	3.5 3.5	10.5 10.5	7.2 7.2	4.3 7.3
T 4.25 DV	3.63 PSIG	13.9 13.9	9.7 9.7	5.4 5.4	16.6 16.6	11.8 11.8	6.7 11.4
	7.25 PSIG	13.0 13.0	8.8 8.8	4.6 4.6	15.8 15.8	10.8 10.8	6.0 10.2
T 4.40 DV	3.63 PSIG	21.1 21.1	15.2 15.2	8.8 8.8	25.0 25.0	17.9 17.9	9.7 16.5
	7.25 PSIG	20.1 20.1	14.1 14.1	7.9 7.9	24.2 24.2	17.2 17.2	7.9 13.5
		50 Hz	60 Hz				
		0 in. Hg	-14.8 in. Hg	-17.7 in. Hg	0 in. Hg	-14.8 in. Hg	-17.7 in. Hg
T 4.25 DSK	7.25 PSIG	13.8 14.6	5.8 10.7	4.2 9.9	16.8 18.1	7.2 12.6	5.4 11.5
	8.70 PSIG	13.5 14.4	5.7 10.5	4.1 9.7	16.6 17.9	7.2 12.5	5.3 11.4
T 4.40 DSK	7.25 PSIG	20.3 19.9	7.9 13.6	5.8 11.8	24.8 24.6	10.0 16.0	7.5 14.0
	8.70 PSIG	20.1 19.6	7.8 13.4	5.7 11.3	24.2 24.2	9.6 15.6	7.1 13.5
DVT 3.60	7.25 PSIG	32.5 33.5	13.1 22.0	9.5 19.3	38.2 40.2	15.9 25.6	12.4 22.8
	8.70 PSIG	32.1 33.1	12.9 21.8	9.2 19.1	37.5 39.5	16.0 25.5	12.1 22.4
DVT 3.80	7.25 PSIG	37.6 38.8	14.7 27.7	10.6 25.3	45.0 47.9	18.8 33.4	13.8 29.8
	8.70 PSIG	37.1 38.1	14.5 27.5	10.3 24.9	44.7 47.4	18.6 32.9	13.8 29.5
DVT 3.100	7.25 PSIG	56.2 57.6	23.6 39.3	17.5 34.6	66.9 70.0	29.4 46.0	22.1 39.9
	8.70 PSIG	56.5 57.9	23.5 39.2	17.6 34.6	66.3 69.3	29.0 45.7	22.1 39.9
DVT 3.140	7.25 PSIG	74.1 81.2	32.3 53.5	24.1 47.1	87.6 95.9	39.1 61.2	29.4 53.5
	8.70 PSIG	74.1 81.2	30.0 52.3	22.3 45.9	87.0 95.3	38.8 60.6	29.4 52.9


Technical data													
	max. PSIG		hp 3~		hp 1~		db(A)		lbs	Length	Inch		Connection
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz			Width	Height	
T 4.10 DV	7.25	7.25	0.5	0.6	0.5	0.6	55	58	35.3	16.9	8.2	7.6	½"
T 4.16 DV	7.25	7.25	0.7	0.9	0.7	0.9	61	63	52.9	17.8	9.1	8.3	½"
T 4.25 DV	7.25	7.25	1.0	1.2	1.1	1.5	69	69	57.3	19.9	10.2	11.4	¾"
T 4.40 DV	7.25	7.25	1.7	2.0			66	68	84.9	22.5	11.0	11.4	¾"
T 4.25 DSK	8.70	8.70	1.5	1.7	1.5		69	69	77.2	21.5	12.9	11.4	¾"
T 4.40 DSK	8.70	8.70	2.5	3.0			68	68	101.4	24.6	12.9	11.4	¾"
DVT 3.60	7.25/8.70	7.25/8.70	3.0/4.0	3.5/4.8			≤75	≤76	185.2	≤29.4	13.9	12.9	1"
DVT 3.80	7.25/8.70	7.25/8.70	5.4/5.4	6.4/6.4			≤76	≤77	250.3	≤34.0	13.9	12.9	1"
DVT 3.100	7.25/8.70	7.25/8.70	7.4/7.4	8.9/8.9			≤77	≤78	296.6	≤37.5	18.5	13.2	1 ½"
DVT 3.140	7.25/8.70	7.25/8.70	10.1/10.1	12.1/12.1			≤78	≤79	321.9	≤37.5	18.5	13.2	1 ½"

¹⁾ Reference (atmosphere): 0 PSIG, 68°F / tolerance: ±5%

PS

ROOTS BOOSTER PACKAGES (PUMPING STATIONS)

- Consisting of an oil-lubricated rotary vane vacuum pump and a booster pump (roots) with integrated bypass as a backup for packaging processes with quick cycling times for high operational reliability and availability



PS 200/500

	Nominal air flow refers to intake pressure ¹⁾		Vacuum	
	CFM		Torr	
	50 Hz	60 Hz	50 Hz	60 Hz
PS 200/500	294	353	< 0.075	< 0.075
PS 300/500	294	353	< 0.075	< 0.075
PS 300/1000	588	706	< 0.075	< 0.075
PS 630/2000	1176	1412	< 0.075	< 0.075

	Technical data										
	RBP	hp 3~		U 5.	hp 3~		lbs total	Inch Length	Inch Width	Inch Height	Connection
		50 Hz	60 Hz		50 Hz	60 Hz					
PS 200/500	RBP 500	3.0	3.5	U 5.200	5.4	6.4	≈728	37.7	27.7	42.9	DN100
PS 300/500	RBP 500	3.0	3.5	U 5.300	7.4	8.9	≈838	40.3	27.7	42.9	DN100
PS 300/1000	RBP 1000	5.4	6.4	U 5.300	7.4	8.9	≈1058	44.7	27.7	44.2	DN100
PS 630/2000	RBP 2000	7.4	8.9	U 4.630	20.1	24.8	≈2426	60.6	34.5	59.0	DN150

¹⁾ Reference (atmosphere): 750 Torr, 68°F / tolerance: ±5%

D1 • D2 • D3 • L1 • L2 • L3

VACUUM SYSTEMS

- 1, 2 or 3 rotary vane vacuum pumps
- Dry-running (D) or oil-lubricated (L)
- D1, D2, L1 and L2 with electrical cabinet 33D
- D3 and L3 with electric cabinet VARIAIR Controller+ (VC+)
- Vacuum vessel, condensate drain and suction filter




D2-250/1000-33D



Systems with dry-running rotary vane vacuum pumps							Technical data per pump 50/60 Hz		
	Pumps	Vessel [US gal]	Filter	Length [Inch]	Width [Inch]	Height [Inch]	CFM	in. Hg V	hp
One pump on vacuum vessel									
D1-016/0090-33D	1x VT 4.16	23.7	F 35	45.3	26.8	41.3	9.4/11.2	25.4/24.4	0.7/0.9
D1-016X/0090-33D	1x VX 4.16	23.7	F 35	45.3	26.8	41.3	9.4/11.2	27/27	0.7/0.9
D1-025/0090-33D	1x VT 4.25	23.7	F 35	45.3	26.5	41.3	14.7/17.6	25.4/24.4	1.0/1.2
D1-025X/0090-33D	1x VX 4.25	23.7	F 35	45.3	26.5	41.3	14.7/17.6	27/27	1.0/1.2
D1-040/0090-33D	1x VT 4.40	23.7	F 35	45.3	26.5	41.3	23.5/28.2	25.4/24.4	1.7/2.0
D1-040X/0090-33D	1x VX 4.40	23.7	F 35	45.3	26.5	41.3	23.5/28.2	27/27	1.7/2.0
D1-060/0250-33D	1x KVT 3.60	66.0	F 110	71.9	34.5	48.9	32/39	27/27	3.0/3.5
D1-060X/0250-33D	1x K VX 3.60	66.0	F 110	71.9	34.5	48.9	32/39	27/27	3.0/3.5
D1-080/0250-33D	1x KVT 3.80	66.0	F 110	71.9	34.5	48.9	39/46	27/27	3.0/3.5
D1-080X/0250-33D	1x K VX 3.80	66.0	F 110	71.9	34.5	48.9	39/46	27/27	3.0/3.5
D1-100/0250-33D	1x KVT 3.100	66.0	F 110	71.9	34.2	48.9	58/66	27/27	4.0/4.8
D1-100X/0250-33D	1x K VX 3.100	66.0	F 110	71.9	34.2	48.9	58/66	27/27	4.0/4.8
D1-140/0250-33D	1x KVT 3.140	66.0	F 110	72.7	34.5	49.1	76/91	27/24	5.4/6.4
D1-140X/0250-33D	1x K VX 3.140	66.0	F 110	72.7	34.5	49.1	76/91	27/24	5.4/6.4
D1-250/0500-33D	1x VTLF 2.250	132.0	F 110	78.6	39.6	55.8	144/168	24/24	7.4/8.9
D1-250X/0500-33D	1x VXL F 2.250	132.0	F 110	78.6	39.6	55.8	144/168	24/24	7.4/8.9
Two pumps on vacuum vessel									
D2-016/0090-33D	2x VT 4.16	23.7	F 35	42.4	29.7	41.3	9.4/11.2	25.4/24.4	0.7/0.9
D2-016X/0090-33D	2x VX 4.16	23.7	F 35	42.4	29.7	41.3	9.4/11.2	27/27	0.7/0.9
D2-025/0090-33D	2x VT 4.25	23.7	F 35	42.4	29.7	41.3	14.7/17.6	25.4/24.4	1.0/1.2
D2-025X/0090-33D	2x VX 4.25	23.7	F 35	42.4	29.7	41.3	14.7/17.6	27/27	1.0/1.2
D2-040/0250-33D	2x VT 4.40	66.0	F 110	71.9	34.3	48.9	23.5/28.2	25.4/24.4	1.7/2.0
D2-040X/0250-33D	2x VX 4.40	66.0	F 110	71.9	34.3	48.9	23.5/28.2	27/27	1.7/2.0
D2-060/0250-33D	2x KVT 3.60	66.0	F 110	71.9	39.2	48.9	32/39	27/27	3.0/3.5
D2-060X/0250-33D	2x K VX 3.60	66.0	F 110	71.9	39.2	48.9	32/39	27/27	3.0/3.5
D2-080/0500-33D	2x KVT 3.80	132.0	F 110	78.6	38.3	51.8	39/46	27/27	3.0/3.5
D2-080X/0500-33D	2x K VX 3.80	132.0	F 110	78.6	38.3	51.8	39/46	27/27	3.0/3.5
D2-100/0500-33D	2x KVT 3.100	132.0	F 110	78.6	43.1	51.8	58/66	27/27	4.0/4.8
D2-100X/0500-33D	2x K VX 3.100	132.0	F 110	78.6	43.1	51.8	58/66	27/27	4.0/4.8
D2-140/0500-33D	2x KVT 3.140	132.0	F 110	78.6	43.1	51.8	76/91	27/24	5.4/6.4
D2-140X/0500-33D	2x K VX 3.140	132.0	F 110	78.6	43.1	51.8	76/91	27/24	5.4/6.4
D2-250/0750-33D	2x VTLF 2.250	198.0	FV 250	86.7	55.5	67.6	144/168	24/24	7.4/8.9
D2-250X/0750-33D	2x VXL F 2.250	198.0	FV 250	86.7	55.5	67.6	144/168	24/24	7.4/8.9
D2-250/1000-33D	2x VTLF 2.250	264.0	FV 250	91.8	56.5	69.9	144/168	24/24	7.4/8.9
D2-250X/1000-33D	2x VXL F 2.250	264.0	FV 250	91.8	56.5	69.9	144/168	24/24	7.4/8.9
Three pumps on vacuum vessel									
D3-025/0250-VC+	3x VT 4.25	66.0	F 110	74.7	35.6	59.2	14.7/17.6	25.4/24.4	1.0/1.2
D3-025X/0250-VC+	3x VX 4.25	66.0	F 110	74.7	35.6	59.2	14.7/17.6	27/27	1.0/1.2
D3-040/0250-VC+	3x VT 4.40	66.0	F 110	73.7	35.6	59.2	23.5/28.2	25.4/24.4	1.7/2.0
D3-040X/0250-VC+	3x VX 4.40	66.0	F 110	73.7	35.6	59.2	23.5/28.2	27/27	1.7/2.0
D3-060/0500-VC+	3x KVT 3.60	132.0	F 110	88.7	41.1	62.2	32/39	27/27	3.0/3.5
D3-060X/0500-VC+	3x K VX 3.60	132.0	F 110	88.7	41.1	62.2	32/39	27/27	3.0/3.5
D3-080/0500-VC+	3x KVT 3.80	132.0	F 110	88.7	41.1	62.2	39/46	27/27	3.0/3.5
D3-080X/0500-VC+	3x K VX 3.80	132.0	F 110	88.7	41.1	62.2	39/46	27/27	3.0/3.5



L1-5.200/0500-33D



L3-5.100/0750-VC+

Systems with dry-running rotary vane vacuum pumps							Technical data per pump 50/60 Hz		
	Pumps	Vessel [US gal]	Filter	Length [Inch]	Width [Inch]	Height [Inch]	CFM	in. Hg V	hp
Three pumps on vacuum vessel									
D3-100/0750-VC+	3x KVT 3.100	198.0	FV 250	95.9	47.7	66.2	58/66	27/27	4.0/4.8
D3-100X/0750-VC+	3x K VX 3.100	198.0	FV 250	95.9	47.7	66.2	58/66	27/27	4.0/4.8
D3-140/0750-VC+	3x KVT 3.140	198.0	FV 250	94.9	47.7	66.2	76/91	27/24	5.4/6.4
D3-140X/0750-VC+	3x K VX 3.140	198.0	FV 250	94.9	47.7	66.2	76/91	27/24	5.4/6.4

Systems with oil-lubricated rotary vane vacuum pumps							Technical data per pump 50/60 Hz		
	Pumps	Vessel [US gal]	Filter	Length [Inch]	Width [Inch]	Height [Inch]	CFM	Torr	hp
One pump on vacuum vessel									
L1-020/0090-33D	1x U 4.20	23.7	F 35	45.3	27.8	41.4	11/12	<0.75/<1.125	0.74/0.89
L1-040/0090-33D	1x U 4.40	23.7	F 35	45.3	27.8	41.4	24/28	0.375/0.375	2.0/2.4
L1-5.70/0250-33D	1x U 5.70	66.0	F 110	72.7	34.5	49.1	41/49	<0.075-300	2.0/2.4
L1-5.100/0250-33D	1x U 5.100	66.0	F 110	71.9	34.2	49.1	59/71	<0.075-300	3.0/3.5
L1-5.165/0250-33D	1x U 5.165	66.0	F 110	71.9	34.5	49.1	97/116	<0.075-300	5.4/6.4
L1-5.200/0500-33D	1x U 5.200	132.0	F 110	79.4	38.1	55.8	118/141	<0.075-300	7.4/8.9
L1-5.300/0750-33D	1x U 5.300	198.0	FV 250	86.6	44.6	60.4	176/212	<0.075-300	10.1/12.1
Two pumps on vacuum vessel									
L2-020/0090-33D	2x U 4.20	23.7	F 35	45.3	27.9	41.3	11/12	<0.75/<1.125	0.55/0.66
L2-040/0250-33D	2x U 4.40	66.0	F 110	71.9	34.2	48.9	24/28	0.375/0.375	2.0/2.4
L2-5.70/0250-33D	2x U 5.70	66.0	F 110	71.9	34.2	48.9	41/49	<0.075-300	2.0/2.4
L2-5.100/0250-33D	2x U 5.100	66.0	F 110	71.9	34.3	48.9	59/71	<0.075-300	3.0/3.5
L2-5.70/0500-33D	2x U 5.70	132.0	F 110	71.9	38.2	51.8	41/49	<0.075-300	2.0/2.4
L2-5.100/0500-33D	2x U 5.100	132.0	F 110	71.9	38.2	51.8	59/71	<0.075-300	3.0/3.5
L2-5.165/0750-33D	2x U 5.165	198.0	FV 250	86.7	44.6	60.4	97/116	<0.075-300	5.4/6.4
L2-5.200/0750-33D	2x U 5.200	198.0	FV 250	86.7	44.6	66.7	118/141	<0.075-300	7.4/8.9
L2-5.300/0750-33D	2x U 5.300	198.0	FV 250	86.7	59.6	66.7	176/218	<0.075-300	10.1/12.1
L2-5.165/1000-33D	2x U 5.165	264.0	FV 250	92.0	45.5	59.7	97/116	<0.075-300	5.4/6.4
L2-5.200/1000-33D	2x U 5.200	264.0	FV 250	92.0	45.5	69.9	118/141	<0.075-300	7.4/8.9
L2-5.300/1000-33D	2x U 5.300	264.0	FV 250	92.0	60.6	69.9	176/218	<0.075-300	10.1/12.1
Three pumps on vacuum vessel									
L3-020/0250-VC+	3x U 4.20	66.0	F 110	73.7	35.5	59.2	11/12	<0.75/<1.125	0.55/0.66
L3-040/0250-VC+	3x U 4.40	66.0	F 110	73.7	35.5	59.2	24/28	0.375/0.375	2.0/2.4
L3-5.70/0500-VC+	3x U 5.70	132.0	F 110	80.4	38.5	62.1	41/49	<0.075-300	2.0/2.4
L3-5.100/0500-VC+	3x U 5.100	132.0	F 110	80.4	38.5	62.1	59/71	<0.075-300	3.0/3.5
L3-5.70/0750-VC+	3x U 5.70	198.0	FV 250	88.5	44.4	66.7	41/49	<0.075-300	2.0/2.4
L3-5.100/0750-VC+	3x U 5.100	198.0	FV 250	87.6	44.4	66.7	59/71	<0.075-300	3.0/3.5
L3-5.165/1000-VC+	3x U 5.165	264.0	FV 250	99.5	45.5	63.8	97/116	<0.075-300	5.4/6.4
L3-5.200/1000-VC+	3x U 5.200	264.0	FV 250	94.8	45.4	79.4	118/141	<0.075-300	7.4/8.9
L3-5.300/1000-VC+	3x U 5.300	264.0	FV 250	95.0	60.3	79.4	176/218	<0.075-300	10.1/12.1
L3-5.165/1500-VC+	3x U 5.165	396.0	FV 540	109.6	44.1	81.2	97/116	<0.075-300	5.4/6.4
L3-5.200/1500-VC+	3x U 5.200	396.0	FV 540	109.6	44.2	90.6	118/141	<0.075-300	7.4/8.9
L3-5.300/1500-VC+	3x U 5.300	396.0	FV 540	109.6	59.3	90.6	176/212	<0.075-300	10.1/12.1

ALBANIA

Šraml Kompresorji d.o.o.
Slovenia

ALGERIA

Becker France S.à.r.l.
France

ARGENTINA

CompVac
Sistemas de Aire Comprimido y Vacío
Bonifacini 4760
B1678CZH - Caseros
Buenos Aires
T +5411 4734-5980
F +5411 4734-5980
M +54911 3589-5050
guillermo.quintin@compvac.com.ar
www.compvac.com.ar

AUSTRALIA

Early Minute Pty Ltd.
Unit 3, 33 Meakin Road
Meadowbrook QLD 4131
T +61 7 3386 0981
F +61 7 3386 0983
sales@beckerpumps.com.au
www.beckerpumps.com.au

AUSTRIA

Korzinek & Weisse GmbH & Co. KG
Schallergasse 11
1120 Wien
T +43 1 8138213
F +43 1 8138300
office@korzinek-weisse.at
www.korzinek-weisse.at

BANGLADESH

Upbringing Technologies PVT. Ltd.
India

BELARUS

Becker Polska Sp. z o. o.
Poland

BELGIUM

Becker
Druk- en Vacuümpompen B.V.
Netherlands

BOSNIA-HERZEGOVINA

Šraml Kompresorji d.o.o.
Slovenia

BRAZIL

Robmaq Comércio de Máquinas e Equipamentos LTDA. EPP.
Rua Paraiba, 2622 - Sala 02
80630-000 Curitiba-PR
T +55 41 33332279
F +55 41 33323460
robmaq@robmaq.com.br
www.robmaq.com.br

BRUNEI

Becker Asia Pacific PTE Ltd.
Singapore

BULGARIA

RST Ltd.
Filipovtsi, 39 Zemedelska Str.
1390 Sofia
T +359 2 824 0121
F +359 2 826 3183
office@rst-bg.com
www.rst-bg.com

CAMBODIA

Becker Asia Pacific PTE Ltd.
Singapore

CARIBBEAN ISLANDS

Soluciones Tecnicas Industriales STIAmerica
Colombia

CANADA

Becker Pumps Corporation
sidharth.sood@beckerpumps.com
www.beckerpumps.ca
USA

CHILE

W&F Ingeniería y Maquinas S.A.
Félix de Amesti 90, Piso 6
Las Condes
Santiago de Chile
T +56 2 206 29 43
F +56 2 206 30 39
info@wyf.cl
www.wyf.cl

CHINA

Becker Vacuum & Air Equipment (Shanghai) Co. Ltd.
Room 737, Sanlian Building
Huajing Road, Waigaoqiao
FTZ 8
Pudong, Shanghai 200131
T +86 021 59867988
F +86 021 33250530
info@becker-china.com
www.becker-china.com

COLOMBIA

Soluciones Tecnicas Industriales STIAmerica
Carrera 14A #71A59
Torre A Of: 601-501 Bogota
T +571 5205927
M +57 3102401208
info@sti-america.com
stiamerica@gmail.com
www.sti-america.com

CROATIA

Šraml Kompresorji d.o.o.
Slovenia

CYPRUS

Lindiridis Emm. Ltd.
Greece

CZECH REPUBLIC

YNNA spol. s.r.o.
Na Zvolenci 64
690 03 Břeclav
T +42 519 322 981
F +42 519 322 173
info@ynna.cz
www.ynna.cz

DENMARK

Becker Danmark A/S
Lunavej 1
8700 Horsens
T +45 7626 0233
F +45 7626 0234
becker@becker-danmark.dk
www.becker-danmark.dk

ECUADOR

Soluciones Tecnicas Industriales STIAmerica
Colombia

EGYPT

Ashtechs – Antoine Ashba & Co.
Borg-Al-Arab-El Guedida,
2nd industrial zone, Block 16, #5
Alexandria
T +203 4626149 - 4626208
info@ashtechs.com
www.ashtechs.com

ESTONIA

Becker Polska Sp. z o. o.
Poland

FINLAND

Graafinen Kunnossapito Grönkvist & Co
Ristikiventie 8 Halli 14
04300 Tuusula
T +358 9 2224004
F +358 9 22430080
graafinen.kunnossapito@co.inet.fi
www.pumputhelsinki.fi

FRANCE

Becker France S.à.r.l.
Rue de Cutesson, Z.A. du
Bel-Air, Gazeran - B.P. 55
78512 Rambouillet Cedex
T +33 1 30418989
F +33 1 30410600
becker@becker-france.fr
www.becker-france.fr

GERMANY

HEADQUARTERS, INTERNATIONAL SALES & SERVICE, MANUFACTURING Gebr. Becker GmbH
Hölker Feld 29-31
42279 Wuppertal
T +49 202 697 0
F +49 202 660855
info@becker-international.com
www.becker-international.com

FORUM GENNEBRECK

Gebr. Becker GmbH
Gennebrecker Str. 8
42279 Wuppertal

MANUFACTURING

Gebr. Becker GmbH
Über dem Dieterstedter Bache 4
99510 Apolda
T +49 3644 543 0

GREAT BRITAIN

Becker UK Ltd.
Link 63
Liverpool Street
Hull HU3 4XS
T +44 1482 835280
F +44 1482 831275
sales@becker.co.uk
www.becker.co.uk

GREECE

Lindiridis Emm. Ltd.
Pneumatic Systems
11A, Kotzia Street
16346 Ilioupolis/Athens
T +30 210 9917800 / 9934091
F +30 210 9956791
info@lindiridis.gr
www.lindiridis.gr

HONG KONG

Becker Vacuum & Air Equipment (Shanghai) Co. Ltd.
China

HUNGARY

Protech Fejlesztő Kft
Pongrác u. 15.
1101 Budapest
T +36 1 460 0580
F +36 1 460 0581
office@protech.hu
www.protech.hu

INDIA

Upbringing Technologies PVT. Ltd.
502, Lane no 5, A J Paramount,
Dahanukar Colony, Kothrud,
Pune MH IN 411038
T +91 20 20251336
F +91 20 20251336
beckerupb@gmail.com
www.upbringingindia.com

INDONESIA

Becker Asia Pacific PTE Ltd.
Singapore

ISRAEL

Polak Bros. Ltd.
9 Hamefalsim Street
Kiryat Arie, Petach-Tikva 49514
T +972 3 9100333
F +972 57 7945221
polak@polak.co.il
www.polak.co.il

ITALY

Becker Italia S.r.l.
Via Bargello, 24
40055 Villanova (Bo)
T +39 051 6063811
F +39 051 6053168
becker@becker.it
www.becker.it

JAPAN

Becker Air Techno Co. Ltd.
Mita 3 Cyome MT-Bldg. 6F
3-14-10, Mita, Minato-ku,
Tokyo, 108-0073
T +81 3 5418 5131
F +81 3 5418 3750
info@becker-japan.co.jp
www.becker-japan.co.jp

JORDAN

Global Industrial Solutions L.L.C.
PO Box 144407
Amman 11814
T +962 (6) 5831900
md@gisjo.com
www.gisjo.com

KOREA

Becker Korea Co., Ltd.
Room 420-425, A dong, Samsung
Techno Valley, 140 Tongil-ro
Deogyang-gu, Goyang city, Gyeong-
gi-do, 412-090
T +82 2 2219-4500
F +82 2 2219-4501
becker@beckerkorea.co.kr
www.beckerkorea.co.kr

LAOS

Becker Asia Pacific PTE Ltd.
Singapore

LATVIA & LITHUANIA

Becker Polska Sp. z o. o.
Poland

LUXEMBOURG

Becker
Druk- en Vacuümpompen B.V.
Netherlands

MACEDONIA

Šraml Kompressorji d.o.o.
Slovenia

MALAYSIA

Becker Asia Pacific PTE Ltd.
Singapore

MAROCRO

Becker France S.à.r.l.
France

MEXICO**Heinser Artes Graficas**

Retorno 406-A No. 18,
Unidad Modelo
09090 Mexico, D.F.
T +52 55 55829192
F +52 55 55827653
heinser@att.net.mx

MEXICO**BRB**

Rafael Najera # 2229 Ote
64550 Monterrey, N.L.
T + 52 81 4739.0115
F + 52 81 8355.6808
Ramos Arizpe, Coah
T +52 844 490.2501
F +52 844 413.0431
Reynosa, Tamp
T +52 899 202.1348
F +52 899 925.1449
ventas@brbdelnorte.com.mx
www.beckerpumps.mx
Office USA:
T +1 214 340 6770
sales@brb-usa.com

MONTENEGRO

Šraml Kompressorji d.o.o.
Slovenia

MYANMAR

Becker Asia Pacific PTE Ltd.
Singapore

NETHERLANDS

Becker Druk- en
Vacuümpompen B.V.
Eurolaan 11
8447 SM Heerenveen
T +31 513 651800
info@beckerdvp.nl
www.beckerdvp.nl

NEW ZEALAND

Early Minute Pty Ltd.
Australia

NORWAY

Becker Vakuumtechnik AB
Sweden

OMAN

Fluidtec Equipment L.L.C
United Arab Emirates

PAKISTAN

Fluidtec Equipment L.L.C
United Arab Emirates

PARAGUAY

CompVac
Argentina

PHILIPPINES

Becker Asia Pacific PTE Ltd.
Singapore

POLAND

Becker Polska Sp. z o. o.
Pianowo 46
64-000 Kościan
T +48 065 5114170
F +48 065 5110828
info@becker-polska.com
www.becker-polska.com

PORTUGAL**EMZ**

Sociedade de Representações, Assis-
tência e Reparações de
Equipamentos de Vácuo e
Eletrotecnia, Lda.
Rua de São Sebastião da
Pedreira 110, 3º Andar
1050-209 Lissabon
T +351 213 140 887
F +351 212 698 530
zickermann@zickermann.pt

QATAR

Fluidtec Equipment L.L.C
United Arab Emirates

ROMANIA**Robital Industrial Supplier SRL**

189 Biruinței Bulevardul
Pantelimon 077145
T +40 21 315 93 29
F +40 21 315 93 31
info@robital.ro
www.robital.ro

RUSSIA**SPC „ZME“ LLC**

Plekhanova 4A
111123 Moscow
T +7 495 221 65 55
F +7 495 221 65 55
sales@becker-russia.ru
www.becker-russia.ru

RUSSIA**SibWest LLC**

Uzhnoportovaya, 7/7 - 309
115088 Moscow
T +7 495 647-49-05
info@becker-pump.ru
www.becker-pump.ru

SAUDI ARABIA**Masader Multi Ltd. Co.**

Building No . 7903
Al Manar District
Qis bin Zuhair street
Jeddah 23462
T +966 2 689 7909
F +966 2 689 8278
info@masadermulti.com
www.masadermulti.com

SERBIA

Šraml Kompressorji d.o.o.
Slovenia

SINGAPORE

Becker Asia Pacific PTE Ltd.
12 Little Road #01-01
Lian Cheong Industrial Building
Singapore 536986
T +65 6487 5951
F +65 6487 5952
info@beckerasia.com.sg
www.beckerasia.com.sg

SLOVAK REPUBLIC**ABRO s.r.o.**

Laskomerského 16
831 03 Bratislava
T +421 2 43427443
F +421 2 43638036
abro@abro.sk
www.abro.sk

SLOVENIA**Šraml Kompressorji d.o.o.**

Dolga Poljana 1h
5271 Vipava
T +386 4 177 1416
F +386 5 368 0214
sraml.bozo@siol.net
www.sraml-kompressorji.si

SOUTH AFRICA**Airflit (Pty.) Ltd.**

21, Orion Street
P.O. Box 979
Germiston 1401
T +27 11 8735555
F +27 11 8731355
berndf@masskotscale.com

SPAIN**Becker Iberica de Bombas de****Vacio y Compresores S.A.**

Calle Masia Nova 3-5, Nave E
P.I. Santa Magdalena
08800 Vilanova i la Geltrú
T +34 93 816 51 53
F +34 93 816 58 74
comercial@becker-iberica.com
www.becker-iberica.com
Servicio técnico oficial Madrid:
T +34 91 662 35 23
F +34 91 661 19 61

SRI LANKA**Upbringing Technologies PVT. Ltd.**

India

SWEDEN**Becker Vakuumtechnik AB**

Söderförsölgatan 33
75228 Uppsala
T +46 18 565200
F +46 18 565209
kundservice@beckervakuum.se
www.beckervakuum.se
Höganäs:
Verkstadsgatan 12 F
26339 Höganäs
T +46 18 565200

SWITZERLAND**Becker AG**

Ringstr. 20
8600 Dübendorf
T +41 44 824 18 18
F +41 44 824 18 19
becker@becker.ch
www.becker.ch

TAIWAN

Becker Pumps Taiwan Co. Ltd.
1F, No. 542-15, Zhongzheng Rd.,
Xinzhuang Dist., New Taipei City 242
T +886 2 29040077
F +886 2 29040500
info@beckertaiwan.com
www.beckertaiwan.com

THAILAND

Becker Asia Pacific PTE Ltd.
Singapore

TUNISIA

Becker France S.à.r.l.
France

TURKEY**UES Teknik**

Makina ve Yedek Parça San. Diş Tic.
Ltd. Şti.
Merkez Mah., Engin Sok. No: 13
34310 Avcılar-Istanbul
T +90 212 6954984
F +90 212 5916210
erdal@questeknik.com

UKRAINE**Becker Polska Sp. z o. o.**

Poland

UNITED ARAB EMIRATES**Fluidtec Equipment L.L.C**

Lake Central Tower - Office 1305
Burj Khalifa District
(P.O. Box: 72903)
Dubai
T +971 4 2776366
F +971 4 2776173
info@fluidtec.ae

URUGUAY**CompVac**

Argentina

USA**Becker Pumps Corporation**

100 East Ascot Lane
Cuyahoga Falls
Ohio 44223
T +1 330 928 9966
F +1 330 928 7065
Cust. Service +1 330 916 6858
info@beckerpumps.com
www.beckerpumps.com
www.beckerpumps.ca

VENEZUELA**Soluciones Tecnicas Industriales****STIAmerica**

Colombia

VIETNAM**Becker Asia Pacific PTE Ltd.**

Singapore



MAKE IT BECKER.