

Dynama Finishing Mowers





3 Cutting Widths - 180, 150 & 120 cm

Central Lubrication fitted as standard on all models for quick and effective maintenance

Anti - Scalping Roller fitted as standard to reduce the risk of turf damage when cutting tightly on uneven surfaces.

Aerodynamically Designed Blades made from hardened and tempered spring steel, give good lift and effective cutting.

Rotor Drive is through easily tensioned B - Section vee belts. Slots are provided so that tension can easily by checked without removal of the guards. A gearbox jacking screw enables tension to be applied easily.

A Mulching Kit is available on all models to produce extra chopping and even spreading. The kit comprises additional special mulching blades and housing enclosures to retain the grass until it is finely chopped





The company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice.



Specifications

Model	120	150	180
Cutting Width	1.2m (3'11")	1.5m (4'11")	1.8m (5'11")
Overall Width	1.3m (4'3")	1.6m (5'3")	1.9m (6'3")
Cutting Height	25-100mm	25-100mm	25-100mm
No. of Rotors	3	3	3
Rotor Overlap	11mm	19mm	24mm
Cutting Speed	74m/sec	92m/sec	110m/sec
Weight	183 kg (403 lb)	205 kg (451 lb)	258 kg (568 lb)
Min. Tractor Size	7.5 kW (10hp)	11kW (15hp)	15kW (20hp)