

### Office

1450 N. Wood Dale Wood Dale, IL 60191

630.594.4795

## **Series: Crete Technical Data**

#### 1. PRODUCT NAME



### 2. PRODUCT DESCRIPTION









(Green Choice includes pre-consumer recycled materials and post-consumer recycled materials)

#### certifications:











#### Melted Ice



Aqua



Weathered Black



#### Size/thickness:

12" x 24" x 5/16" nominal Stocked 18" x 36" x 5/16" nominal Special Order

#### Finishes:

Honed

Recommended Grout Joint: 3/32" or greater All sizes modular with 3/16" grout joint (≈5 mm)

Grout joints of 1/8" inch or less, especially with larger format tiles or running bond patterns, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

See ANSI A108.01 2.6.2.2

For patterns with running bond/brick joints patterns a 33% offset recommended.

See ANSI A108.02 section 4.3.8

## **Series: Crete Technical Data**

#### 3. TECHNICAL DATA

Physical Properties	ASTM Test	Industry Standards	Iris US Results
Water Absorption	C373	Impervious <0.5%	≤ 0.1%
Thickness Dimension	C499	Range ±0.04in Max.	≤ ±0.04 in
Facial Dimension	C499	C499 ±0.25%	
Warpage Average	C485	± 0.40% on any edge	≤ ± 0.40%
Warpage Average	C485	± 0.40% on diagonal	≤ ± 0.40%
Wedging Average	C502	± 0.25%	≤ ± 0.25%
Bond Strength	C482	≥ 50 psi	≥ 200 psi
Breaking Strength	C648	≥ 250 lbf	≥ 400 lbf
Hardness (Mohs)	Scratch Test (No regulated)	Range 0 - 10	≥7
Visible Abrasion Resistance for Glaze Tile	C1027	No requirement Range 0 - 5	Class 4
Frost Resistance (Freeze/Thaw)	C1026	No sample must show alterations to surface	No evidence of damage
Chemical Resistance	C650	No Requirement Range E - A	Class A
Stain Resistance	C1378	No Requirement Range E - A	Class A*
Coefficient of Friction (Dynamic)	DCOF Acutest Sm (wet)	≥ 0.42	Honed finish ≥ 0.50 ≤ 0.60  Rigato finish ≥ 0.65 ≤ 0.75
Aesthetic Classification	Visual Evaluation Shade & Texture	No Requirement Range VO – V4	V2

<sup>\*</sup> All values given are for matte or honed material. No values are given for polished material. Iris U.S. does not recommend polished surfaces in area subject to exposure from grease, oil or water.

For level interior spaces to be walked upon when wet (see ANSI A137.1 section 6.2.2.1.10 – Section 9.6 for test procedure).



1450 N. Wood Dale Wood Dale, IL 60191

630.594.4795

#### 4. INSTALLATION

All installation work using Iris US tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCNA Handbook for Ceramic Tile installations.

Installation or setting materials:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; A108.02 – 4.4. and TCNA Details EJ171.

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.

#### WARRANTY

The factory guarantees that its products will be free of manufacturing defects and they will meet or exceed the performance specifications set forth in ANSI 137.1.

#### 6. MAINTENANCE

Care and Maintenance Recommendations
Guide

Please contact your representative

#### 7. TECHNICAL SERVICES

#### **Technical Assistance**

Guide Specifications, literature, MSDS, tile samples, details and installation procedures are all available for your use or libraries.

Please contact your representative for catalogues, physical samples, or architectural binders.

# **Series: Crete Packaging**

#### **COLORS**



Melted Ice



Aqua




Weathered Black

SIZES	Stocked 12"x24" Honed *	Special Order 18"x36" Honed
Melted Ice	IRG1224129	IRG1836129
Aqua	IRG1224128	IRG1836128
Weathered Black	IRG1224131	IRG1836131

Stocked MOSAICS Honed	2"×2" MOSAIC 12"×12"
Melted Ice	IRG12MO129
Aqua	IRG12MO128
Weathered Black	IRG12MO131

	Special Order	Stocked
TRIMS	COVE BASE	BULLNOSE
Honed	6"x12"	3"x24"
Melted Ice	IRG612C129	IRG324BT129
Aqua	IRG612C128	IRG324BT128
Weathered Black	IRG612C131	IRG324BT131

#### PACKAGING INFORMATION









## **Office**

1450 N. Wood Dale Wood Dale, IL 60191

630.594.4795

# **Series: Crete**







