

Series: Nexus Recified Porcelain

Stocked



12 x 24 in / 30 x 60 cm
 Pressed
 Matte 4500-0452-0

Stocked



13 x 13 in / 33 x 33 cm
 Pressed
 Matte 4500-0450-0

Mosaic Stocked



2 x 2 in / 5 x 5 cm
 Mosaic
 Matte 4501-0167-0

Trim Stocked



3 x 12 in / 7.5 x 30 cm
 Bullnose
 Matte 4502-0146-0

Stocked



12 x 24 in / 30 x 60 cm
 Pressed
 Matte 4500-0458-0

Stocked



13 x 13 in / 33 x 33 cm
 Pressed
 Matte 4500-0456-0

Mosaic Stocked



2 x 2 in / 5 x 5 cm
 Mosaic
 Matte 4501-0169-0

Trim Stocked



3 x 12 in / 7.5 x 30 cm
 Bullnose
 Matte 4502-0148-0

Stocked



12 x 24 in / 30 x 60 cm
 Pressed
 Matte 4500-0461-0

Stocked



13 x 13 in / 33 x 33 cm
 Pressed
 Matte 4500-0459-0

Mosaic Stocked



2 x 2 in / 5 x 5 cm
 Mosaic
 Matte 4501-0170-0

Trim Stocked



3 x 12 in / 7.5 x 30 cm
 Bullnose
 Matte 4502-0149-0


Series: Nexus Recified Porcelain

Stocked




12 x 24 in / 30 x 60 cm
Pressed
Matte 4500-0455-0

Stocked



13 x 13 in / 33 x 33 cm
Pressed
Matte 4500-0453-0

Mosaic Stocked



2 x 2 in / 5 x 5 cm
Mosaic
Matte 4501-0168-0

Trim Stocked



3 x 12 in / 7.5 x 30 cm
Bullnose
Matte 4502-0147-0

Usage recommendations

Legacy's recommendations for suitable applications.

*Usage Recommendations**

MATTE GLAZED PORCELAIN

	APPLICATION	WALL	FLOOR
INTERIOR	RESIDENTIAL	•	ID, IW, IW+
	COMMERCIAL	•	ID, IW, IW+
	HEAVY COMMERCIAL	•	
EXTERIOR	RESIDENTIAL / COMMERCIAL	•	

These recommendations are not defined by ANSI/ISO standards.










DCOF Classifications per ANSI A326.3: (ID): Interior, Dry (IW): Interior, Wet (IW+): Interior, Wet Plus (EW): Exterior, Wet (O/G): Oils/Greases

Factors other than the noted DCOF result must also be taken into consideration. Such factors include, but are not limited to, expected contaminants, drainage, surface texture, effect of structure on the DCOF measurement, number of grout joints, traction-enhancing features, and intended use in addition to the other criteria noted in standard ANSI A326.3

Series: Nexus Recified Porcelain

Tile collection performance based on industry standards.

Technical Information

	WATER ABSORPTION	ANSI / ISO - (%)	< 0.5%
	ABRASION RESISTANCE	ANSI / ISO	CLASS 4
	SCRATCH HARDNESS	ANSI / ISO - (Mohs)	7
	BREAKING STRENGTH	ANSI - (Ibf) ISO - (N)	≥450 ≥2000
	SHADE VARIATION		V3
	SLIP RESISTANCE	ANSI - DCOF (WET) ISO - R VALUE	MATTE ≥0.50 (ID, IW, IW+) MATTE R10
	CHEMICAL RESISTANCE	ANSI / ISO	CLASS A
	STAIN RESISTANCE	ANSI ISO	CLASS A CLASS 5
	FROST RESISTANCE	ANSI / ISO	PASS

Test values are based on ANSI / ISO standards according to: ANSI A137.1 - Porcelain tile P1 Class, ISO 13006 - G - Bia Group, En 14411 - G - Bia Group. Variances in test values can occur in different production lots.

Series: Nexus Recified Porcelain

Packaging information

Key logistical details including item codes and product specifications.

Nexus Product & Packaging Information

		ACTUAL DIMENSIONS	THICKNESS	CLAY ITEM CODE	GRAPHITE ITEM CODE	ICE ITEM CODE	MICA ITEM CODE	LBS BOX	KGS BOX	PCS BOX	SOFT BOX	MF BOX	BXS SKID	SOFT SKID	MF SKID
12 x 24 in / 30 x 60 cm MATTE PRESSED GLAZED PORCELAIN TILE	Stocked	300 x 600 mm	9.5 mm	4500-0452-0	4500-0455-0	4500-0458-0	4500-0461-0	63.96	29.01	8	15.5	1.44	32	496	46.08
13 x 13 in / 33 x 33 cm MATTE PRESSED GLAZED PORCELAIN TILE	Stocked	330 x 330 mm	8 mm	4500-0450-0	4500-0453-0	4500-0456-0	4500-0459-0	52.83	23.06	13	15.28	1.42	46	702.88	65.32
MOSAIC															
2 x 2 in / 5 x 5 cm MATTE GLAZED PORCELAIN MOSAIC	Stocked	299 x 299 mm	9.5 mm	4501-0167-0	4501-0168-0	4501-0169-0	4501-0170-0	38.45	17.44	10	9.89	0.89	48	465.12	42.91
TRIM															
3 x 12 in / 7.1 x 30 cm MATTE GLAZED PORCELAIN BULLNOSE	Stocked	70.5 x 300 mm	9.5 mm	4502-0148-0	4502-0147-0	4502-0148-0	4502-0149-0	16.46	7.47	20	N/A	N/A	84	1680 pcs.	1680 pcs.



Nexus Graphite 12 x 24 Matte Pressed Tile