



(WWRD-3 drive roll and WWRI-3 idler roll)

WELDWIRE 1 TO 3 TON PIPE ROLL SPECIFICATIONS

	SIZE 1	SIZE 3	SIZE 3S
Drive, Rubber tired	WWRD-1	WWRD-3	WWRD-3S
Idler, Rubber tired	WWRI-1	WWRI-3	WWRI-3S
Capacity per Unit	½ ton 1,000lbs.	1 ½ ton 3,000lbs.	1 ½ ton 3,000lbs.
Capacity Driver & 1 Idler	1 ton 2,000lbs.	3 ton 6,000lbs.	3 ton 6,000lbs.
Capacity Driver & 2 Idlers	1 ½ ton 2,500lbs.	4 ½ ton 9,000lbs.	4 ½ ton 9,000lbs.
Diameter Range, standard	2" to 20"	3 ½" to 40"	2" to 8'
Wheels	8" diameter w/2 ½" face	12" diameter w/4" face	12" diameter with 2 1/2" face
Motor	1/6 HP DC	1/4HP AC	1/2HP AC
Speed	0-104 IPM	0 to 91 IPM (60:1) standard 0 to 68 IPM (80:1) optional 0 to 55 IPM (100:1) optional	0 to 91 IPM (60:1) standard 0 to 68 IPM (80:1) optional 0 to 55 IPM (100:1) optional
Gearbox	Direct Drive	Direct Drive	Primary drive w/secondary gearboxes
Electrical Power	110volt	110volt	110volt
Control	High frequency protected, variable speed control station	AC Vector	AC Vector
Foot Control	On/Off w/25' cable	On/Off w/25' cable	On/Off w/25' cable
Drive Train	Knurled friction wheel	Knurled friction wheel	
Dimensions Drive	26"L X 15"W X 9"H	33"L X 19"W X 15"H	65"L X 20"W X 15"H
Dimensions Idler	21"L X 8"W X 9"H	33"L X 8"W X 15"H	58"L X 20"W X 15"H
Shipping Weight Drive	95 lbs.	275 lbs.	410 lbs.
Shipping Weight Idler	36 lbs.	145 lbs.	230 lbs.
Options:			
Foot Controls		Variable speed	Variable speed
Hand Pendant			Speed control, rapid, For/Rev, Start, Stop w/25' cable

Please note that all specifications and prices are subject to change without notice. Prices are F.O.B. The Woodlands, Texas. Revised 6/1/09