"The Solution Is Science" Formulating advanced chemistry and lubricant solutions for the metalworking industry. Products proven to improve manufacturing performance, part quality and cost savings!



3900-FTH Stamping Compound



Nanotechnology Formula

- 1) Prevent Part Galling 3900-FTH Nanotechnology Formula spreads out completely over metal blanks to provide a complete lubrication interface between part and press, maximizing surface tension for precision forming and optimum finish, while resisting galling and scoring.
- 2) Save The High Cost Of Tool & Die Recoating Manufacturer's spend thousands maintaining their tools and recoating their dies. 3900 greatly extends the life of your tooling and reduces these costs.
- **3) No Washing Prior To Welding** 3900 does not require washing prior to welding, but instead resists spatter and actually enhances weld strength by acting as a flux.
- 4) Avoid Risks Involved With Using Straight Oils Operators appreciate the cleaner environment and atmosphere that using 3900 provides.

The 3900 Series Nanotechnology stamping compound is formulated for extreme forming operations without the use of oil. It is recommended for use on heavy duty drawing and forming operations.

A unique benefit of the 3900 Series is the ability to perform difficult operations and eliminate the need to wash parts prior to welding. It will provide antispatter protection to the part and assists as a flux during the welding process. The 3900 Series is completely stable both in concentrate and after water

dilution. It washes off easily and is compatible with pretreatment systems, thus, extending bath life.

The 3900 Series is also treated with metal deactivators to provide corrosion protection after the operation. Operators benefit from this product as it is safe and "runs clean". 3900 performs well at higher dilutions than

standard lubricants.

AUTOMOTIVE TESTED & APPROVED



Request A Trial Sample and Prove It For Yourself!









