

# “The Solution Is Science®”

Formulating advanced chemistry and lubricant solutions for the metalworking industry. Products proven to improve manufacturing performance, part quality and cost savings!

STAMPING LUBRICANT



Consultant Lubricants, Inc

## 7500 Stamping Compound

*Minimal Residue - Dry Film*

- 1) Minimal Smoking Residue** - If a non-evaporative product is used to form heat shields there is a huge risk that they could begin to smoke when heated after being installed on motor vehicles.
- 2) Reduced Lubricant Film Pooling or Wicking** - Many lubricant products will run and collect after heat shields are formed and stacked. This film left on the part will wick into the cardboard boxes during storage and can cause customer rejects.
- 3) Extend Tool Life** - It is a challenge to maintain the sharpness of all forming knives, tools and punches. 7500 RNO is formulated for use on aluminum, stainless steel and aluminized steel material.
- 4) Forming Precision** - Lubrication can greatly affect the precision of forms and the amount of hand work required after the fact.

**7500 Dry Film EP Stamping Compound** was developed for heat shield stamping operations for the automotive industry. Intended for use on aluminum, stainless steel, and aluminized steel materials formed over glass insulation.

**7500** is a single, high performing stamping lubricant with the ability to form interfaces when forming heat shields as well as activating under heat and pressure to resist galling and die wear when forming stainless and aluminized steel.

**7500** is safe and will not attack machine components. **7500's** low residue film eliminates excess oil from the part through evaporation, minimizing wicking or smoking risk.

Unique high lubricity synthetic additives provide optimum interface forming with minimal residue.

**Tested - Proven Performance!**

Improved Customer Satisfaction  
& Reduced Scrap Rate!

*Request A Trial Sample and Prove It For Yourself!*

