

“The Solution Is Science®”

Formulating advanced chemistry and lubricant solutions for the metalworking industry. Products proven to improve manufacturing performance, part quality and cost savings!

TANK-SIDE ADDITIVES



Consultant Lubricants, Inc

C-66 Tankside Defoamer

Water Soluble Concentrate

- 1) Instantaneous and Long-lasting Foam Control** - C-66 reduces surface tension to resist bubbles from forming and to “break” foam instantaneously that already exists.
- 2) Paintline Compatible** - C-66 is a highly effective tankside defoamer that will “break” foam in water-based coolant and parts cleaning systems. This product is free rinsing and will not cause painting issues downstream.
- 3) Compatible with All Coolants** - C-66 is non-hazardous and fully compatible with synthetic, semi-synthetic and water soluble oils. Even with frequent use, C-66 will not contaminate coolants, reduce coolant life or affect stability.
- 4) Application** - Defoamers are generally “consumed” during use and depending on circulation rate, nozzle pressure, etc., may require continued use. See your CLI Sales Representative to specify the lowest foaming coolant and add C-66 only as needed.

The C-66 product is a concentrated defoaming agent designed for tank side applications for metalworking fluids or alkaline-acid based cleaners to immediately “drop” foam from the system.

This product is not harmful to operators and should be added to the sump or tank fluid or pre-diluted mixtures to prevent “foam outs.”

The C-66 is approved for H-1 incidental food contact. Thus, this product can be used to reduce foam in plants producing food type products, but, is not approved for use in food products themselves.

DIRECTIONS: Add 2-4 oz. tankside with pumps circulating. Repeat as necessary.

Request A Trial Sample and Prove It For Yourself!

