
VW Weighing Indicator

CE IM M







Features

Flexible positioning, e.g. free-standing or mounted to the wall.

Full function: unit change, accumulation, checkweighing, simply counting, Gross/Net shift, accumulating.

Weighing with tolerance range

(check-weighing): a visual and audible signal helps with portioning, dispensing or grading Hold function: When the weighing conditions are unstable, a stable weight is calculated determining an average value.

RS-232 interface can connect to PC or printer.

Technical Data


Display: LCD display, digit height 52mm , with white color LED backlight **Power:** AC adapter (100~240VAC/12V500mA),

rechargeable battery (lead acid battery 6V/4Ah), operation time 50 hours

Accessories

- Connection parts to install on pole for platform scale
- RS-232 cable for PC
- RS-232 cable for printer
- Mini printer
- Label printer
- Bluetooth data interface, data transfer to PC
- Analogue output (0~10V or 4~20mA selectable)
- 3 color light tower





Model	VW
Housing	ABS plastic
Dimensions	252x162x56 mm
Net weight	1.2kg
nmax.	7.500e
Load cell input resistance	43~1600 ohms
Load cell excitation voltage	5VDC
Vmin(only for approval)	0.5uV
Cable length	461m/mm ²
Load cell connector	Air connector, 7pin for EC type approved model.