

PONY / FRONT WHEEL DRIVE

ENGINES

- A. No rotary or turbo engines
- B. Must be steel block.
- C. Engine must be in stock location.
- D. Any steel rod
- E. Must have stock crank and stroke
- F. Crank may be lightened
- G. Must have stock lifters

WEIGHTS

- A. One pound per engine CC displacement. (Example 2300 C.C. must weigh 2300lbs.)
- B. NO CAR (regardless of cc) can weigh under 2000 LBS.
- C. Track reserves the right to adjust weights in interest of competition should it deem necessary.

HEADS

- A. OEM Steel (except Toyota - Aluminum)
- B. Porting and polishing allowed.

CAMS

- A. Solid lift cam permitted
- B. Hydraulic Cams will receive a 100 LB weight break
- C. Roller cams permitted (add 50#)

VALVES

- A. Any valve job
- B. Porting and Polishing allowed
- C. Any valve

INTAKE MANIFOLDS

- A. Any intake manifold allowed.
- B. Porting and polishing allowed.

CARBURETORS

- A. Holley 500 cfm maximum.

HEADERS

- A. Headers permitted.

TRANSMISSION

- A. Must have working forward and reverse gears.

FLYWHEEL

- A. Minimum of 16 lbs. (ANY OTHER MUST ADD 70 lbs.)

ROLL CAGE

- A. ROLL CAGE REQUIRED

SEATS

- A. Must have racing seat
- B. Seat must be mounted with grade 5 or better hardware
- C. All car must have 3 inch seat belts with shoulder harness and must be attached to roll cage.

BODIES

- A. Maximum wheelbase is 101 inches (+ – 1-inch)
- B. Minimum wheelbase is 92 inches (+ – 1-inch).
- C. Wheelbase must match body.
- D. No rear engines cars.
- E. Interior body panels and dash may be removed.
- F. All plastic, glass, emblems, etc. must be removed.
- G. All exterior body panels and hood must be stock appearing.
- H. Front and rear bumper covers allowed (must be made of rubber or flexible plastic material)
- I. Stock type bumpers or tube bumpers permitted.
- J. No skid plates, bars, and pipes anywhere on racecar
- K. Push bars front and rear permitted.
- L. Front push bar must stay behind front bumper.
- M. Rear push bar may be attached to rear bumper.

FUEL/FUEL CELL

- A. Gas or E85 only! No alcohol, nitrous oxide, nitro methane, or any other nitrate additives
- B. Fuel cell with steel can and 2" steel straps mounted in rear of car only
- C. Racing fuel allowed.
- D. Fuel cell may be relocated to trunk area.
- E. Must have adequate firewall between the driver and fuel cell.

FIREWALL

- A. Factory firewall and floor pan must remain

WHEELS/TIRES

- A. Bead locks permitted.
- B. 8" maximum
- C. Front tires open

- D. All rear tires must punch / stick 50 AT ANY GIVEN TIME with the track's durometer
- E. No chemical treating allowed

WEIGHTS

- A. One pound per engine CC displacement. (Example 2300 C.C. must weigh 2300lbs.)
- B. NO CAR (regardless of cc) can weigh under 2000 LBS.
- C. Track reserves the right to adjust weights in interest of competition should it deem necessary.

PONY PROTEST FEES

\$200.00 to pull head, check head, intake, carburetor and bore & stroke.

\$150.00 to pull transmission and check clutch and weigh flywheel