



LED Round Canopy Multi Wattage Multi CCT



Bronze Housing



White Housing



Wall Mounting Quick Mount Back Plate

FEATURES

- IP65 rated
- Housing choice bronze or white
- Rust & corrosion proof
- 50,000 hours lifetime

APPLICATIONS

- Warehouses
- Stadiums
- Factories
- Parking Lots
- Shopping Malls
- Supermarkets
- Logistic Centers
- Auto dealerships



CONSTRUCTION	CONTROLS AND DIMMING
Heavy die-cast aluminum housing with polyester powder-coated finish.	0-10V dimming standard.
OPTICAL SYSTEM	INSTALLATION AND MOUNTING
Seoul 2835 LED chips. Frosted lens. 135° beam angle.	Wall mount with quick mount back plate.
ELECTRICAL	WARRANTY
120-277V input. -20°C to 50°C (-4°F to 122°F).	5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

OPTIONAL ACCESSORIES



Microwave Sensor
120-MWS-MW-ACYG1
Compatible with 120-RCU-G1 White



Microwave Bluetooth Sensor
120-MWS-BT-ACYG1
Compatible with App



PIR Sensor
120-PIR-ACYG1
Compatible with 120-RCU-G1 White



PIR Bluetooth Sensor
120-PIR-BT-ACYG1
Compatible with App



Remote Control
120-RCU-ACYG1-White



Photocell / Daylight Sensor
120-PCU-DS-226
Not Compatible with Remote Control 120-RCU-100



Motion Sensor
120-MSU-BM-ANT54T
Compatible with 120-RCU-100



Remote Control
120-RCU-100



LED Round Canopy Multi Wattage Multi CCT

Part Number 120-CPRDXX-75-50-27-DIM-BR (Bronze Housing)

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
40W	3000K/4000K/5000K	5,400LM	135lm/w	120-277V	70	.9	20%	100-320W HID
50W	3000K/4000K/5000K	6,750LM	135lm/w	120-277V	70	.9	20%	100-320W HID
60W	3000K/4000K/5000K	8,100LM	135lm/w	120-277V	70	.9	20%	100-320W HID
75W	3000K/4000K/5000K	10,125LM	135lm/w	120-277V	70	.9	20%	100-320W HID

Part Number 120-CPRDXX-75-50-27-DIM-WH (White Housing)

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
40W	3000K/4000K/5000K	5,400LM	135lm/w	120-277V	70	.9	20%	100-320W HID
50W	3000K/4000K/5000K	6,750LM	135lm/w	120-277V	70	.9	20%	100-320W HID
60W	3000K/4000K/5000K	8,100LM	135lm/w	120-277V	70	.9	20%	100-320W HID
75W	3000K/4000K/5000K	10,125LM	135lm/w	120-277V	70	.9	20%	100-320W HID

PRODUCT DIMENSIONS

